

AstroManager

User manual

Astrophotography file manager and analyser

Version 1.5.0

MIT | github.com/ARP273-ROSE/astromanager

Contents

1 Introduction **1**
1.1 What is AstroManager? . . . 1
1.2 Supported Formats . . . 1
1.3 System Requirements . . . 1
1.4 What's New in v1.2.0 . . . 2
1.5 What's New in v1.3.0 . . . 2

2 Installation **3**
2.1 The installer (recommended) . . . 3
2.2 Updates . . . 3
2.3 Problem reports . . . 3
2.4 From the sources . . . 3

3 User Interface Overview **4**
3.1 18-Tab Layout . . . 4
3.2 Cosmic Dark Theme . . . 4
3.3 Bilingual Support (EN/FR) . . . 4
3.4 Console Output . . . 5
3.5 Progress Bar . . . 5
3.6 Keyboard Shortcuts . . . 5
3.7 Help menu, manual and look . . . 5

4 Analysis Tab **5**
4.1 Folder Selection . . . 6
4.2 Analysis Options . . . 6
4.3 SIMBAD Integration . . . 6
4.4 Plate Solving . . . 7
4.5 Weather Integration . . . 7
4.6 Report Generation . . . 7

5 Compression Tab **7**
5.1 Overview . . . 7
5.2 Compression Profiles . . . 8
5.3 Format Conversion . . . 8
5.4 SHA-256 Integrity Verification . . . 9
5.5 Parallel Processing . . . 9

6 ASIAIR Import Tab **9**
6.1 Overview . . . 9
6.2 Import Workflow . . . 9
6.3 Header Fixes . . . 9

7 Header Editor Tab **9**
7.1 Overview . . . 9
7.2 Categories . . . 10
7.3 NINA Pattern Builder . . . 10
7.4 Auto-Rename After Edit . . . 10
7.5 Undo . . . 10

8 Flat Manager Tab **11**

8.1 Overview . . . 11
8.2 Automatic Grouping . . . 11
8.3 Coverage Report . . . 11
8.4 Master Flat Tracking . . . 11

9 Quality Analysis Tab **11**
9.1 Overview . . . 11
9.2 Star Detection . . . 12
9.3 PSF Fitting . . . 12
9.4 Per-Frame Metrics . . . 13
9.5 Quality Score (0–100) . . . 13
9.6 Auto-Reject Suggestions . . . 13
9.7 Satellite Trail Detection . . . 13
9.8 Star Map Visualization . . . 14
9.9 Export . . . 14

10 WBPP Export Tab **14**
10.1 Overview . . . 14
10.2 Template Tokens . . . 14
10.3 Calibration Auto-Matching . . . 15
10.4 Calibration Scoring (0–1) . . . 15
10.5 Preview Tree . . . 15
10.6 Validation Warnings . . . 15
10.7 Export Modes . . . 16

11 Target Tracking Tab **16**
11.1 Overview . . . 16
11.2 Observation Timeline . . . 16
11.3 Integration Statistics . . . 16
11.4 Weather Forecast . . . 16
11.5 Target Visibility . . . 16

12 Sky Chart Tab **17**
12.1 Overview . . . 17
12.2 Projection Modes . . . 17
12.3 Color Modes . . . 18
12.4 Target Size . . . 18
12.5 Milky Way Band . . . 18
12.6 Interactive Features . . . 18
12.7 Export . . . 18

13 Calendar Tab **18**
13.1 Overview . . . 18
13.2 Monthly View . . . 19
13.3 Yearly Heatmap . . . 19
13.4 Statistics Dashboard . . . 19
13.5 Session Details . . . 19
13.6 Export . . . 19

14 PixInsight Tab **20**
14.1 Overview . . . 20
14.2 Log Analysis . . . 20
14.3 Per-Frame Statistics . . . 20

15 Mount Tracking Tab **20**
15.1 Overview . . . 20
15.2 Supported Log Formats . . . 20
15.3 Tracking Quality Dashboard . . . 20
15.4 Target Segmentation . . . 20
15.5 Deviation Timeline . . . 21
15.6 FFT Periodic Error Analysis . . . 21
15.7 Per-Target Statistics . . . 21

16 History & Statistics Tab **21**
16.1 Overview . . . 21
16.2 Dashboard . . . 21
16.3 Target Rankings . . . 21
16.4 Per-Filter Statistics . . . 21
16.5 Equipment Statistics . . . 22
16.6 Temporal Analysis . . . 22
16.7 Best Nights . . . 22
16.8 Object Type Statistics . . . 22
16.9 Export and Import . . . 22

17 Database Browser Tab **23**
17.1 Overview . . . 23
17.2 Built-in Databases . . . 23
17.3 Search and Filter . . . 23

18 Disk Space Tab **23**
18.1 Overview . . . 23
18.2 Storage Breakdown . . . 23
18.3 Duplicate Detection . . . 24
18.4 Optimization Recommendations . . . 24
18.5 File Organization . . . 24
18.6 Storage Type Detection . . . 24

19 Configuration **24**
19.1 Settings Dialog . . . 24
19.2 Configuration File . . . 25
19.3 Command-Line Options . . . 25

20 SQLite Database **26**
20.1 Overview . . . 26
20.2 Schema Versions . . . 26
20.3 Thread Safety . . . 26
20.4 Maintenance . . . 26

21 DBSCAN Clustering & Tags **27**
21.1 Target Clustering by RA/Dec . . . 27
21.1.1 How It Works . . . 27
21.1.2 Safe Merging . . . 27
21.1.3 Nearby Target Search . . . 27
21.2 Tags System . . . 27
21.2.1 Colored Tags . . . 27
21.2.2 Workflow Stages . . . 28

22 Analytics Tab **28**
22.1 Overview . . . 28
22.2 N.I.N.A. CSV Import . . . 28
22.3 Imaging Efficiency . . . 28
22.4 Correlations . . . 29
22.5 Time Series . . . 29
22.6 Equipment Performance . . . 29
22.7 Session Notes . . . 30

23 Image Viewer Tab **30**
23.1 Overview . . . 30
23.2 File Browser . . . 30
23.3 Display Engine . . . 30
23.4 STF Autostretch . . . 31
23.5 FWHM Heatmap . . . 31
23.6 Corner Inspector . . . 31
23.7 Star Overlay . . . 31
23.8 Header Viewer . . . 32
23.9 Image Info Panel . . . 32
23.10 FWHM Statistics Panel . . . 32

24 Cross-Section Tab **32**
24.1 Overview . . . 32
24.2 Dual Image Viewer . . . 32
24.3 Line Profile Tool . . . 33
24.4 Color Modes . . . 33
24.5 Histogram Comparison . . . 33
24.6 Filter Attenuation Analysis . . . 33
24.6.1 Region Selection . . . 33
24.6.2 Statistical Analysis . . . 34
24.7 Auto-Alignment . . . 34
24.8 CSV Export . . . 34

25 NAS Portability **35**
25.1 Architecture . . . 35
25.2 Local Virtual Environment . . . 35
25.3 Launcher Scripts . . . 35
25.4 Desktop Shortcuts . . . 35

26 Troubleshooting & FAQ **36**
26.1 No FITS Files Found . . . 36
26.2 Database Locked . . . 36
26.3 Slow Performance . . . 36
26.4 LaTeX Report Compilation Fails . . . 36
26.5 Missing Dependencies . . . 36
26.6 XISF Header Editing Errors . . . 36
26.7 ASIAIR Files Fail to Read . . . 36
26.8 Plate Solving Fails . . . 37
26.9 Update Checker Not Working . . . 37
26.10 Broken Virtual Environment . . . 37
26.11 Crash Reports . . . 37

27 Acknowledgments **37**
27.1 Inspiration 37
27.2 Core Libraries 38
27.3 Astronomical Services 38
27.4 Community 38

1 Introduction

1.1 What is AstroManager?

AstroManager is a comprehensive, professional-grade file management suite designed specifically for astrophotographers. Built with Python and PyQt6, it provides a modern, cosmic-themed interface with **18 organized tabs** covering every aspect of astrophotography data management:

- Universal file analysis (FITS, XISF, FITS.FZ)
- Multi-codec compression with 9 profiles
- Mass header editing with NINA compatibility
- Flat frame management and coverage tracking
- Frame quality analysis with PSF fitting and star detection
- WBPP-ready export with automatic calibration matching
- Target tracking over time with SIMBAD integration
- Interactive celestial sky chart
- Observation shoot calendar with heatmap
- PixInsight log analysis
- Mount tracking analysis (MountMonitor)
- Observation history and statistics dashboard
- Built-in database browser (cameras, telescopes, filters, targets)
- Disk space analysis and duplicate detection
- ASIAIR import workflow
- N.I.N.A. CSV analytics with correlation analysis and efficiency tracking
- FITS/XISF image viewer with FWHM heatmap, corner inspector, STF autostretch
- Cross-section comparison with filter attenuation analysis and auto-alignment

AstroManager handles **200,000+ files** efficiently through parallel processing, multi-tier caching, and automatic hardware detection.

1.2 Supported Formats

Format	Extension	Description
FITS	`.fits`, `.fit`, `.fts`	Standard astronomical image format
XISF	`.xisf`	PixInsight native format with XML metadata
FITS.FZ	`.fits.fz`, `.fz`	RICE tile-compressed FITS (fpack)

1.3 System Requirements

Component	Requirement
Python	3.8 or newer (3.11+ recommended)
Operating System	Windows 10/11, Linux (Ubuntu 20.04+, Manjaro, etc.), macOS 12+
RAM	4 GB minimum, 8 GB+ recommended for large datasets
Storage	SSD recommended for best performance
GUI Framework	PyQt6 6.2+
Core Libraries	numpy, astropy, matplotlib, pandas, Pillow, reportlab, tqdm, requests, xisf
Optional	scipy (PSF fitting, DBSCAN), astroquery (SIMBAD), psutil (auto-tuning), zstandard, lz4, pyqtgraph≥0.13 (GPU viewer), photutils≥1.5 (DAOStarFinder), astroalign (auto-alignment), scikit-image (phase correlation)

1.4 What's New in v1.2.0

Version 1.2.0 is a major feature release inspired by Athenaeum/rustafits (Vilen Sharifov). It introduces five new tabs and several cross-cutting features:

New Tabs in v1.2.0

- **Quality Analysis** — Per-frame star detection, 2D PSF Moffat/Gaussian fitting, quality scoring 0–100, satellite trail detection, interactive star maps
- **WBPP Export** — PixInsight WBPP-ready folder organization with 8-parameter calibration matching, scoring 0–1, template tokens, and preview tree
- **Sky Chart** — Aitoff/Mollweide projection of all targets, color-coded by object type, filter, or integration time, with Milky Way band overlay
- **Calendar** — Monthly grid and yearly GitHub-style heatmap of imaging sessions with statistics dashboard
- **Tags & Workflow** — Colored tags and Stage/WIP/Archive workflow stages for target classification

New Cross-Cutting Features in v1.2.0

- **DBSCAN Clustering** — Automatic target deduplication by RA/Dec coordinates using DBSCAN with Haversine distance
- **Database Schema v4** — New tables for tags, workflow stages, and frame quality cache
- **Batch Plate Solving** — Solve all unsolved raw LIGHT frames in one click, with in-place XISF header update

1.5 What's New in v1.3.0

Version 1.3.0 adds three major analytical tabs, each inspired by a dedicated open-source astrophotography project. Together they bring imaging session analytics, deep image inspection, and comparative filter analysis into a single integrated suite.

New Tabs in v1.3.0

- **Analytics** — N.I.N.A. CSV import, imaging efficiency vs. astronomical dark time, metric correlations (HFR, FWHM, eccentricity vs. temperature, humidity, wind), time-series trending with moving averages, and per-equipment performance statistics. Inspired by GalactiLog (chvvkumar).
- **Image Viewer** — FITS/XISF browser with GPU-accelerated display (pyqtgraph), PixInsight-style STF autostretch, FWHM heatmap with Nadaraya–Watson kernel regression, 3×3 corner inspector with per-cell quality grading, and star overlay. Inspired by Astronalyze (ricksastro).
- **Cross-Section** — Side-by-side dual image viewer with line profile comparison, histogram overlay, filter attenuation analysis (Welch t-test, Cohen's d, SNR, exposure factor), and star-based auto-alignment via astroalign. Inspired by AstroCrossSections (brentmantooth).

New Cross-Cutting Features in v1.3.0

- **Database Schema v5** — New tables for N.I.N.A. exposure data, weather correlation, imaging efficiency, session notes, and equipment performance tracking
- **Session Notes** — Per-date text notes with target association, saved in the database for long-term annotation of imaging sessions
- **Target Resolver** — Automatic SIMBAD coordinate lookup when importing N.I.N.A. CSV data

2 Installation

2.1 The installer (recommended)

Ready-to-use packages, Python and every dependency included, are published on the releases page: `https://github.com/ARP273-ROSE/astromanager/releases/latest`. No administrator rights are needed: everything installs into your own profile.

System	File and first launch
Windows	`AstroManager-Setup.exe`. If SmartScreen warns that the installer is unsigned: *More info*, then *Run anyway* (only once).
macOS	`AstroManager-X.Y.Z-macos-arm64.dmg` (Apple Silicon) or `-macos-x86_64.dmg` (Intel): drag the application into Applications, then the first time *right-click* > *Open*.
Linux	`AstroManager-X.Y.Z-linux-x86_64.tar.gz` (or `-linux-arm64`): unpack, then run `./installer.sh` (installs into `~/.local/share`, adds the menu entry, no sudo).

This address always points at the latest Windows installer:

`https://github.com/ARP273-ROSE/astromanager/releases/latest/download/AstroManager-Setup.exe`

Settings, database and reports live outside the installation folder (`%APPDATA%\AstroManager` on Windows, `~/.astromanager` elsewhere) and survive updates.

2.2 Updates

Once installed, AstroManager looks for a new version at start-up (can be turned off in **Tools** > **Settings**) and on demand (**Help** > **Check for Updates**). It downloads only the small application archive from GitHub (any other address is refused), applies it and restarts, on Windows, macOS and Linux. The release notes are shown in the language of the interface.

2.3 Problem reports

At first launch, AstroManager asks whether it may send a short technical report automatically when it crashes or freezes (version, system, error trace; none of your files). The choice can be changed in the **Help** menu, where **Report a problem...** also lets you write a report yourself.

2.4 From the sources

Python 3.10 or newer. The portable launchers `launch.bat` (Windows) and `launch.sh` (Linux, macOS) create the virtual environment and install the dependencies on first launch; by hand:

```
pip install -r requirements.txt
python astromanager.py            # interface
python astromanager.py --help     # command-line analysis
```

3 User Interface Overview

3.1 18-Tab Layout

AstroManager organizes its features into 18 tabs, listed in order from left to right:

#	Tab	Purpose
1	Analysis	Universal file analysis with SIMBAD, plate solving, weather
2	Compression	Multi-codec compression and format conversion
3	ASIAIR Import	Import workflow for ASIAIR capture sequences
4	Header Editor	Mass FITS/XISF header editing
5	Flat Manager	Flat frame grouping and coverage
6	Quality Analysis	Per-frame star detection and quality scoring
7	WBPP Export	PixInsight-ready file export with calibration matching
8	Target Tracking	Observation timeline and integration statistics
9	Sky Chart	Interactive celestial map of observed targets
10	Calendar	Monthly grid and yearly heatmap
11	PixInsight	WBPP/FBP log analysis
12	Mount Tracking	MountMonitor log analysis
13	History & Stats	Dashboard, rankings, temporal analysis
14	Database Browser	Built-in cameras, telescopes, filters, targets
15	Disk Space	Storage analysis and duplicate detection
16	Analytics	N.I.N.A. CSV analytics, correlations, efficiency (NEW)
17	Image Viewer	FITS/XISF viewer with FWHM heatmap, STF autostretch (NEW)
18	Cross-Section	Dual image comparison with filter attenuation (NEW)

3.2 Cosmic Dark Theme

AstroManager uses a custom "Cosmic Dark" theme optimized for use in dark observatory environments. The palette is built around deep space backgrounds (`#0a0e1a`) with muted, desaturated accents:

- **Accent cyan** (`#94b8c8`) — Primary interactive elements, links, progress bars
- **Accent purple** (`#a8a0c0`) — Secondary accents
- **Success green** (`#88b098`) — Positive indicators, good quality scores
- **Warning tan** (`#b8a880`) — Caution indicators, mediocre scores
- **Error coral** (`#b89090`) — Error indicators, poor scores

All colors are deliberately low-saturation to avoid eye strain during nighttime use.

3.3 Bilingual Support (EN/FR)

AstroManager automatically detects the system language and displays all text, tooltips, labels, error messages, and menu items in either English or French. The detection uses `locale.getdefaultlocale()` with English as the fallback.

You can override the language in **Tools** → **Settings** → **General** → **Language** (choices: `auto`, `en`, `fr`).

3.4 Console Output

A collapsible console panel at the bottom of the window shows real-time operation logs. It uses a monospace font (Consolas) and supports colored output for errors (coral), warnings (tan), and info (cyan).

Toggle the console with `Ctrl+‘` or resize the splitter.

3.5 Progress Bar

A global progress bar at the bottom displays:

- Current phase name (e.g., “Scanning files...”, “Fitting PSF...”)
- Percentage complete
- Estimated time remaining (ETA)

3.6 Keyboard Shortcuts


Shortcut	Action
`Ctrl+,`	Open Settings dialog
`Ctrl+Q`	Quit the application
`Ctrl+O`	Open a folder (Analysis tab)
`Ctrl+‘`	Toggle console panel
`F1`	Open User Guide

3.7 Help menu, manual and look

The **Help** menu opens this **PDF manual** in the language of the interface (**User manual (PDF)**, `Shift+F1`), the built-in guide (F1), the shortcuts, the update check, **Report a problem...** and the **Send problem reports automatically** option.

The look is **fixed**: Fusion style, complete cosmic palette and embedded font (Source Sans 3), identical on the three systems and independent of their light or dark theme. On Linux, the *Open*, *Save* and *Choose a folder* dialogs are Qt’s complete file browser (sidebar with home, Desktop, Documents, mounted drives) rather than the reduced desktop-portal dialog.

4 Analysis Tab



The Analysis tab is the core of AstroManager. It performs recursive analysis of entire folder trees containing FITS, XISF, and FITS.FZ files, extracting comprehensive metadata and generating professional reports.

4.1 Folder Selection

Click **Browse** to select a root folder. AstroManager will recursively scan all subdirectories, excluding system folders and previously extracted duplicate folders (prefixed with `extracted_`, `duplicates_`, etc.).

4.2 Analysis Options

Option	Description
SIMBAD Resolution	Query the SIMBAD astronomical database for canonical target names and object types
Duplicate Detection	Detect duplicates using both name-based and content-based signature matching
Plate Solving	Solve astrometry using ASTAP or Astrometry.net to detect focal reducers and correct WCS
Weather Fetch	Retrieve historical weather data from Open-Meteo for each observation night
Workers	Number of parallel threads for I/O (0 = auto-detect based on CPU cores)

4.3 SIMBAD Integration

When enabled, AstroManager queries the SIMBAD database (CDS, Strasbourg) to resolve target names to their canonical designations and retrieve object types (Galaxy, Emission Nebula, Planetary Nebula, Open Cluster, etc.). Results are cached in the local SQLite database for offline access.

4.4 Plate Solving

AstroManager supports two plate solving backends:

- **ASTAP** (Han Kleijn) — Fast local solver, recommended
- **Astrometry.net** — Online or local solver

Plate solving automatically detects focal reducers (0.67x, 0.72x, 0.8x) by comparing the solved focal length to the expected value from the telescope database. The WCS solution and corrected focal length are written back to the file headers.

Batch solving: AstroManager can solve all unsolved raw LIGHT frames in one click. Large images are automatically binned for faster solving. XISF headers are updated in-place (modifying only the ~8 KB header block, not the full 60 MB image data). PixInsight processed files, masters, and calibration frames (Dark/Flat/Bias) are automatically skipped.

4.5 Weather Integration

Historical weather data is fetched from the Open-Meteo API (free, no API key required). Data includes:

- Temperature, humidity, dew point
- Cloud cover percentage
- Precipitation and wind speed
- Atmospheric pressure

Results are cached in a 365-day SQLite cache for offline access.

4.6 Report Generation

AstroManager generates reports in multiple formats:


Format	Description
LaTeX/PDF	Professional report with tables, charts, and statistics (requires pdflatex)
HTML	Standalone HTML file with embedded CSS (always available)
CSV	Spreadsheet-compatible data export
AstroBin CSV	Specialized CSV with AstroBin filter ID mapping (Ha=4663, OIII=4752, SII=4844, L=2906, R/G/B, NII)

Reports include per-night, per-target, and per-filter statistics, equipment identification from built-in databases, mosaic panel detection, and duplicate analysis.

5 Compression Tab

5.1 Overview

The Compression tab provides bidirectional format conversion between FITS, XISF, and FITS.FZ with 9 compression profiles. All output is fully compatible with PixInsight.



5.2 Compression Profiles

Profile	Ratio	Speed	Best For
`zlib_1`	~30%	Fast	Temporary files
`zlib_6`	~50%	Medium	**General archival (recommended)**
`zlib_9`	~55%	Slow	Maximum zlib compression
`zstd_3`	~45%	Fast	Quick archival
`zstd_6`	~55%	Medium	Better than zlib_6
`zstd_10`	~60%	Slow	High compression
`zstd_19`	~65%	Very slow	Long-term archival
`lz4`	~25%	Ultra-fast	Working files, fast iteration
`lz4_hc`	~35%	Fast	Better LZ4 compression

Choosing a Profile

For most astrophotographers, `zlib_6` offers the best balance of compression ratio and speed. Use `lz4` when you need to quickly compress working files and plan to recompress later. Use `zstd_19` for permanent deep archival where speed is not a concern.

5.3 Format Conversion

Supported conversion paths:

- **FITS** → **XISF**: Converts to PixInsight native format with chosen compression
- **XISF** → **FITS**: Decompresses back to standard FITS
- **FITS** → **FITS.FZ**: RICE tile compression via Astropy (no external fpack needed)
- **FITS.FZ** → **FITS**: Decompresses tile-compressed files

5.4 SHA-256 Integrity Verification

When enabled, AstroManager computes SHA-256 checksums before and after conversion to verify data integrity. Any mismatch triggers an error and the output file is discarded.

5.5 Parallel Processing

Compression uses `ProcessPoolExecutor` for CPU-bound work, automatically scaling to the number of physical CPU cores. You can override the worker count in Settings.

Disk Space

Ensure you have sufficient disk space for the output files. Compression creates new files without deleting the originals (unless "Delete source after conversion" is enabled in Settings).

6 ASIAIR Import Tab

6.1 Overview

The ASIAIR Import tab provides a dedicated workflow for importing capture sequences from ZWO ASIAIR controllers. ASIAIR organizes files differently from NINA or SGPro, so this tab handles the translation.

6.2 Import Workflow

1. **Select ASIAIR capture folder** — Browse to the root of your ASIAIR output (typically organized as `autorun/` or `plan/`).
2. **Configure target settings** — Set the target name, organization preferences, and output folder.
3. **Import and organize** — AstroManager copies and reorganizes files by target, filter, and date.

6.3 Header Fixes

ASIAIR cameras (ZWO ASI series) produce FITS files with BZERO/BSCALE/BLANK keywords for unsigned integer storage (per the FITS standard). AstroManager automatically handles these keywords during import, ensuring compatibility with PixInsight, Siril, and other processing software.

Note

The BZERO/BSCALE handling was a critical fix in v1.1.5. Files are read with `memmap=False` to avoid memory-mapping issues with these keywords.

7 Header Editor Tab

7.1 Overview

The Header Editor allows mass editing of FITS and XISF headers across hundreds or thousands of files simultaneously. It is organized by category for easy navigation.

7.2 Categories

Category	Keywords
Acquisition	EXPTIME, DATE-OBS, IMAGETYP, FRAME, GAIN, OFFSET
Camera	INSTRUME, CCD-TEMP, XPIXSZ, YPIXSZ, XBINNING, YBINNING
Filter	FILTER
Telescope	TELESCOP, FOCALLEN, APTDIA, SITEOBS
Observer	OBSERVER, SITENAME, SITELAT, SITELONG, SITEELEV
Object	OBJECT, RA, DEC, EQUINOX
Software	SWCREATE, PROGRAM

7.3 NINA Pattern Builder

AstroManager supports NINA-style filename patterns using tokens:

Token	Expands To
`$IMAGETYPE$`	LIGHT, DARK, FLAT, BIAS
`$TARGETNAME$`	Object name from OBJECT keyword
`$FILTER$`	Filter name
`$EXPOSURE$`	Exposure time in seconds
`$DATE$`	Date from DATE-OBS
`$CAMERA$`	Camera name from INSTRUME
`$TELESCOPE$`	Telescope name from TELESCOP
`$GAIN$`	Gain value
`$TEMP$`	Sensor temperature
`$BINNING$`	Binning (e.g., 1x1)

7.4 Auto-Rename After Edit

After applying header changes, AstroManager automatically proposes renaming files to match the NINA pattern configured in Settings. This ensures filenames stay synchronized with their header metadata.

7.5 Undo

All header edits support undo. AstroManager stores the original values before modification and can revert changes if needed.

Warning

While header editing supports FITS, XISF, and FITS.FZ formats, XISF editing uses `defusedxml` for XML security. Always verify critical files after editing.

8 Flat Manager Tab

8.1 Overview

The Flat Manager helps organize, analyze, and track flat calibration frames. Proper flat field correction is essential for removing vignetting, dust shadows, and optical path artifacts.

8.2 Automatic Grouping

Flat frames are automatically grouped by:

- Date of acquisition
- Optical setup (telescope + focal length)
- Filter name
- Binning mode
- Rotation angle
- Sensor temperature

8.3 Coverage Report

For each group, the Flat Manager reports:

- **Complete** — Sufficient flats for reliable master creation (typically 20+)
- **Insufficient** — Some flats exist but below recommended count
- **Missing** — No flats found for this configuration

8.4 Master Flat Tracking

The Flat Manager tracks which master flats have been created and links them to target light frames based on matching criteria (setup, filter, binning, date proximity).


9 Quality Analysis Tab

New in v1.2.0

This tab is new in v1.2.0, inspired by Athenaeum/rustafits's PSF analysis pipeline.

9.1 Overview

The Quality Analysis tab performs automated per-frame quality assessment using star detection and Point Spread Function (PSF) fitting. It produces a quality score from 0 to 100 for each frame, enabling data-driven frame rejection decisions.



9.2 Star Detection

AstroManager uses **scipy peak detection** to identify stars in each frame:

1. The image is loaded and background-subtracted.
2. Local maxima above a configurable threshold (typically 5σ above background) are identified.
3. Candidate peaks are filtered by size, brightness, and edge proximity.
4. The brightest N stars (configurable, default 200) are selected for PSF fitting.

9.3 PSF Fitting

For each detected star, AstroManager fits a 2D elliptical PSF model:

- **Primary model: Moffat function** — More accurate for astronomical seeing, with a power-law wing profile:

$$I(r) = I_0 \left(1 + \left(\frac{r}{\alpha}\right)^2\right)^{-\beta}$$

- **Fallback: Gaussian function** — Used when Moffat fitting fails to converge:

$$I(r) = I_0 \exp\left(-\frac{r^2}{2\sigma^2}\right)$$

Both models are fitted as 2D elliptical functions to capture asymmetric star profiles caused by tracking errors, optical aberrations, or atmospheric effects.

9.4 Per-Frame Metrics

Metric	Description
FWHM	Full Width at Half Maximum (arcseconds or pixels). Measures star sharpness. Lower is better.
HFR	Half-Flux Radius. Alternative sharpness measure used by autofocus systems.
Eccentricity	Ellipticity of star profiles (0 = perfect circle, 1 = line). Measures tracking/guiding quality.
SNR	Signal-to-Noise Ratio of detected stars. Higher is better.
Star Count	Number of successfully fitted stars. Very low counts indicate problems.
Background	Mean background level and noise (standard deviation).
Roundness	Average roundness of star profiles (complement of eccentricity).

9.5 Quality Score (0–100)

Each frame receives a composite quality score computed from weighted metrics:

Metric	Weight
FWHM (sharpness)	35%
Eccentricity (roundness)	20%
SNR (signal quality)	20%
Star Count (detection)	15%
Roundness (symmetry)	10%

Scores are color-coded in the results table:

- **80–100**: Excellent quality
- **60–79**: Good quality
- **40–59**: Mediocre quality
- **0–39**: Poor quality — consider rejection

9.6 Auto-Reject Suggestions

AstroManager can automatically suggest frames for rejection based on:

- **Absolute thresholds**: Configurable limits for FWHM, eccentricity, SNR, and star count
- **Batch-relative outliers**: Frames that deviate significantly from the batch median (e.g., FWHM $> 2\sigma$ above median)

9.7 Satellite Trail Detection

AstroManager detects satellite trails using a **Rayleigh R^2 test** for directional coherence:

1. The elongation direction (position angle) of each detected star is measured.
2. A Rayleigh test checks whether elongation directions are randomly distributed or aligned along a common axis.
3. Strong directional coherence (high R^2) indicates a satellite or aircraft trail contaminating the frame.

9.8 Star Map Visualization

Double-click any frame in the results table to open the **Star Map** dialog. This interactive visualization shows:

- Each detected star's position on the frame
- PSF ellipse shape and orientation (elongation direction)
- Color coding by individual star quality
- Summary statistics overlaid on the image

9.9 Export

- **Accepted file list** (`.txt`): List of filenames that passed quality thresholds, ready for import into PixInsight or Siril.
- **Full metrics report** (`.csv`): Complete per-frame statistics including all metrics, scores, and rejection flags.

10 WBPP Export Tab

New in v1.2.0

This tab is new in v1.2.0, inspired by Athenaeum/rustafits's WBPP-ready export with calibration tree visualization.

10.1 Overview

The WBPP Export tab organizes your FITS/XISF files into a folder structure ready for PixInsight's **Weighted Batch PreProcessing (WBPP)** script. It automatically matches calibration frames (darks, flats, biases) to light frames and provides a preview of the planned structure before exporting.

10.2 Template Tokens

The output folder structure is defined using template tokens:

Token	Expands To
`{OBJECT}`	Target name from OBJECT keyword
`{IMAGETYP}`	Frame type: LIGHT, DARK, FLAT, BIAS
`{FILTER}`	Filter name
`{DATE}`	Observation date
`{CAMERA}`	Camera identifier
`{TELESCOPE}`	Telescope identifier
`{EXPTIME}`	Exposure time
`{TEMP}`	Sensor temperature
`{GAIN}`	Gain value
`{BINNING}`	Binning mode

The default template produces, for lights and for darks:

`{OBJECT}/{IMAGETYP}/{FILTER}/` `{OBJECT}/DARK/{EXPTIME}s_{TEMP}C/`

10.3 Calibration Auto-Matching

AstroManager matches calibration frames to lights using an 8-parameter scoring system:

Parameter	Exact	Warning	Ignore
Camera (INSTRUME)	Required	—	—
Temperature (±2°C)	Match	±5°C	Skip
Filter (FILTER)	Match	Similar	Skip
Exposure (EXPTIME)	Match	±20%	Skip
Binning (XBINNING)	Match	—	Skip
Gain (GAIN)	Match	±10%	Skip
Date proximity	Same week	Same month	Skip
Image dimensions	Match	—	Skip

10.4 Calibration Scoring (0–1)

Each calibration match receives a quality score from 0.0 (worst) to 1.0 (perfect). The scoring considers:

- **Parameter match quality**: Exact matches score higher than approximate matches.
- **Fallback chains**: If no matching darks are found, AstroManager tries DarkFlat → Dark → Bias (in order of preference).
- **Three matching modes per parameter**: Exact (strict), Warning (loose), and Ignore (skip the parameter entirely).

10.5 Preview Tree

Before exporting, the preview tree shows the planned folder structure as an interactive tree widget. Each folder node displays:

- Number of files
- Total size
- Calibration match quality (color-coded green/yellow/red)
- Warnings for missing or poorly matched calibrations

10.6 Validation Warnings

AstroManager validates the export plan and warns about:

- Missing calibration frames (no darks, flats, or biases)
- Temperature mismatches beyond the tolerance threshold
- Incomplete filter groups
- Mismatched binning between lights and calibrations

10.7 Export Modes

Mode	Description
Copy	Physically copy files to the destination (safest, uses most disk space)
Symlink	Create symbolic links (saves disk space, requires OS support)
Preview-only	Show the planned structure without writing any files

Tip

Use **Preview-only** mode first to verify the structure and calibration matching before committing to a full copy.

11 Target Tracking Tab

11.1 Overview

The Target Tracking tab provides a historical view of your observations for each target. It combines data from the analysis database with SIMBAD lookups and weather forecasts to give a complete picture of your imaging history.

11.2 Observation Timeline

A bar chart displays the integration time accumulated for each observation session, organized chronologically. Bars are color-coded by filter (e.g., blue for Luminance, red for H-alpha, teal for OIII).

11.3 Integration Statistics

Per-target statistics include:

- Total integration time (hours) across all sessions
- Integration per filter (with bar chart)
- Number of sessions, frames, and unique filters
- Best session identification by HFR, FWHM, and weather quality
- Equipment usage (telescopes, cameras, mounts)

11.4 Weather Forecast

The Target Tracking tab displays a multi-day weather forecast for upcoming nights, helping you plan future observation sessions. Data comes from the Open-Meteo API using your observatory coordinates (configured in Settings).

11.5 Target Visibility

Altitude charts show when a target is observable from your location, taking into account:

- Target declination and right ascension
- Observatory latitude, longitude, and elevation
- Twilight boundaries (civil, nautical, astronomical)
- Meridian transit time


12 Sky Chart Tab

New in v1.2.0

This tab is new in v1.2.0, inspired by Athenaeum/rustafits's interactive sky chart with d3-celestial.

12.1 Overview

The Sky Chart tab displays an interactive celestial map of all your observed targets using an Aitoff or Mollweide all-sky projection. It provides a visual overview of your imaging coverage across the sky.



12.2 Projection Modes

- **Aitoff projection**: Equal-area projection that preserves area relationships. Good for seeing the overall distribution of targets.
- **Mollweide projection**: Another equal-area projection with a more elliptical shape. Often used in astronomical catalogs.

Both projections display the full celestial sphere with coordinate grid lines (Right Ascension and Declination).

12.3 Color Modes

Switch between three color-coding schemes:

Mode	Description
Object Type	Galaxies (rose), Emission nebulae (green), Planetary nebulae (lavender), Clusters (gold), Dark nebulae (grey), etc.
Filter	Colors match your dominant filter: H-alpha (red), OIII (teal), SII (orange), Luminance (blue), RGB (mixed)
Integration Time	Gradient from dim (low integration) to bright (high integration)

12.4 Target Size

Each target is drawn as a circle whose size is proportional to the total integration time accumulated. Targets with many hours of data appear larger, making it easy to spot your most-invested objects.

12.5 Milky Way Band

A semi-transparent overlay approximates the Milky Way's galactic plane. This is toggleable and helps visualize the relationship between your targets and the galaxy.

12.6 Interactive Features

- **Hover tooltips**: Move your mouse over any target to see its name, object type, RA/Dec coordinates, and total integration time.
- **Click to select**: Clicking a target emits a signal for cross-tab navigation (e.g., jump to the Target Tracking tab for that object).
- **Toggle labels**: Show or hide target name labels on the chart.
- **Toggle grid**: Show or hide the RA/Dec coordinate grid.

12.7 Export

Export the sky chart as a high-resolution PNG image (200 DPI) for inclusion in presentations, reports, or social media posts.

13 Calendar Tab

New in v1.2.0

This tab is new in v1.2.0, inspired by Athenaeum/rustafits's shoot calendar.

13.1 Overview

The Calendar tab provides a visual overview of your imaging activity over time, combining a monthly calendar grid with a yearly heatmap and statistics dashboard.

13.2 Monthly View

The monthly view displays a standard calendar grid where each day cell shows:

- Number of frames captured
- Total integration time
- Target names observed
- Color intensity reflecting activity level

Navigate between months using arrow buttons. Days with imaging sessions are highlighted; click any day to see detailed session information.

13.3 Yearly Heatmap

The yearly heatmap displays a GitHub-style contribution map: 52 weeks × 7 days, where each cell's color intensity reflects the amount of imaging activity on that night. The color scale ranges from the dark background color (no data) through increasingly bright shades of the accent cyan:

Level	Color	Meaning
None	Dark (`#0a0e1a`)	No imaging
Low	`#1a2a3a`	Brief session
Medium	`#4a7a8a`	Moderate session
High	`#6a9aaa`	Long session
Very High	`#94b8c8`	Extensive session

13.4 Statistics Dashboard

Six stat cards display aggregate metrics:

- **Imaging Nights**: Total number of nights with at least one frame
- **Total Integration**: Cumulative integration time across all sessions
- **Best Month**: The month with the most imaging activity
- **Avg Frames/Night**: Average number of frames per imaging session
- **Longest Streak**: Maximum consecutive imaging nights
- **Unique Targets**: Number of distinct objects observed

13.5 Session Details

Click any day in the calendar or heatmap to see a detailed breakdown:

- Per-target breakdown: filter, frame count, integration time
- HFR and FWHM averages
- Telescope and camera used
- Weather conditions (if available)

13.6 Export

Export the calendar view as a PNG image for your records or sharing.

14 PixInsight Tab

14.1 Overview

The PixInsight tab imports and analyzes processing logs from PixInsight's WBPP (Weighted Batch PreProcessing) and FBP (Fast Batch Preprocessing) scripts.

14.2 Log Analysis

After importing a log file, AstroManager extracts:

- Per-frame quality metrics: FWHM, SNR, eccentricity, weight
- Rejection statistics: percentage of frames rejected per filter
- Integration results: total accepted frames, effective integration time
- Calibration tracking: which master darks, flats, and biases were applied

14.3 Per-Frame Statistics

A detailed table shows each subframe with its quality metrics. Frames are color-coded by quality, and rejected frames are clearly marked. This helps identify which frames were dropped and why.

15 Mount Tracking Tab

15.1 Overview

The Mount Tracking tab analyzes log files from **MountMonitor**, a mount tracking quality assessment tool. It provides deviation charts, FFT periodic error analysis, and per-target quality grades.

15.2 Supported Log Formats

Extension	Content
`.dat`	Main tracking data (RA/DEC deviations)
`.dti`	Time synchronization data
`.fft`	FFT periodic error analysis
`.env`	Environment data (temperature, pressure)
`.log`	General log entries

15.3 Tracking Quality Dashboard

The dashboard displays:

- **RA RMS**: Root Mean Square deviation in Right Ascension (arcseconds)
- **DEC RMS**: Root Mean Square deviation in Declination (arcseconds)
- **Tracking %**: Percentage of time in TRACKING state (vs. SLEWING/PARKED/IDLE)
- **Quality Grade**: A through F rating based on combined RMS

RA deviations are corrected by $\cos(\delta)$ to reflect true arcseconds on the sky (where δ is the declination).

15.4 Target Segmentation

AstroManager automatically detects pointing changes by analyzing jumps in RA/DEC values. Each pointing segment is treated as a separate target observation, with independent statistics.

15.5 Deviation Timeline

An interactive chart shows RA and DEC deviations over time. Only TRACKING samples are plotted (SLEWING, PARKED, and IDLE states are excluded).

15.6 FFT Periodic Error Analysis

Periodic error peaks are identified using Fast Fourier Transform:

- Dominant PE periods and amplitudes for each axis
- Worm gear frequency detection (typically 8–10 minute period for common mounts)
- Harmonic identification

15.7 Per-Target Statistics

A table lists each detected target segment with:

- RMS deviations (RA and DEC)
- Peak-to-peak range
- Duration
- Quality grade

16 History & Statistics Tab

16.1 Overview

The History & Statistics tab provides a comprehensive dashboard of your entire observation history stored in the SQLite database.

16.2 Dashboard

Six stat cards provide an at-a-glance summary:

- Total targets observed
- Cumulative integration time
- Total frames captured
- Number of imaging nights
- Average HFR across all sessions
- Number of telescopes used

16.3 Target Rankings

Targets are ranked by total integration time, with per-target breakdowns showing:

- Filter distribution (bar chart)
- Number of sessions
- Best session quality

16.4 Per-Filter Statistics

Usage statistics for each filter across all targets:

- Number of targets using this filter
- Total sessions and frames
- Average HFR and FWHM
- Total integration time

16.5 Equipment Statistics

Aggregated statistics per:

- Telescope (frames, integration, targets, nights)
- Camera (same breakdown)
- Setup combination (telescope + camera pair)

16.6 Temporal Analysis

- **Monthly**: Activity trend over months
- **Yearly**: Year-over-year comparison
- **Day of week**: Which days produce the most imaging (usually clear weeknights!)

16.7 Best Nights

Nights ranked by:

- **Quality**: Best average HFR (sharpest seeing)
- **Productivity**: Most integration time accumulated

16.8 Object Type Statistics

Integration time broken down by astronomical object type:

- Galaxies, Emission nebulae, Planetary nebulae
- Open clusters, Globular clusters
- Dark nebulae, Reflection nebulae
- Other types

16.9 Export and Import

Format	Description
JSON export	Complete history dump including all observations, targets, weather, and metadata
CSV export	Spreadsheet-compatible export of observations
JSON import	Restore a previously exported history

17 Database Browser Tab

17.1 Overview

The Database Browser tab provides read-only access to AstroManager's built-in reference databases. These databases are used internally for automatic identification of cameras, telescopes, filters, and astronomical targets.

17.2 Built-in Databases

Database	Entries	Coverage
Cameras	1,614 sensors + 2,448 mappings	ZWO, QHY, Atik, FLI, SBIG, Player One, Touptek, Moravian, Canon, Nikon, Sony, and more
Telescopes	3,991 models + 6,605 mappings	Takahashi, Celestron, Sky-Watcher, Meade, APM, William Optics, PlaneWave, Officina Stellare, TEC, RCOS, and more
Filters	1,612 filters + 701 aliases	Baader, Astronomik, Chroma, ZWO, Optolong, Antlia, IDAS, Astrodon, Custom Scientific
Targets	32,923 objects	Messier (110), NGC/IC (32,411), Arp (338), Solar System (64), plus Sharpless, Barnard, Caldwell, RCW, LBN, PGC, Abell, LDN, Hickson, UGC

Total: approximately 41,000 reference entries.

17.3 Search and Filter

Each database tab supports:

- Free-text search by name
- Filter by brand, type, or catalog
- Sorting by any column

18 Disk Space Tab

18.1 Overview

The Disk Space tab analyzes your storage usage by file format, identifies duplicates, and recommends optimization strategies.

18.2 Storage Breakdown

A summary shows total space used by each format:

- FITS files (uncompressed)
- XISF files (compressed)
- FITS.FZ files (RICE tile-compressed)
- Duplicates (name-based and content-based)

18.3 Duplicate Detection

AstroManager uses a two-level duplicate detection system:

1. **Phase 1 — Name-based**: Groups files by base name (without extension). When the same image exists in multiple formats (e.g., `NGC7000_L_001.fits` and `NGC7000_L_001.xisf`), the preferred format is kept (.xisf > .fits > .fits.fz).
2. **Phase 2 — Content-based**: Groups files by a 10-field signature tuple:
   - DATE-OBS, image type, exposure time, dimensions (NAXIS1/NAXIS2)
   - Binning, filter, object, instrument, telescope, frame number

Content-Based Signature

Both INSTRUMENT and TELESCOPE are included in the signature (added in v1.1.12) to prevent false duplicates between different hardware setups. DATE-OBS is required — files without a valid timestamp are treated as unique.

18.4 Optimization Recommendations

AstroManager suggests:

- Compressing uncompressed FITS to XISF (estimated savings)
- Removing duplicate files (estimated savings)
- Archiving old data to slower storage
- Organizing files by type, date, or target

18.5 File Organization

Built-in organization presets:

- By image type (LIGHT, DARK, FLAT, BIAS)
- By date (year/month/day)
- By target name
- Custom patterns

18.6 Storage Type Detection

AstroManager detects whether your storage is SSD or HDD and adjusts I/O strategies accordingly:

- Windows: WMI queries
- Linux: `/sys/block` inspection
- macOS: `diskutil` commands

19 Configuration

19.1 Settings Dialog

Access the Settings dialog via **Tools** → **Settings** or **Ctrl+,**.

Section	Settings
General	Language (auto/en/fr), Check for updates on startup
Observatory	Latitude, Longitude, Elevation, Timezone
Performance	Workers (0 = auto-detect), Batch size
Compression	Default profile, Delete source after conversion, Verify integrity
Analysis	SIMBAD, Plate solving, Weather defaults
Bug Reporting	Enable/disable anonymous crash reports

19.2 Configuration File

Settings are stored in `config.yaml` in the project directory:

```
application:
  language: "auto"    # auto, en, fr
  theme: "cosmic_dark"

system:
  workers: 0          # 0 = auto-detect
  batch_size: 1000

observatory:
  latitude: 51.4769   # Update for your location!
  longitude: -0.0005
  elevation_m: 46
  timezone: "UTC"

analysis:
  enable_simbad: true
  enable_plate_solving: false
  enable_weather_fetch: false

compression:
  default_profile: "zlib_6"
  verify_integrity: true

plate_solving:
  solver: "astap"     # astap or astrometry

weather:
  api_provider: "open-meteo"
  cache_duration_days: 365

bug_reporting:
  enabled: true
```

Observatory Coordinates

Make sure to update the observatory coordinates to match your actual location. These are used for weather forecasts, target visibility calculations, and altitude charts.

19.3 Command-Line Options

AstroManager can be used from the command line for scripted analysis:

```
python astromanager.py                                  # Launch GUI
python astromanager.py --folder /path/to/fits           # CLI analysis
python astromanager.py --folder /path --resolve-simbad  # With SIMBAD
python astromanager.py --folder /path --export-csv      # Export CSV
python astromanager.py --folder /path --workers 8       # 8 workers
python astromanager.py --optimize-storage /backup       # Optimize storage
python astromanager.py --version                        # Show version
python astromanager.py --reset-config                   # Reset config
python astromanager.py --vacuum-db                      # Optimize database
python astromanager.py --debug                          # Debug logging
```

20 SQLite Database

20.1 Overview

AstroManager uses an SQLite database in **WAL mode** (Write-Ahead Logging) for concurrent read access. The database file (`astromanager.db`) is stored in the project directory and syncs across PCs via NAS.

Single-PC Access

SQLite WAL mode does not support simultaneous access from multiple computers over a network filesystem. Only run AstroManager on one PC at a time.

20.2 Schema Versions

The database uses an automatic migration system. Each schema version adds new tables:

Version	Tables Added
v1	`targets`, `observations`, `weather_cache`, `header_cache`, `analysis_results`
v2	`pixinsight_sessions`, `pixinsight_subframes`, `pixinsight_integrations`, `pixinsight_frame_weights`, `pixinsight_calibrations`
v3	`mount_sessions`, `mount_tracking_data`, `mount_time_data`, `mount_fft_data`, `mount_environment_data`
v4	`tags`, `target_tags`, `observation_tags`, `frame_quality` + `workflow_stage` column on `targets`
v5	`nina_exposures`, `nina_weather`, `imaging_efficiency`, `session_notes`, `equipment_performance`

20.3 Thread Safety

Database access is thread-safe through:

- Thread-local connections via `get_connection()` context manager
- WAL mode with 30-second busy timeout
- Nested transaction depth tracking for commit/rollback
- WAL checkpoint with TRUNCATE at application exit

20.4 Maintenance

- **Vacuum**: Run `python astromanager.py -vacuum-db` to reclaim space and optimize the database.
- **Backup**: The database is automatically backed up on application exit.
- **Reset**: Delete `astromanager.db` to recreate from scratch (all history will be lost).

21 DBSCAN Clustering & Tags

New in v1.2.0

These features are new in v1.2.0, inspired by Athenaeum/rustafits's DBSCAN clustering and tags system.

21.1 Target Clustering by RA/Dec

Over time, the same target may appear under different names or with slightly different coordinates. DBSCAN clustering helps identify and merge these duplicates.

21.1.1 How It Works

1. **Coordinate extraction**: All targets with valid RA/Dec coordinates are loaded from the database.
2. **DBSCAN clustering**: The algorithm groups targets using **Haversine angular distance** on the celestial sphere. Two configurable parameters:
   - **Epsilon** (ε): Maximum angular separation to consider targets as neighbors (default: 15 arcminutes)
   - **Min samples**: Minimum number of targets to form a cluster (default: 2)
3. **Merge suggestions**: Clusters are classified as:
   - **Strong match** (< 5 arcmin): Very likely the same object
   - **Moderate match** (< 15 arcmin with name similarity): Probably the same object, manual verification recommended

21.1.2 Safe Merging

Merging operates in **dry-run mode by default**:

1. Preview which targets would be merged and what the canonical name would be
2. Confirm the merge
3. Observations are moved to the canonical target, statistics are recalculated
4. The duplicate target entry is removed

21.1.3 Nearby Target Search

Search for all targets within a given angular radius of a specified position. Useful for:

- Finding objects near a target of interest
- Checking if a "new" target already exists under a different name
- Planning mosaic sessions by finding nearby objects

21.2 Tags System

21.2.1 Colored Tags

Create custom colored tags to classify your targets and observations. Examples:

- "Priority" (red), "Narrowband" (teal), "Mosaic" (purple)
- "Needs More Data" (orange), "Processing Done" (green)

Tags are stored in the database with many-to-many relationships: each target or observation can have multiple tags, and each tag can be applied to multiple targets.

21.2.2 Workflow Stages

Three predefined workflow stages help track the processing status of each target:

Stage	Meaning
Stage	New data, not yet started processing
WIP (Work In Progress)	Currently being processed in PixInsight/Siril
Archive	Processing complete, final result archived

Workflow stages are stored as a column on the `targets` table and persist across sessions.

22 Analytics Tab

New in v1.3.0

This tab is new in v1.3.0, inspired by GalactiLog (chvvkumar) — an open-source N.I.N.A. imaging log analyzer.

22.1 Overview

The Analytics tab imports N.I.N.A. imaging session logs (CSV format) and provides deep statistical analysis of your imaging performance over time. It answers questions like: *How efficient are my imaging nights? Which conditions produce the sharpest stars? How does my equipment compare across setups?*

All heavy computation runs in background QThread workers and never blocks the user interface.

22.2 N.I.N.A. CSV Import

Click **Browse** to select a folder containing N.I.N.A. session logs. AstroManager recursively scans for:

- `ImageMetaData.csv` — Per-frame exposure metadata (HFR, FWHM, eccentricity, temperature, filter, target, etc.)
- `WeatherData.csv` — Per-session weather readings (temperature, humidity, wind speed, pressure, cloud cover)

A progress bar shows the import status, and a summary table lists the sessions found with frame counts, date ranges, and target names.

22.3 Imaging Efficiency

A bar chart compares **astronomical dark hours** (the available imaging window each night) against **actual integration time** accumulated. This reveals how much of each clear night you actually spent collecting photons versus setup, focusing, meridian flips, and weather interruptions.

Observatory Coordinates Required

Imaging efficiency requires your observatory latitude, longitude, and elevation to compute astronomical twilight boundaries. Configure these in **Tools** → **Settings** → **Observatory**.

22.4 Correlations

An interactive scatter plot lets you explore relationships between environmental conditions and image quality:

Axis	Available Metrics
X (conditions)	Temperature, humidity, wind speed, dew point, pressure, cloud cover, altitude, moon illumination
Y (quality)	HFR, FWHM, eccentricity, star count, SNR, background level

For each pair of metrics, the chart displays:

- Individual data points (color-coded by filter or date)
- Linear regression line
- **Pearson** r (linear correlation strength)
- **Spearman** ρ (rank correlation — robust to outliers)
- R^2 (coefficient of determination — how much variance is explained)
- **95% confidence band** around the regression line

Interpreting Correlations

A strong negative correlation between temperature and HFR (e.g., $r = -0.6$) would suggest that colder nights produce tighter stars at your site — useful for planning observing sessions. Always verify with Spearman ρ as well, since Pearson r can be misleading with outliers.

22.5 Time Series

Select any imaging metric (HFR, FWHM, eccentricity, star count, etc.) to plot its nightly median over time. The chart overlays:

- Individual nightly medians as data points
- **7-day moving average** (short-term trend)
- **30-day moving average** (seasonal trend)

This helps identify long-term trends such as gradual collimation drift, seasonal seeing variations, or the impact of equipment upgrades.

22.6 Equipment Performance

A statistics table breaks down imaging quality by **telescope + camera + filter** combination:

Metric	Description
Median HFR	Typical star half-flux radius for this setup
Median FWHM	Typical star full-width at half maximum
Median Eccentricity	Typical star elongation
Frame Count	Total frames captured with this combination
Integration Time	Total accumulated exposure time

This makes it easy to compare performance across different optical trains — for example, comparing your refractor with your reflector, or evaluating whether a new camera produces tighter stars.

22.7 Session Notes

The Session Notes panel lets you annotate individual imaging nights with free-text notes:

- Select a date from the session list
- Type your observations (e.g., "Excellent seeing, no wind, collimation perfect after star test")
- Optionally associate the note with a specific target
- Notes are saved in the SQLite database and persist across sessions

23 Image Viewer Tab

New in v1.3.0

This tab is new in v1.3.0, inspired by Astronalyze (ricksastro) — an open-source FITS quality analysis tool with FWHM mapping and corner inspection.

23.1 Overview

The Image Viewer tab provides a full-featured FITS and XISF image browser with integrated quality analysis tools. It goes beyond simple display to offer PixInsight-style autostretch, FWHM heatmaps, corner quality inspection, and star overlay — all without leaving AstroManager.

Images are cached (LRU, 5 images) with prefetching of ±2 neighbors for instant navigation. All analysis runs in background QThread workers.

23.2 File Browser

Click **Browse** to scan a folder for FITS and XISF files. The file list supports:

- Sorting by name, FWHM, or star count
- Navigation with arrow keys (**Up**/**Down**) and mouse wheel
- Double-click to load an image

23.3 Display Engine

AstroManager uses two rendering backends:

Backend	Description
pyqtgraph (preferred)	GPU-accelerated display via OpenGL. Smooth zoom and pan at full resolution. Requires `pyqtgraph >= 0.13`.
matplotlib (fallback)	Software rendering via the Agg backend. Works everywhere but slower for large images.

Both backends support zoom, pan, and pixel value readout under the cursor.

23.4 STF Autostretch

The STF (Screen Transfer Function) autostretch applies a PixInsight-style nonlinear stretch for display purposes only (the underlying data is never modified). The algorithm:

1. Computes shadow and highlight clipping points using percentile analysis
2. Estimates the noise floor via MAD (Median Absolute Deviation) shadow clipping
3. Applies a MTF (Midtone Transfer Function) curve to map the linear data to a visually pleasing display range

STF vs. Permanent Stretch

STF autostretch is a *display-only* operation, exactly like PixInsight's STF. It does not modify your data. Use it to quickly evaluate frame quality without running a full stretch workflow.

23.5 FWHM Heatmap

The FWHM heatmap reveals optical quality variations across the entire field of view:

1. Stars are detected using **DAOStarFinder** (from photutils, if available) or a scipy-based peak finder as fallback.
2. Each star is fitted with a **2D elliptical Moffat** function to measure its FWHM.
3. The per-star FWHM values are interpolated across a **300×300 grid** using **Nadaraya–Watson kernel regression** (a non-parametric smoother).
4. The result is overlaid as a semi-transparent green-to-red color map with contour lines.

- **Green** regions have tight stars (low FWHM) — excellent optical quality
- **Red** regions have bloated stars (high FWHM) — possible tilt, coma, or field curvature

This is invaluable for diagnosing backfocus issues, tilt in your imaging train, or field curvature from fast optics.

23.6 Corner Inspector

The corner inspector divides the image into a **3×3 grid** and displays 100% crops from each cell:

TL	Top	TR
Left	Center	Right
BL	Bottom	BR

Each cell shows:

- A 100% pixel crop of that region
- Per-cell FWHM statistics (median, mean, star count)
- A color-coded quality grade (green = sharp, yellow = acceptable, red = poor)

Diagnosing Tilt

If the corners on one side are consistently worse than the opposite side (e.g., TL and BL are red while TR and BR are green), you likely have sensor tilt. The corner inspector makes this immediately obvious.

23.7 Star Overlay

Toggle the star overlay to draw circles on each detected star, colored by FWHM quality:

- **Green circles**: Stars with FWHM below the field median
- **Yellow circles**: Stars near the median
- **Red circles**: Stars with FWHM above the median (worst quality)

23.8 Header Viewer

Press **Ctrl+H** to open a modal dialog displaying all FITS or XISF header keywords for the current image. Keywords are listed in their original order with name, value, and comment columns.

23.9 Image Info Panel

A sidebar panel displays key metadata extracted from the image header:

- Object name (OBJECT)
- Image dimensions (NAXIS1 × NAXIS2)
- Filter name
- Exposure time
- Camera and telescope
- Observation date

23.10 FWHM Statistics Panel

A dedicated statistics panel shows aggregate star quality for the current image:

Statistic	Description
Star Count	Number of stars successfully detected and fitted
Median FWHM	Middle value — robust to outlier stars
Mean FWHM	Average value — sensitive to outliers
Std Dev	Standard deviation — measures FWHM uniformity across the field
Min / Max	Tightest and most bloated stars in the frame

24 Cross-Section Tab

New in v1.3.0

This tab is new in v1.3.0, inspired by AstroCrossSections (brentmantooth) — an open-source tool for comparing FITS image cross-sections and analyzing filter attenuation.

24.1 Overview

The Cross-Section tab loads two FITS or XISF images side by side and provides tools for direct visual and statistical comparison. Typical use cases include:

- Comparing the same target through different filters (e.g., L vs. Ha)
- Evaluating the effect of a light pollution filter on star intensity
- Comparing images before and after processing (e.g., deconvolution, noise reduction)
- Measuring filter attenuation to compute optimal exposure ratios

24.2 Dual Image Viewer

Load two images using the **Image 1** and **Image 2** browse buttons. Both images are displayed side by side with synchronized zoom and pan. STF autostretch is applied independently to each image for optimal display.

24.3 Line Profile Tool

Draw a line across Image 1 by clicking and dragging. The same line is automatically mirrored onto Image 2. AstroManager extracts the pixel intensity along both lines and plots them as overlaid profiles:

- Image 1 profile in the primary color
- Image 2 profile in a contrasting color
- Both profiles share the same X-axis (position along the line) and Y-axis (intensity)

This reveals differences in star sharpness, background level, and signal strength along any cross-section of the image.

24.4 Color Modes

Choose which channel(s) to analyze in the line profile and histogram:

Mode	Description
Luminance (BT.709)	Perceptual luminance: $0.2126R + 0.7152G + 0.0722B$
Red	Red channel only
Green	Green channel only
Blue	Blue channel only
RGB	All three channels overlaid

For monochrome images (single-channel FITS), only the Luminance mode is available.

24.5 Histogram Comparison

A dual histogram displays 256-bin log-scale intensity distributions for both images side by side:

- Vertical median markers for each image
- Log scale on the Y-axis to reveal faint signal detail
- Overlay mode for direct visual comparison

24.6 Filter Attenuation Analysis

The filter attenuation analysis is the core scientific feature of this tab. It quantifies how much signal is lost (or gained) between two images taken through different filters or under different conditions.

24.6.1 Region Selection

Interactively select two rectangular regions on the image:

- **Signal region**: An area containing the target signal (nebulosity, galaxy arms, etc.)
- **Background region**: An empty sky area for noise floor estimation

24.6.2 Statistical Analysis

AstroManager computes the following for the selected regions:

Metric	Description
Welch t-test	Tests whether the signal difference between the two images is *statistically significant* (not due to random noise). Reports the t-statistic and p-value.
Attenuation %	Percentage of signal lost in Image 2 relative to Image 1
Attenuation magnitude	Signal difference expressed in astronomical magnitudes
Cohen's d	Effect size — how large the difference is relative to the noise ($d > 0.8$ = large effect)
SNR (photon model)	Signal-to-noise ratio estimated from photon statistics ($\sqrt{N}$)
SNR (flux ratio)	Signal-to-noise ratio from the flux ratio between signal and background regions
Exposure factor	How much longer you need to expose with the attenuating filter to achieve the same SNR

Practical Example: Light Pollution Filter

Load a Luminance image (Image 1) and an IDAS LPS image (Image 2) of the same target. Select a bright nebula region as signal and a nearby empty sky region as background. The attenuation analysis will tell you exactly how much signal the LPS filter blocks (e.g., 22% attenuation) and how much extra exposure time you need to compensate (e.g., 1.65× longer exposures).

24.7 Auto-Alignment

If the two images are not perfectly registered (different framing, rotation, or scale), enable **Auto-Align** to automatically register Image 2 to Image 1:

- Uses **astroalign** for star-based triangulation registration
- Reports diagnostic information: translation shift (pixels), rotation angle (degrees), and number of matched stars
- Falls back to **phase correlation** (scikit-image) if astroalign fails to find sufficient star matches

Optional Dependencies

Auto-alignment requires `astroalign` (star-based) and optionally `scikit-image` (phase correlation fallback). Install with: `pip install astroalign scikit-image`

24.8 CSV Export

Export the line profiles and histogram data as CSV files for further analysis in spreadsheet software or Python scripts:

- **Profile CSV**: Position, Image 1 intensity, Image 2 intensity
- **Histogram CSV**: Bin center, Image 1 count, Image 2 count

25 NAS Portability

25.1 Architecture

AstroManager is designed to run from a project folder stored on a NAS (Synology, QNAP, etc.) or any cloud-synced directory (OneDrive, Dropbox, Google Drive). The key principle is:

- **Project data** (database, config, analysis results) stays in the project folder and syncs across PCs.
- **Python virtual environment** is stored locally on each PC (never in the project folder).

25.2 Local Virtual Environment

The launcher scripts store the venv outside the project directory:

OS	Venv Location
Windows	`%LOCALAPPDATA%\AstroManager\venv`
Linux	`$XDG_DATA_HOME/AstroManager/venv`
macOS	`~/.local/share/AstroManager/venv`

This prevents NAS synchronization from constantly overwriting platform-specific Python binaries. Each PC gets its own native venv, while shared data syncs normally.

25.3 Launcher Scripts

`launch.bat` (Windows):

- Detects Python via `py -3` → `python` → `python3`
- Creates venv in `%LOCALAPPDATA%\AstroManager\venv`
- Uses a `.deps_installed` marker (copy of requirements.txt) to detect when dependencies need reinstalling
- Launches via `pythonw.exe` with `start ""` (no console window)
- Validates the venv works (`python -c "import sys"`) to detect broken venvs from uninstalled Python versions

`launch.sh` (Linux/macOS):

- Detects Python via `python3` → `python`
- Creates venv in `$XDG_DATA_HOME/AstroManager/venv`
- Same marker and validation logic as the Windows version

25.4 Desktop Shortcuts

Use **Help** → **Create Desktop Shortcut** to create a desktop shortcut that targets the launcher script (not the Python executable directly). This ensures the shortcut works regardless of which drive letter the NAS is mapped to.

On Windows, the application icon is copied locally to `%APPDATA%\AstroManager\logo.ico` because Windows `.lnk` shortcuts cannot display icons from network paths.

Tip

If you move the project folder to a different location or drive, simply re-run **Help** → **Create Desktop Shortcut** to update the shortcut path.

26 Troubleshooting & FAQ

26.1 No FITS Files Found

- Verify the folder path and check that files have recognized extensions: `.fits`, `.fit`, `.fts`, `.fz`, `.xisf`
- Check file read permissions
- Ensure the folder is not excluded (folders prefixed with `extracted_`, `duplicates_`, etc. are skipped)

26.2 Database Locked

- Close all other AstroManager instances
- SQLite WAL mode does not support concurrent network access — ensure only one PC is running AstroManager at a time
- As a last resort, delete `astromanager.db` (it will be recreated, but all history will be lost)

26.3 Slow Performance

- **Check storage type**: HDD is significantly slower than SSD for scanning large folder trees
- **Reduce workers**: If RAM is limited, lower the worker count in Settings
- **Disable optional features**: Turn off SIMBAD and weather for faster analysis
- **Clear old cache**: Use **Tools** → **Clear Old Cache** to remove stale cache entries
- **Vacuum database**: Run `python astromanager.py -vacuum-db` to optimize the database

26.4 LaTeX Report Compilation Fails

- AstroManager always generates an HTML report as a fallback
- A ReportLab PDF is also generated automatically when LaTeX is unavailable
- Ensure `pdflatex` is in your system PATH if you want LaTeX PDF reports

26.5 Missing Dependencies

- AstroManager auto-installs missing packages on first launch
- For manual installation: `pip install -r requirements.txt`
- If using a system Python with restricted permissions, try: `pip install -user -r requirements.txt`

26.6 XISF Header Editing Errors

- XISF files use XML metadata. AstroManager uses `defusedxml` for secure parsing
- If you encounter namespace corruption, update to v1.1.8+ which fixed this issue
- Always back up files before bulk header editing

26.7 ASIAIR Files Fail to Read

- ASIAIR cameras produce FITS with BZERO/BSCALE keywords
- This was fixed in v1.1.5 — ensure you are running v1.1.5 or newer
- If the issue persists, try importing through the ASIAIR Import tab which applies additional header fixes

26.8 Plate Solving Fails

- Ensure ASTAP is installed and its path is in your system PATH, or configure the path in Settings
- Check that the ASTAP star database is downloaded (G17 or H17 catalog)
- For very wide-field images, you may need to adjust the search radius
- Large images are automatically binned for faster solving

26.9 Update Checker Not Working

- The check needs internet access to reach the GitHub releases API and fails silently offline
- It runs at start-up in the installed version (can be turned off in **Tools > Settings**) and on demand: **Help > Check for Updates**
- Run from the sources, it only opens the download page

26.10 Broken Virtual Environment

If you see "did not find executable" errors:

- This typically happens when a Windows Store Python installation is removed
- The launcher scripts (`launch.bat`/`launch.sh`) automatically detect and recreate broken venvs
- Alternatively, delete the venv folder manually and re-launch

26.11 Crash Reports

- Python crashes, native (Qt) crashes and interface freezes (watchdog) produce a short technical report, sent automatically if you agreed at first launch
- Otherwise, **Help > Report a problem...** lets you write a report (offline, it is saved as a `.zip` on the desktop)
- Reports live outside the installation folder; none of your files is ever sent

27 Acknowledgments

AstroManager v1.3.0 would not be possible without the following projects and communities:

27.1 Inspiration

- **Athenaeum / rustafits** (Vilen Sharifov) — Major inspiration for v1.2.0 features: frame quality analysis with PSF pipeline, WBPP export with calibration tree visualization, interactive sky chart, shoot calendar, calibration scoring system, DBSCAN target clustering, and tags with workflow stages.
- **Astronalyze** (ricksastro) — Inspiration for v1.3.0 Image Viewer: FWHM heatmap with kernel regression, 3×3 corner inspector with quality grading, and PixInsight-style STF autostretch.
- **GalactiLog** (chvvkumar) — Inspiration for v1.3.0 Analytics: N.I.N.A. CSV import, imaging efficiency analysis, metric correlations, and target resolver.
- **AstroCrossSections** (brentmantooth) — Inspiration for v1.3.0 Cross-Section: dual image comparison, line profiles, filter attenuation analysis with statistical testing, and auto-alignment.

27.2 Core Libraries

- **Astropy** — FITS handling, RICE compression, coordinate transforms, and time utilities
- **PyQt6** — Cross-platform GUI framework
- **NumPy** / **SciPy** — Scientific computing, PSF fitting, DBSCAN clustering
- **Matplotlib** — Charts, sky projections, and visualizations
- **Pandas** — Data manipulation and analysis
- **Pillow** — Image processing
- **ReportLab** — PDF report generation

27.3 Astronomical Services

- **SIMBAD** (CDS, Strasbourg) — Astronomical database for target identification and object classification
- **Open-Meteo** — Free weather API for historical and forecast data (no API key required)
- **ASTAP** (Han Kleijn) — Fast local plate solving engine
- **Astrometry.net** — Plate solving engine
- **PixInsight** — XISF format specification, WBPP/FBP processing scripts

27.4 Community

- **CloudyNights** community — Testing, feedback, and feature suggestions
- All astrophotographers who have submitted bug reports and feature requests

---

AstroManager v1.3.0

Comprehensive Astrophotography File Management Suite

MIT License — `https://github.com/ARP273-ROSE/astromanager`

Clear skies!