

CRITERIA-1D

Technical manual

(Draft 2021.01)

Fausto Tomei ftomei@arpae.it
Gabriele Antolini gantolini@arpae.it
Giulia Villani gvillani@arpae.it

1 DATA

1.1 Weather data

1.2 Soil data

1.2.1 Table soils

1.2.2 Table horizons

1.3 Crop data

1.3.1 Table crop_class

1.3.2 Table crop

1.3.3 Crop parameters description

2 ALGORITHMS

2.1 Water

2.1.1 Water retention curve

2.1.2 Maximum infiltration

2.1.3 Infiltration and redistribution

2.1.4 Surface and subsurface runoff

2.1.5 Capillary rise

2.2 Crop

2.2.1 Potential evapotranspiration

2.2.2 Crop development and transpiration

2.2.3 Irrigation

CRITERIA references

Other references

1 DATA

CRITERIA-1D input and output data are stored in SQLite databases (.db files) that can be easily managed by open source software, such as **sqlitebrowser**. You can download it at: <https://github.com/sqlitebrowser/sqlitebrowser>

1.1 Weather data

Weather dataset should be organised in a SQLite database where a **meteo_locations** table identifies and describes the cells of the meteo analysis grid.

In the **meteo_locations** table, the following fields are listed:

- id_meteo: identifier of the grid cell;
- table_name: name of the table, by default it is composed by "GRD_" followed by the identifier of the grid cell;
- meteo_name: toponym of the grid cell;
- longitude: longitude of the center of the cell for the WGS82 system coordinates, unit of measure: decimal degree;
- latitude: latitude of the center of the cell for the WGS82 system coordinates, unit of measure: decimal degree;
- height (optional): height of the center of the cell, unit of measure: meters;


Table: meteo_locations						
	id_meteo	table_name	meteo_name	longitude	latitude	height
	Filter	Filter	Filter	Filter	Filter	Filter
1	01878	GRD_01878	VALSAVIGNONE	12.033825	43.7325	816.26
2	01918	GRD_01918	MONTE DELLA ZUCCA	12.096875	43.7325	915.44
3	01958	GRD_01958	SAN PATRIGNANO	12.159925	43.7325	781.15
4	01998	GRD_01998	POGGIO DELLE CAMPANE	12.222975	43.7325	575.14
5	01797	GRD_01797	BADIA PRATAGLIA	11.907725	43.7775	979.62
6	01837	GRD_01837	VERGHERETO	11.970775	43.7775	844.81
7	01877	GRD_01877	MONTECORONARO	12.033825	43.7775	922.14
8	01917	GRD_01917	MONTE FUMAILO	12.096875	43.7775	1052.27
9	01957	GRD_01957	CASTELDELCI	12.159925	43.7775	758.5
10	01997	GRD_01997	MIRATOIO	12.222975	43.7775	621.36

example of meteo_locations table

The other tables of the database store the weather data, one table for each cell of the analysis grid. The name of each table corresponds to the table_name field of the **meteo_locations** table.

The weather data for each cell are organized according to the following format:

- date: ISO8601 format (YYYY-MM-DD);
- tmin: daily minimum air temperature, unit of measure: °C;
- tmax: daily maximum air temperature, unit of measure: °C;
- tavg: daily average air temperature, unit of measure: °C;
- prec: daily total precipitation, unit of measure: mm;
- etp (optional): potential evapotranspiration, unit of measure: mm;
- watertable (optional): water table depth, unit of measure: m.

Table:  GRD_01785							
	date	tmin	tmax	tavg	prec	etp	watertable
	Filter	Filter	Filter	Filter	Filter	Filter	Filter
1	2018-07-19	22.5	35.4	28.7	0.0		
2	2018-07-20	22.9	35.4	28.8	0.0		
3	2018-07-21	22.9	36.0	29.1	0.0		
4	2018-07-22	19.6	28.7	23.8	3.3		
5	2018-07-23	19.8	26.0	22.9	2.7		
6	2018-07-24	21.8	31.8	26.7	0.1		

Example of weather data table

If potential evapotranspiration is not available, the SWB will compute the variable by means of the Hargreaves-Samani equation using temperatures and latitude of the meteo cell. If water table depth is missing the SWB model simulates free drainage at the soil bottom.

You can download an example of weather database (meteo.db) at:

<https://github.com/ARPA-SIMC/CRITERIA1D/tree/master/DATA/PROJECT/test/data>

1.2 Soil data

Soil database should be organized in two tables: *soils* and *horizons*.

Name	Type	Schema
Tables (2)		
horizons		<pre> CREATE TABLE "horizons" (`soil_code` TEXT, `horizon_nr` INTEGER, `upper_depth` INTEGER, `lower_depth` INTEGER, `coarse_fragment` REAL, `organic_matter` REAL, `sand` REAL, `silt` REAL, `clay` REAL, `bulk_density` REAL, `theta_sat` REAL, `ksat` REAL) </pre>
soils		<pre> CREATE TABLE "soils" (`id_soil` INTEGER, `soil_code` TEXT, PRIMARY KEY(id_soil)) </pre>

soil.db structure

You can download the **template_soil.db** from:

<https://github.com/ARPA-SIMC/CRITERIA1D/tree/master/DATA/TEMPLATE>

1.2.1 Table soils

The table **soils** is an identifier table where each soil has to be defined by an alphanumeric code (*soil_code*) linked to an integer field *id_soil*. Typically this numeric field refers to a soil map shapefile for a geographical project.

Table: soils		
	id_soil	soil_code
	Filter	Filter
1	1	AGO1
2	2	AGOz
3	3	ARC1
4	4	ARC2
5	5	BAD

example of soils table

1.2.2 Table horizons

Each soil is typically composed by several pedological horizons, described in the **horizons** table, where each record describes the horizon in terms of pedological features as texture,

structure, and organic matter content, that determines the shape of the soil water retention curve in the Soil Water Balance model.

In more details, each record of the **horizons** table contains:

- **soil_code**: univocal alphanumeric code to identify the soil *
- **horizon_nr**: number of horizon *
- **upper_depth**: upper depth of the horizon, [cm] *
- **lower_depth**: lower depth of the horizon, [cm] *
- **coarse_fragment**: percentage of soil particles > 2 mm
- **organic_matter**: percentage of organic matter
- **sand**: fraction of sand, [-] *
- **silt**: fraction of silt, [-] *
- **clay**: fraction of clay, [-] *
- **bulk_density**: bulk density, [g cm⁻³]
- **theta_sat**: water content at saturation, [m³ m⁻³]
- **ksat**: water conductivity at saturation, [cm day⁻¹]

* The data marked with a star are mandatory.

soil_code	horizon_nr	upper_depth	lower_depth	coarse_fragment	organic_matter	sand	silt	clay	bulk_density	theta_sat	ksat
Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter
AGO1	1	0	60	0.0	32.4	0.66	0.25	0.09	0.6		
AGO1	2	60	80	0.0	8.6	0.23	0.49	0.28	0.8		
AGO1	3	80	110	0.0	2.0	0.44	0.46	0.1	1.42		
AGO1	4	110	150	0.0	0.8	0.83	0.13	0.04	1.76		
AGOz	1	0	50	0.0	11.96	0.426	0.334	0.24	0.7		
AGOz	2	50	65	0.0	6.08	0.252	0.35	0.398	0.9		
AGOz	3	65	74	0.0	24.35	0.722	0.198	0.08	0.7		
AGOz	4	74	85	0.0	10.42	0.668	0.262	0.07	0.8		
AGOz	5	85	150	0.0	2.46	0.778	0.149	0.073	1.76		
ARC1	1	0	50	10.0	1.2	0.189	0.414	0.397	1.35		
ARC1	2	50	75	0.0	0.1	0.189	0.417	0.394	1.4		
ARC1	3	75	150	0.0	0.1	0.116	0.48	0.404	1.45		
ARC2	1	0	50	10.0	1.2	0.189	0.414	0.397	1.35		
ARC2	2	50	75	0.0	0.1	0.189	0.417	0.394	1.4		
ARC2	3	75	150	0.0	0.1	0.116	0.48	0.404	1.45		
BAD	1	0	35	10.0	1.2	0.48	0.3	0.22	1.35		
BAD	2	35	125	80.0	0.5	0.67	0.22	0.11			

*example of **horizons** table*

TODO: table UNITS, van_genuchten and water_retention


TODO: Soil_editor

1.3 Crop data

The *Crop* database is a SQLite file organized in two tables that have to be checked and calibrated: *crop_class* and *crop*.

1.3.1 Table *crop_class*

The table *crop_class* is a table where each crop is defined by a model identifier (*id_crop*) linked to the corresponding crop class identifier (*id_class*), used in the Early Crop Map

Tabella:  *crop_class*

	id_class	type	id_crop	irri_ratio
	Filtro	Filtro	Filtro	Filtro
1	HPad	perennial herbaceous alfalfa	ALFALFA	0.0
2	HPma	perennial herbaceous generic	ALFALFA	0.0
3	HHmz	summer herbaceous maize	CORN	1.0
4	HHhh	summer herbaceous generic	CORN	0.6
5	WPkk	woody perennial kaki	GRAPEVINE	1.0
6	WPol	woody perennial olive	GRAPEVINE	0.0
7	WPvi	woody perennial grapevine	GRAPEVINE	1.0
8	HPme	perennial herbaceous meadow	GRASS	0.0
9	IRRIWHEAT	irrigated wheat	IRRIWHEAT	1.0
10	WPkw	woody perennial kiwifruit	KIWIFRUIT	1.0
11	WPps	woody perennial peach	PEACH	1.0

example of *crop_class* table

The field *type* is a description of the crop class and the field *irri_ratio* [-] defines the irrigated percentage of the class. For instance, if in a study area, the alfalfa is not irrigated (as in Romagna area), the *irri_ratio* has to be set to 0, whereas if it is partially irrigated (as in Emilia) *irri_ratio* has to be set to a value greater than zero.

If in a pilot area the class of 'summer herbaceous generic' includes both irrigated and not irrigated crops, *irri_ratio* has to be set to the ratio between the two categories. For example *irri_ratio* = 0.6 means that the irrigated area is 60% of the total area covered by 'summer herbaceous generic'.

Warning: in some cases the *id_crop* is not defined. This means that this crop is not set at all in the model (e.g. the cotton). There are two solutions about this:

1) the user can choose a crop that can be considered similar for development and water needs; for example: pear is used to simulate the apple tree that is missing in the model;

2) a new crop can be added in the crop table, following the instructions explained in the following paragraphs.

1.3.2 Table crop

Each crop is typically characterized by several parameters, described in the **crop** table, where each record describes the crop in terms of phenological characteristics, water needs and irrigation parameters.

In the table below, key parameters for crop development and irrigation are listed.

Parameter name	Description	Unit
Crop development		
plant_cycle_max_duration	Crop cycle max duration	days
thermal_threshold	Thermal threshold	°C
degree_days_lai_increase	Degree days sum for LAI increase	°C
degree_days_lai_decrease	Degree days sum for LAI decrease	°C
lai_min	Minimum value of LAI	m ² m ⁻²
lai_max	Maximum value of LAI	m ² m ⁻²
lai_curve_factor_a	Factor <i>a</i> of exponential curve of LAI increase	[-]
lai_curve_factor_b	Factor <i>b</i> of exponential curve of LAI increase	[-]
kc_max	Value of crop coefficient (Kc) corresponding to the maximum LAI	[-]
Roots		
root_depth_zero	Start of rooting system depth	m
root_depth_max	Max root depth	m
degree_days_root_increase	Degree days sum for the maximum development of the rooting system	°C
root_shape	Root shape (gamma function, cardioid, cylinder, ellipsoid)	[-]
psi_leaf	Leaf resistance	hPa

Water demand and irrigation		
degree_days_start_irrigation	Degree days sum for the start of the irrigation period	°C
degree_days_end_irrigation	Degree days sum for the end of the irrigation period	°C
irrigation_shift	Minimum number of days from the last irrigation	days
irrigation_volume	Crop irrigation volume	mm/day
stress_tolerance	Tolerated threshold on the ratio T_r/T_{max} (real transpiration vs maximum transpiration) 1 = no stress is tolerated	[-]
raw_fraction	Fraction of Readily Available Water	[-]

crop table

1.3.3 Crop parameters description

To define the crop cycle, key parameters to set are *sowing_doy* (the day of the year in which usually the crop is seeded) and *plant_cycle_max_duration* (the maximum length of the crop cycle in days). The computation of the phenological stages is carried out on the basis of the thermal threshold, that the user has to define in *thermal_threshold* field.

From this data, the degree days needed by the crop for the emergence (*degree_days_emergence*), for the maximum leaf area index development (*degree_days_lai_increase*) and for the leaf area index senescence (*degree_days_lai_decrease*) have to be set.

Moreover the *upper_thermal_threshold* field defines the threshold above which the crop stops to grow.

The leaf area index development is calculated on the basis of these parameters: the minimum leaf area index at the beginning of the crop cycle (*lai_min*), the maximum lai reached during the season (*lai_max*) and, especially for fruit trees, if the orchards have a grass cover, the user has to define the leaf area index of the grass (*lai_grass*).

The maximum crop coefficient (*kc_max*) has to be defined in order to compute actual evapotranspiration.

In order to describe the rooting system of the crop, the user has to set how much is the depth of the beginning of roots with respect to the ground (*root_depth_zero*, in other words the height of the root collar) the maximum reachable depth of the roots (*root_depth_max*),

and the degree days sum for the full development of the rooting system (*degree_days_root_increase*).

For the computation of the root density It is important the definition of the shape of the roots (*root_shape*), selecting the following codes:

1 → cylinder

4 → cardioids

In addition, the coefficient of deformation (*root_shape_deformation*), expressed as percentage ranging from 1 to 2, can be used to adapt the selected shape to the actual shape of the crop.

In order to assess the crop water demand, the irrigation process is controlled by the parameters listed in the table such as *irrigation_shift* (the number of days between two irrigations) and *irrigation_volume* (the maximum volume of water distributed for each irrigation during the crop cycle in mm).

These parameters allows the user to define the irrigation methods (i.e. micro irrigation, sprinkler irrigation) depending on time shifts and maximum volumes for each irrigation.


The irrigation season length is controlled by *degree_days_start_irrigation* and *degree_days_end_irrigation* parameters: the actual irrigation period starts and stops according to a degree days sum, taking into account the weather conditions of every specific year, anticipating it in warm years and delaying it in cold ones.

The water stress sensitivity specific for the crop is expressed by the *raw_fraction*, i.e. the fraction of readily available water between the wilting point and the field capacity.

Another parameter useful to calibrate the irrigation needs for the crop is *stress_tolerance*: it expresses the tolerance of the crop to water stress as the ratio between actual transpiration and maximum transpiration, where 1 means that no water stress is tolerated by the crop.

2 ALGORITHMS

The Soil Water Balance (SWB) is the result of interactions of hydrological processes occurring between soil, crop and atmosphere.



SWB conceptual scheme

The amount of water from rain or irrigation that infiltrates into the ground depends on surface conditions, on the hydrological characteristics of the first layer of soil and its water content. The water that cannot be absorbed from the soil is collected in puddles formed by surface roughness. Once puddles are filled, surface runoff occurs.

The processes of storage and infiltration are governed by soil water potential differences. Each soil horizon is characterized by its water retention curve. Depending on the water content, the layer can absorb water or transfer it to the layer below. In the presence of a water table, there may also be a supply of water to deeper layers because of capillary rise.

The presence of a crop produces water loss in the root zone through transpiration, and simultaneously reduces evaporation loss in the surface layers. Depending on the type of soil,

its water content and the phenological stage of the crop, the water in the soil is more or less available to plants, thus affecting its transpiration rate.

So that, once the crop parameters are properly set, it is possible by means of the SWB to forecast the crop water needs not fulfilled by the soil water content that have to be provided by irrigations.

CRITERIA-1D model follows the approach of Driessen (1986), Driessen, and Konijn (1992) but it assumes a multilayered soil and explicitly computes approximate values of daily actual evaporation and transpiration, water flows between layers, deep drainage, surface and subsurface runoff and capillary rise. The software is written in C++ language with QT libraries, thus it can be compiled on several platforms.

2.1 Water

In the soil water balance model the following concepts play a key role:

- Field Capacity (FC): the presumed water content at which internal drainage ceases.
- Wilting Point (WP): the minimal water content the plant requires not wilting.
- Soil texture classification: soil is classified by the fractions of specific ranges of particle sizes (typically sand, silt, and clay). Classifications are named for the primary constituent particle size or a combination of the most abundant particles sizes, e.g. "sandy clay"; a fourth term, "loam" is used to describe a roughly equal concentration of sand, silt, and clay
- Infiltration: is the process of transferring water from the soil surface into the soil, where it becomes *soil water content* and originates redistribution processes such as *subsurface flow* in the unsaturated zone and *groundwater flow* in the saturated zone.
- Conceptual models: approximation of the physical processes through simplified schemes adapted to describe reality by means of semi-empirical models.

While conceptual models are not able to describe the processes with the same precision of physically-based models, they present some advantages with respect to the latter, in particular the greater computational speed, which facilitates their use in computer models designed for simulations at the regional (or territorial) scale. Moreover, a simple modeling approach is mandatory in many cases because of the lack of the necessary parameters needed for a more detailed representation of the phenomena.

2.1.1 Water retention curve

The soil water retention in the model is described by the van Genuchten equation (van Genuchten, 1980), modified by Ippish et al. (2006). The original van Genuchten equation is:

$$\theta(h) = \theta_r + (\theta_s - \theta_r) \left(\frac{1}{[1 + (\alpha h)^n]^m} \right)$$

where $\theta(h)$ is the volumetric water content at the water potential h , θ_s and θ_r are the saturated and residual water contents, α is the coordinate of the inflexion point of the retention curve, m and n are dimensionless factors related to the pore-size distribution.

We used the typical restriction $m = 1 - 1/n$

The hydraulic conductivity was calculated by the equation of Mualem (1976):

$$K(h) = \frac{K_s (1 - (\alpha h)^{mn} [1 + (\alpha h)^n]^{-m})^2}{[1 + (\alpha h)^n]^{ml}}$$

where K_s is the saturated hydraulic conductivity, and l is an empirical parameter that accounts for pore tortuosity.

Ippisch et al. (2006) pointed out that the van Genuchten-Mualem model, under certain conditions, is problematic when water retention data are used to predict the hydraulic conductivities and they demonstrated that if $n < 2$ or $\alpha h_e > 1$ (where h_e is the air-entry value of the soil, corresponding to the largest pore radius), the van Genuchten-Mualem predicts erroneous hydraulic conductivities. In these cases, an explicit air-entry value h_e has to be included, leading to a modified van Genuchten-Mualem model (Ippisch et al., 2006):

$$S_e = \begin{cases} \frac{1}{S_c} [1 + (\alpha h)^n]^{-m} & \text{if } (h > h_e) \\ 1 & \text{if } (h \leq h_e) \end{cases}$$

where S_e is the degree of saturation and $S_c = [1 + (\alpha h_e)^n]^{-m}$ is the water saturation at the air-entry potential h_e .

The resulting hydraulic conductivity using the Mualem model is:

$$K = \begin{cases} K_s S_e^l \left[\frac{1 - (1 - (S_e S_c)^{1/m})^m}{1 - (1 - S_c^{1/m})^m} \right]^2 & \text{if } (S_e < 1) \\ K_s & \text{if } (S_e \geq 1) \end{cases}$$

where l is the same parameter as in the original Mualem equation.

The following table lists the parameters used in the model for the USDA texture classification.

texture	alpha	n	he	theta_r	theta_s	k_sat	l
Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter
sand	0.39	1.7	0.07	0.01	0.38	192.0	0.5
loamy sand	0.35	1.5	0.1	0.02	0.39	96.0	0.5
sandy loam	0.29	1.4	0.15	0.02	0.4	48.0	0.5
silt loam	0.13	1.2	0.26	0.03	0.44	9.6	0.5
loam	0.17	1.21	0.23	0.03	0.42	12.0	0.5
silt	0.1	1.24	0.27	0.03	0.44	2.4	0.5
sandy clayloam	0.22	1.22	0.2	0.03	0.41	12.0	0.5
silty clayloam	0.13	1.2	0.31	0.03	0.46	2.4	0.5
clayloam	0.18	1.18	0.27	0.04	0.45	4.8	0.5
sandy clay	0.21	1.18	0.25	0.04	0.44	3.6	0.5
silty clay	0.17	1.16	0.33	0.05	0.48	1.2	0.5
clay	0.16	1.16	0.33	0.05	0.48	0.8	0.5

Soil parameters for USDA texture classes

The values of the table were produced by a comparison of data presented in several papers on this subject (Wösten et al., 1998; Simota and Mayr, 1996; Carsel and Parrish, 1988; Schaap, Leji and van Geuchten, 2001).

2.1.2 Maximum infiltration

The amount of water that can flow through the layer depends on its water content and the permeability of the same and is estimated using the following equation (Driessen, 1986):

$$I_{max} = 10 \left[S_0 \left(1 - \theta / \theta_{sat} \right) + A \right]$$

Where:

I_{max}	maximum infiltration	[mm d ⁻¹]
S_0	standard sorptivity	[cm d ⁻¹]
θ	volumetric water content of the layer	[m ³ m ⁻³]
θ_{sat}	volumetric water content at saturation	[m ³ m ⁻³]
A	hydraulic conductivity at the wetting front	[cm d ⁻¹]


The sorptivity represents the infiltration rate determined by the single matrix potential, the standard sorptivity S_0 is defined for a completely dry matrix. Reference values for these parameters, depending on the different soil textural classes, are reported in the following table:

Textural classes	A [cm d-1]	S_0 [cm d-1]	K_0 [cm d-1]
Sand (S)	30.33	21.44	50

Sandy Loam (SL)	17.80	19.20	26.5
Loamy Sand (LS)	9.36	17.57	12
Silt Loam (SiL)	5.32	14.46	6.5
Loam (L)	3.97	11.73	5
Silt (Si)	8.88	13.05	14.5
Sandy Clay Loam (SCL)	16.51	19.05	23.5
Silty Clay Loam (SiCL)	1.18	6.15	1.5
Clay Loam (CL)	0.76	4.70	0.98
Sandy Clay (SC)	2.94	10.74	3.5
Silty Clay (SiC)	0.80	3.98	1.3
Clay (C)	0.15	1.93	0.5

Reference values of infiltration speed of the wetting front (A), of the standard sorptivity (S_0) and the saturated conductivity (K_0) depending on the different textural classes (Driessen, 1986).

The absolute values of I_{max} vary by several orders of magnitude as a function of textural class: in particular, maximum infiltration is greatly reduced in both dry and wet conditions by increasing the clay content. The following figure shows the effect of soil moisture on I_{max} values.



Maximum daily infiltration (I_{max}) after a rain at field capacity and wilting point for the different textures (S =Sand, Si =Silt, C =Clay, L =Loam).

2.1.3 Infiltration and redistribution

The soil profile is divided by the model into a number of thin computational layers (usually 2 cm of thickness), and the computation of water flow by layer starts from the bottom of the profile, depending on soil maximum depth.

A wetting front is determined when a layer has water content greater than its field capacity (FC), and an initial flow is defined considering the amount of water that can be moved and by the difference between the actual water content and the field capacity. The amount of water that actually moves and the length of the downward shift depends on the water content and the texture of the underlying layers.


Each layer is characterized by an infiltration of the maximum daily amount (I_{max}). To estimate the maximum displacement of the waterfront the maximum infiltration of the underlying layer at the waterfront is calculated. If the water content of the layer exceeds the field capacity it passes to the next one. This computation continues until the waterfront encounters a layer in which the amount of incoming water determines a total water content of that layer that is less than FC , then the waterfront is stopped.

Two conditions have to be satisfied:

1. the sum of the flows previously passed through a layer cannot exceed its maximum daily infiltration;
2. In the case the waterfront meets a saturated layer, the front stops at the layer above the saturated layer.

The first condition restricts the passage of water in the case that it meets a layer of clay with low maximum daily infiltration: in this case it forms a suspended water table.

The second condition instead simulates the slowing down of the waterfront when it approaches a saturation condition: the waterfront that is arriving lays on the previous one.



Infiltration into the soil profile of moisture fronts A, B, C and D

In the previous figure, the infiltration of several wetting fronts in different conditions of permeability is shown:

- the front A, crossing through medium permeable layers, moves downwards while remaining separate from the other fronts;
- the front B crosses the same permeable layers and merges with front C, whose infiltration is slowed by the presence of a not very permeable layer;
- the rain partially infiltrates creating a new front D;
- The water in excess of the I_{max} of the surface layer creates a puddle on the ground.

In cases where the free water reaches the last layer, it leaves the system as deep drainage.

2.1.4 Surface and subsurface runoff

The agricultural fields are usually delimited by drains and ditches, therefore surface and sub-surface runoff can be assumed as outflow from the system through these means.

The surface runoff occurs when the soil surface roughness cannot hold puddle water. The process is simulated considering the maximum height of storage surface, which depends on:

- crop species; for instance *Oryza sativa* (rice) has typically a puddle higher to other cereals.
- crop type, i.e. annual and perennial. Annual crops are typically herbaceous crops that need tillages and thus a default value of 5-10 mm of clod height is simulated. For perennial crops (trees) usually tillages are not performed.

Maximum sub-surface runoff is estimated by the following equation, which solves the universal flow equation as a function of distance and radius of drains (Driessen, 1986):

$$D_{max} = 10 \cdot k_0 \cdot \psi / (\psi + L_d / \pi \cdot \ln(L_d / r_d \pi))$$

where:

D_{max} is maximum subsurface runoff (lateral drainage) [mm]

k_0 is saturated hydraulic conductivity (see table in maximum infiltration paragraph) [cm/day]

ψ is hydraulic head midway between drains [m]

L_d is drain spacing [m]; default: 100 m

r_d is drain radius [m]M default: 0.25 m

2.1.5 Capillary rise

Capillary rise is computed by the steady state solution of Darcy's equation.

The vertical water flow between two arbitrary points follows Darcy's law:

$$F = k_h \cdot dH/dL$$

where:

F is the flow rate (cm d⁻¹)

dH is the difference in hydraulic head (cm)

dL is the distance of flow (cm)

k_h is the hydraulic conductivity at matric suction h (cm d⁻¹)

The total hydraulic head H is composed of both gravity forces and matric suction:

$$H = h + g$$

Where h is the matric suction at soil layer n and g the gravity head, equal to the vertical distance (cm) between soil layer and the groundwater level.

The total hydraulic head H is positive if the matric suction h exceeds the vertical distance between point n and the groundwater. A positive hydraulic head allows positive water flow from the groundwater to the point with matric suction h . This water flow is called capillary rise.

Therefore capillary rise at soil layer n can be computed by the steady state solution of Darcy's equation:

$$CR = k_h \cdot (dh/dz - 1)$$

Where:

CR is the capillary rise (cm d⁻¹)

h is the matric suction at soil layer n (cm)

z is the distance between the soil layer and the groundwater level.

2.2 Crop

2.2.1 Potential evapotranspiration

The term evapotranspiration refers to the total water that is moved from the soil to the atmosphere by evaporation from surface and soil and by transpiration from plants.

The value of evapotranspiration increases until a limit value that cannot be exceeded for more availability of water. The limit is called the *maximum evapotranspiration* (ET_m) and is defined as the amount of water evapotranspired per unit time from a uniform crop that has full water availability.

The *reference evapotranspiration* (ET_0) is the amount of water evapotranspired from a reference crop (*Festuca arundinacea* Schreb., multispecies grass) maintained between 8 and 15 cm height, completely covering the ground with plenty of water availability.

The ET_0 estimation methods proposed in literature are many, characterized by different input variables and made for different time scales integration. In CRITERIA-1D, **Hargreaves and Samani equation** (1985) is used to calculate daily potential evapotranspiration.

The Hargreaves method needs only latitude of the computation area and daily maximum and minimum temperature for the estimation; in more details, the equation is:

$$ET_0 = 0.0023 \cdot \frac{Rad_{ext}}{2.456} \cdot (T_{avg} + 17.78) \cdot (T_{max} - T_{min})^{0.5}$$

Where:

ET_0 is reference evapotranspiration [mm d⁻¹];

Rad_{ext} is extraterrestrial radiation [MJ m⁻² d⁻¹];

T_{max} and T_{min} are daily maximum and minimum temperature of the air [°C];

T_{avg} is the daily average temperature, computed as $T_{avg} = (T_{max} + T_{min})/2$

Rad_{ext} is the potential radiation that would reach Earth's surface in the absence of the atmosphere and it can be computed by:

$$Rad_{ext} = 24 \cdot 4.921 \cdot d_r / \pi \cdot (\Omega \sin(lat) \cdot \sin(\delta) + \cos(lat) \cdot \cos(\delta) \cdot \sin(\Omega))$$

where:

4.921 is the hourly solar constant [MJ m⁻² h⁻¹];

lat is the latitude of the computation area [rad];

doy is the day of the year;

d_r is the inverse Earth-Sun relative distance, compute by:

$$d_r = 1 + 0.033 \cdot \cos(2 \cdot \pi \cdot \text{doy} / 365)$$

Ω is the sunset hour angle [rad] computed by:

$$\Omega = \arccos(-\tan(\text{lat}) * \tan(\delta))$$

Finally δ is the solar declination [rad], computed by:

$$\delta = 0.4093 \cdot \sin((2\pi/365) \cdot \text{doy} - 1.39)$$

2.2.2 Crop development and transpiration

Crop development in the SWB model is computed by means of daily minimum and maximum temperature, driving the leaf area index (LAI) curve in three stages: emergence, increase and senescence (LAI decrease). In addition, the root development is driven by temperatures and the root density follows two main root shapes: cylinder and cardioid.

The LAI values drive the partitioning of the evapotranspiration in potential evaporation and transpiration. Potential evaporation is assigned to the surface layer (if it is wet) and to the first soil layers (up to 15 cm), while potential transpiration is assigned to the rooting system, subdivided depending on the root density.

The actual evaporation and transpiration can be lower than the potential, depending on the actual soil water content and to the crop physiological parameters.

All these processes are described by a set of equations that are detailed at the following address:

https://www.arpae.it/it/temi-ambientali/meteo/scopri-di-piu/strumenti-di-modellistica/criteria/criteria_2016_technical-manual.pdf

2.2.3 Irrigation

Every crop has its own sensitivity to water stress, defined by the ability to use the water present in the rooting system. This value is defined by the fraction of readily available water by the root.

The amount of water that can be easily available in the root profile is calculated using this function, which integrates the height of water that can be easily used on the layer of ground affected by the roots:

$$H_2O_{available} = \sum_{l=iniRootDepth}^{rootDepth} (WC_l - (FC_l - fRAW * (FC_l - WP_l)))$$

where:

H_2O_{avb} is the easily available water content [mm]

$fRAW$ is the fraction of readily available water [-]

WC_l , FC_l and WP_l are the water content, field capacity and wilting point of the layer [mm]

The easily available water is used to assess when to irrigate the crop: the model defines the irrigation time when H_2O_{avb} has value less than zero.

In more detail, the irrigation algorithm can be summarized in this sequence of checks:

1. if the current day of simulation is included in the irrigation season;
2. if the number of days from the last irrigation is higher than the irrigation shift;
3. If the forecast rain is lower than 5 mm;
4. if the actual ratio between actual transpiration and potential transpiration is lower than the tolerated stress percentage for the crop;
5. if the easily available water is lower than zero.

If all the previous conditions are true, an irrigation volume is distributed. This is computed as the minimum between the predefined irrigation quantity for the crop and the maximum quantity of water that can daily infiltrate without runoff, so an irrigation without losses is computed.

CRITERIA references

2020. Suci, N., et al. Evaluation of groundwater contamination sources by plant protection products in hilly vineyards of Northern Italy. *Science of The Total Environment*, 141495.

2020. Ricchi, T., Alagna, V., Villani, G., Tomei, F., Toscano, A., & Baroni, G. Sensitivity of the agro-hydrological model CRITERIA-1D to the Leaf Area Index parameter. In 2020 IEEE International Workshop on Metrology for Agriculture and Forestry (MetroAgriFor) (pp. 247-251).

2020. Martini, E., Wollschläger, U., Bittelli, M., Tomei, F., Werban, U., Zacharias, S., & Roth, K. Process-based hydrological modeling: accounting for subsurface heterogeneity by integrating pedology, geophysics and soil hydrology. In EGU General Assembly Conference Abstracts (p. 9894).

2020. Chitu, Z., Tomei, F., Villani, G., Di Felice, A., Zampelli, G., Paltineanu, I. C., ... & Costache, R. Improving Irrigation Scheduling Using MOSES Short-Term Irrigation Forecasts and In Situ Water Resources Measurements on Alluvial Soils of Lower Danube Floodplain, Romania. *Water*, 12(2), 520.

2019. Villani, G., Nanni, S., Tomei, F., Pasetti, S., Mangiaracina, R., Agnetti, A., ... & Castellari, S. The RainBO Platform for Enhancing Urban Resilience to Floods: An Efficient Tool for Planning and Emergency Phases. *Climate*, 7(12), 145.

2018. Villani, G., et al. Soil Water Balance Model CRITERIA-ID in SWAMP Project: Proof of Concept. 23rd Conference of Open Innovations Association (FRUCT) (pp. 398-404). IEEE.

2018. Strati, V., Albéri, M., Anconelli, S., Baldoncini, M., Bittelli, M., Bottardi, C., Solimando, D., Tomei, F., Villani, G., & Mantovani, F. Modelling soil water content in a tomato field: proximal gamma ray spectroscopy and soil-crop system models. *Agriculture*, 8(4), 60.

2017. Chitu, Z., Villani, G., Tomei, F., Minciuna, M., Aldea, A., Dumitrescu, A., ... & Neagu, D. Water balance analysis for efficient water allocation in agriculture. A case study: Balta Brailei, Romania. *EGUGA*, 18943.

2016. Consoli, S., Licciardello, F., Vanella, D., Pasotti, L., Villani, G., & Tomei, F. Testing the water balance model criteria using TDR measurements, micrometeorological data and satellite-based information. *Agricultural Water Management*, 170, 68-80.

2015. Campi, P., Modugno, F., Navarro, A., Tomei, F., Villani, G., & Mastrorilli, M. Evapotranspiration simulated by CRITERIA and AquaCrop models in stony soils. *Italian Journal of Agronomy*, 10(2), 67-73.

2015. Bittelli, M., Campbell, G. S., Tomei, F. Soil Physics with Python, Transport in the Soil-Plant-Atmosphere System. Oxford University Press, 464 pages, ISBN: 978-0-19-968309-3.

2014. Dottori, F., Grazzini, F., Di Lorenzo, M., Spisni, A., & Tomei, F. Analysis of flash flood scenarios in an urbanized catchment using a two-dimensional hydraulic model. Proceedings of the International Association of Hydrological Sciences, 364, 198-203.

2014. Villani G., Botarelli L., Marletto V., Spisni A., Pavan V., Pratizzoli W. & Tomei F. iCOLT – Seasonal forecasts of crop irrigation needs at ARPA-SIMC. ECMWF Newsletter, 138: 30-33.

2014. Campi, P., Modugno, F., Mastroilli, M., Tomei, F., Villani, G., & Marletto. Evapotranspiration of tomato simulated with the CRITERIA model. Italian Journal of Agronomy, 93-98.

2011. Bittelli M., Pistocchi A., Tomei F., Roggero P.P., Orsini R., Toderi M., Antolini G. and Flury M. CRITERIA-3D: A Mechanistic Model for Surface and Subsurface Hydrology for Small Catchments. In: Soil Hydrology, Land Use and Agriculture: Measurement and Modelling. M. Shukla Ed. 416 pp.

2011. Villani G., Tomei F., Tomozeiu R., Marletto V. Climate scenarios and their impacts on irrigated agriculture in Emilia-Romagna, Italy. Italian J. Agrometeorol., 16.

2010. Bittelli M., Tomei F., Pistocchi A., Flury M., Boll J., Brooks E.S., Antolini G. Development and testing of a physically based, three-dimensional model of surface and subsurface hydrology. Adv. Wat. Resour., 33, 106-122.

2009. Antolini G., Bertacchini A., Carnevali G., Dal Re L., Laruccia N., Marletto V., Missiroli A., Ponzoni G., Quartieri M., Scotti C., Selmi C., Tabaglio V., Tagliavini M. Regional scale validation of two soil water and nitrogen models on wheat (*Triticum aestivum* L.) and peach (*Prunus persica* L.). Proc. 16th Nitrogen Workshop, June 28 - July 1 Torino

2007. Marletto V., Ventura F., Fontana G., Tomei F. Wheat growth simulation and yield prediction with seasonal forecasts and a numerical model. Agric. For. Meteor. 147:71-79.

2007. Tomei F., Antolini G., Bittelli M., Marletto V., Pasquali A., Van Soetendaal M. 1. Validazione del modello di bilancio idrico CriteriA. AIAM 2007, Quaderno riassunti, 66-67.

2007. Rinaldo S., Carollo F., Leoni C., Marletto V., Tonelli T., Bonaiti G. Water requirements calculation for crops irrigated with the Adige river water. ICID 22nd European Regional Conference 2007, 2-7 September 2007 - Pavia

2006. Marletto V.. CRITERIA: ecco il modello regionale di bilancio idrico. Agricoltura 34(6): 127-128
2006. Carollo F., Rinaldo S., Marletto V., Tonelli T., Bonaiti G. Monitoraggio e calcolo del fabbisogno idrico di singole colture agrarie. Atti ASITA 2006.
2006. Tomei F., Fontana G. Studio di validazione del modello CRITeRIA nella descrizione del trasporto dei nitrati. Convenzione Assessorato Agricoltura.
2006. Fontana G., Ventura F., Tomei F., Tonelli T., Marletto V. Modelli agrometeorologici e previsioni stagionali per la stima delle rese agricole. Atti Aiam 2006.
2005. Marletto V., Zinoni F., Botarelli L., Alessandrini C. Studio dei fenomeni siccitosi in Emilia-Romagna con il modello di bilancio idrico Criteria (extended abstract). RIAM 9: 32-33. Quaderno dei riassunti Convegno AIAM Vasto/Caramanico 3-5/5/2005.
2005. Marletto V., Zinoni F., Criscuolo L., Fontana G., Marchesi S., Morgillo A., Van Soetendaal M., Ceotto E., Andersen U. Evaluation of downscaled DEMETER multi-model ensemble seasonal hindcasts in a northern Italy location by means of a model of wheat growth and soil water balance. Tellus A, 57(3), 488-497.
2004. Zinoni F., Tonelli T., Marletto V. Studio dell'effetto della tecnica agronomica sul rilascio di nutrienti (azoto) in falda nella pianura piacentina. Appendice: descrizione del modello Criteria. In: Progetto AQUANET, Rapporto finale, Provincia di Piacenza, 93-115.
2004. Zinoni F., Alessandrini C., Marletto V. Bilancio idrico dei suoli agricoli. Applicazione del modello CRITERIA per la stima dei consumi idrici e delle irrigazioni relative ai principali ordinamenti colturali, nonché dei flussi idrici superficiali e profondi. Studio ambientale sul comprensorio ceramico.
2004. Pistocchi A., Tomei F. Analisi numerica dei processi idrologici nel suolo agrario: integrazione del modello CRITERIA con un modello di bilancio idrologico fisicamente basato. Approfondimenti. Relazione tecnica finale progetto CLIMAGRI, 38 pp.
2003. Zinoni F., Tonelli T. Studio del rilascio di azoto di origine agricola nei suoli del comune di Castelfranco Emilia utilizzando il modello CRITERIA.
2003. Pistocchi A., Tomei F. Un modello accoppiato 3D di runoff e deflusso nel mezzo poroso nel quadro del sistema di supporto alle decisioni Criteria. Atti AIAM 2003, 285-296.
2002. Zinoni F., Marletto V., Tiberi M., Accorsi C., Roggero P.P., Toderi M. CRITERIA: prime valutazioni per l'applicazione del modello nelle Marche. Relazione tecnica. Nota Interna ASSAM, Agenzia Sviluppo Agricolo Marche.

2002. Zinoni F., Bardasi G., Battilani A., Ducco G., Marletto V., Van Soetendael M., Tonelli T. Studio del carico di inquinanti di origine agricola: applicazione del modello CRITERIA a un comprensorio della bassa bolognese.

2001. Marletto V., Criscuolo L., Van Soetendael M. Implementation of Wofost in the framework of the Criteria geographical tool. Proc. of the 2nd Int. Symp. Modelling Cropping Systems, European Society for Agronomy, Florence, 16-18 July 2001, 219-220.

2001. Marletto V., Zinoni F. Messa a punto del modello CRITERIA per la valutazione del trasporto di nutrienti. Atti del seminario "Iniziative per contenere il fenomeno dell'eutrofizzazione nel Mare Adriatico" promosso da Direzione Generale Agricoltura - Direzione Generale Ambiente - ARPA Regione Emilia Romagna, Bologna, giovedì 7 Ottobre 1999, 114-120.

2001. Zinoni F., Ducco G., Marletto V., Van Soetendael M. Uso del modello CRITERIA per la valutazione del rischio di inquinamento azotato dei corpi idrici. Modellistica e qualità ambientale. ANPA RTI CTN_SSC 1/2001, 67-77. Anche in Atti di GEOFLUID 2000, Piacenza, 5 ottobre 2000, a cura di Elisabetta Russo.

2000. Ducco G. Completamento ed attivazione delle procedure per la simulazione del bilancio dell'azoto in CRITERIA. Relazione conclusiva. Nota interna SMR, 51 pp.

1999. Zinoni F., Marletto V. CRITERIA: bilancio idrico e GIS per la prevenzione dell'impatto ambientale di origine agricola. Agricoltura Ricerca n. 180/181 p: 102-109

1999. Zinoni F., Sarno G. Sviluppo, calibrazione e validazione del programma CRITERIA. Relazione finale, Feb. 1999. Piano Trien. per la Tutela amb. 1994-1996. Sch. Int. N.23-24. Messa a punto di un modello previs. rel. al bil. idrico di tipologie di suolo rinvenibili princip. in aree di conoide e interconoide tra i fiumi Secchia e Panaro.

1998. Zinoni F., Marletto V., Ducco G. CRITERIA - un sistema per la gestione territoriale del bilancio idrico. Atti Seminario AIAM '98, Firenze 2 aprile 1998: 67-74.

1998. Marletto V., Zinoni F., Tonelli T., Ducco G. CRITERIA: a Geographical Soil Water Balance Modelling Tool for Environmental Applications at the Regional Scale. Convegno 7th ICCTA International Congress for Computer Technology in Agriculture. Firenze 15-18 Novembre 1998, p. 43.

1998. Marletto V., Zinoni F. The Criteria project: integration of satellite, radar, and traditional agro climatic data in a GIS-supported water balance modelling environment. In: EUR 18328, Dalezios N.R. (ed.), 1998. Proc. COST 77, 79, 711 Int. Symp. on Applied Agrometeorology and Agroclimatology, Volos, Grecia, 24-26 april 1996, ISBN 92-828-4137-5, 173-178.

1998. Zinoni F., Marletto V. CRITERIA: progetto per ridurre l'impatto ambientale di origine agricola. Rivista ARPA, Luglio-Agosto 1998

1996. Zinoni F., Marletto V., Libè A., Raggi C., Tonelli T., Trevisan M., Capri E. Pesticide transport simulated within the CRITERIA model (poster). 10th Symposium Pesticide Chemistry, Environmental Fate of Xenobiotics, Castelnuovo Fogliani (PC, Italy) 30/9-2/10/1996.

1995. Lega P, Libè A., Raggi C., Tonelli T., Marletto V., Zinoni F. Applicazione del modello CRITERIA a due aree test della provincia di Piacenza. Nota interna dell'Amm. Provinciale di Piacenza, pp. 70.

1995. Marletto V., Zinoni F., Tonelli T. Il progetto CRITERIA: un ambiente geografico per modellare il bilancio idrico di suoli coltivati. Atti del Congresso annuale AICA, Chia, Cagliari, 27-29/9/1995, 785-787.

1994. Marletto V., Zinoni F. CRITERIA: un modello per l'idrologia e la salvaguardia ambientale. Mensile AER, Servizio Meteorologico Regionale, Maggio 1994.

1993. Zinoni F. CRITERIA. Analisi delle fasi di realizzazione del modello e di gestione delle banche dati e delle informazioni nei programmi di assistenza tecnica e nella programmazione del territorio. Documento a cura di F. Zinoni, Novembre 1993.

1993. Marletto V., Zinoni F., Filippi N., Angelelli A., Laruccia N., Lega P., Tonelli T. CRITERIA: an integrated geographical system for soil water monitoring (poster summary). Proc. of the JRC-IRSA Conf. on the MARS project, Belgirate, 17-18/11/93.

1993. Marletto V., Zinoni F., Filippi N., Angelelli A., Laruccia N., Lega P., Tonelli T. CRITERIA: an integrated geo-graphical system for soil water monitoring. Proc. IX Symposium Pesticide Chemistry, Mobility and Degradation of Xenobiotics, Piacenza 12-13 october 1993, 695-706.

1993. Marletto V., Zinoni F. CRITERIA: un sistema geografico integrato per la simulazione del comportamento idrologico dei suoli. Atti del 1° convegno nazionale Fisica dell'Ambiente, Brescia, 15-17/12/93, 299-301.

1992. Marletto V., Zinoni F. Il progetto CRITERIA. Relazione preliminare. Bologna 10 Dicembre 1992.

Other references

Driessen P.M., 1986. *The water balance of the soil*. In: *Modelling of agricultural production: weather, soils and crops*. van Keulen, H., Wolf, J., (eds.), Pudoc, Wageningen, 479 pp.

Driessen P.M., Konijn N.T., 1992. Land-use systems analysis. Wageningen: Wageningen Agricultural University.

Hargreaves, G. H., & Samani, Z. A. (1985). Reference crop evapotranspiration from temperature. *Applied engineering in agriculture*, 1(2), 96-99.

Ippisch O., Vogel H.J., Bastian P., 2006. Validity limits for the van Genuchten–Mualem model and implications for parameter estimation and numerical simulation. *Adv Water Resour.*, 29: 1780–9.

Mualem Y., 1976. A new model for predicting the hydraulic conductivity of unsaturated porous media. *Water Resour. Res.*, 12: 513–22.

Van Genuchten MT., 1980. A closed-form equation for predicting the hydraulic conductivity of unsaturated soils. *Soil Sci. Soc. Am. J.*, 44: 892–8.