

Package ‘REDCapR’

July 4, 2014

Title Interaction between R and REDCap

Description Encapsulates functions to streamline calls from R

Version 0.3-3

Date 2014-07-04

Author Will Beasley, David Bard, Thomas Wilson

Maintainer 'Will Beasley' <wibeasley@hotmail.com>

URL <http://ouhsc.edu/bbmc/>

Depends R(>= 3.0.0),stats

Imports httr,plyr,RCurl,stringr

Suggests devtools,knitr,methods,testit,testthat

License GPL-3

LazyData TRUE

VignetteBuilder knitr

Roxygen list(wrap = TRUE)

R topics documented:

Account-class	2
create_batch_glossary	2
REDCapR	3
redcap_column_sanitize	4
redcap_project	5
redcap_read	5
redcap_read_oneshot	7
validate_for_write	9

Index	11
--------------	-----------

Account-class	<i>A Reference Class to represent a bank account.</i>
---------------	---

Description

A Reference Class to represent a bank account.

Fields

balance1 A length-one numeric vector

balance2 A length-one numeric vector

Methods

withdraw1(x) Withdraw1 money from account. Allows overdrafts

withdraw2(x) Withdraw2 money from account. Allows overdrafts

create_batch_glossary	<i>Creates a data.frame that help batching long-running read and writes.</i>
-----------------------	--

Description

The function returns a `data.frame` that other functions use to separate long-running read and write REDCap calls into multiple, smaller REDCap calls. The goal is to (1) reduce the chance of time-outs, and (2) introduce little breaks between batches so that the server isn't continually tied up.

Usage

```
create_batch_glossary(row_count, batch_size)
```

Arguments

row_count The number records in the large dataset, before it's split.

batch_size The maximum number of subject records a single batch should contain.

Details

This function can also assist splitting and saving a large `data.frame` to disk as smaller files (such as a `.csv`). The padded columns allow the OS to sort the batches/files in sequential order.

Value

Currently, a `data.frame` is returned with the following columns,

1. `id`: an integer that uniquely identifies the batch, starting at 1.
2. `start_index`: the index of the first row in the batch. integer.
3. `stop_index`: the index of the last row in the batch. integer.
4. `id_pretty`: a character representation of `id`, but padded with zeros.
5. `start_index`: a character representation of `start_index`, but padded with zeros.
6. `stop_index`: a character representation of `stop_index`, but padded with zeros.
7. `label`: a character concatenation of `id_pretty`, `start_index`, and `stop_index_pretty`.

Author(s)

Will Beasley

See Also

See [redcap_read](#) for a function that uses `create_batch_glossary`.

Examples

```
library(REDCapR) #Load the package into the current R session.
create_batch_glossary(100, 50)
create_batch_glossary(100, 25)
create_batch_glossary(100, 3)
d <- data.frame(
  recordid = 1:100,
  iv = sample(x=4, size=100, replace=TRUE),
  dv = rnorm(n=100)
)
create_batch_glossary(nrow(d), batch_size=40)
```

REDCapR

REDCapR

Description

REDCapR

redcap_column_sanitize

Sanitize to adhere to REDCap character encoding requirements.

Description

Replace non-ASCII characters with legal characters that won't cause problems when writing to a REDCap project.

Usage

```
redcap_column_sanitize(d, column_names = colnames(d),
  encoding_initial = "latin1", substitution_character = "?")
```

Arguments

d	The data.frame containing the dataset used to update the REDCap project. Required.
column_names	An array of character values indicating the names of the variables to sanitize. Optional.
encoding_initial	An array of character values indicating the names of the variables to sanitize. Optional.
substitution_character	The character value that replaces characters that were unable to be appropriately matched.

Details

Letters like an accented 'A' are replaced with a plain 'A'.

This is a thin wrapper around `base::iconv()`. The ASCII//TRANSLIT option does the actual transliteration work. As of R 3.1.0, the OSes use similar, but different, versions to convert the characters. Be aware of this in case you notice slight OS-dependent differences.

Value

A data.frame with same columns, but whose character values have been sanitized.

Author(s)

Will Beasley

Examples

```
# Examples are not shown because they require non-ASCII encoding,
# which makes the package documentation less portable.
```

redcap_project	<i>A Reference Class to make later calls to REDCap more convenient.</i>
----------------	---

Description

This Reference Class represents a REDCap project. Once some values are set that are specific to a REDCap project (such as the URI and token), later calls are less verbose (such as reading and writing data). The functionality

Fields

`redcap_uri` The URI (uniform resource identifier) of the REDCap project. Required.
`token` `token` The user-specific string that serves as the password for a project. Required.

Methods

`read(batch_size = 100L, interbatch_delay = 0, records = NULL, records_collapsed = NULL, fields = NULL)`
 Reads records in a REDCap project.

Examples

```
library(REDCapR) #Load the package into the current R session.
uri <- "https://bbmc.ouhsc.edu/redcap/api/"
token <- "9A81268476645C4E5F03428B8AC3AA7B"
project <- redcap_project$new(redcap_uri=uri, token=token)
ds <- project$read()
```

redcap_read	<i>Read records from a REDCap project in subsets, and stacks them together before returning a data.frame.</i>
-------------	---

Description

From an external perspective, this function is similar to [redcap_read_one-shot](#). The internals differ in that `redcap_read` retrieves subsets of the data, and then combines them before returning (among other objects) a single `data.frame`. This function can be more appropriate than [redcap_read_one-shot](#) when returning large datasets that could tie up the server.

Usage

```
redcap_read(batch_size = 100L, interbatch_delay = 0, redcap_uri, token,
  records = NULL, records_collapsed = NULL, fields = NULL,
  fields_collapsed = NULL, export_data_access_groups = FALSE,
  raw_or_label = "raw", verbose = TRUE, cert_location = NULL)
```

Arguments

batch_size	The maximum number of subject records a single batch should contain. The default is 100.
interbatch_delay	The number of seconds the function will wait before requesting a new subset from REDCap. The default is 0.5 seconds.
redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
records	An array, where each element corresponds to the ID of a desired record. Optional.
records_collapsed	A single string, where the desired ID values are separated by commas. Optional.
fields	An array, where each element corresponds a desired project field. Optional.
fields_collapsed	A single string, where the desired field names are separated by commas. Optional.
export_data_access_groups	A boolean value that specifies whether or not to export the “redcap_data_access_group” field when data access groups are utilized in the project. Default is FALSE. See the details below.
raw_or_label	A string (either 'raw' or 'label' that specifies whether to export the raw coded values or the labels for the options of multiple choice fields. Default is 'raw'.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. Optional.
cert_location	If present, this string should point to the location of the cert files required for SSL verification. If the value is missing or NULL, the server’s identity will be verified using a recent CA bundle from the cURL website . See the details below. Optional.

Details

Specifically, it internally uses multiple calls to [redcap_read_oneshot](#) to select and return data. Initially, only primary key is queried through the REDCap API. The long list is then subsetted into partitions, whose sizes are determined by the batch_size parameter. REDCap is then queried for all variables of the subset’s subjects. This is repeated for each subset, before returning a unified data.frame.

The function allows a delay between calls, which allows the server to attend to other users’ requests.

Value

Currently, a list is returned with the following elements,

1. data: an R data.frame of the desired records and columns.
2. records_collapsed: the desired records IDs, collapsed into a single string, separated by commas.
3. fields_collapsed: the desired field names, collapsed into a single string, separated by commas.
4. elapsed_seconds: the duration of the function.
5. outcome_message: a boolean value indicating if the operation was apparently successful.

Author(s)

Will Beasley

References

The official documentation can be found on the REDCap wiki (<https://iwg.devguard.com/trac/redcap/wiki/ApiDocumentation>). Also see the ‘API Examples’ page on the REDCap wiki (<https://iwg.devguard.com/trac/redcap/wiki/ApiExamples>). A user account is required to access the wiki, which typically is granted only to REDCap administrators. If you do not

The official [cURL site](#) discusses the process of using SSL to verify the server being connected to.

Examples

```
## Not run:
library(REDCapR) #Load the package into the current R session.
uri <- "https://bbmc.ouhsc.edu/redcap/api/"
token <- "9A81268476645C4E5F03428B8AC3AA7B"
redcap_read(batch_size=2, redcap_uri=uri, token=token)

## End(Not run)
```

redcap_read_one-shot	<i>Read records from a REDCap project.</i>
----------------------	--

Description

This function uses REDCap’s [API](#) to select and return data.

Usage

```
redcap_read_one-shot(redcap_uri, token, records = NULL,
  records_collapsed = NULL, fields = NULL, fields_collapsed = NULL,
  export_data_access_groups = FALSE, raw_or_label = "raw", verbose = TRUE,
  cert_location = NULL)
```

Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
records	An array, where each element corresponds to the ID of a desired record. Optional.
records_collapsed	A single string, where the desired ID values are separated by commas. Optional.
fields	An array, where each element corresponds a desired project field. Optional.
fields_collapsed	A single string, where the desired field names are separated by commas. Optional.
export_data_access_groups	A boolean value that specifies whether or not to export the “redcap_data_access_group” field when data access groups are utilized in the project. Default is FALSE. See the details below.

raw_or_label	A string (either 'raw' or 'label' that specifies whether to export the raw coded values or the labels for the options of multiple choice fields. Default is 'raw'.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. Optional.
cert_location	If present, this string should point to the location of the cert files required for SSL verification. If the value is missing or NULL, the server's identity will be verified using a recent CA bundle from the cURL website . See the details below. Optional.

Details

I like how **PyCap** creates a 'project' object with methods that read and write from REDCap. However this isn't a style that R clients typically use. I like the logic that it's associated with a particular REDCap project that shouldn't change between calls. As a compromise, I think I'll wrap the uri, token, and cert location into a single S4 object that's passed to these methods. It will make these calls take less space.

The 'REDCapR' package includes a recent version of the [Bundle of CA Root Certificates](#) from the official [cURL site](#). This version is used by default, unless the 'cert_location' parameter is given another location.

If you do not pass in this export_data_access_groups value, it will default to FALSE. The following is from the API help page for version 5.2.3: This flag is only viable if the user whose token is being used to make the API request is **not** in a data access group. If the user is in a group, then this flag will revert to its default value.

Value

Currently, a list is returned with the following elements,

1. data: An R data.frame of the desired records and columns.
2. status_code: The [http status code](#) of the operation.
3. status_message: The message associated with the [http status code](#).
4. raw_text: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the 'raw_text' is returned as an empty string to save RAM.
5. records_collapsed: The desired records IDs, collapsed into a single string, separated by commas.
6. fields_collapsed: The desired field names, collapsed into a single string, separated by commas.
7. elapsed_seconds: The duration of the function.
8. outcome_message: A boolean value indicating if the operation was apparently successful.

Author(s)

Will Beasley

References

The official documentation can be found on the 'API Examples' page on the REDCap wiki (<https://iwg.devguard.com/trac/redcap/wiki/ApiExamples>). A user account is required.

The official [cURL site](#) discusses the process of using SSL to verify the server being connected to.

Examples

```
## Not run:
library(REDCapR) #Load the package into the current R session.
uri <- "https://bbmc.ouhsc.edu/redcap/api/"
token <- "9A81268476645C4E5F03428B8AC3AA7B"
#Return all records and all variables.
ds_all_rows_all_fields <- redcap_read_oneshot(redcap_uri=uri, token=token)$data

#Return only records with IDs of 1 and 3
desired_records_v1 <- c(1, 3)
ds_some_rows_v1 <- redcap_read_oneshot(
  redcap_uri=uri,
  token=token,
  records=desired_records_v1
)$data

#Return only the fields recordid, first_name, and age
desired_fields_v1 <- c("recordid", "first_name", "age")
ds_some_fields_v1 <- redcap_read_oneshot(
  redcap_uri=uri,
  token=token,
  fields=desired_fields_v1
)$data

## End(Not run)
```

validate_for_write	<i>Inspect a data.frame to anticipate problems before writing to a RED-Cap project.</i>
--------------------	---

Description

This set of functions inspect a data.frame to anticipate problems before writing with REDCap's [API](#).

Usage

```
validate_for_write( d )

validate_no_logical( d )

validate_no_uppercase( d )
```

Arguments

d	The data.frame containing the dataset used to update the REDCap project. Required.
---	--

Details

All functions listed in the Usage section above inspect a specific aspect of the dataset. The validate_for_read() function executes all these individual validation checks. It allows the client to check everything with one call.

Value

A `data.frame`, where each potential violation is a row. The two columns are:

1. `field_name`: The name of the `data.frame` that might cause problems during the upload.
2. `field_index`: The position of the field. (For example, a value of '1' indicates the first column, while a '3' indicates the third column.)
3. `concern`: A description of the problem potentially caused by the field.
4. `suggestion`: A *potential* solution to the concern.

Author(s)

Will Beasley

Examples

```
d <- data.frame(
  recordid = 1:4,
  flag_logical = c(TRUE, TRUE, FALSE, TRUE),
  flag_Uppercase = c(4, 6, 8, 2)
)
validate_for_write(d = d)
```

Index

Account (Account-class), [2](#)
Account-class, [2](#)

create_batch_glossary, [2](#)

redcap_column_sanitize, [4](#)
redcap_project, [5](#)
redcap_read, [3](#), [5](#)
redcap_read_oneshot, [5](#), [6](#), [7](#)
REDCapR, [3](#)
REDCapR-package (REDCapR), [3](#)

validate_for_write, [9](#)
validate_no_logical
 (validate_for_write), [9](#)
validate_no_uppercase
 (validate_for_write), [9](#)