Status
Changes
Console Output
Edit Build Information
Delete build '#2'
Polling Log
Git Build Data
Pipeline Overview
Restart from Stage
Replay
Pipeline Steps
Workspaces
Previous Build

Console

Download | Copy | View as plain text

```
Started by GitHub push by ARQ31
Obtained Jenkinsfile from git https://github.com/ARQ31/python-get-crud.git
[Pipeline] Start of Pipeline
[Pipeline] node
Running on Jenkins in /var/jenkins_home/workspace/python-crud-api-pipeline
[Pipeline] {
[Pipeline] stage
[Pipeline] { (Declarative: Checkout SCM)
[Pipeline] checkout
Selected Git installation does not exist. Using Default
The recommended git tool is: NONE
using credential github-pat-readonly
 > git rev-parse --resolve-git-dir /var/jenkins_home/workspace/python-crud-api-
pipeline/.git # timeout=10
Fetching changes from the remote Git repository
 > git config remote.origin.url https://github.com/ARQ31/python-get-crud.git # timeout=10
Fetching upstream changes from https://github.com/ARQ31/python-get-crud.git
 > git --version # timeout=10
 > git --version # 'git version 2.47.3'
using GIT_ASKPASS to set credentials
 > git fetch --tags --force --progress -- https://github.com/ARQ31/python-get-crud.git
+refs/heads/*:refs/remotes/origin/* # timeout=10
 > git rev-parse refs/remotes/origin/main^{commit} # timeout=10
Checking out Revision bc65727be0e6d2acd55c2677bbf77da22b0acada (refs/remotes/origin/main)
 > git config core.sparsecheckout # timeout=10
 > git checkout -f bc65727be0e6d2acd55c2677bbf77da22b0acada # timeout=10
Commit message: "ci: trigger automated Jenkins build via GitHub push webhook"
 > git rev-list --no-walk f9803c88b0e8e0b8f5e5650b6e81d6a2daf6fde0 # timeout=10
```

```
[Pipeline] }
[Pipeline] // stage
[Pipeline] withEnv
[Pipeline] {
[Pipeline] withEnv
[Pipeline] {
[Pipeline] stage
[Pipeline] { (1. Checkout Code)
[Pipeline] echo
Checking out source code from GitHub
[Pipeline] checkout
Selected Git installation does not exist. Using Default
The recommended git tool is: NONE
using credential github-pat-readonly
 > git rev-parse --resolve-git-dir /var/jenkins_home/workspace/python-crud-api-
pipeline/.git # timeout=10
Fetching changes from the remote Git repository
 > git config remote.origin.url https://github.com/ARQ31/python-get-crud.git # timeout=10
Fetching upstream changes from https://github.com/ARQ31/python-get-crud.git
 > git --version # timeout=10
 > git --version # 'git version 2.47.3'
using GIT_ASKPASS to set credentials
 > git fetch --tags --force --progress -- https://github.com/ARQ31/python-get-crud.git
+refs/heads/*:refs/remotes/origin/* # timeout=10
 > git rev-parse refs/remotes/origin/main^{commit} # timeout=10
Checking out Revision bc65727be0e6d2acd55c2677bbf77da22b0acada (refs/remotes/origin/main)
 > git config core.sparsecheckout # timeout=10
 > git checkout -f bc65727be0e6d2acd55c2677bbf77da22b0acada # timeout=10
Commit message: "ci: trigger automated Jenkins build via GitHub push webhook"
[Pipeline] sh
+ git rev-parse HEAD
bc65727be0e6d2acd55c2677bbf77da22b0acada
+ git rev-parse --short HEAD
bc65727
```

```
[Pipeline] }
[Pipeline] // stage
[Pipeline] stage
[Pipeline] { (2. Code Syntax Verification)
[Pipeline] sh
+ python3 -m py_compile app.py test_app.py
[Pipeline] }
[Pipeline] // stage
[Pipeline] stage
[Pipeline] { (3. Automated API Tests)
[Pipeline] sh
+ python3 -m unittest -v test_app.py
test_health_endpoint (test_app.BackendAPITestCase.test_health_endpoint) ... [07/Nov/2026
23:57:48] "GET /health HTTP/1.1" 200 -
ok
test_post_message_empty_validation
(test_app.BackendAPITestCase.test_post_message_empty_validation) ... [07/Nov/2026
23:57:48] "POST /messages HTTP/1.1" 400 -
ok
test_post_message_too_long_validation
(test_app.BackendAPITestCase.test_post_message_too_long_validation) ... [07/Nov/2026
23:57:48] "POST /messages HTTP/1.1" 400 -
ok
test_post_message_valid (test_app.BackendAPITestCase.test_post_message_valid) ...
[07/Nov/2026 23:57:48] "POST /messages HTTP/1.1" 201 -
ok

----------------------------------------------------------------------
Ran 4 tests in 0.526s

OK
[Pipeline] }
[Pipeline] // stage
[Pipeline] stage
```

```
[Pipeline] { (4. Build Docker Image)
[Pipeline] sh
+ git rev-parse --short HEAD
+ COMMIT_SHA=bc65727
+ echo Building image for BUILD_NUMBER=2, COMMIT_SHA=bc65727
Building image for BUILD_NUMBER=2, COMMIT_SHA=bc65727
+ docker build -t python-crud-api:2 .
DEPRECATED: The legacy builder is deprecated and will be removed in a future release.
            Install the buildx component to build images with BuildKit:
            https://docs.docker.com/go/buildx/

Sending build context to Docker daemon   7.68kB

Step 1/6 : FROM python:3.11-slim
 ---> 65bd3d9f1d7f
Step 2/6 : ENV PYTHONUNBUFFERED=1
 ---> Using cache
 ---> 8d16f241a269
Step 3/6 : WORKDIR /app
 ---> Using cache
 ---> d9702c915e2f
Step 4/6 : COPY app.py .
 ---> Using cache
 ---> 97b92d21ba06
Step 5/6 : EXPOSE 5000
 ---> Using cache
 ---> e4b7ef177d06
Step 6/6 : CMD ["python", "app.py"]
 ---> Using cache
 ---> ce1945a00b8e
Successfully built ce1945a00b8e
Successfully tagged python-crud-api:2
+ docker tag python-crud-api:2 python-crud-api:bc65727
+ docker tag python-crud-api:2 python-crud-api:latest
```

```
+ docker images python-crud-api
IMAGE                     ID             DISK USAGE   CONTENT SIZE   EXTRA
python-crud-api:1         ce1945a00b8e        187MB         45.6MB   U
python-crud-api:2         ce1945a00b8e        187MB         45.6MB   U
python-crud-api:bc65727   ce1945a00b8e        187MB         45.6MB   U
python-crud-api:f9803c8   ce1945a00b8e        187MB         45.6MB   U
python-crud-api:latest    ce1945a00b8e        187MB         45.6MB   U
python-crud-api:manual    1b252c6a53af        187MB         45.6MB
[Pipeline] }
[Pipeline] // stage
[Pipeline] stage
[Pipeline] { (5. Automated Deployment)
[Pipeline] sh
+ docker network inspect jenkins-net
+ docker stop production-api-container
production-api-container
+ docker rm production-api-container
production-api-container
+ docker volume create production-api-data
production-api-data
+ docker run -d --name production-api-container --network jenkins-net -p 5000:5000 -v
production-api-data:/var/lib/backend_data python-crud-api:latest
58a08ecf5c4e29c0959cb78c9b16b8fc5cedfdd958c8ba7c89e084d71a4e2e56
+ docker ps --filter name=production-api-container
CONTAINER ID   IMAGE                    COMMAND           CREATED                  STATUS
PORTS                                       NAMES
58a08ecf5c4e   python-crud-api:latest   "python app.py"   Less than a second ago   Up Less
than a second   0.0.0.0:5000->5000/tcp, [::]:5000->5000/tcp   production-api-container
[Pipeline] }
[Pipeline] // stage
[Pipeline] stage
[Pipeline] { (6. Health Check)
[Pipeline] sh
+ sleep 3
```

```
+ curl -fsS http://production-api-container:5000/health
{"status": "active", "service": "Backend API"}+ echo

+ docker logs --tail 20 production-api-container
Backend API listening on 0.0.0.0:5000
[07/Nov/2026 23:57:56] "GET /health HTTP/1.1" 200 -
[Pipeline] }
[Pipeline] // stage
[Pipeline] stage
[Pipeline] { (Declarative: Post Actions)
[Pipeline] echo
Pipeline completed successfully.
[Pipeline] }
[Pipeline] // stage
[Pipeline] }
[Pipeline] // withEnv
[Pipeline] }
[Pipeline] // withEnv
[Pipeline] }
[Pipeline] // node
[Pipeline] End of Pipeline
Finished: SUCCESS
```