

Introduction to Python Sequences, List, Tuples

Christopher Barker

UW Continuing Education

October 15, 2013

Table of Contents

- 1 Review/Questions
- 2 Sequences
- 3 Lists, Tuples...
- 4 Looping
- 5 Fun with Strings

Review of Previous Class

- Recursive functions
- Truthiness
- Modules and name spaces

New sublime theme...

Note about homework

About a 1/3 of you have been sending me homework to review.

Which is jsut fine!

But how do I know if you have learned the material?

Final Project...

Lightning Talks

Lightning talks today:

Nate Flagg

Duane Wright

Jo-Anne Antoun

Josh Rakita

Homework review

Homework Questions?

My Solution

Gary's Solution

Sequences

Sequences are ordered collections of objects

They can be indexed, sliced, iterated over,...

They have a length: `len(sequence)`

Common sequences (Remember Duck Typing?):

- strings
- tuples
- lists

Indexing

square brackets for indexing: `[]`

Indexing starts at zero

```
In [98]: s = "this is a string"
```

```
In [99]: s[0]
```

```
Out[99]: 't'
```

```
In [100]: s[5]
```

```
Out[100]: 'i'
```


Indexing

Negative indexes count from the end

```
In [105]: s = "this is a string"
```

```
In [106]: s[-1]
```

```
Out[106]: 'g'
```

```
In [107]: s[-6]
```

```
Out[107]: 's'
```

Slices

Slicing: Pulling a range out of a sequence

```
sequence[start:finish]
```

indexes for which:

```
start <= i < finish
```

Slices

```
In [121]: s = "a bunch of words"
```

```
In [122]: s[2]
```

```
Out[122]: 'b'
```

```
In [123]: s[6]
```

```
Out[123]: 'h'
```

```
In [124]: s[2:6]
```

```
Out[124]: 'bunc'
```

```
In [125]: s[2:7]
```

```
Out[125]: 'bunch'
```

Slices

the indexes point to the spaces between the items

	X		X		X		X		X		X		X	
0		1		2		3		4		5		6		7

Slices

Slicing satisfies nifty properties:

$$\text{len}(\text{seq}[a:b]) == b - a$$
$$\text{seq}[a:b] + \text{seq}[b:c] == \text{seq}$$

Slicing vs. Indexing

Indexing returns a single element

```
In [86]: 1
```

```
Out[86]: [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
```

```
In [87]: type(1)
```

```
Out[87]: list
```

```
In [88]: 1[3]
```

```
Out[88]: 3
```

```
In [89]: type( 1[3] )
```

```
Out[89]: int
```

Slicing vs. Indexing

Unless it's a string:

```
In [75]: s = "a string"
```

```
In [76]: s[3]
```

```
Out[76]: 't'
```

```
In [77]: type(s[3])
```

```
Out[77]: str
```

There is no single character type

Slicing vs. Indexing

Slicing returns a sequence:

```
In [68]: 1
```

```
Out[68]: [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
```

```
In [69]: 1[2:4]
```

```
Out[69]: [2, 3]
```

Even if it's one element long

```
In [70]: 1[2:3]
```

```
Out[70]: [2]
```

```
In [71]: type(1[2:3])
```

```
Out[71]: list
```


Slicing vs. Indexing

Indexing out of range produces an error

```
In [129]: s = "a bunch of words"
```

```
In [130]: s[17]
```

```
----> 1 s[17]
```

```
IndexError: string index out of range
```

Slicing just gives you what's there

```
In [131]: s[10:20]
```

```
Out[131]: ' words'
```

```
In [132]: s[20:30]
```

```
Out[132]: ''
```

(demo)

Multiplying and slicing

from CodingBat: Warmup-1 – front3

```
def front3(str):  
    if len(str) < 3:  
        return str+str+str  
    else:  
        return str[:3]+str[:3]+str[:3]
```

or

```
def front3(str):  
    return str[:3] * 3
```

Slicing

from CodingBat: Warmup-1 – missing_char

```
def missing_char(str, n):  
    front = str[0:n]  
    l = len(str)-1  
    back = str[n+1:l+1]  
    return front + back  
  
def missing_char(str, n):  
    return str[:n] + str[n+1:]
```

Slicing

you can skip items, too

```
In [289]: string = "a fairly long string"
```

```
In [290]: string[0:15]
```

```
Out[290]: 'a fairly long s'
```

```
In [291]: string[0:15:2]
```

```
Out[291]: 'afil ogs'
```

```
In [292]: string[0:15:3]
```

```
Out[292]: 'aallg'
```

LAB

Write some functions that:

- return a string with the first and last characters exchanged.
- return a string with every other character removed
- return a string with the first and last 4 characters removed, and every other char in between
- return a string reversed (just with slicing)
- return a string with the middle, then last, then first third in a new order

Lightning Talk

Lightning Talks:

Nate Flag

Duane Wright

Lists

List Literals

```
>>> []  
[]  
>>> list()  
[]  
>>> [1, 2, 3]  
[1, 2, 3]  
>>> [1, 3.14, "abc"]  
[1, 3.14, 'abc']
```

Lists

List “type”
(also constructor)

```
>>> type(list)
<type 'type'>
>>> list( (1,2,3) )
[1, 2, 3]
>>> list( "a string" )
```

Takes any sequence, tries to turn it into a list
like `int()`, `float()`, etc.

List Indexing

Indexing just like all sequences

```
>>> food = ['spam', 'eggs', 'ham']
```

```
>>> food[2]
```

```
'ham'
```

```
>>> food[0]
```

```
'spam'
```

```
>>> food[42]
```

```
Traceback (most recent call last):
```

```
  File "<stdin>", line 1, in <module>
```

```
IndexError: list index out of range
```

List Mutability

Lists are mutable

```
>>> food = ['spam', 'eggs', 'ham']  
>>> food[1] = 'raspberries'  
>>> food  
['spam', 'raspberries', 'ham']
```

List Elements

Each element is a value, and can be in multiple lists and have multiple names (or no name)

```
>>> name = 'Brian'
>>> a = [1, 2, name]
>>> b = [3, 4, name]
>>> name
'Brian'
>>> a
[1, 2, 'Brian']
>>> b
[3, 4, 'Brian']
>>> a[2]
'Brian'
>>> b[2]
```

List Methods

`.append()`, `.insert()`

```
>>> food = ['spam', 'eggs', 'ham']  
>>> food.append('sushi')  
>>> food  
['spam', 'eggs', 'ham', 'sushi']  
>>> food.insert(0, 'carrots')  
>>> food  
['carrots', 'spam', 'eggs', 'ham', 'sushi']
```

List Methods

`.extend()`

```
>>> food = ['spam', 'eggs', 'ham']  
>>> food.extend(['fish', 'chips'])  
>>> food  
['spam', 'eggs', 'ham', 'fish', 'chips']
```

could be any sequence:

```
>>> food  
>>> ['spam', 'eggs', 'ham']  
>>> silverware = ('fork', 'knife', 'spoon') # a tuple  
>>> food.extend(silverware)  
>>> food  
>>> ['spam', 'eggs', 'ham', 'fork', 'knife', 'spoon']
```

List Methods

`pop()`, `remove()`

```
In [203]: food = ['spam', 'eggs', 'ham', 'toast']
```

```
In [204]: food.pop()
```

```
Out[204]: 'toast'
```

```
In [205]: food.pop(0)
```

```
Out[205]: 'spam'
```

```
In [206]: food
```

```
Out[206]: ['eggs', 'ham']
```

```
In [207]: food.remove('ham')
```

```
In [208]: food
```

```
Out[208]: ['eggs']
```

List Constructor

`list()` accepts any sequence and returns a list of that sequence

```
>>> word = 'Python '  
>>> chars = []  
>>> for char in word:  
...     chars.append(char)  
>>> chars  
['P', 'y', 't', 'h', 'o', 'n', ' ']  
>>> list(word)  
['P', 'y', 't', 'h', 'o', 'n', ' ']
```

String to List to String

If you need to change individual letters... you can do this, but usually `somestring.replace()` will be enough

```
In [216]: name = 'Chris'
In [217]: lname = list(name)
In [218]: lname[0:2] = 'K'
In [219]: name = ''.join(lname)
In [220]: name
Out[220]: 'Kris'
```


Building up strings in a list

```
In [221]: msg = []
```

```
In [222]: msg.append('The first line of a message')
```

```
In [223]: msg.append('The second line of a message')
```

```
In [224]: msg.append('And one more line')
```

```
In [225]: print '\n'.join(msg)
```

```
The first line of a message
```

```
The second line of a message
```

```
And one more line
```

List Slicing

Slicing makes a copy

```
In [227]: food = ['spam', 'eggs', 'ham', 'sushi']
```

```
In [228]: some_food = food[1:3]
```

```
In [229]: some_food[1] = 'bacon'
```

```
In [230]: food
```

```
Out[230]: ['spam', 'eggs', 'ham', 'sushi']
```

```
In [231]: some_food
```

```
Out[231]: ['eggs', 'bacon']
```

List Slicing

Easy way to copy a whole list

```
In [232]: food
```

```
Out[232]: ['spam', 'eggs', 'ham', 'sushi']
```

```
In [233]: food2 = food[:]
```

```
In [234]: food is food2
```

```
Out[234]: False
```

but the copy is “shallow”:

<http://docs.python.org/library/copy.html>

List Slicing

“Shallow” copy

```
In [249]: food = ['spam', ['eggs', 'ham']]
In [251]: food_copy = food[:]
In [252]: food[1].pop()
Out[252]: 'ham'
In [253]: food
Out[253]: ['spam', ['eggs']]
In [256]: food.pop(0)
Out[256]: 'spam'
In [257]: food
Out[257]: [['eggs']]
In [258]: food_copy
Out[258]: ['spam', ['eggs']]
```

Name Binding

Assigning to a name does not copy:

```
>>> food = ['spam', 'eggs', 'ham', 'sushi']
>>> food_again = food
>>> food_copy = food[:]
>>> food.remove('sushi')
>>> food
['spam', 'eggs', 'ham']
>>> food_again
['spam', 'eggs', 'ham']
>>> food_copy
['spam', 'eggs', 'ham', 'sushi']
```

List Iterating

Iterating over a list

```
>>> food = ['spam', 'eggs', 'ham', 'sushi']  
>>> for x in food:  
...     print x  
...  
spam  
eggs  
ham  
sushi
```

Processing Lists

A common pattern

```
filtered = []  
for x in somelist:  
    if should_be_included(x):  
        filtered.append(x)  
del(somelist)  # maybe
```

you don't want to be deleting items from the list while iterating...

Mutating Lists

if you're going to change the list, iterate over a copy for safety

```
>>> food = ['spam', 'eggs', 'ham', 'sushi']  
>>> for x in food[:]:  
...     # change the list somehow  
...
```

insidious bugs otherwise

operators vs methods

What's the difference?

```
>>> food = ['spam', 'eggs', 'ham']  
>>> more = ['fish', 'chips']  
>>> food = food + more  
>>> food  
['spam', 'eggs', 'ham', 'fish', 'chips']
```

```
>>> food = ['spam', 'eggs', 'ham']  
>>> more = ['fish', 'chips']  
>>> food.extend(more)  
>>> food  
['spam', 'eggs', 'ham', 'fish', 'chips']
```

(the operator makes a new list...)

in

```
>>> food = ['spam', 'eggs', 'ham']  
>>> 'eggs' in food  
True  
>>> 'chicken feet' in food  
False
```

reverse()

```
>>> food = ['spam', 'eggs', 'ham']  
>>> food.reverse()  
>>> food  
['ham', 'eggs', 'spam']
```

sort()

```
>>> food = ['spam', 'eggs', 'ham', 'sushi']  
>>> food.sort()  
>>> food  
['eggs', 'ham', 'spam', 'sushi']
```

note:

```
>>> food = ['spam', 'eggs', 'ham', 'sushi']  
>>> result = food.sort()  
>>> print result  
None
```

Sorting

How should this sort?

```
>>> s  
[[2, 'a'], [1, 'b'], [1, 'c'], [1, 'a'], [2, 'c']]
```

Sorting

How should this sort?

```
>>> s
[[2, 'a'], [1, 'b'], [1, 'c'], [1, 'a'], [2, 'c']]

>>> s.sort()
>>> s
[[1, 'a'], [1, 'b'], [1, 'c'], [2, 'a'], [2, 'c']]
```

Sorting

You can specify your own compare function:

```
In [279]: s = [[2, 'a'], [1, 'b'], [1, 'c'], [1, 'a'], [2, 'c']]
In [281]: def comp(s1,s2):
.....:     if s1[1] > s2[1]: return 1
.....:     elif s1[1]<s2[1]: return -1
.....:     else:
.....:         if s1[0] > s2[0]: return 1
.....:         elif s1[0] < s2[0]: return -1
.....:     return 0
In [282]: s.sort(comp)
In [283]: s
Out[283]: [[1, 'a'], [2, 'a'], [1, 'b'], [1, 'c'], [2, 'c']]
```

Sorting

Mixed types can be sorted.

“objects of different types always compare unequal,
and are ordered consistently but arbitrarily.”

`http:
//docs.python.org/reference/expressions.html#not-in`

Searching

Finding or Counting items

```
In [288]: l = [3,1,7,5,4,3]
```

```
In [289]: l.index(5)
```

```
Out[289]: 3
```

```
In [290]: l.count(3)
```

```
Out[290]: 2
```

List Performance

- indexing is fast and constant time: $O(1)$
- x in s proportional to n : $O(n)$
- visiting all is proportional to n : $O(n)$
- operating on the end of list is fast and constant time: $O(1)$
append(), pop()
- operating on the front (or middle) of the list depends on n :
 $O(n)$
pop(0), insert(0, v)
But, reversing is fast. Also, collections.deque

<http://wiki.python.org/moin/TimeComplexity>

Lists vs. Tuples

List or Tuples

If it needs to be mutable: list

If it needs to be immutable: tuple
(dict key, safety when passing to a function)

Otherwise ... taste and convention

List vs Tuple

Convention:

Lists are Collections (homogeneous):

- contain values of the same type
- simplifies iterating, sorting, etc

tuples are mixed types:

- Group multiple values into one logical thing – Kind of like simple C structs.

List vs Tuple

- Do the same operation to each element?
- Small collection of values which make a single logical item?
- To document that these values won't change?
- Build it iteratively?
- Transform, filter, etc?

List vs Tuple

- Do the same operation to each element? **list**
- Small collection of values which make a single logical item? **tuple**
- To document that these values won't change? **tuple**
- Build it iteratively? **list**
- Transform, filter, etc? **list**

List Docs

The list docs:

`http://docs.python.org/library/stdtypes.html#
mutable-sequence-types`

(actually any mutable sequence....)

tuples and commas..

Tuples don't NEED parentheses...

```
In [161]: t = (1,2,3)
```

```
In [162]: t
```

```
Out[162]: (1, 2, 3)
```

```
In [163]: t = 1,2,3
```

```
In [164]: t
```

```
Out[164]: (1, 2, 3)
```

```
In [165]: type(t)
```

```
Out[165]: tuple
```


tuples and commas..

Tuples do need commas...

```
In [156]: t = ( 3 )
```

```
In [157]: type(t)
```

```
Out[157]: int
```

```
In [158]: t = (3,)
```

```
In [159]: t
```

```
Out[159]: (3,)
```

```
In [160]: type(t)
```

```
Out[160]: tuple
```

LAB

List Lab

`week-03/code/list_lab.rst`

Lightning Talk

Lightning Talks:

Jo-Anne Antoun

Josh Rakita

for loops

looping through sequences

```
for x in sequence:  
    do_something_with_x
```

for loops

```
In [170]: for x in "a string":  
.....:     print x  
.....:  
a  
  
s  
  
t  
  
r  
  
i  
  
n  
  
g
```

range

looping a known number of times..

```
In [171]: for i in range(5):  
.....:     print i  
.....:
```

0
1
2
3
4

(you don't need to do anything with i...

range

range defined similarly to indexing

```
In [183]: range(4)
```

```
Out[183]: [0, 1, 2, 3]
```

```
In [184]: range(2,4)
```

```
Out[184]: [2, 3]
```

```
In [185]: range(2,10,2)
```

```
Out[185]: [2, 4, 6, 8]
```

indexing?

Python only loops through a sequence – not like C, Javascript, etc...

```
for(var i=0; i<arr.length; i++) {  
    var value = arr[i];  
    alert(i +" "+value);  
}
```


indexing?

Use range?

```
In [193]: letters = "Python"
```

```
In [194]: for i in range(len(letters)):
.....:     print letters[i]
.....:
```

P
y
t
h
o
n

indexing?

More Pythonic – for loops through sequences

```
In [196]: for l in letters:  
.....:     print l  
.....:
```

P
y
t
h
o
n

Never index in normal cases

enumerate

If you need an index – enumerate

```
In [197]: for i, l in enumerate(letters):  
.....:     print i, l  
.....:  
0 P  
1 y  
2 t  
3 h  
4 o  
5 n
```

multiple sequences – zip

If you need to loop through parallel sequences – zip

```
In [200]: first_names = ['Fred', 'Mary', 'Jane']
```

```
In [201]: last_names = ['Baker', 'Jones', 'Miller']
```

```
In [203]: for first, last in zip(first_names, last_names):  
.....:     print first, last
```

```
.....:
```

```
Fred Baker
```

```
Mary Jones
```

```
Jane Miller
```

xrange

range creates the whole list

xrange is a generator – creates it as it's needed –

a good idea for large numbers

```
In [207]: for i in xrange(3):  
.....:     print i
```

0

1

2

(Python 3 – range == xrange)

for

for does NOT create a name space:

```
In [172]: x = 10
```

```
In [173]: for x in range(3):  
.....:     pass  
.....:
```

```
In [174]: x
```

```
Out[174]: 2
```

while

`while` is for when you don't know how many loops you need

Continues to execute the body until condition is not `True`

```
while a_condition:  
    some_code  
    in_the_body
```

while

`while` is more general than `for` – you can always express `for` as `while`, but not always vice-versa.

`while` is more error-prone – requires some care to terminate

loop body must make progress, so condition can become `False`

potential error: infinite loops

while vs. for

```
letters = 'Python'  
i=0  
while i < len(letters):  
    print letters[i]  
    i += 1
```

vs.

```
letters = 'Python'  
for c in letters:  
    print c
```

while

Shortcut: recall – 0 or empty sequence is False

break

break ends a loop early

```
x = 0
while True:
    print x
    if x > 2:
        break
    x = x + 1
```

In [216]: run for_while.py

```
0
1
2
3
```

(This is a pretty common idiom)

break

same way with a for loop

```
name = "Chris Barker"
for c in name:
    print c,
    if c == "B":
        break
print "I'm done"
```

```
C h r i s   B
I'm done
```

continue

continue skips to the start of the loop again

```
print "continue in a for loop"
name = "Chris Barker"
for c in name:
    if c == "B":
        continue
    print c,
print "\nI'm done"
```

```
continue in a for loop
C h r i s   a r k e r
I'm done
```

continue

continue works for a while loop too.

```
print "continue in a while loop"
x = 6
while x > 0:
    x = x-1
    if x%2:
        continue
    print x,
print "\nI'm done"
```

```
continue in a while loop
4 2 0
I'm done
```

else again

else block run if the loop finished naturally – no break

```
print "else in a for loop"
x = 5
for i in range(5):
    print i
    if i == x:
        break
else:
    print "else block run"
```

Strings

A string literal creates a string type

```
"this is a string"
```

Can also use `str()`

```
In [256]: str(34)
```

```
Out[256]: '34'
```

or "back ticks"

```
In [258]: '34'
```

```
Out[258]: '34'
```

(demo)

The String Type

Lots of nifty methods:

```
s.lower()  
s.upper()  
...  
s.capitalize()  
s.swapcase()  
s.title()
```

<http://docs.python.org/library/stdtypes.html#index-23>

The String Type

Lots of nifty methods:

```
x in s  
s.startswith(x)  
s.endswith(x)  
...  
s.index(x)  
s.find(x)  
s.rfind(x)
```

<http://docs.python.org/library/stdtypes.html#index-23>

The String Type

Lots of nifty methods:

```
s.split()  
s.join(list)  
...  
s.splitlines()
```

<http://docs.python.org/library/stdtypes.html#index-23>

Joining Strings

The Join Method:

```
In [289]: t = ("some", "words","to","join")
```

```
In [290]: " ".join(t)
```

```
Out[290]: 'some words to join'
```

```
In [291]: ",".join(t)
```

```
Out[291]: 'some,words,to,join'
```

```
In [292]: "".join(t)
```

```
Out[292]: 'somewordstojoin'
```

(demo – join)

The string module

Lots of handy constants, etc.

```
string.ascii_letters  
string.ascii_lowercase  
string.ascii_uppercase  
string.letters  
string.hexdigits  
string.whitespace  
string.printable  
string.digits  
string.punctuation
```

(and the string methods – legacy)

<http://docs.python.org/2/library/string.html#module-string>

String Literals

Common Escape Sequences

```
\\  Backslash (\)
\a  ASCII Bell (BEL)
\b  ASCII Backspace (BS)
\n  ASCII Linefeed (LF)
\r  ASCII Carriage Return (CR)
\t  ASCII Horizontal Tab (TAB)
\ooo Character with octal value ooo
\xhh Character with hex value hh
```

```
(http:
//docs.python.org/release/2.5.2/ref/strings.html)
```

Raw Strings

Escape Sequences Ignored

```
In [408]: print "this\nthat"  
this  
that
```

```
In [409]: print r"this\nthat"  
this\nthat
```

Gotcha:

```
In [415]: r"  
SyntaxError: EOL while scanning string literal
```

(handy for regex, windows paths...)

Building Strings

Please don't do this:

```
'Hello ' + name + '!'
```

(much)

Character Values

Characters in strings are stored as numeric values

“ASCII” values: 1-127

“ANSI” values: 1-255

To get the value:

```
In [109]: for i in 'Chris':  
.....:     print ord(i),  
67 104 114 105 115
```

```
In [110]: for i in (67,104,114,105,115):  
.....:     print chr(i),  
C h r i s
```

(next week: unicode!)

Building Strings

Do this instead:

```
'Hello %s!' % name
```

much faster and safer:

easier to modify as code gets complicated

```
http://docs.python.org/library/stdtypes.html#  
string-formatting-operations
```

String Formatting

The string format operator: %

```
In [261]: "an integer is: %i"%34
```

```
Out[261]: 'an integer is: 34'
```

```
In [262]: "a floating point is: %f"%34.5
```

```
Out[262]: 'a floating point is: 34.500000'
```

```
In [263]: "a string is: %s"%anything
```

```
Out[263]: 'a string is: anything'
```

String Formatting

multiple arguments:

```
In [264]: "the number %s is %i"%( 'five', 5)
```

```
Out[264]: 'the number five is 5'
```

```
In [266]: "the first 3 numbers are: %i, %i, %i"%(1,2,3)
```

```
Out[266]: 'the first 3 numbers are: 1, 2, 3'
```

String formatting

Gotcha

```
In [127]: "this is a string with %i formatting item"%1
Out[127]: 'this is a string with 1 formatting item'
```

```
In [128]: "string with %i formatting %s: "%2, "items"
TypeError: not enough arguments for format string
```

Done right:

```
In [131]: "string with %i formatting %s"%(2, "items")
Out[131]: 'string with 2 formatting items'
```

```
In [132]: "string with %i formatting item"%(1,)
Out[132]: 'string with 1 formatting item'
```

String formatting

Named arguments

```
'Hello %(name)s!' % {'name': 'Joe'}  
'Hello Joe!'
```

```
'Hello %(name)s, how are you, %(name)s!' % {'name': 'Joe'}  
'Hello Joe, how are you, Joe!'
```

That last bit is a dictionary (next week)

String formatting

The format operator works with string variables, too:

```
In [45]: s = "%i / %i = %i"
```

```
In [46]: a, b = 12, 3
```

```
In [47]: s%(a, b, a/b)
```

```
Out[47]: '12 / 3 = 4'
```

So you can dynamically build a format string

Advanced Formatting

The format method

```
In [14]: 'Hello {0} {1}!'.format('Joe', 'Barnes')
```

```
Out[14]: 'Hello Joe Barnes!'
```

```
In [12]: 'Hello {name}!'.format(name='Joe')
```

```
Out[12]: 'Hello Joe!'
```

pick one (probably regular string formatting):
– get comfy with it

LAB

Fun with strings

- Rewrite:
the first 3 numbers are: %i, %i, %i"%(1,2,3)
for an arbitrary number of numbers...
- write a format string that will take:
(2, 123.4567, 10000)
and produce:
'file_002 : 123.46, 1e+04'
- Write a (really simple) mail merge program
- ROT13 – see next slide

LAB

ROT13 encryption

Applying ROT13 to a piece of text merely requires examining its alphabetic characters and replacing each one by the letter 13 places further along in the alphabet, wrapping back to the beginning if necessary

- Implement rot13 decoding
- decode this message:

Zntargvp sebz bhgfvqr arne pbeare
(from a geo-caching hint)

Homework

Recommended Reading:

- Think Python: Chapt. 9 – 14
- Dive Into Python: Chapt. 6
- String methods: <http://docs.python.org/library/stdtypes.html#string-methods>
- Extra: unicode: <http://www.joelonsoftware.com/articles/Unicode.html>

Do:

- Finish the LABs
- Six more CodingBat exercises.
- LPTHW: for extra practice with the concepts – some of: exercises 5 – 14