

Introduction to Python

More OO – Inheritance and Duck Typing

Special methods

Christopher Barker

UW Continuing Education

November 12, 2013

Table of Contents

- 1 Review/Questions
- 2 Overriding methods

Lightning Talks

Lightning talks today:

Linh Tran

Maitri Kashyap

Sridharan Rajagopalan

Richard Smith

Review of Previous Class

- lambda
- Intro to OO
- Start of HTML generation code

Homework review

Questions?

Overview of my html-generating classes so far...

Demo of class vs. instance attributes

Lightning Talks

Lightning Talks:

Linh Tran

Maitri Kashyap

Overriding `__init__`

`__init__` common method to override

You often need to call the super class `__init__` as well

```
class Circle(object):
    color = "red"
    def __init__(self, diameter):
        self.diameter = diameter
...
class CircleR(Circle):
    def __init__(self, radius):
        diameter = radius*2
        Circle.__init__(self, diameter)
```

exception to: "don't change the method signature" rule.

More subclassing

You can also call the superclass's other methods:

```
class Circle(object):  
    ...  
    def get_area(self, diameter):  
        return math.pi * diameter / 2.0  
  
class CircleR2(Circle):  
    ...  
    def get_area(self):  
        return Circle.get_area(self, self.radius*2)
```

There is nothing special about `__init__` except that it gets called automatically.

When to Subclass

“Is a” relationship: Subclass/inheritance

“Has a” relationship: Composition

When to Subclass

“Is a” vs “Has a”

You may have a class that needs to accumulate an arbitrary number of objects.

A list can do that – so should you subclass list?

Ask yourself:

- Is your class a list (with some extra functionality)?
or
- Does your class HAVE a list?

You only want to subclass list if your class could be used anywhere a list can be used.

Attribute resolution order

When you access an attribute:

`An_Instance.something`

Python looks for it in this order:

- 1 Is it an instance attribute ?
- 2 Is it a class attribute ?
- 3 Is it a superclass attribute ?
- 4 Is it a super-superclass attribute ?
- 5 ...

It can get more complicated...

<http://www.python.org/getit/releases/2.3/mro/>

[http://python-history.blogspot.com/2010/06/
method-resolution-order.html](http://python-history.blogspot.com/2010/06/method-resolution-order.html)

What are Python classes, really?

Putting aside the OO theory...

Python classes are:

- Namespaces
 - One for the class object
 - One for each instance
- Attribute resolution order
- Auto tacking-on of `self`

That's about it – really!

Type-Based dispatch

From Think Python:

```
if isinstance(other, A_Class):  
    Do_something_with_other  
else:  
    Do_something_else
```

Usually better to use “duck typing” (polymorphism)

But when it's called for:

- `isinstance()`
- `issubclass()`

GvR: “Five Minute Multi- methods in Python”:

<http://www.artima.com/weblogs/viewpost.jsp?thread=101605>

LAB

We're going to the rest: steps 4 - 8
(Still using week-06/code/htmlrender)

Step 4:

- Extend the Element class to accept a set of attributes as keywords to the constructor, i.e.:

```
Element("some text content",  
        id="TheList",  
        style="line-height:200\\%")
```

(remember `**kwargs` ?)

- The render method will need to be extended to render the attributes properly.

You can now render some `<p>` tags (and others) with attributes

LAB

Step 5:

- Create a `SelfClosingTag` subclass of `Element`, to render tags like:
`<hr />` and `
` (horizontal rule and line break).
- You will need to override the render method to render just the one tag and attributes.
- create a couple subclasses of `SelfClosingTag` for `<hr>` and `
` (Line break) or ??? if you like

You can now render an html page with a proper `<head>`
(`<meta />` and `<title>` elements)

LAB

Step 6:

- Create an A class for an anchor (link) element. Its constructor should look like: `A(self, link, content)` – where link is the link, and content is what you see. It can be called like so: `A("http://google.com", "link")`
- You should be able to subclass from Element, and only override the `__init__`
 - Calling the Element `__init__` from the A `__init__`

You can now add a link to your web page.

LAB

Step 7:

- Create `Ul` class for an unordered list (really simple subclass of `Element`)
- Create `Li` class for an element in a list (also really simple)
- add a list to your web page.
- Create a `Header` class – this one should take an integer argument for the header level. i.e `<h1>`, `<h2>`, `<h3>`, called like:
 - `H(2, "The text of the header")` for an `<h2>` header
- It can subclass from `OneLineTag` – overriding the `__init__`, then calling the superclass `__init__`

LAB

Step 8:

- Update the `Html` element class to render the `"<!DOCTYPE html>"` tag at the head of the page, before the `html` element.
- You can do this by subclassing `Element`, overriding `render()`, but then calling `Element.render()` from `Html.render()`.
- Create a subclass of `SelfClosingTag` for `<meta charset="UTF-8" />` and add the meta element to the beginning of the head element to give your document an encoding.
- The doctype and encoding are HTML 5 and you can check this at: validator.w3.org.

You now have a pretty full-featured html renderer

Review of HTML renderer lab

You have built an html generator, using:

- A Base Class with a couple methods
- Subclasses overriding class attributes
- Subclasses overriding a method
- Subclasses overriding the `__init__`

These are the core OO approaches

If you don't have it working, or don't think you "get" it:
work on it for homework, and ask questions.

Lightning Talks

Lightning Talks:

Sridharan Rajagopalan

Richard Smith

multiple inheritance

Multiple inheritance:
Pulling from more than one class

```
class Combined(Super1, Super2, Super3):  
    def __init__(self, something, something else):  
        Super1.__init__(self, .....)  
        Super2.__init__(self, .....)  
        Super3.__init__(self, .....)
```

(calls to the super class `__init__` are optional – case dependent)

Attribute resolution – left to right

(Why would you want to do this?)

mix-ins

Hierarchies are not always simple

- Animal
 - Mammal
 - GiveBirth()
 - Bird
 - LayEggs()

Where do you put a Platypus or an Armadillo?

Real World Example: FloatCanvas

New Style classes

You will see reference to “new style” classes

These derive from `object`

Introduced in python2.2 to better merge types and classes, and clean up a few things

differences in method resolution order and properties

Mostly the same, often makes no difference

My advice: always subclass from `object`

Wrap Up

Thinking OO in Python:

Think about what makes sense for your code:

- Code re-use
- Clean APIs
- ...

Don't be a slave to what OO is *supposed* to look like.

Let OO work for you, not *create* work for you

Wrap Up

OO in Python:

The Art of Subclassing: Raymond Hettinger

<http://pyvideo.org/video/879/the-art-of-subclassing>

"classes are for code re-use – not creating taxonomies"

Stop Writing Classes: Jack Diederich

<http://pyvideo.org/video/880/stop-writing-classes>

"If your class has only two methods – and one of them is `__init__` – you don't need a class "

Homework

Finish the labs.

Watch the videos.

Readup more on OO design.

Your Project:

- By next week, send me a project proposal: can be short and sweet.
- Think about how you might use OO:
 - What classes naturally fall out of the problem?
 - NOTE: maybe none!

Homework

Recommended Reading:

- some stuff

Do:

- Some things