

```
app.use(express.urlencoded({ extended: true }))
     app.use(express.static(__dirname))
     app.get('/get-students', (req, res) => {
21
         conn.query('select * from Students',
             function (err, rows) {
                if (err) {
                    console.log("☆ ~ app.get ~ err:", err)
                    rows.forEach(element => {
                        console.log("৵ ~ app.get ~ element:", element)
34
PROBLEMS 1
                                      TERMINAL
                                                        SQL CONSOLE
 serverStatus: 2,
 warningStatus: 0,
 changedRows: 0
(base) akshaypatel@Akshays-MacBook-Pro Q1 %
(base) akshaypatel@Akshays-MacBook-Pro Q1 % node server.js
fieldCount: 0, affectedRows: 1,
  insertId: 793,
 info: '
 serverStatus: 2, warningStatus: 0,
 changedRows: 0
(base) akshaypatel@Akshays-MacBook-Pro Q1 %
(base) akshaypatel@Akshays-MacBook-Pro Q1 % node server.js
server is up
```

← → C (i) 127.0.0.1:3000/students.html
Name ? Akshay
GPA ? 3.4
save





G ① 127.0.0.1:3000/get-students-by-gpa?min=3&max=4

- 1. Akshay = 3.4
- 2. Akshay = 3.4
- 3. Akshay = 3.4 4. Akshay = 3.4 5. Maria = 3.3

- 6. Susan = 3.1

