

Hydrostatics

Water density : 1.0250

Trim: 0.000 m

Draft m	Displ FW t	Displ. t	LCB m	VCB m	TCB m	KMt m	KMI m	MCT t*m/cm	TpCm t/cm
0.200	1.023	1.049	6.607	0.130	0.000	2.386	21.289	0.02	0.097
0.300	2.138	2.191	6.450	0.194	0.000	2.035	20.661	0.04	0.131
0.400	3.565	3.654	6.308	0.257	0.000	1.835	19.484	0.06	0.161
0.500	5.256	5.388	6.178	0.320	0.000	1.722	18.199	0.08	0.186
0.600	7.182	7.362	6.057	0.382	0.000	1.660	17.063	0.10	0.209
0.700	9.322	9.555	5.941	0.443	0.000	1.624	16.178	0.13	0.230
0.800	11.660	11.951	5.831	0.505	0.000	1.596	15.471	0.15	0.249
0.900	14.156	14.510	5.733	0.566	0.000	1.565	14.145	0.16	0.262
1.000	16.755	17.174	5.657	0.626	0.000	1.525	12.837	0.17	0.270

NOTE 1: Draft (and all other vertical heights) is measured from base Z=0.000

NOTE 2: All calculated coefficients based on project length, draft and beam.

Nomenclature

Draft	<i>Moulded draft, measured from baseline</i>
Displ FW	<i>Displacement fresh water</i>
Displ.	<i>Displacement</i>
LCB	<i>Longitudinal center of buoyancy, measured from the aft perpendicular at X=0.0</i>
VCB	<i>Vertical center of buoyancy</i>
TCB	<i>Transverse center of buoyancy</i>
KMt	<i>Transverse metacentric height</i>
KMI	<i>Longitudinal metacentric height</i>
MCT	<i>Moment to change trim one unit</i>
TpCm	<i>Weight to change the immersion with one unit</i>