

Assignment-17

AI Assisted Coding

NAME : P.Arun Reddy

HT NO : 2303A52278

BATCH : 36

Lab 17 – AI for Data Processing: Data Cleaning and Preprocessing Scripts

Objective

- To clean raw datasets using Python and AI-assisted scripting.
- To handle missing values, remove duplicates, and standardize data.
- To encode categorical variables and normalize numerical data.
- To automate preprocessing tasks for efficient data analysis.
- To understand the importance of preprocessing in improving model performance.

Task 1 – Customer Data Cleaning

Aim

To clean and preprocess a customer shopping dataset.

Procedure

- Loaded dataset using Pandas.
- Handled missing values in Age, Income, and City columns.
- Removed duplicate records.
- Standardized city names to lowercase.
- Encoded categorical variables such as Gender and City.

Code

```
import pandas as pd
```

```
df = pd.read_csv("shopping_trends.csv")
```

```
df['Age'] = df['Age'].fillna(df['Age'].median())
```

```
df['Purchase Amount (USD)'] = df['Purchase Amount (USD)'].fillna(df['Purchase Amount
```

```
(USD)'].mean())
df['Location'] = df['Location'].fillna(df['Location'].mode()[0])

df = df.drop_duplicates()

df['Location'] = df['Location'].str.lower().str.strip()

df = pd.get_dummies(df, columns=['Gender', 'Location'], drop_first=True)

print(df.head())
```

Result

A cleaned dataset with no missing values, standardized text, and encoded categorical features.

```
import pandas as pd

# Load dataset
df = pd.read_csv("../content/shopping_trends_updated.csv")

# Handle missing values
df['Age'] = df['Age'].fillna(df['Age'].median())
df['Purchase Amount (USD)'] = df['Purchase Amount (USD)'].fillna(df['Purchase Amount (USD)'].mean())
df['Location'] = df['Location'].fillna(df['Location'].mode()[0])

# Remove duplicates
df = df.drop_duplicates()

# Standardize text (city/location)
df['Location'] = df['Location'].str.lower().str.strip()

# Encode categorical variables
df = pd.get_dummies(df, columns=['Gender', 'Location'], drop_first=True)

print(df.head())
```

	Customer ID	Age	Item Purchased	Category	Purchase Amount (USD)	Size	\
0	1	35	Blouse	Clothing	53	L	
1	2	19	Sweater	Clothing	64	L	
2	3	50	Jeans	Clothing	73	S	
3	4	21	Sandals	Footwear	90	M	
4	5	45	Blouse	Clothing	49	M	

	Color	Season	Review Rating	Subscription Status	...	\
0	Gray	Winter	3.1	Yes	...	
1	Maroon	Winter	3.1	Yes	...	
2	Maroon	Spring	3.1	Yes	...	
3	Maroon	Spring	3.5	Yes	...	
4	Turquoise	Spring	2.7	Yes	...	

	Location_south_dakota	Location_tennessee	Location_texas	Location_utah	\
0	False	False	False	False	
1	False	False	False	False	
2	False	False	False	False	
3	False	False	False	False	
4	False	False	False	False	

	Location_vermont	Location_virginia	Location_washington	\
0	False	False	False	
1	False	False	False	
2	False	False	False	
3	False	False	False	
4	False	False	False	

	Location_west_virginia	Location_wisconsin	Location_wyoming
0	False	False	False
1	False	False	False
2	False	False	False
3	False	False	False
4	False	False	False

[5 rows x 66 columns]

Task 2 – Sales Data Preprocessing

Aim

To preprocess sales transaction data and create useful features.

Procedure

- Converted date column into datetime format.
- Extracted month, year, and day of the week.

- Normalized the sales column using Min-Max scaling.
- Detected and removed outliers using the IQR method.

Code

```
import pandas as pd
from sklearn.preprocessing import MinMaxScaler

df = pd.read_csv("sales_data.csv")

df['date'] = pd.to_datetime(df['date'])

df['month'] = df['date'].dt.month
df['year'] = df['date'].dt.year
df['day_of_week'] = df['date'].dt.dayofweek

scaler = MinMaxScaler()
df['sales'] = scaler.fit_transform(df[['sales']])

Q1 = df['sales'].quantile(0.25)
Q3 = df['sales'].quantile(0.75)
IQR = Q3 - Q1

df = df[(df['sales'] >= Q1 - 1.5*IQR) & (df['sales'] <= Q3 + 1.5*IQR)]

print(df.head())
```

Result

A transformed dataset with normalized values and additional time-based features.

```

import pandas as pd
from sklearn.preprocessing import MinMaxScaler

df = pd.read_csv("/content/sales_data.csv")

# Convert date
df['Sale Date'] = pd.to_datetime(df['Sale Date'])

# Feature engineering
df['month'] = df['Sale Date'].dt.month
df['year'] = df['Sale Date'].dt.year
df['day_of_week'] = df['Sale Date'].dt.dayofweek

# Normalize sales
scaler = MinMaxScaler()
df['sales'] = scaler.fit_transform(df[['Sales Amount']])

# Outlier removal (IQR method)
Q1 = df['sales'].quantile(0.25)
Q3 = df['sales'].quantile(0.75)
IQR = Q3 - Q1

df = df[(df['sales'] >= Q1 - 1.5*IQR) & (df['sales'] <= Q3 + 1.5*IQR)]

print(df.head())

```

	Product ID	Sale Date	Sales Rep	Region	Sales Amount	Quantity Sold	\
0	1052	2023-03-03	Bob	North	5853.97	18	
1	1093	2023-04-21	Bob	West	4386.02	17	
2	1015	2023-09-21	David	South	4631.23	30	
3	1072	2023-08-24	Bob	South	2187.94	39	
4	1061	2023-03-24	Charlie	East	3750.20	13	

	Product Category	Unit Cost	Unit Price	Customer Type	Discount	\
0	Furniture	152.75	267.22	Returning	0.09	
1	Furniture	3816.30	4289.44	Returning	0.11	
2	Food	261.56	371.68	Returning	0.20	
3	Clothing	4330.03	4667.75	New	0.02	
4	Electronics	637.37	692.71	New	0.08	

	Payment Method	Sales Channel	Region and Sales Rep	month	year	day_of_week	\
0	Cash	Online	North-Bob	2	2023	4	
1	Cash	Retail	West-Bob	4	2023	4	
2	Bank Transfer	Retail	South-David	9	2023	3	
3	Credit Card	Retail	South-Bob	8	2023	3	
4	Credit Card	Online	East-Charlie	3	2023	4	

	sales
0	0.508950
1	0.433202
2	0.458201
3	0.200105
4	0.300108

Task 3 – Healthcare Data Preparation

Aim

To preprocess healthcare data for machine learning.

Procedure

- Filled missing values in blood pressure and cholesterol.
- Encoded categorical variables using Label Encoding.
- Scaled numerical features using Standard Scaling.
- Split dataset into training and testing sets.

Code

```

import pandas as pd
from sklearn.preprocessing import StandardScaler, LabelEncoder
from sklearn.model_selection import train_test_split

df = pd.read_csv("healthcare_dataset.csv")

df['blood_pressure'] = df['blood_pressure'].fillna(df['blood_pressure'].mean())
df['cholesterol'] = df['cholesterol'].fillna(df['cholesterol'].mean())

le = LabelEncoder()

```

```
for col in df.select_dtypes(include='object').columns:
```

```
    df[col] = le.fit_transform(df[col])
```

```
scaler = StandardScaler()
```

```
df[['blood_pressure', 'cholesterol']] = scaler.fit_transform(df[['blood_pressure', 'cholesterol']])
```

```
X = df.drop('target', axis=1)
```

```
y = df['target']
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2)
```

```
print(X_train.shape, X_test.shape)
```

Result

A fully preprocessed dataset split into training and testing sets, ready for model training.

```
import pandas as pd
from sklearn.preprocessing import StandardScaler, LabelEncoder
from sklearn.model_selection import train_test_split

df = pd.read_csv("/content/dirty_v1_path.csv")

# Handle missing values
df['Blood Pressure'] = df['Blood Pressure'].fillna(df['Blood Pressure'].mean())
df['Cholesterol'] = df['Cholesterol'].fillna(df['Cholesterol'].mean())

# Encode categorical
le = LabelEncoder()
for col in df.select_dtypes(include='object').columns:
    df[col] = le.fit_transform(df[col])

# Scale numerical features
scaler = StandardScaler()
num_cols = ['Blood Pressure', 'Cholesterol']
df[num_cols] = scaler.fit_transform(df[num_cols])

# Split data
X = df.drop('Medical Condition', axis=1)
y = df['Medical Condition']

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2)

print(X_train.shape, X_test.shape)

(20000, 10) (5000, 10)
```

Task 4 – Employee Salary Data Preprocessing

Aim

To clean and preprocess employee salary data for analysis.

Procedure

- Handled missing values using forward fill.
- Removed salary outliers using the IQR method.
- Standardized department names to lowercase.
- Encoded job location and department using Label Encoding.

Code

```
import pandas as pd
```

```
from sklearn.preprocessing import LabelEncoder
```

```
df = pd.read_csv("employee_salary.csv")
```

```
df = df.fillna(method='ffill')
```

```
Q1 = df['salary'].quantile(0.25)
```

```
Q3 = df['salary'].quantile(0.75)
```

```
IQR = Q3 - Q1
```

```
df = df[(df['salary'] >= Q1 - 1.5*IQR) & (df['salary'] <= Q3 + 1.5*IQR)]
```

```
df['department'] = df['department'].str.lower().str.strip()
```

```
le = LabelEncoder()
```

```
df['job_location'] = le.fit_transform(df['job_location'])
```

```
df['department'] = le.fit_transform(df['department'])
```

```
print(df.head())
```

Result

A structured dataset with cleaned and encoded features suitable for HR analytics.

```
import pandas as pd
from sklearn.preprocessing import MinMaxScaler

df = pd.read_csv("../content/sales_data.csv")

# Convert date
df['Sale_Date'] = pd.to_datetime(df['Sale_Date'])

# Feature engineering
df['month'] = df['Sale_Date'].dt.month
df['year'] = df['Sale_Date'].dt.year
df['day_of_week'] = df['Sale_Date'].dt.dayofweek

# Normalize sales
scaler = MinMaxScaler()
df['sales'] = scaler.fit_transform(df[['Sales_Amount']])

# Outlier removal (IQR method)
Q1 = df['sales'].quantile(0.25)
Q3 = df['sales'].quantile(0.75)
IQR = Q3 - Q1

df = df[(df['sales'] >= Q1 - 1.5*IQR) & (df['sales'] <= Q3 + 1.5*IQR)]

print(df.head())
```

	Product_ID	Sale_Date	Sales_Rep	Region	Sales_Amount	Quantity_Sold	\
0	1852	2023-02-03	Bob	North	5853.97	18	
1	1803	2023-04-21	Bob	West	4384.82	17	
2	1815	2023-09-21	David	South	4631.23	38	
3	1872	2023-08-24	Bob	South	2167.94	39	
4	1861	2023-01-24	Charlie	East	3758.20	13	

	Product_Category	Unit_Cost	Unit_Price	Customer_Type	Discount	\
0	Furniture	152.75	267.22	Returning	0.09	
1	Furniture	3116.20	4209.44	Returning	0.11	
2	Food	261.56	371.68	Returning	0.28	
3	Clothing	4338.83	4467.75	New	0.82	
4	Electronics	637.37	692.71	New	0.08	

	Payment_Method	Sales_Channel	Region_and_Sales_Rep	month	year	day_of_week	\
0	Cash	Online	North-Bob	2	2023	4	
1	Cash	Retail	West-Bob	4	2023	4	
2	Bank Transfer	Retail	South-David	9	2023	3	
3	Credit Card	Retail	South-Bob	8	2023	3	
4	Credit Card	Online	East-Charlie	3	2023	4	

	sales
0	0.508958
1	0.433282
2	0.458281
3	0.389185
4	0.389188

Conclusion

Data preprocessing is a crucial step in machine learning as it ensures data quality, consistency, and reliability. Proper handling of missing values, encoding, normalization, and outlier removal significantly improves model accuracy and performance.

