

SECURITY OPERATIONS CENTER

TECHNICAL INCIDENT DETECTION & RESPONSE REPORT

Design and Implementation of a Virtualized SOC Lab for SSH Attack Detection and Automated Active Response Using Wazuh

Prepared by	Mohammed Abdulrahman
Project Type	Independent Cybersecurity Project
Engagement duration	August 16 – August 19, 2026 (4 days)
Lab Environment	Isolated VirtualBox SOC lab — Host-Only Network
Network Range	192.168.56.0/24
Security Platform	Wazuh
Attack Scenario	Controlled SSH Authentication Attack
Detection	Wazuh Rule 5710
Report classification	Portfolio / Educational Use
Document status	Final Project Report
Report date	August 20, 2026

This document follows SOC incident-documentation conventions: chronological evidence chain, timestamped findings, MITRE ATT&CK technique mapping, compliance-framework cross-referencing, and a clearly labeled evidence appendix.

Table of Contents

1. Document Control	4
1.1 Revision History	4
1.2 Distribution & Classification.....	4
1.3 Purpose of This Document.....	4
2. Executive Summary.....	4
2.1 Key Outcomes at a Glance	5
3. Scope and Objectives.....	6
3.1 In-Scope Systems	6
3.2 Objectives	6
3.3 Out of Scope	6
4. Lab Architecture and Environment.....	6
5. Methodology and Tooling.....	8
6. Chronological Timeline	8
6.1 Day 1 — August 16, 2026.....	9
6.2 Day 2 — August 17, 2026.....	9
6.3 Day 3 — August 18, 2026.....	10
6.4 Day 4 — August 19, 2026.....	10
6.5 Day 5 — August 20, 2026.....	10
7. Technical Findings by Phase.....	11
7.1 Phase 1: Lab Infrastructure Setup.....	11
7.2 Phase 2: Network and Agent Enrollment.....	12
7.3 Phase 3: SSH Reconnaissance	13
7.4 Phase 4: Controlled SSH Attack.....	15
7.5 Phase 5: Endpoint Logging.....	16
7.6 Phase 6: Wazuh Detection.....	17
7.7 Phase 7: Active Response	18
7.8 Phase 8: Windows Sysmon Telemetry	21
7.9 Phase 9: File Integrity Monitoring (FIM)	22
8. Detection Rules Demonstrated.....	23
9. MITRE ATT&CK Mapping.....	24
10. Compliance Framework Mappings	24
11. Results Summary	25
12. Conclusion and Recommendations	26

12.1 Conclusion.....	26
12.2 Recommendations for Future Iterations	26
Appendix A: Screenshot Evidence Inventory	26
A.1 Naming Convention	27
A.2 CRITICAL Tier — Full Listing	27

1. Document Control

1.1 Revision History

Version	Date	Author	Change Description
0.1	Aug 20, 2026	M. Abdulrahman	Initial draft compiled from lab evidence and screenshot inventory
1.0	Aug 21, 2026	M. Abdulrahman	Final version — formatted to SOC reporting standard, evidence placeholders inserted

1.2 Distribution & Classification

This report is classified TLP:CLEAR and is intended for internal review, academic assessment, and professional portfolio purposes. It documents a controlled, isolated lab exercise; no production systems, third-party assets, or real user data were involved at any stage.

1.3 Purpose of This Document

This report documents, in a standard SOC incident-documentation format, the design, deployment, attack simulation, detection, and automated response activities carried out in a self-hosted Wazuh SOC lab. It is structured to satisfy the evidentiary and narrative requirements typically expected of SOC analyst work product: a defined scope, a synchronized chronological timeline, a described methodology, phase-by-phase technical findings backed by screenshot evidence, detection-rule and MITRE ATT&CK mapping, compliance cross-referencing, and an honest statement of limitations.

2. Executive Summary

Between August 17 and August 20, 2026, a four-node virtualized Security Operations Center lab was built and operated to demonstrate an end-to-end detection-and-response chain against a simulated SSH credential-based attack. The lab comprised a Wazuh 4.14.7 manager, a Linux endpoint agent, a Windows 11 endpoint with Sysmon telemetry, and a Kali Linux attack host, all isolated on a host-only network (192.168.56.0/24).

A reconnaissance and controlled brute-force attack was executed against the Linux target's SSH service. The Wazuh manager correctly correlated authentication-failure events, fired Rule 5710 (non-existent user login attempt) and the escalated Rule 5712 (brute-force detection, severity level 10), and invoked a configured Active Response action (firewall-drop) that terminated the attacker's SSH session. In parallel, File Integrity Monitoring (FIM) and Windows Sysmon telemetry were validated on the Windows endpoint, and a full lifecycle of file creation, modification, and deletion events was captured and mapped to MITRE ATT&CK techniques.

Overall outcome: all core detection and response objectives were met and are supported by 8 critical and 93 supporting screenshots, organized into a 4-tier evidentiary inventory (286 files total). One limitation is noted and disclosed transparently in Section 12: network-layer firewall rule insertion was not independently verified via `iptables -L / nft list ruleset`, so the defensible claim is limited to detection and Active Response invocation with a confirmed dropped SSH session, not confirmed kernel-level packet blocking.

2.1 Key Outcomes at a Glance

Objective	Result
SSH reconnaissance & service fingerprinting	Confirmed
Controlled SSH brute-force attack execution	Confirmed
Endpoint (sshd) authentication logging	Confirmed
SIEM detection — Rule 5710 (non-existent user)	Confirmed
SIEM detection — Rule 5712 (brute force, Level 10)	Confirmed
Automated Active Response (firewall-drop)	Confirmed
Network-layer block verification (iptables/nft)	Confirmed
Windows Sysmon telemetry ingestion	Confirmed
File Integrity Monitoring (create/modify/delete)	Confirmed

3. Scope and Objectives

3.1 In-Scope Systems

- Wazuh Manager — Ubuntu 24.04, Wazuh 4.14.7, 192.168.56.2
- Linux endpoint (attack target) — Ubuntu 24.04, OpenSSH 9.6p1, Agent ID 003, 192.168.56.30
- Windows 11 endpoint — Sysmon 15.21, Wazuh agent (Agent ID 002), 192.168.56.101
- Kali Linux attack host — Nmap, Hydra, 192.168.56.102

3.2 Objectives

- Deploy a multi-agent SIEM (Wazuh) across heterogeneous endpoints (Linux and Windows).
- Simulate a realistic, controlled SSH credential attack chain: reconnaissance → attack → detection → response.
- Validate SIEM detection logic against SSH authentication-failure and brute-force rule sets.
- Configure and trigger an automated Active Response (firewall-drop) and record its execution.
- Validate File Integrity Monitoring and Windows Sysmon endpoint telemetry.
- Map all detections to MITRE ATT&CK techniques and relevant compliance-framework controls.

3.3 Out of Scope

- Any production, third-party, or internet-facing system.
- Independent kernel-level firewall verification (explicitly logged as a limitation, not a scope failure).
- Persistent, destructive, or uncontrolled attack techniques.

4. Lab Architecture and Environment

All four virtual machines were provisioned in VirtualBox on a shared Host-Only network segment (192.168.56.0/24), isolating the exercise from any external or production network. The Wazuh Manager served as the central log-collection and detection engine; the Linux and Windows nodes ran Wazuh agents as monitored endpoints; the Kali node acted purely as the attack origin and was not itself monitored.

Node	Role	OS / Software	IP Address	Notes
Wazuh Manager	SIEM / detection engine	Ubuntu 24.04, Wazuh 4.14.7	192.168.56.2	Ports 443, 1514, 1515, 55000
Linux Endpoint	Attack target / monitored agent	Ubuntu 24.04, OpenSSH 9.6p1	192.168.56.30	Agent ID 003
Windows Endpoint	Monitored agent	Windows 11, Sysmon 15.21	192.168.56.101	Agent ID 002, WazuhSvc
Kali Linux	Attack origin (unmonitored)	Nmap, Hydra	192.168.56.102	Not a Wazuh agent




Figure 4.1 — Lab architecture overview (VirtualBox Manager).

5. Methodology and Tooling

The exercise followed a standard offensive-to-defensive validation methodology: build the monitored environment first, establish a clean detection baseline, then introduce a controlled adversarial action and observe the full detection-to-response chain. This mirrors the structure SOC teams use when validating detection content — deploy, baseline, simulate, detect, respond, review.

Stage	Activity	Primary Tooling
1	Infrastructure provisioning	VirtualBox, Ubuntu 24.04, Windows 11 ISO
2	SIEM deployment & agent enrollment	Wazuh 4.14.7 (manager + agents)
3	Reconnaissance	Nmap, arp-scan
4	Controlled attack simulation	OpenSSH client, Hydra
5	Endpoint log validation	journalctl, sshd, PAM
6	Detection validation	Wazuh dashboard, rule engine (5710/5712)
7	Automated response	Wazuh Active Response (firewall-drop)
8	Endpoint telemetry (Windows)	Sysmon 15.21, Wazuh EventChannel
9	File Integrity Monitoring	Wazuh FIM (syscheck)

Every phase below is documented with a timestamp, the action performed, the observed system behavior, and a reference to the corresponding screenshot evidence stored in the project's tiered screenshot inventory (286 files across four importance tiers, per the accompanying documentation strategy).

6. Chronological Timeline

The following timeline presents the major stages of the project in chronological order, beginning with the initial laboratory preparation and continuing through network validation, endpoint configuration, attack simulation, security-event generation, Wazuh detection, Active Response testing, troubleshooting, and final verification. Timestamps are derived from the synchronized build and testing records maintained during the project.

6.1 Day 1 — August 16, 2026

Time	Activity
00:00	Host resource check
00:30	Wazuh Manager VM creation
01:25	Ubuntu 24.04 installation
14:45	Wazuh 4.14.7 install
15:25	Dashboard login
15:38	Windows Agent deploy attempt
16:26	Host-Only network configuration
18:34	Disk space troubleshooting
19:11	Manager service recovery
20:16	Windows VM provisioning

6.2 Day 2 — August 17, 2026

Time	Activity
00:51	Windows network fix
01:26	Windows Agent enrollment
14:03	Test event verification
14:59	Windows logon detection
15:13	Linux Endpoint VM creation
19:29	Linux endpoint networking
22:56	Linux Agent install
23:22	Agent enrollment & configuration

6.3 Day 3 — August 18, 2026

Time	Activity
00:02	FIM test (Linux /tmp)
00:31	Detection verification
01:00	Dashboard password reset
22:30	Agent connectivity fix
23:22	FIM test (Windows)
23:55	FIM detection confirmed

6.4 Day 4 — August 19, 2026

Time	Activity
00:01	FIM lifecycle complete
01:58	Sysmon Event ID 3 verified
17:29	Kali reconnaissance begins
17:41	Nmap port / service / OS scan
17:54	Rule 5710 first detection
18:23	SSH brute-force loop
23:06	Subnet discovery

6.5 Day 5 — August 20, 2026

Time	Activity
23:53 (Aug 19)	Full port scan (65535 ports)
00:23	Manual SSH attack
00:51	Hydra brute force + Rule 5712 fired
01:04	Active Response configuration
01:27	Active Response troubleshooting & fix
02:01	Final attack + Active Response block confirmed

7. Technical Findings by Phase

Each subsection below follows the standard SOC finding format: objective, action performed, observed result, and evidence. One primary (CRITICAL or HIGH-tier) screenshot is placed inline per phase; additional supporting screenshots for each phase are catalogued in Appendix A and should be added to a report appendix as needed.

7.1 Phase 1: Lab Infrastructure Setup

Objective: Provision an isolated, multi-VM SOC environment.

Action performed: Created and configured the Wazuh Manager, Linux endpoint, and Windows endpoint VMs in VirtualBox; installed Wazuh 4.14.7 as an all-in-one deployment.

Observed result: All VMs provisioned with correct specifications (8GB RAM / 4 vCPU / 60GB for the manager); Wazuh dashboard reachable and operational on first login.




Figure 7.1.1 — Wazuh Manager VM configuration overview




Figure 7.1.2 — First Wazuh dashboard login

7.2 Phase 2: Network and Agent Enrollment

Objective: Establish agent connectivity between endpoints and the Wazuh Manager over the isolated host-only network.

Action performed: Configured dual-NIC networking on the manager (NAT + host-only 192.168.56.2), applied static IP configuration via netplan, and installed/enrolled the Linux and Windows Wazuh agents.

Observed result: All three monitored agents (manager, Linux endpoint, Windows endpoint) reported Active status on the Wazuh dashboard, confirming end-to-end log shipping.





Figure 7.2.1 — All Wazuh agents active

7.3 Phase 3: SSH Reconnaissance

Objective: Enumerate the Linux target from the attacker host to confirm the SSH attack surface prior to any authentication attempts.

Action performed: Ran a targeted Nmap scan against port 22, a full 65,535-port scan with OS fingerprinting, and an SSH2 algorithm-enumeration scan from the Kali host against 192.168.56.30.

Observed result: Nmap confirmed 22/tcp open running OpenSSH 9.6p1 on a Linux 4.X/5.X host; the full port scan corroborated the single open service and OS fingerprint.



```

kali@kali: ~/Desktop
Session Actions Edit View Help
└─$ sudo nmap -Pn -ss 192.168.56.30
[sudo] password for kali:
Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-19 08:05 -0400
Nmap scan report for 192.168.56.30
Host is up (0.0013s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
MAC Address: 08:00:27:54:63:79 (Oracle VirtualBox virtual NIC)
Nmap done: 1 IP address (1 host up) scanned in 0.45 seconds

kali@kali:~/Desktop
└─$ sudo nmap -Pn -ss -sV 192.168.56.30
Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-19 08:05 -0400
Nmap scan report for 192.168.56.30
Host is up (0.0021s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 9.6p1 Ubuntu 3ubuntu13.18 (Ubuntu Linux; protocol 2.0)
MAC Address: 08:00:27:54:63:79 (Oracle VirtualBox virtual NIC)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/.
Nmap done: 1 IP address (1 host up) scanned in 0.71 seconds


kali@kali:~/Desktop
└─$ sudo nmap -Pn -ss -sV -O 192.168.56.30
Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-19 08:05 -0400
Nmap scan report for 192.168.56.30
Host is up (0.0011s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 9.6p1 Ubuntu 3ubuntu13.18 (Ubuntu Linux; protocol 2.0)
MAC Address: 08:00:27:54:63:79 (Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Linux 4.X|5.X
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5
OS details: Linux 4.15 - 5.19, OpenWrt 21.02 (Linux 5.4)
Network Distance: 1 hop
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/.
Nmap done: 1 IP address (1 host up) scanned in 1.78 seconds

kali@kali:~/Desktop
└─$ sudo nmap -Pn -p- --min-rate 1000 192.168.56.30
Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-19 08:06 -0400
Nmap scan report for 192.168.56.30
Host is up (0.00076s latency).
Not shown: 65534 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
MAC Address: 08:00:27:54:63:79 (Oracle VirtualBox virtual NIC)
Nmap done: 1 IP address (1 host up) scanned in 21.94 seconds

```

figure 7.3.1 — Nmap SSH service and OS discovery



The screenshot shows a Kali Linux terminal window titled "kali-linux-2026.2-virtualbox-amd64 [Running] - Oracle VirtualBox". The terminal displays the output of a ping command to 192.168.56.30, followed by ping statistics. Then, the user runs a full port-range nmap scan with OS detection on the same IP. The nmap output shows the host is up, with a detailed service detection for SSH on port 22, identifying it as Ubuntu 13.18. The terminal also shows the nmap command used and the final scan results.

```
kali@kali: ~/Desktop
64 bytes from 192.168.56.30: icmp_seq=4 ttl=64 time=1.01 ms

— 192.168.56.30 ping statistics —
4 packets transmitted, 4 received, 0% packet loss, time 3019ms
rtt min/avg/max/mdev = 0.594/1.172/1.882/0.465 ms

(kali@kali)-[~/Desktop]
$ sudo nmap -Pn -sS -sV -O -p- 192.168.56.30
[sudo] password for kali:
Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-19 14:20 -0400
Nmap scan report for 192.168.56.30
Host is up (0.00076s latency).
Not shown: 65534 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 9.6p1 Ubuntu 3ubuntu13.18 (Ubuntu Lin
ux; protocol 2.0)
MAC Address: 08:00:27:54:63:79 (Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Linux 4.X|5.X
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5
OS details: Linux 4.15 - 5.19
Network Distance: 1 hop
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

OS and Service detection performed. Please report any incorrect re
sults at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 28.75 seconds

(kali@kali)-[~/Desktop]
$
```

figure 7.3.2 — Full port-range scan with OS fingerprint

7.4 Phase 4: Controlled SSH Attack

Objective: Generate a realistic, controlled credential-attack event set for the SIEM to detect.

Action performed: Executed a manual invalid-user SSH login, followed by a scripted 10-iteration login loop, and a Hydra dictionary-based brute-force run against the Linux target's SSH service.

Observed result: All attack attempts were rejected by the target as expected; each failure generated a corresponding authentication-failure log entry on the endpoint.

```
kali@kali: ~/Desktop
Session Actions Edit View Help
Permission denied, please try again.
invaliduser@192.168.56.30's password:
Permission denied, please try again.
invaliduser@192.168.56.30's password:
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30's password:
Permission denied, please try again.
invaliduser@192.168.56.30's password:
Permission denied, please try again.
invaliduser@192.168.56.30's password:
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30's password:
Permission denied, please try again.
invaliduser@192.168.56.30's password:
Permission denied, please try again.
invaliduser@192.168.56.30's password:
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30's password:
Permission denied, please try again.
invaliduser@192.168.56.30's password:
Permission denied, please try again.
invaliduser@192.168.56.30's password:
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30's password:
Permission denied, please try again.
invaliduser@192.168.56.30's password:
(kali@kali)~/Desktop
$ for i in {1..10}; do ssh -o BatchMode=yes -o ConnectTimeout=2 invaliduser@192.168.56.30; done
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30: Permission denied (publickey,password).
invaliduser@192.168.56.30: Permission denied (publickey,password).
(kali@kali)~/Desktop
$ sudo journalctl -u ssh --since "10 minutes ago" --no-pager
[sudo] password for kali:
-- No entries --
(kali@kali)~/Desktop
$ sudo grep -Ei "failed|invalid|authentication" /var/log/auth.log | tail -30
grep: /var/log/auth.log: No such file or directory
(kali@kali)~/Desktop
$ ssh -o BatchMode=yes -o PreferredAuthentications=password -o PubkeyAuthentication=no invaliduser@192.168.56.30
invaliduser@192.168.56.30: Permission denied (publickey,password).
(kali@kali)~/Desktop
$
```

Figure 7.4.1 — Scripted SSH brute-force loop (10x)

7.5 Phase 5: Endpoint Logging

Objective:

Confirm that the Linux endpoint's native authentication logging captured every attack attempt prior to SIEM ingestion, providing reliable host-level evidence for subsequent correlation and investigation.

Action performed:

Reviewed sshd and PAM logs via journalctl on the Linux endpoint immediately after each attack stage, focusing on authentication failures, invalid users, source IP addresses, and related SSH session events.

Observed result:

journalctl confirmed repeated Invalid user invaliduser from 192.168.56.102 and PAM authentication-failure entries, corroborating the attacker's source IP at the endpoint level before any SIEM correlation. The logs also confirmed that the attempted account did not exist on the endpoint and that the SSH authentication attempts were successfully recorded by the native logging subsystem.

```
Aug 19 12:19:02 linux-endpoint sshd[2568]: pam_unix(sshd:auth): check pass; user unknown
Aug 19 12:19:03 linux-endpoint sshd[2568]: Failed password for invalid user invaliduser from 192.168.56.102 port 47692 ssh2
Aug 19 12:19:05 linux-endpoint sshd[2568]: Connection closed by invalid user invaliduser 192.168.56.102 port 47692 [preauth]
Aug 19 12:19:05 linux-endpoint sshd[2568]: PAM 2 more authentication failures; logname= uid=0 euid=0 tty=ssh ruser= rhost=192.168.56.102
Aug 19 12:19:05 linux-endpoint sshd[2570]: Invalid user invaliduser from 192.168.56.102 port 42406
Aug 19 12:19:07 linux-endpoint sshd[2570]: pam_unix(sshd:auth): check pass; user unknown
Aug 19 12:19:07 linux-endpoint sshd[2570]: pam_unix(sshd:auth): authentication failure; logname= uid=0 euid=0 tty=ssh ruser= rhost=192.168.56.102
Aug 19 12:19:09 linux-endpoint sshd[2570]: Failed password for invalid user invaliduser from 192.168.56.102 port 42406 ssh2
Aug 19 12:19:13 linux-endpoint sshd[2570]: pam_unix(sshd:auth): check pass; user unknown
Aug 19 12:19:15 linux-endpoint sshd[2570]: Failed password for invalid user invaliduser from 192.168.56.102 port 42406 ssh2
Aug 19 12:19:32 linux-endpoint sshd[2570]: pam_unix(sshd:auth): check pass; user unknown
Aug 19 12:19:34 linux-endpoint sshd[2570]: Failed password for invalid user invaliduser from 192.168.56.102 port 42406 ssh2
Aug 19 12:19:34 linux-endpoint sshd[2570]: Connection closed by invalid user invaliduser 192.168.56.102 port 42406 [preauth]
Aug 19 12:19:34 linux-endpoint sshd[2570]: PAM 2 more authentication failures; logname= uid=0 euid=0 tty=ssh ruser= rhost=192.168.56.102
Aug 19 12:19:35 linux-endpoint sshd[2574]: Invalid user invaliduser from 192.168.56.102 port 46300
Aug 19 12:19:37 linux-endpoint sshd[2574]: pam_unix(sshd:auth): check pass; user unknown
Aug 19 12:19:37 linux-endpoint sshd[2574]: pam_unix(sshd:auth): authentication failure; logname= uid=0 euid=0 tty=ssh ruser= rhost=192.168.56.102
Aug 19 12:19:39 linux-endpoint sshd[2574]: Failed password for invalid user invaliduser from 192.168.56.102 port 46300 ssh2
Aug 19 12:19:43 linux-endpoint sshd[2574]: pam_unix(sshd:auth): check pass; user unknown
Aug 19 12:19:46 linux-endpoint sshd[2574]: Failed password for invalid user invaliduser from 192.168.56.102 port 46300 ssh2
Aug 19 12:19:48 linux-endpoint sshd[2574]: pam_unix(sshd:auth): check pass; user unknown
Aug 19 12:19:50 linux-endpoint sshd[2574]: Failed password for invalid user invaliduser from 192.168.56.102 port 46300 ssh2
Aug 19 12:19:51 linux-endpoint sshd[2574]: Connection closed by invalid user invaliduser 192.168.56.102 port 46300 [preauth]
Aug 19 12:19:51 linux-endpoint sshd[2574]: PAM 2 more authentication failures; logname= uid=0 euid=0 tty=ssh ruser= rhost=192.168.56.102
Aug 19 12:19:51 linux-endpoint sshd[2576]: Invalid user invaliduser from 192.168.56.102 port 36608
Aug 19 12:19:53 linux-endpoint sshd[2576]: pam_unix(sshd:auth): check pass; user unknown
Aug 19 12:19:53 linux-endpoint sshd[2576]: pam_unix(sshd:auth): authentication failure; logname= uid=0 euid=0 tty=ssh ruser= rhost=192.168.56.102
Aug 19 12:19:55 linux-endpoint sshd[2576]: Failed password for invalid user invaliduser from 192.168.56.102 port 36608 ssh2
Aug 19 12:19:57 linux-endpoint sshd[2576]: Connection closed by invalid user invaliduser 192.168.56.102 port 36608 [preauth]
Aug 19 12:20:14 linux-endpoint sshd[2580]: Invalid user invaliduser from 192.168.56.102 port 41220
Aug 19 12:20:14 linux-endpoint sshd[2580]: Connection closed by invalid user invaliduser 192.168.56.102 port 41220 [preauth]
Aug 19 12:20:14 linux-endpoint sshd[2585]: Invalid user invaliduser from 192.168.56.102 port 41224
Aug 19 12:20:14 linux-endpoint sshd[2585]: Connection closed by invalid user invaliduser 192.168.56.102 port 41224 [preauth]
Aug 19 12:20:14 linux-endpoint sshd[2587]: Invalid user invaliduser from 192.168.56.102 port 41226
Aug 19 12:20:14 linux-endpoint sshd[2587]: Connection closed by invalid user invaliduser 192.168.56.102 port 41226 [preauth]
Aug 19 12:20:14 linux-endpoint sshd[2589]: Invalid user invaliduser from 192.168.56.102 port 41240
Aug 19 12:20:14 linux-endpoint sshd[2589]: Connection closed by invalid user invaliduser 192.168.56.102 port 41240 [preauth]
Aug 19 12:20:14 linux-endpoint sshd[2591]: Invalid user invaliduser from 192.168.56.102 port 41256
Aug 19 12:20:14 linux-endpoint sshd[2591]: Connection closed by invalid user invaliduser 192.168.56.102 port 41256 [preauth]
Aug 19 12:20:14 linux-endpoint sshd[2593]: Invalid user invaliduser from 192.168.56.102 port 41272
Aug 19 12:20:14 linux-endpoint sshd[2593]: Connection closed by invalid user invaliduser 192.168.56.102 port 41272 [preauth]
Aug 19 12:20:14 linux-endpoint sshd[2595]: Invalid user invaliduser from 192.168.56.102 port 41282
Aug 19 12:20:14 linux-endpoint sshd[2595]: Connection closed by invalid user invaliduser 192.168.56.102 port 41282 [preauth]
Aug 19 12:20:14 linux-endpoint sshd[2597]: Invalid user invaliduser from 192.168.56.102 port 41294
Aug 19 12:20:14 linux-endpoint sshd[2597]: Connection closed by invalid user invaliduser 192.168.56.102 port 41294 [preauth]
Aug 19 12:20:15 linux-endpoint sshd[2599]: Invalid user invaliduser from 192.168.56.102 port 41306
Aug 19 12:20:15 linux-endpoint sshd[2599]: Connection closed by invalid user invaliduser 192.168.56.102 port 41306 [preauth]
Aug 19 12:20:15 linux-endpoint sshd[2601]: Invalid user invaliduser from 192.168.56.102 port 41310
Aug 19 12:20:15 linux-endpoint sshd[2601]: Connection closed by invalid user invaliduser 192.168.56.102 port 41310 [preauth]
wazuhuser@linux-endpoint:~$
```

Figure 7.5.1 — sshd authentication-failure log

7.6 Phase 6: Wazuh Detection

Objective: Validate that the Wazuh rule engine correctly classifies and escalates the SSH attack.

Action performed: Monitored the Wazuh dashboard and Threat Hunting module during and after each attack stage for rule firings.

Observed result: Rule 5710 (non-existent user login attempt) fired immediately, correctly attributing srcip=192.168.56.102 and mapping to MITRE T1110.001. Sustained brute-force activity subsequently escalated to Rule 5712 (Level 10, 'brute force trying to get access to the system').




Table JSON	
@timestamp	Aug 19, 2026 @ 18:28:45.966
_index	wazuh-alerts-4.x-2026.08.19
agent.id	003
agent.ip	192.168.56.30
agent.name	linux-endpoint
data.srcip	192.168.56.102
data.srcport	39856
data.srcuser	invaliduser
decoder.name	sshd
decoder.parent	sshd
full_log	Aug 19 12:50:46 linux-endpoint sshd[2716]: Invalid user invaliduser from 192.168.56.102 port 39856
id	1787143845.2436912
input.type	log
location	journalld
manager.name	wazuh-manager
predecoder.hostname	linux-endpoint
predecoder.program_name	sshd
predecoder.timestamp	Aug 19 12:50:46
rule.description	sshd: Attempt to login using a non-existent user
rule.firedtimes	29
rule.gdpr	IV_35.7.d, IV_32.2
rule.gpg13	7.1
rule.groups	syslog, sshd, authentication_failed, invalid_login
rule.hipaa	164.312.b
rule.id	5710
rule.level	5
rule.mail	false
rule.mitre.id	T1110.001, T1021.004

Figure 7.6.1 — Rule 5710 detection with MITRE mapping




Figure 7.6.2 — Rule 5712 brute-force escalation (Level 10)

7.7 Phase 7: Active Response

Objective:

Configure and validate an automated containment action triggered by the brute-force detection, ensuring that a qualifying SSH authentication event is automatically associated with the appropriate Wazuh Active Response mechanism and that the response operates within the defined containment window.

Action performed:

Configured a Wazuh Active Response command binding firewall-drop to Rule 5710 with a 60-second timeout. During configuration, an initial XML tag/typographical misconfiguration was identified and corrected to ensure that the Active Response definition was properly parsed by the Wazuh Manager. The required Wazuh service was then restarted after the configuration was corrected. A controlled SSH authentication attack was subsequently re-triggered from the Kali attacker machine to generate another Rule 5710 detection and verify the complete detection-to-response workflow.

Observed result:

The Active Response mechanism successfully fired when the qualifying Rule 5710 event was generated. The Active Response log recorded the execution of the configured response mechanism following the detected SSH authentication activity. The subsequent SSH connection attempt from the Kali attacker was dropped, consistent with the configured automated

containment action taking effect. The 60-second timeout provided a temporary containment period rather than a permanent firewall modification, allowing the response to operate within the defined test window.

The result demonstrated the intended SOC workflow in which an authentication-based security event is detected by Wazuh and automatically passed to the configured response mechanism without requiring manual intervention. This established the relationship between attack generation, rule-based detection, automated response execution, and containment within the controlled laboratory environment.


```
<!--
Wazuh - Manager - Default configuration for ubuntu 24.04
More info at: https://documentation.wazuh.com
Mailing list: https://groups.google.com/forum/#!forum/wazuh
-->

<ossec_config>
  <global>
    <jsonout_output>yes</jsonout_output>
    <alerts_log>yes</alerts_log>
    <logall>no</logall>
    <logall_json>no</logall_json>
    <email_notification>no</email_notification>
    <smtp_server>smtp.example.wazuh.com</smtp_server>
    <email_from>wazuh@example.wazuh.com</email_from>
    <email_to>recipient@example.wazuh.com</email_to>
    <email_maxperhour>12</email_maxperhour>
    <email_log_source>alerts.log</email_log_source>
    <agents_disconnection_time>15m</agents_disconnection_time>
    <agents_disconnection_alert_time>0</agents_disconnection_alert_time>
    <update_check>yes</update_check>
  </global>

  <active-response>
    <disabled>no</disabled>
    <command>firewall-drop</command>
    <location>local</location>
    <rules_id>5710</rules_id>
    <timeout>60</timeout>
  </active-response>

  <alerts>
    <log_alert_level>3</log_alert_level>
    <email_alert_level>12</email_alert_level>
  </alerts>
```

Figure 7.7.1 — Active Response configuration (firewall-drop, 60s)



The screenshot shows a Kali Linux terminal window titled "kali-linux-2026.2-virtualbox-amd64 [Running] - Oracle VirtualBox". The terminal displays the following commands and output:

```
kali@kali: ~/Desktop
Session Actions Edit View Help
64 bytes from 192.168.56.30: icmp_seq=4 ttl=64 time=0.955 ms
— 192.168.56.30 ping statistics —
4 packets transmitted, 4 received, 0% packet loss, time 3020ms
rtt min/avg/max/mdev = 0.650/0.819/0.955/0.120 ms

(kali@kali)-[~/Desktop]
$ sudo nmap -Pn -p 22 192.168.56.30
[sudo] password for kali:
Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-19 16:30 -0400
Nmap scan report for 192.168.56.30
Host is up (0.0012s latency).

PORT      STATE SERVICE
22/tcp    open  ssh
MAC Address: 08:00:27:54:63:79 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 0.12 seconds

(kali@kali)-[~/Desktop]
$ ssh invaliduser@192.168.56.30
invaliduser@192.168.56.30's password:
kjhguig
jhbhjbjuh
^C

(kali@kali)-[~/Desktop]
$ ssh invaliduser@192.168.56.30
invaliduser@192.168.56.30's password:
█
```

A "Screenshot taken" notification is visible in the top right corner of the terminal window.


Figure 7.7.2 — Attacker SSH connection dropped

7.8 Phase 8: Windows Sysmon Telemetry

Objective: Validate endpoint-level telemetry ingestion from the Windows host via Sysmon.

Action performed: Installed and configured Sysmon 15.21 on the Windows endpoint and mapped its EventChannel into the Wazuh agent configuration (ossec.conf).

Observed result: Sysmon64 service confirmed running with 1,608 events recorded; Event ID 3 (network connection) telemetry was observed flowing from the agent to the manager over port 1514.



```

Windows-Agent [Running] - Oracle VirtualBox
Administrator: Windows PowerShell

026/08/19 20:58:07 sca: INFO: Starting Security Configuration Assessment scan.
026/08/19 20:58:07 wazuh-agent: INFO: (4102): Connected to the server ([192.168.56.2]:1514/tcp).
026/08/19 20:58:07 wazuh-modulesd:osquery: INFO: Module disabled. Exiting...
026/08/19 20:58:07 wazuh-modulesd:ciscat: INFO: Module disabled. Exiting...
026/08/19 20:58:07 rootcheck: INFO: Starting rootcheck scan.
026/08/19 20:58:07 wazuh-modulesd:syscollector: INFO: Module started.
026/08/19 20:58:07 wazuh-modulesd:syscollector: INFO: Starting evaluation.
026/08/19 20:58:07 sca: INFO: Starting evaluation of policy: 'C:\Program Files (x86)\ossec-agent\ruleset\sca\cis_win
1 enterprise.yml'
026/08/19 20:58:07 wazuh-agent: INFO: Started (pid: 8544).
026/08/19 20:58:07 wazuh-agent: INFO: (6008): File integrity monitoring scan started.
026/08/19 20:58:09 wazuh-modulesd:syscollector: INFO: Evaluation finished.
026/08/19 20:58:12 rootcheck: INFO: Ending rootcheck scan.
026/08/19 20:58:21 wazuh-agent: INFO: (6009): File integrity monitoring scan ended.
026/08/19 20:58:21 wazuh-agent: INFO: FIM sync module started.
026/08/19 20:58:21 wazuh-agent: INFO: (6012): Real-time file integrity monitoring started.
026/08/19 20:58:37 sca: INFO: Evaluation finished for policy 'C:\Program Files (x86)\ossec-agent\ruleset\sca\cis_win
1 enterprise.yml'
026/08/19 20:58:37 sca: INFO: Security Configuration Assessment scan finished. Duration: 30 seconds.
S C:\WINDOWS\system32> Get-Service Sysmon64

Status      Name      DisplayName
-----
Running     Sysmon64   Sysmon64

S C:\WINDOWS\system32> Get-WinEvent -FilterHashtable @{
>   LogName='Microsoft-Windows-Sysmon/Operational'
>   Id=3
> } -MaxEvents 1 |
> Format-List TimeCreated, Id, Message

TimeCreated : 19-08-2026 20:58:08
Id           : 3
Message      : Network connection detected:
               RuleName: -
               UtcTime: 2026-08-19 15:28:06.050
               ProcessGuid: {aed9bd1b-cb85-6a85-e501-000000001800}
               ProcessId: 8544
               Image: C:\Program Files (x86)\ossec-agent\wazuh-agent.exe
               User: NT AUTHORITY\SYSTEM
               Protocol: tcp
               Initiated: true
               SourceIsIpv6: false
               SourceIp: 192.168.56.101
               SourceHostname: DESKTOP-Q9BD8DM
               SourcePort: 50773
               SourcePortName: -
               DestinationIsIpv6: false
               DestinationIp: 192.168.56.2
               DestinationHostname: -
               DestinationPort: 1514
               DestinationPortName: -

```

Figure 7.8.1 — Sysmon Event ID 3 — agent-to-manager telemetry

7.9 Phase 9: File Integrity Monitoring (FIM)

Objective: Validate

Wazuh's Syscheck (FIM) module across the complete create–modify–delete file lifecycle on the monitored endpoint, confirming that file-system changes are detected and recorded as security-relevant events.

Action performed:

Performed a controlled file write using Add-Content on the Windows endpoint to create a dedicated test file, followed by modification of the same file to generate a detectable checksum change. The test file was then deliberately deleted to complete the lifecycle and verify that Wazuh continued monitoring the file through each stage.

Observed result:

Wazuh FIM correctly logged all three lifecycle events through Rules 554, 550, and 553, corresponding to file creation, checksum/content modification, and deletion respectively. The deletion event was additionally mapped to MITRE ATT&CK techniques T1070.004 and T1485, providing additional threat-context classification for the observed file activity. This confirmed that the Syscheck module was actively monitoring the configured Windows endpoint and successfully detecting changes across the complete file lifecycle.




Figure 7.9.1 — FIM lifecycle — create, modify, delete

8. Detection Rules Demonstrated

The following Wazuh rules were triggered and validated during the engagement. Rule levels reflect Wazuh's default severity scale (0–16); Level 10+ is treated as a high-priority alert requiring analyst attention or automated response.

Rule ID	Level	Description	Evidence Reference
5710	5	sshd: attempt to login using a non-existent user	1_CRITICAL/DETECT_dashboard_rule5710_srcip102_mitre.png
5712	10	sshd: brute force trying to get access to the system	1_CRITICAL/DETECT_dashboard_rule5712_brute_force_lv10.png
550	7	Integrity checksum changed (FIM modification)	2_HIGH/DETECT_dashboard_rule550_checksum.png
553	7	File deleted (FIM deletion)	2_HIGH/DETECT_dashboard_fim_delete_mitre_t1070.png
554	5	File added to the system (FIM creation)	2_HIGH/DETECT_dashboard_fim_rules_550_553_554.png
5402	3	Successful sudo to ROOT executed	2_HIGH/DETECT_manager_sudo_rule5402_compliance.png
60122	5	Logon failure — unknown user or bad password (Windows)	2_HIGH/DETECT_dashboard_failed_logon_4625_rule60122.png

9. MITRE ATT&CK Mapping

Mapping detections to MITRE ATT&CK is standard SOC practice: it translates raw alert data into adversary technique language that is portable across tools, reports, and stakeholders.

Technique	ID	Tactic	Evidence
Password Guessing	T1110.001	Credential Access	Rule 5710 + 5712
Remote Services: SSH	T1021.004	Lateral Movement	SSH attack from Kali
Sudo and Sudo Caching	T1548.003	Privilege Escalation	Rule 5402
File Deletion	T1070.004	Defense Evasion	FIM Rule 553
Data Destruction	T1485	Impact	FIM Rule 553

10. Compliance Framework Mappings

Cross-referencing detections against recognized compliance frameworks demonstrates how the lab's monitoring controls would satisfy common audit and regulatory evidence requirements.

Framework	Controls	Evidence
PCI DSS	10.2.4, 10.2.5, 10.6.1, 11.5	Rules 5710, 550
HIPAA	164.312(b), 164.312(c)(1)	Authentication monitoring, FIM
NIST 800-53	AU-6, AU-14, AC-7, SI-7	Audit log review, integrity monitoring
GDPR	Art. 32(2), 35(7)(d), 5(1)(f)	Security event processing
SOC 2 (TSC)	CC6.1, CC6.8, CC7.2, CC7.3	Access control, monitoring

11. Results Summary

Capability	Status	Evidence Location
Kali → Linux connectivity	Confirmed	2_HIGH/NETCFG_kali_ip_ping_target_manager.png
SSH service discovery (22/tcp)	Confirmed	1_CRITICAL/RECON_kali_nmap_ssh22_openssh_os.png
Controlled SSH auth failure	Confirmed	1_CRITICAL/ATTACK_kali_ssh_brute_force_loop_10x.png
Linux sshd logging	Confirmed	1_CRITICAL/LOGGING_sshd_auth_failures_192_168_56_102.png
Wazuh event collection	Confirmed	2_HIGH/CONFIG_dashboard_3_agents_all_active.png
Rule 5710 detection	Confirmed	1_CRITICAL/DETECT_dashboard_rule5710_srcip102_mitre.png
Rule 5712 brute-force detection	Confirmed	1_CRITICAL/DETECT_dashboard_rule5712_brute_force_lv10.png
Attacker source attribution	Confirmed	srcip 192.168.56.102 in Rule 5710
Active Response invocation	Confirmed	1_CRITICAL/AR_config_firewall_drop_rule5710_60s.png
Attacker session dropped	Confirmed	1_CRITICAL/AR_kali_attacker_blocked_firewall_drop.png
Firewall rule verification (iptables/nft)	Not verified	Documented as limitation — see Section 12
Windows Sysmon telemetry	Confirmed	2_HIGH/SYSMON_eventid3_agent_to_manager_1514.png
FIM detection (Windows)	Confirmed	2_HIGH/DETECT_dashboard_fim_lifecycle_4hits.png
Windows failed logon (4625)	Confirmed	2_HIGH/DETECT_dashboard_failed_logon_4625_rule60122.png

12. Conclusion and Recommendations

12.1 Conclusion

The lab successfully demonstrated a complete, evidence-backed SSH attack detection and automated response chain across a multi-agent Wazuh SIEM deployment, spanning reconnaissance, controlled attack execution, endpoint logging, SIEM correlation, automated containment, and cross-platform (Linux + Windows) telemetry validation. All primary objectives defined in Section 3.2 were met, with one transparently disclosed evidentiary gap.

12.2 Recommendations for Future Iterations

Independently verify Active Response network-layer effects using iptables -L / nft list ruleset immediately after each firing, and capture this as CRITICAL-tier evidence.

- Extend Active Response coverage to additional rule IDs (e.g., repeated sudo escalation, FIM deletion bursts) to broaden automated containment scope.
- Introduce a second, independent detection source (e.g., Suricata or Zeek) to cross-validate Wazuh's SSH brute-force detections.
- Formalize the screenshot-tiering workflow used here (CRITICAL / HIGH / MEDIUM / LOW) as a reusable SOC evidence-handling template for future lab and production investigations.

Appendix A: Screenshot Evidence Inventory

Tier	Folder	File Count	Use
1 — CRITICAL	1_CRITICAL/	8	Report essentials — used inline in Sections 4 and 7
2 — HIGH	2_HIGH/	93	Important supporting evidence — 1–3 per phase recommended
3 — MEDIUM	3_MEDIUM/	75	Supporting context — reference only if challenged
4 — LOW	4_LOW/	110	Troubleshooting / debug — summarize as text, do not embed

A.1 Naming Convention

Every screenshot follows the convention CATEGORY_descriptive_function_name.png, where CATEGORY is one of: RECON, ATTACK, DETECT, AR, LOGGING, SYSMON, CONFIG, SETUP, NETCFG, TROUBLESHOOT, or OTHER.

A.2 CRITICAL Tier — Full Listing

#	File	What It Proves
1	RECON_kali_nmap_ssh22_openssh_os.png	Nmap discovers 22/tcp open, OpenSSH 9.6p1, OS Linux 4.X 5.X
2	RECON_kali_nmap_full_65535_ssh_os.png	Full 65535-port scan with OS fingerprint
3	ATTACK_kali_ssh_brute_force_loop_10x.png	for i in {1..10}; do ssh invaliduser@192.168.56.30
4	LOGGING_sshd_auth_failures_192_168_56_102.png	sshd logs: Invalid user invaliduser from 192.168.56.102
5	DETECT_dashboard_rule5710_srcip102_mitre.png	Rule 5710 alert: srcip=192.168.56.102, MITRE T1110.001
6	DETECT_dashboard_rule5712_brute_force_lv10.png	Rule 5712 Level 10: brute force trying to get access
7	AR_config_firewall_drop_rule5710_60s.png	Final AR XML: firewall-drop on rule 5710, timeout 60s
8	AR_kali_attacker_blocked_firewall_drop.png	SSH connection dropped — attacker blocked

— End of Report —