

class: center, middle

# Programming in R

Adam Rawles

---

## Recap

—

- Loading data from .csv and .xlsx

—

- Cleaning data
  - `is/as.xxxxxx()` functions

—

- Summary statistics

—

- `mean()`, `median()`, `sd()`...
- `summary()`

—

- Plotting

—

- `plot()`
  - `hist()`
- 

## Overview

- User-defined functions

—

- For loops

—

- If/else statements
-

## Functions

- Functions are how we perform any action in R
  - 
  - We pass arguments to a function as an input, there is some form of transformation, and we get an output
  - 
  - For example, `read.csv()` takes a .csv file, and turns it into a dataframe
  - 
  - There are thousands of predefined functions in base R, and even more with packages
  - 
  - But often, you'll need a specific function for a specific task...
  - 
  - And that's where user-defined functions come in
- 

## User-defined functions - basics

- Functions can have multiple inputs, but only one output
- 
- Functions are named\*, and are always followed by `()` when used
- 
- Functions names should be unique but memorable/logical
- 
- Functions should be as simple and applicable as possible
- 
- Functions will return the last evaluated (not assigned) variable, or whatever is included in the `return()` call
- 
- Functions can only return *one* thing (but vectors and lists still count as one thing)
- 

\* There are unnamed functions called “anonymous functions” but that's for a different module

---

## User-defined functions - structure

- Functions are created with the following structure:

```
some_function <- function(some_input, ...){  
  operation  
  return(return_value)  
}
```

- We name the function, define what inputs we want, and then what we want to do with those inputs

---

## User-defined functions - example

```
sum_custom <- function(x, y){  
  new_value <- x + y  
  return(new_value)  
}  
  
sum_custom(1,2)
```

```
## [1] 3
```

---

## User-defined functions - example

This same function can also be written without an explicit `return()` call:

```
sum_custom <- function(x, y){  
  x + y  
}  
  
sum_custom(1,2)
```

```
## [1] 3
```

## User-defined functions - example

—

- You can specify default values for any of your input parameters, making that argument optional:

—

```
combine_custom <- function(string1, string2, delimiter = " ") {  
  new_string <- paste0(string1, delimiter, string2)  
  return(new_string)  
}  
  
combine_custom(string1 = "hello", string2 = "world")
```

```
## [1] "hello world"
```

---

## User-defined functions - example

- But you can override the default by providing a value to that parameter when using the function

—

```
combine_custom(string1 = "hello",  
               string2 = "world",  
               delimiter = "!")
```

```
## [1] "hello!world"
```

---

## User-defined functions - exercise

- Option 1 (easy)
  - Write a function that takes 2 numbers, multiplies them together and divides the result by 2

---

-  
Op-  
tion  
2  
(in-  
ter-  
me-  
di-  
ate)  
-  
Write  
a  
func-  
tion  
that  
takes  
2  
vec-  
tors,  
and  
mul-  
ti-  
plies  
the  
largest  
value  
of  
vec-  
tor  
1 by  
the  
small-  
est  
value  
in  
vec-  
tor  
2

---

- Option 3 (advanced)
  - Write a function that takes 2 strings, and returns the 1st and 2nd values of each one (hint available)

—

- Option 4 (theoretical)
  - Think of how you would write a function that can sum an indefinite number of numbers

---

## User-defined functions - answers

- Option 1
  - Write a function that takes 2 numbers, multiplies them together and divides the result by 2

```
option1_function <- function(x,y){  
  new_val <- (x * y)/2  
  return(new_val)  
}  
  
option1_function(4,4)
```

```
## [1] 8
```

---

## User-defined functions - answers

- Option 2
  - Write a function that takes 2 vectors, and multiplies that largest value of vector 1 by the smallest value in vector 2

```
option2_function <- function(v1, v2){  
  new_val <- max(v1) * min(v2)  
  return(new_val)  
}  
  
option2_function(v1 = c(1,2,3,4), v2 = c(1,2,3,4,5))
```

```
## [1] 4
```

---

## User-defined functions - answers

- Option 3
  - Write a function that takes 2 strings, and returns the 1st and 2nd values of each one

```
option3_function <- function(string1, string2){  
  ret1 <- substr(string1,1,2)  
  ret2 <- substr(string2, 1,2)  
  ret <- c(ret1, ret2)  
  return(ret)  
}  
  
option3_function("hello", "world")
```

```
## [1] "he" "wo"
```

---

## User-defined functions

- In some cases, you may want to provide a variable number of inputs to a function (like if you want to add an indefinite number of values together)

—

- For example, if you have a function that combines strings, you may want to accept any number of strings to combine

—

- To do this, we use the ellipsis (...) argument when defining our function

```
some_function <- function(...){  
  arguments <- list(...)  
  return(arguments)  
}
```

---

## User-defined functions

```
some_function("hello", "world")
```

```
## [[1]]  
## [1] "hello"  
##  
## [[2]]  
## [1] "world"
```

```
some_function("hello", "world", "again")
```

```
## [[1]]  
## [1] "hello"  
##  
## [[2]]  
## [1] "world"  
##  
## [[3]]  
## [1] "again"
```

---

## User-defined functions - environment

- Functions have a local environment, meaning that anything calculated in the function is not accessible outside the function (except the value that is returned)

```
some_function <- function(x, y){  
  m <- x * y  
  s <- x + y  
  return(m)  
}  
  
some_function(1, 2)
```

```
## [1] 2
```

```
print(s)
```

```
## Error in print(s): object 's' not found
```

- 

This code errors, because the `s` variable isn't accessible outside of the function

## User-defined functions - returning

- As previously mentioned, a function will return the last evaluated object, or whatever is returned via the `return()` function.

- What's really important to remember however, is that a function will return a *copy* of the return value, not the return object

```
some_function <- function(x) {  
  return(x + 1)  
}  
  
x <- 1  
some_function(x)
```

```
## [1] 2
```



```
x
```

```
## [1] 1
```

---

## User-defined functions - returning

- To change the original object, we need to reassign the result of the function back to the object...

—

```
x <- 1
x <- some_function(x)
x
```

```
## [1] 2
```

---

## For loops

—

- Sometimes, we may want to repeat the same action more than once

—

- For example, we might want a function to add 4 to every item in a vector, or get the mean for every column in a dataframe

—

- You could copy and paste the code required each time, or you could use a for loop
- 

## For loops

- With a for loop, you can iterate over every item in a list or vector and perform an action

—

- While loops (which iterate until a condition is met) also exist, but we're going to focus on for loops

—

- For loops follow a basic structure:

```
for (identifier in list or vector){  
  what we want to do with each item  
}
```

—

- The identifier becomes the variable name for accessing the current value in the body of the loop

—

- On each iteration, the identifier variable will take on a new value

---

## For loops - structure

- You can also perform a for loop a defined number of times rather than iterating through a list/vector:

```
for (identifier in seq_along(1:some_number)){  
  what we want to do with each item  
}
```

- In this case, the value of our identifier variable will change to the next number in our set of numbers

---

## For loops - example

- Say we want to loop through a vector and print each value...

—

```
vector1 <- c(1,2,3,4,5,6,7,8)  
for (i in vector1){  
  print(i)  
}
```

```
## [1] 1  
## [1] 2  
## [1] 3  
## [1] 4  
## [1] 5  
## [1] 6  
## [1] 7  
## [1] 8
```

---

## For loops - exercise

- Option 1 (easy)
  - Write a for loop that divides each number in a vector of numbers by 2

–

- Option 2 (intermediate)

–

**Write a for loop that produces a running average from a vector of numbers**

- Option 3 (advanced)
  - Write a for loop that adds each value from one vector to the value at the next index in a second vector

---

## For loops - answers

- Option 1
  - Write a for loop that divides each number in a vector of numbers by 2

```
vector1 <- c(2,4,6,8,10)
for (i in vector1){
  print(i/2)
}
```

```
## [1] 1
## [1] 2
## [1] 3
## [1] 4
## [1] 5
```

---

## For loops - answers

- Option 2
  - Write a for loop that produces a running average from a vector of numbers

```
vector1 <- c(10,20,30,40,70,100)
total <- 0
counter <- 0
for (i in vector1){
  counter <- counter + 1
  total <- total + i
  print(total/counter)
}
```

```
## [1] 10
## [1] 15
## [1] 20
## [1] 25
## [1] 34
## [1] 45
```

---

## For loops - answers

- Option 3
  - Write a for loop that adds each value from one vector to the value at the next index in a second vector

```
vector1 <- c(1,5,10,15)
vector2 <- c(2,6,10,14,18)

for (i in seq_along(vector)){
  print(vector1[i] + vector2[i+1])
}
```

```
## [1] 7
```

---

## If else statements

- Sometimes, you'll only want to perform an action if a certain criteria is met
  - 
  - For example, you may only want to add 4 to a number if it's greater than 10
  - 
  - To perform a certain action based on multiple criteria, you use an if else statement
- 

## If else statements - structure

- There are 3 main 'types' of if else statements
- 
- Simple if statements
  - If the criteria is fulfilled, perform the action, otherwise do nothing:
-

```
if (criteria){
  do something
}
```

—

- If else statements
  - If the criteria is fulfilled, perform the action, otherwise do something else:

—

```
if (criteria){
  do something
} else {
  do something else
}
```

---

## If else statements - structure

- If and if else statements
  - If the criteria is fulfilled perform the action, otherwise if a different criteria is fulfilled do something else, otherwise do nothing:

—

```
if (criteria){
  do something
} else if (other criteria) {
  do something else
}
```

---

## If else statements - criteria

- You can include multiple criteria in one if or else statement...

—

```
if (criteria 1 | criteria 2){
}

if (criteria 1 & criteria 2){
}
```

---

## If else statements - example

```
vector1 <- c(1,2,3,4,5)

for (i in vector1){
  if (i == 1) {
    print("The value is 1")
  } else if (i == 2) {
    print("The value is 2")
  } else if (i == 3 | i == 4){
    print("The value is 3 or 4")
  } else {
    print("The value is not 1, 2, 3 or 4")
  }
}
```

```
## [1] "The value is 1"
## [1] "The value is 2"
## [1] "The value is 3 or 4"
## [1] "The value is 3 or 4"
## [1] "The value is not 1, 2, 3 or 4"
```

---

## Final - exercise

- Option 1 (easy)
    - Write a function that loops through a vector of numbers and returns only the even ones
    - Hint: you can use `x %% y` to check if a number is even
  - Option 2 (intermediate)
    - Write a function that loops through a vector of numbers and returns the values that are smaller than the value at the same index in a second vector
    - You can assume that the two vectors will always be the same length
  - Option 3 (advanced)
    - Write a function that loops through a vector of numbers and square it if it is a multiple of 4, otherwise replace the value with the previous value in the vector or 0 if the value is first in the vector and return
    - Hint: use `x / y %% 2` to check for multiples
-

## Final - answers

- Option 1
  - Write a function that loops through a vector of numbers and returns only the even ones

```
option1_function <- function(v) {  
  return_vector <- c()  
  for (i in v){  
    if (i %% 2 == 0){  
      return_vector <- append(return_vector, i)  
    }  
  }  
}  
  
option1_function(v = c(1,2,3,4,5,6,7,8))
```

---

## Final - answers

- Option 2
  - Write a function that loops through a vector of numbers and returns the values that are smaller than the value at the same index in a second vector

```
option2_function <- function(v1, v2) {  
  return_vector <- c()  
  for (i in seq_along(v1)){  
    if (v1[i] < v2[i]){  
      return_vector <- append(return_vector, v1[i])  
    }  
  }  
}  
  
option2_function(v1 = c(1,2,3,4,5,6,7,8), v2 = c(2,1,4,5,2,1,1,1))
```

---

## Final - answers

- Option 3
    - Write a function that loops through a vector of numbers and squares it if it is a multiple of 4, otherwise replace the value with the previous value in the vector or 0 if the value is first in the vector and return
- 

## Final - answers

```
option3_function <- function(v) {
  for (i in seq_along(v)){
    if ((v[i] / 4) %% 2 == 0){
      v[i] <- v[i]^2
    } else {
      if (i == 1){
        v[i] = 0
      } else {
        v[i] = v[i-1]
      }
    }
  }
  return(v)
}

option3_function(v = c(1,2,3,4,5,6,7,8))
```

```
## [1] 0 0 0 0 0 0 0 64
```

---

## Conclusion

—

- User-defined functions
  - We use functions to perform repeatable and generalizable tasks

—

- For loops
  - We use for loops to iterate over vectors/lists, or to perform an action a certain number of times

—

- If else statements
  - With if, else if, and else statements, we can perform actions only when a certain criteria is met

---

## Future modules (optional)

- Statistical analysis
- Simulations
- Improving efficiency