S9 RUN CONFIGURATIONS

Per-run settings. In the Inkling-Small and DeepSeek V4 Flash runs, the detector runs in Codex CLI with reasoning effort set to high, served through Tinker and OpenRouter, respectively. In the Opus 4.6 run, it runs in Claude Code through our subscription, and in the GLM-5.3 run, in Claude Code through OpenRouter. In the DeepSeek V4 Flash, Opus 4.6, and GLM-5.3 runs, the optimizer uses the same agent and model as the detector. The Inkling-Small, DeepSeek V4 Flash, and GLM-5.3 runs allow up to 15 refinement iterations with a patience of 4 (GLM-5.3 stopped after iteration 8); each detector call has a 900-second timeout and up to three retries, with 30 concurrent calls in the Codex runs and 60 in the GLM-5.3 run. Opus 4.6 ran four refinement iterations because of subscription limits. The run configurations specify greedy decoding (temperature 0, top-p 1, at most 4,096 output tokens), but the Claude CLI does not forward these settings to the model. The Opus 4.6 and Opus 5 seed baselines come from standalone runs of the seed harness rather than from the discovery session.

Opus 4.6 ran through our Claude subscription rather than per-token API billing. Subscription limits motivated a maximum of five iterations; the recorded run contains the seed and four refinement iterations. OpenRouter and Tinker runs instead used hosted inference through the local LiteLLM proxy. The OpenRouter configuration pins DeepSeek V4 Flash to FP8 providers and Nemotron to BF16 providers; the Tinker Nemotron run uses the explicit BF16 model identifier. These are separate serving routes, not interchangeable pricing records. We routed Claude Code through a local LiteLLM proxy, which translated its Anthropic Messages API requests into OpenRouter chat completion requests. Each model was registered in the proxy configuration with authentication supplied through an API key (environment variable). Claude Code's auxiliary model aliases were accordingly pinned to the same target model. For GLM-5.3 experimentation, both the optimizer and evaluator used this route. For the GLM-5.3 run, each evaluation attempt had a 900-second timeout and up to three retries. The Claude CLI output cap was 32,000 tokens. Although the saved configuration lists temperature 0, top-p 1 and a 4,096-token limit, the Claude CLI model client does not forward these decoding fields; we therefore do not report them as effective sampling settings. Current provider prices are listed in Supp. S12; they are not measurements of total experiment cost. Run lengths depended on inference budgets and stopping criteria. GLM-5.3 used maximum of 15 refinement iterations (T=15) and patience of 4 iterations without improvement (K=4), stopping after iteration 8.