

`fitr`

July 1, 2018

Contents

I Overview & Foundations	3
II Tutorials	4
III API	5
fitr.data	6
BehaviouralData	6
merge_behavioural_data	8
fitr.environments	10
Graph	10
TwoArmedBandit	15
OrthogonalGoNoGo	18
TwoStep	22
ReverseTwoStep	27
RandomContextualBandit	31
fitr.agents	36
SoftmaxPolicy	36
StickySoftmaxPolicy	37
EpsilonGreedyPolicy	39
ValueFunction	40
DummyLearner	42
InstrumentalRescorlaWagnerLearner	44
QLearner	46
SARSA Learner	48
Agent	51
BanditAgent	51
MDP Agent	52
RandomBanditAgent	53

RandomMDPAgent	54
Notes	54
SARSA SoftmaxAgent	55
QLearning SoftmaxAgent	56
RW SoftmaxAgent	57
RW SoftmaxAgent RewardSensitivity	58
fitr.utils	60
softmax	60
sigmoid	60
stable_exp	61
logsumexp	61
log_loss	61

Part I

Overview & Foundations

Part II

Tutorials

Part III

API

fitr.data

A module containing a generic class for behavioural data.

BehaviouralData

`fitr.data.BehaviouralData()`

A flexible and generic object to store and process behavioural data across tasks

Arguments:

- **ngroups**: Integer number of groups represented in the dataset. Only > 1 if data are merged
 - **nsubjects**: Integer number of subjects in dataset
 - **ntrials**: Integer number of trials done by each subject
 - **dict**: Dictionary storage indexed by subject.
 - **params**: `ndarray((nsubjects, nparams + 1))` parameters for each (simulated) subject
 - **meta**: Array of covariates of type `ndarray((nsubjects, nmetadata_features+1))`
 - **tensor**: Tensor representation of the behavioural data of type `ndarray((nsubjects, ntrials, nfeatures))`
-

BehaviouralData.add_subject

`fitr.data.add_subject(self, subject_index, parameters, subject_meta)`

Appends a new subject to the dataset

Arguments:

- **subject_index**: Integer identification for subject
 - **parameters**: list of parameters for the subject
 - **subject_meta**: Some covariates for the subject (list)
-

BehaviouralData.initialize__data__dictionary

```
fitr.data.initialize_data_dictionary(self)
```

BehaviouralData.make__behavioural__ngrams

```
fitr.data.make_behavioural_ngrams(self, n)
```

Creates N-grams of behavioural data

BehaviouralData.make__cooccurrence__matrix

```
fitr.data.make_cooccurrence_matrix(self, k, dtype=<class 'numpy.float32'>)
```

BehaviouralData.make__tensor__representations

```
fitr.data.make_tensor_representations(self)
```

Creates a tensor with all subjects' data

Notes

Assumes that all subjects did same number of trials.

BehaviouralData.numpy__tensor__to__bdf

```
fitr.data.numpy_tensor_to_bdf(self, X)
```

Creates **BehaviouralData** formatted set from a dataset stored in a numpy ndarray.

Arguments:

- **X**: ndarray((nsubjects, ntrials, m)) with m being the size of flattened single-trial data
-

BehaviouralData.unpack_tensor

```
fitr.data.unpack_tensor(self, x_dim, u_dim, r_dim=1, terminal_dim=1, get='sarsat')
```

Unpacks data stored in tensor format into separate arrays for states, actions, rewards, next states, and next actions.

Arguments:

x_dim : Task state space dimensionality (**int**) **u_dim** : Task action space dimensionality (**int**) **r_dim** : Reward dimensionality (**int**, default=1) **terminal_dim** : Dimensionality of the terminal state indicator (**int** , default=1) **get** : String indicating the order that data are stored in the array. Can also be shortened such that fewer elements are returned. For example, the default is **sarsat**.

Returns:

List with data, where each element is in the order of the argument **get**

BehaviouralData.update

```
fitr.data.update(self, subject_index, behav_data)
```

Adds behavioural data to the dataset

Arguments:

- **subject_index**: Integer index for the subject
 - **behav_data**: 1-dimensional ndarray of flattened data
-

merge_behavioural_data

```
fitr.data.merge_behavioural_data(datalist)
```

Combines BehaviouralData objects.

Arguments:

- **datalist**: List of BehaviouralData objects

Returns:

BehaviouralData with data from multiple groups merged.

fitr.environments

Functions to synthesize data from behavioural tasks.

Graph

`fitr.environments.Graph()`

Base object that defines a reinforcement learning task.

Definitions

- $\mathbf{x} \in \mathcal{X}$ be a one-hot state vector, where $|\mathcal{X}| = n_x$
- $\mathbf{u} \in \mathcal{U}$ be a one-hot action vector, where $|\mathcal{U}| = n_u$
- $\mathbf{T} = p(\mathbf{x}_{t+1}|\mathbf{x}_t, \mathbf{u}_t)$ be a transition tensor
- $p(\mathbf{x})$ be a distribution over starting states
- $\mathcal{J} : \mathcal{X} \rightarrow \mathcal{R}$, where $\mathcal{R} \subseteq \mathbb{R}$ be a reward function

Arguments:

- **T**: Transition tensor
- **R**: Vector of rewards for each state such that scalar reward $r_t = \mathbf{r}^o p \mathbf{x}$
- **end_states**: A vector $\{0, 1\}^{n_x}$ identifying which states terminate a trial (aka episode)
- **p_start**: Initial state distribution
- **label**: A string identifying a name for the task
- **state_labels**: A list or array of strings labeling the different states (for plotting purposes)
- **action_labels**: A list or array of strings labeling the different actions (for plotting purposes)
- **rng**: `np.random.RandomState` object
- **f_reward**: A function whose first argument is a vector of rewards for each state, and whose second argument is a state vector, and whose output is a scalar reward
- **cmap**: Matplotlib colormap for plotting.

Notes

There are two critical methods for the **Graph** class: `observation()` and `step`. All instances of a **Graph** must be able to call these functions. Let's

say you have some bandit task `MyBanditTask` that inherits from `Graph`. To run such a task would look something like this:

```
env = MyBanditTask()           # Instantiate your environment object
agent = MyAgent()              # Some agent object (arbitrary, really)
for t in range(ntrials):
    x = env.observation()       # Samples initial state
    u = agent.action(x)         # Choose some action
    x_, r, done = agent.step(u) # Transition based on action
```

What differentiates tasks are the transition tensor T , starting state distribution $p(\mathbf{x})$ and reward function \mathcal{J} (which here would include the reward vector \mathbf{r}).

Graph.adjacency_matrix_decomposition

```
fitr.environments.adjacency_matrix_decomposition(self)
```

Singular value decomposition of the graph adjacency matrix

Graph.get_graph_depth

```
fitr.environments.get_graph_depth(self)
```

Returns the depth of the task graph.

Calculated as the depth from **START** (pre-initial state) to **END** (which absorbs trial from all terminal states), minus 2 to account for the **START**->**node** & **node**->**END** transitions.

Returns:

An `int` identifying the depth of the current graph for a single trial of the task

Graph.laplacian_matrix_decomposition

```
fitr.environments.laplacian_matrix_decomposition(self)
```

Singular value decomposition of the graph Laplacian

Graph.make_action_labels

```
fitr.environments.make_action_labels(self)
```

Creates labels for the actions (for plotting) if none provided

Graph.make_digraph

```
fitr.environments.make_digraph(self)
```

Creates a `networkx` DiGraph object from the transition tensor for the purpose of plotting and some other analyses.

Graph.make_state_labels

```
fitr.environments.make_state_labels(self)
```

Creates labels for the states (for plotting) if none provided

Graph.make_undirected_graph

```
fitr.environments.make_undirected_graph(self)
```

Converts the DiGraph to undirected and computes some stats

Graph.observation

```
fitr.environments.observation(self)
```

Samples an initial state from the start-state distribution $p(\mathbf{x})$

$$\mathbf{x}_0 \sim p(\mathbf{x})$$

Returns:

A one-hot vector `ndarray((nstates,))` indicating the starting state.

Examples:

```
x = env.observation()
```

Graph.plot_action_outcome_probabilities

```
fitr.environments.plot_action_outcome_probabilities(self, figsize=None, outfile=None,
```

Plots the probabilities of different outcomes given actions.

Each plot is a heatmap for a starting state showing the transition probabilities for each action-outcome pair within that state.

Graph.plot_graph

```
fitr.environments.plot_graph(self, figsize=None, node_size=2000, arrowsize=20, lw=1.5
```

Plots the directed graph of the task

Graph.plot_spectral_properties

```
fitr.environments.plot_spectral_properties(self, figsize=None, outfile=None, outfile
```

Creates a set of subplots depicting the graph Laplacian and its spectral decomposition.

Graph.random_action

`fitr.environments.random_action(self)`

Samples a random one-hot action vector uniformly over the action space.

Useful for testing that your environment works, without having to create an agent.

$$\mathbf{u} \sim \text{Multinomial}\left(1, \mathbf{p} = \{p_i = \frac{1}{|\mathcal{U}|}\}_{i=1}^{|\mathcal{U}|}\right)$$

Returns:

A one-hot action vector of type `ndarray((nactions,))`

Examples:

```
u = env.random_action()
```

Graph.step

`fitr.environments.step(self, action)`

Executes a state transition in the environment.

Arguments:

`action` : A one-hot vector of type `ndarray((naction,))` indicating the action selected at the current state.

Returns:

A 3-tuple representing the next state (`ndarray((noutcomes,))`), scalar reward, and whether the current step terminates a trial (`bool`).

Raises:

`RuntimeError` if `env.observation()` not called after a previous `env.step(...)` call yielded a terminal state.

TwoArmedBandit

`fitr.environments.TwoArmedBandit()`

Two armed bandit just as a tester

TwoArmedBandit.adjacency_matrix_decomposition

`fitr.environments.adjacency_matrix_decomposition(self)`

Singular value decomposition of the graph adjacency matrix

TwoArmedBandit.get_graph_depth

`fitr.environments.get_graph_depth(self)`

Returns the depth of the task graph.

Calculated as the depth from **START** (pre-initial state) to **END** (which absorbs trial from all terminal states), minus 2 to account for the **START**->**node** & **node**->**END** transitions.

Returns:

An `int` identifying the depth of the current graph for a single trial of the task

TwoArmedBandit.laplacian_matrix_decomposition

`fitr.environments.laplacian_matrix_decomposition(self)`

Singular value decomposition of the graph Laplacian

TwoArmedBandit.make__action_labels

```
fitr.environments.make_action_labels(self)
```

Creates labels for the actions (for plotting) if none provided

TwoArmedBandit.make__digraph

```
fitr.environments.make_digraph(self)
```

Creates a `networkx` DiGraph object from the transition tensor for the purpose of plotting and some other analyses.

TwoArmedBandit.make__state_labels

```
fitr.environments.make_state_labels(self)
```

Creates labels for the states (for plotting) if none provided

TwoArmedBandit.make__undirected_graph

```
fitr.environments.make_undirected_graph(self)
```

Converts the DiGraph to undirected and computes some stats

TwoArmedBandit.observation

```
fitr.environments.observation(self)
```

Samples an initial state from the start-state distribution $p(\mathbf{x})$

$$\mathbf{x}_0 \sim p(\mathbf{x})$$

Returns:

A one-hot vector `ndarray((nstates,))` indicating the starting state.

Examples:

```
x = env.observation()
```

TwoArmedBandit.plot_action_outcome_probabilities

```
fitr.environments.plot_action_outcome_probabilities(self, figsize=None, outfile=None,
```

Plots the probabilities of different outcomes given actions.

Each plot is a heatmap for a starting state showing the transition probabilities for each action-outcome pair within that state.

TwoArmedBandit.plot_graph

```
fitr.environments.plot_graph(self, figsize=None, node_size=2000, arrowsize=20, lw=1.5
```

Plots the directed graph of the task

TwoArmedBandit.plot_spectral_properties

```
fitr.environments.plot_spectral_properties(self, figsize=None, outfile=None, outfile
```

Creates a set of subplots depicting the graph Laplacian and its spectral decomposition.

TwoArmedBandit.random_action

```
fitr.environments.random_action(self)
```

Samples a random one-hot action vector uniformly over the action space.

Useful for testing that your environment works, without having to create an agent.

$$\mathbf{u} \sim \text{Multinomial}\left(1, \mathbf{p} = \{p_i = \frac{1}{|\mathcal{U}|}\}_{i=1}^{|\mathcal{U}|}\right)$$

Returns:

A one-hot action vector of type `ndarray((nactions,))`

Examples:

```
u = env.random_action()
```

TwoArmedBandit.step

```
fitr.environments.step(self, action)
```

Executes a state transition in the environment.

Arguments:

`action` : A one-hot vector of type `ndarray((naction,))` indicating the action selected at the current state.

Returns:

A 3-tuple representing the next state (`ndarray((noutcomes,))`), scalar reward, and whether the current step terminates a trial (`bool`).

Raises:

`RuntimeError` if `env.observation()` not called after a previous `env.step(...)` call yielded a terminal state.

OrthogonalGoNoGo

```
fitr.environments.OrthogonalGoNoGo()
```

The orthogonal GoNogo task from Guitart-Masip et al. (2012)

OrthogonalGoNoGo.adjacency_matrix_decomposition

`fitr.environments.adjacency_matrix_decomposition(self)`

Singular value decomposition of the graph adjacency matrix

OrthogonalGoNoGo.get_graph_depth

`fitr.environments.get_graph_depth(self)`

Returns the depth of the task graph.

Calculated as the depth from **START** (pre-initial state) to **END** (which absorbs trial from all terminal states), minus 2 to account for the **START**->**node** & **node**->**END** transitions.

Returns:

An `int` identifying the depth of the current graph for a single trial of the task

OrthogonalGoNoGo.laplacian_matrix_decomposition

`fitr.environments.laplacian_matrix_decomposition(self)`

Singular value decomposition of the graph Laplacian

OrthogonalGoNoGo.make_action_labels

`fitr.environments.make_action_labels(self)`

Creates labels for the actions (for plotting) if none provided

OrthogonalGoNoGo.make__digraph

```
fitr.environments.make_digraph(self)
```

Creates a `networkx` `DiGraph` object from the transition tensor for the purpose of plotting and some other analyses.

OrthogonalGoNoGo.make__state_labels

```
fitr.environments.make_state_labels(self)
```

Creates labels for the states (for plotting) if none provided

OrthogonalGoNoGo.make__undirected_graph

```
fitr.environments.make_undirected_graph(self)
```

Converts the `DiGraph` to undirected and computes some stats

OrthogonalGoNoGo.observation

```
fitr.environments.observation(self)
```

Samples an initial state from the start-state distribution $p(\mathbf{x})$

$$\mathbf{x}_0 \sim p(\mathbf{x})$$

Returns:

A one-hot vector `ndarray((nstates,))` indicating the starting state.

Examples:

```
x = env.observation()
```

OrthogonalGoNoGo.plot_action_outcome_probabilities

```
fitr.environments.plot_action_outcome_probabilities(self, figsize=None, outfile=None,
```

Plots the probabilities of different outcomes given actions.

Each plot is a heatmap for a starting state showing the transition probabilities for each action-outcome pair within that state.

OrthogonalGoNoGo.plot_graph

```
fitr.environments.plot_graph(self, figsize=None, node_size=2000, arrowsize=20, lw=1.5
```

Plots the directed graph of the task

OrthogonalGoNoGo.plot_spectral_properties

```
fitr.environments.plot_spectral_properties(self, figsize=None, outfile=None, outfile
```

Creates a set of subplots depicting the graph Laplacian and its spectral decomposition.

OrthogonalGoNoGo.random_action

```
fitr.environments.random_action(self)
```

Samples a random one-hot action vector uniformly over the action space.

Useful for testing that your environment works, without having to create an agent.

$$\mathbf{u} \sim \text{Multinomial}\left(1, \mathbf{p} = \{p_i = \frac{1}{|\mathcal{U}|}\}_{i=1}^{|\mathcal{U}|}\right)$$

Returns:

A one-hot action vector of type `ndarray((nactions,))`

Examples:

```
u = env.random_action()
```

OrthogonalGoNoGo.step

```
fitr.environments.step(self, action)
```

Executes a state transition in the environment.

Arguments:

`action` : A one-hot vector of type `ndarray((naction,))` indicating the action selected at the current state.

Returns:

A 3-tuple representing the next state (`ndarray((noutcomes,))`), scalar reward, and whether the current step terminates a trial (`bool`).

Raises:

`RuntimeError` if `env.observation()` not called after a previous `env.step(...)` call yielded a terminal state.

TwoStep

```
fitr.environments.TwoStep()
```

An implementation of the Two-Step Task from Daw et al. (2011).

Arguments:

- **mu**: float identifying the drift of the reward-determining Gaussian random walks
- **sd**: float identifying the standard deviation of the reward-determining Gaussian random walks

TwoStep.adjacency_matrix_decomposition

```
fitr.environments.adjacency_matrix_decomposition(self)
```

Singular value decomposition of the graph adjacency matrix

TwoStep.f_reward

```
fitr.environments.f_reward(self, R, x)
```

TwoStep.get_graph_depth

```
fitr.environments.get_graph_depth(self)
```

Returns the depth of the task graph.

Calculated as the depth from **START** (pre-initial state) to **END** (which absorbs trial from all terminal states), minus 2 to account for the **START->node** & **node->END** transitions.

Returns:

An `int` identifying the depth of the current graph for a single trial of the task

TwoStep.laplacian_matrix_decomposition

```
fitr.environments.laplacian_matrix_decomposition(self)
```

Singular value decomposition of the graph Laplacian

TwoStep.make__action_labels

```
fitr.environments.make_action_labels(self)
```

Creates labels for the actions (for plotting) if none provided

TwoStep.make__digraph

```
fitr.environments.make_digraph(self)
```

Creates a `networkx` DiGraph object from the transition tensor for the purpose of plotting and some other analyses.

TwoStep.make__state_labels

```
fitr.environments.make_state_labels(self)
```

Creates labels for the states (for plotting) if none provided

TwoStep.make__undirected_graph

```
fitr.environments.make_undirected_graph(self)
```

Converts the DiGraph to undirected and computes some stats

TwoStep.observation

```
fitr.environments.observation(self)
```

Samples an initial state from the start-state distribution $p(\mathbf{x})$

$$\mathbf{x}_0 \sim p(\mathbf{x})$$

Returns:

A one-hot vector `ndarray((nstates,))` indicating the starting state.

Examples:

```
x = env.observation()
```

TwoStep.plot_action_outcome_probabilities

```
fitr.environments.plot_action_outcome_probabilities(self, figsize=None, outfile=None,
```

Plots the probabilities of different outcomes given actions.

Each plot is a heatmap for a starting state showing the transition probabilities for each action-outcome pair within that state.

TwoStep.plot_graph

```
fitr.environments.plot_graph(self, figsize=None, node_size=2000, arrowsize=20, lw=1.5
```

Plots the directed graph of the task

TwoStep.plot_reward_paths

```
fitr.environments.plot_reward_paths(self, outfile=None, outfiletype='pdf', figsize=No
```

TwoStep.plot_spectral_properties

```
fitr.environments.plot_spectral_properties(self, figsize=None, outfile=None, outfilet
```

Creates a set of subplots depicting the graph Laplacian and its spectral decomposition.

TwoStep.random_action

```
fitr.environments.random_action(self)
```

Samples a random one-hot action vector uniformly over the action space.

Useful for testing that your environment works, without having to create an agent.

$$\mathbf{u} \sim \text{Multinomial}\left(1, \mathbf{p} = \{p_i = \frac{1}{|\mathcal{U}|}\}_{i=1}^{|\mathcal{U}|}\right)$$

Returns:

A one-hot action vector of type `ndarray((nactions,))`

Examples:

```
u = env.random_action()
```

TwoStep.step

```
fitr.environments.step(self, action)
```

Executes a state transition in the environment.

Arguments:

`action` : A one-hot vector of type `ndarray((naction,))` indicating the action selected at the current state.

Returns:

A 3-tuple representing the next state (`ndarray((noutcomes,))`), scalar reward, and whether the current step terminates a trial (`bool`).

Raises:

`RuntimeError` if `env.observation()` not called after a previous `env.step(...)` call yielded a terminal state.

ReverseTwoStep

`fitr.environments.ReverseTwoStep()`

From Kool & Gershman 2016.

ReverseTwoStep.adjacency_matrix_decomposition

`fitr.environments.adjacency_matrix_decomposition(self)`

Singular value decomposition of the graph adjacency matrix

ReverseTwoStep.f_reward

`fitr.environments.f_reward(self, R, x)`

ReverseTwoStep.get_graph_depth

`fitr.environments.get_graph_depth(self)`

Returns the depth of the task graph.

Calculated as the depth from **START** (pre-initial state) to **END** (which absorbs trial from all terminal states), minus 2 to account for the **START->node** & **node->END** transitions.

Returns:

An `int` identifying the depth of the current graph for a single trial of the task

ReverseTwoStep.laplacian_matrix_decomposition

```
fitr.environments.laplacian_matrix_decomposition(self)
```

Singular value decomposition of the graph Laplacian

ReverseTwoStep.make_action_labels

```
fitr.environments.make_action_labels(self)
```

Creates labels for the actions (for plotting) if none provided

ReverseTwoStep.make_digraph

```
fitr.environments.make_digraph(self)
```

Creates a `networkx` `DiGraph` object from the transition tensor for the purpose of plotting and some other analyses.

ReverseTwoStep.make_state_labels

```
fitr.environments.make_state_labels(self)
```

Creates labels for the states (for plotting) if none provided

ReverseTwoStep.make_undirected_graph

```
fitr.environments.make_undirected_graph(self)
```

Converts the `DiGraph` to undirected and computes some stats

ReverseTwoStep.observation

```
fitr.environments.observation(self)
```

Samples an initial state from the start-state distribution $p(\mathbf{x})$

$$\mathbf{x}_0 \sim p(\mathbf{x})$$

Returns:

A one-hot vector `ndarray((nstates,))` indicating the starting state.

Examples:

```
x = env.observation()
```

ReverseTwoStep.plot_action_outcome_probabilities

```
fitr.environments.plot_action_outcome_probabilities(self, figsize=None, outfile=None,
```

Plots the probabilities of different outcomes given actions.

Each plot is a heatmap for a starting state showing the transition probabilities for each action-outcome pair within that state.

ReverseTwoStep.plot_graph

```
fitr.environments.plot_graph(self, figsize=None, node_size=2000, arrowsize=20, lw=1.5
```

Plots the directed graph of the task

ReverseTwoStep.plot_spectral_properties

```
fitr.environments.plot_spectral_properties(self, figsize=None, outfile=None, outfile
```

Creates a set of subplots depicting the graph Laplacian and its spectral decomposition.

ReverseTwoStep.random_action

`fitr.environments.random_action(self)`

Samples a random one-hot action vector uniformly over the action space.

Useful for testing that your environment works, without having to create an agent.

$$\mathbf{u} \sim \text{Multinomial}\left(1, \mathbf{p} = \{p_i = \frac{1}{|\mathcal{U}|}\}_{i=1}^{|\mathcal{U}|}\right)$$

Returns:

A one-hot action vector of type `ndarray((nactions,))`

Examples:

```
u = env.random_action()
```

ReverseTwoStep.step

`fitr.environments.step(self, action)`

Executes a state transition in the environment.

Arguments:

`action` : A one-hot vector of type `ndarray((naction,))` indicating the action selected at the current state.

Returns:

A 3-tuple representing the next state (`ndarray((noutcomes,))`), scalar reward, and whether the current step terminates a trial (`bool`).

Raises:

`RuntimeError` if `env.observation()` not called after a previous `env.step(...)` call yielded a terminal state.

RandomContextualBandit

`fitr.environments.RandomContextualBandit()`

Generates a random bandit task

Arguments:

- **nactions**: Number of actions
- **noutcomes**: Number of outcomes
- **nstates**: Number of contexts
- **min_actions_per_context**: Different contexts may have more or fewer actions than others (never more than **nactions**). This variable describes the minimum number of actions allowed in a context.
- **alpha**:
- **alpha_start**:
- **shift_flip**:
- **reward_lb**: Lower bound for drifting rewards
- **reward_ub**: Upper bound for drifting rewards
- **reward_drift**: Values (**on** or **off**) determining whether rewards are allowed to drift
- **drift_mu**: Mean of the Gaussian random walk determining reward
- **drift_sd**: Standard deviation of Gaussian random walk determining reward

RandomContextualBandit.adjacency_matrix_decomposition

`fitr.environments.adjacency_matrix_decomposition(self)`

Singular value decomposition of the graph adjacency matrix

RandomContextualBandit.f_reward

`fitr.environments.f_reward(self, R, x)`

RandomContextualBandit.get__graph__depth

```
fitr.environments.get_graph_depth(self)
```

Returns the depth of the task graph.

Calculated as the depth from **START** (pre-initial state) to **END** (which absorbs trial from all terminal states), minus 2 to account for the **START->node** & **node->END** transitions.

Returns:

An `int` identifying the depth of the current graph for a single trial of the task

RandomContextualBandit.laplacian__matrix__decomposition

```
fitr.environments.laplacian_matrix_decomposition(self)
```

Singular value decomposition of the graph Laplacian

RandomContextualBandit.make__action__labels

```
fitr.environments.make_action_labels(self)
```

Creates labels for the actions (for plotting) if none provided

RandomContextualBandit.make__digraph

```
fitr.environments.make_digraph(self)
```

Creates a `networkx DiGraph` object from the transition tensor for the purpose of plotting and some other analyses.

RandomContextualBandit.make__state__labels

```
fitr.environments.make_state_labels(self)
```

Creates labels for the states (for plotting) if none provided

RandomContextualBandit.make__undirected__graph

```
fitr.environments.make_undirected_graph(self)
```

Converts the DiGraph to undirected and computes some stats

RandomContextualBandit.observation

```
fitr.environments.observation(self)
```

Samples an initial state from the start-state distribution $p(\mathbf{x})$

$$\mathbf{x}_0 \sim p(\mathbf{x})$$

Returns:

A one-hot vector `ndarray((nstates,))` indicating the starting state.

Examples:

```
x = env.observation()
```

RandomContextualBandit.plot__action__outcome__probabilities

```
fitr.environments.plot_action_outcome_probabilities(self, figsize=None, outfile=None,
```

Plots the probabilities of different outcomes given actions.

Each plot is a heatmap for a starting state showing the transition probabilities for each action-outcome pair within that state.

RandomContextualBandit.plot_graph

```
fitr.environments.plot_graph(self, figsize=None, node_size=2000, arrowsize=20, lw=1.5)
```

Plots the directed graph of the task

RandomContextualBandit.plot_spectral_properties

```
fitr.environments.plot_spectral_properties(self, figsize=None, outfile=None, outfile)
```

Creates a set of subplots depicting the graph Laplacian and its spectral decomposition.

RandomContextualBandit.random_action

```
fitr.environments.random_action(self)
```

Samples a random one-hot action vector uniformly over the action space.

Useful for testing that your environment works, without having to create an agent.

$$\mathbf{u} \sim \text{Multinomial}\left(1, \mathbf{p} = \{p_i = \frac{1}{|\mathcal{U}|}\}_{i=1}^{|\mathcal{U}|}\right)$$

Returns:

A one-hot action vector of type `ndarray((nactions,))`

Examples:

```
u = env.random_action()
```

RandomContextualBandit.step

```
fitr.environments.step(self, action)
```

Executes a state transition in the environment.

Arguments:

action : A one-hot vector of type `ndarray((naction,))` indicating the action selected at the current state.

Returns:

A 3-tuple representing the next state (`ndarray((noutcomes,))`), scalar reward, and whether the current step terminates a trial (`bool`).

Raises:

`RuntimeError` if `env.observation()` not called after a previous `env.step(...)` call yielded a terminal state.

`fitr.agents`

A modular way to build and test reinforcement learning agents.

There are three main submodules:

- `fitr.agents.policies`: which describe a class of functions essentially representing $f : \mathcal{X} \rightarrow \mathcal{U}$
- `fitr.agents.value_functions`: which describe a class of functions essentially representing $\mathcal{V} : \mathcal{X} \rightarrow \mathbb{R}$ and/or $\mathcal{Q} : \mathcal{Q} \times \mathcal{U} \rightarrow \mathbb{R}$
- `fitr.agents.agents`: classes of agents that are combinations of policies and value functions, along with some convenience functions for generating data from `fitr.environments.Graph` environments.

SoftmaxPolicy

`fitr.agents.policies.SoftmaxPolicy()`

Action selection by sampling from a multinomial whose parameters are given by a softmax.

Action sampling is

$$\mathbf{u} \sim \text{Multinomial}(1, \mathbf{p} = \varsigma(\mathbf{v})).$$

Parameters of that distribution are

$$p(\mathbf{u}|\mathbf{v}) = \varsigma(\mathbf{v}) = \frac{e^{\beta \mathbf{v}}}{\sum_i e^{\beta v_i}}.$$

Arguments:

- `inverse_softmax_temp`: Inverse softmax temperature β
 - `rng`: `np.random.RandomState` object
-

`SoftmaxPolicy.action_prob`

`fitr.agents.policies.action_prob(self, x)`

Computes the softmax

SoftmaxPolicy.log_prob

`fitr.agents.policies.log_prob(self, x)`

Computes the log-probability of an action **u**

$$\log p(\mathbf{u}|\mathbf{v}) = \beta \mathbf{v} - \log \sum_{v_i} e^{\beta \mathbf{v}_i}$$

Arguments:

- **x**: State vector of type `ndarray((nstates,))`

Returns:

Scalar log-probability

SoftmaxPolicy.sample

`fitr.agents.policies.sample(self, x)`

Samples from the action distribution

StickySoftmaxPolicy

`fitr.agents.policies.StickySoftmaxPolicy()`

Action selection by sampling from a multinomial whose parameters are given by a softmax, but with accounting for the tendency to perseverate (i.e. choosing the previously used action without considering its value).

Let $\mathbf{u}_{t-1} = (u_{t-1}^{(i)})_{i=1}^{|\mathcal{U}|}$ be a one hot vector representing the action taken at the last step, and β^ρ be an inverse softmax temperature for the influence of this last action.

Action sampling is thus:

$$\mathbf{u} \sim \text{Multinomial}(1, \mathbf{p} = \varsigma(\mathbf{v}, \mathbf{u}_{t-1})).$$

Parameters of that distribution are

$$p(\mathbf{u}|\mathbf{v}, \mathbf{u}_{t-1}) = \varsigma(\mathbf{v}, \mathbf{u}_{t-1}) = \frac{e^{\beta\mathbf{v} + \beta^\rho \mathbf{u}_{t-1}}}{\sum_i^{|\mathbf{v}|} e^{\beta v_i + \beta^\rho u_{t-1}^{(i)}}}.$$

Arguments:

- **inverse_softmax_temp**: Inverse softmax temperature β
 - **perseveration**: Inverse softmax temperature β^ρ capturing the tendency to repeat the last action taken.
 - **rng**: `np.random.RandomState` object
-

StickySoftmaxPolicy.action_prob

`fitr.agents.policies.action_prob(self, x)`

Computes the softmax

Arguments:

- **x**: `ndarray((nstates,))` one-hot state vector

Returns:

`ndarray((nstates,))` vector of action probabilities

StickySoftmaxPolicy.log_prob

`fitr.agents.policies.log_prob(self, x)`

Computes the log-probability of an action \mathbf{u}

$$\log p(\mathbf{u}|\mathbf{v}, \mathbf{u}_{t-1}) = (\beta\mathbf{v} + \beta^\rho \mathbf{u}_{t-1}) - \log \sum_{v_i} e^{\beta v_i + \beta^\rho u_{t-1}^{(i)}}$$

Arguments:

- **x**: State vector of type `ndarray((nstates,))`

Returns:

Scalar log-probability

StickySoftmaxPolicy.sample

`fitr.agents.policies.sample(self, x)`

Samples from the action distribution

Arguments:

- **x**: `ndarray((nstates,))` one-hot state vector

Returns:

`ndarray((nstates,))` one-hot action vector

EpsilonGreedyPolicy

`fitr.agents.policies.EpsilonGreedyPolicy()`

EpsilonGreedyPolicy.action_prob

`fitr.agents.policies.action_prob(self, x)`

Creates vector of action probabilities for e-greedy policy

EpsilonGreedyPolicy.sample

`fitr.agents.policies.sample(self, x)`

ValueFunction

`fitr.agents.value_functions.ValueFunction()`

A general value function object.

A value function here is task specific and consists of several attributes:

- **nstates**: The number of states in the task, $|\mathcal{X}|$
- **nactions**: Number of actions in the task, $|\mathcal{U}|$
- **V**: State value function $\mathbf{v} = \mathcal{V}(\mathbf{x})$
- **Q**: State-action value function $\mathbf{Q} = \mathcal{Q}(\mathbf{x}, \mathbf{u})$
- **etrace**: An eligibility trace (optional)

Note that in general we rely on matrix-vector notation for value functions, rather than function notation. Vectors in the mathematical typesetting are by default column vectors.

Arguments:

- **env**: A `fitr.environments.Graph`
-

ValueFunction.Qmax

`fitr.agents.value_functions.Qmax(self, x)`

Return maximal action value for given state

$$\max_{u_i} Q(\mathbf{x}, u_i) = \max_{\mathbf{u}'} \mathbf{u}'^T \mathbf{Q} \mathbf{x}$$

Arguments:

- **x**: `ndarray((nstates,))` one-hot state vector

Returns:

Scalar value of the maximal action value at the given state

ValueFunction.Qmean

```
fitr.agents.value_functions.Qmean(self, x)
```

Return mean action value for given state

$$\text{Mean}(\mathcal{Q}(\mathbf{x}, :)) = \frac{1}{|\mathcal{U}|} \mathbf{1}^\top \mathbf{Q}\mathbf{x}$$

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector

Returns:

Scalar value of the maximal action value at the given state

ValueFunction.Qx

```
fitr.agents.value_functions.Qx(self, x)
```

Compute action values for a given state

$$\mathcal{Q}(\mathbf{x}, :) = \mathbf{Q}\mathbf{x}$$

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector

Returns:

ndarray((nactions,)) vector of values for actions in the given state

ValueFunction.Vx

```
fitr.agents.value_functions.Vx(self, x)
```

ValueFunction.uQx

```
fitr.agents.value_functions.uQx(self, u, x)
```

DummyLearner

```
fitr.agents.value_functions.DummyLearner()
```

A critic for the random learner

DummyLearner.Qmax

```
fitr.agents.value_functions.Qmax(self, x)
```

Return maximal action value for given state

$$\max_{u_i} Q(\mathbf{x}, u_i) = \max_{\mathbf{u}'} \mathbf{u}'^\top \mathbf{Q} \mathbf{x}$$

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector

Returns:

Scalar value of the maximal action value at the given state

DummyLearner.Qmean

```
fitr.agents.value_functions.Qmean(self, x)
```

Return mean action value for given state

$$Mean(Q(\mathbf{x}, :)) = \frac{1}{|\mathcal{U}|} \mathbf{1}^\top \mathbf{Q} \mathbf{x}$$

Arguments:

- `x`: `ndarray((nstates,))` one-hot state vector

Returns:

Scalar value of the maximal action value at the given state

DummyLearner.Qx

`fitr.agents.value_functions.Qx(self, x)`

Compute action values for a given state

$$Q(\mathbf{x}, :) = \mathbf{Qx}$$

Arguments:

- `x`: `ndarray((nstates,))` one-hot state vector

Returns:

`ndarray((nactions,))` vector of values for actions in the given state

DummyLearner.Vx

`fitr.agents.value_functions.Vx(self, x)`

DummyLearner.uQx

`fitr.agents.value_functions.uQx(self, u, x)`

DummyLerner.update

```
fitr.agents.value_functions.update(self, x, u, r, x_, u_)
```

InstrumentalRescorlaWagnerLerner

```
fitr.agents.value_functions.InstrumentalRescorlaWagnerLerner()
```

A general value function object.

A value function here is task specific and consists of several attributes:

- **nstates**: The number of states in the task, $|\mathcal{X}|$
- **nactions**: Number of actions in the task, $|\mathcal{U}|$
- **V**: State value function $\mathbf{v} = \mathcal{V}(\mathbf{x})$
- **Q**: State-action value function $\mathbf{Q} = \mathcal{Q}(\mathbf{x}, \mathbf{u})$
- **etrace**: An eligibility trace (optional)

Note that in general we rely on matrix-vector notation for value functions, rather than function notation. Vectors in the mathematical typesetting are by default column vectors.

Arguments:

- **env**: A `fitr.environments.Graph`
-

InstrumentalRescorlaWagnerLerner.Qmax

```
fitr.agents.value_functions.Qmax(self, x)
```

Return maximal action value for given state

$$\max_{u_i} \mathcal{Q}(\mathbf{x}, u_i) = \max_{\mathbf{u}'} \mathbf{u}'^\top \mathbf{Q} \mathbf{x}$$

Arguments:

- **x**: `ndarray((nstates,))` one-hot state vector

Returns:

Scalar value of the maximal action value at the given state

InstrumentalRescorlaWagnerLearner.Qmean

`fitr.agents.value_functions.Qmean(self, x)`

Return mean action value for given state

$$Mean(Q(\mathbf{x}, :)) = \frac{1}{|\mathcal{U}|} \mathbf{1}^\top \mathbf{Q} \mathbf{x}$$

Arguments:

- `x`: `ndarray((nstates,))` one-hot state vector

Returns:

Scalar value of the maximal action value at the given state

InstrumentalRescorlaWagnerLearner.Qx

`fitr.agents.value_functions.Qx(self, x)`

Compute action values for a given state

$$Q(\mathbf{x}, :) = \mathbf{Q} \mathbf{x}$$

Arguments:

- `x`: `ndarray((nstates,))` one-hot state vector

Returns:

`ndarray((nactions,))` vector of values for actions in the given state

InstrumentalRescorlaWagnerLearner.Vx

```
fitr.agents.value_functions.Vx(self, x)
```

InstrumentalRescorlaWagnerLearner.uQx

```
fitr.agents.value_functions.uQx(self, u, x)
```

InstrumentalRescorlaWagnerLearner.update

```
fitr.agents.value_functions.update(self, x, u, r, x_, u_)
```

QLearner

```
fitr.agents.value_functions.QLearner()
```

A general value function object.

A value function here is task specific and consists of several attributes:

- **nstates**: The number of states in the task, $|\mathcal{X}|$
- **nactions**: Number of actions in the task, $|\mathcal{U}|$
- **V**: State value function $\mathbf{v} = \mathcal{V}(\mathbf{x})$
- **Q**: State-action value function $\mathbf{Q} = \mathcal{Q}(\mathbf{x}, \mathbf{u})$
- **etrace**: An eligibility trace (optional)

Note that in general we rely on matrix-vector notation for value functions, rather than function notation. Vectors in the mathematical typesetting are by default column vectors.

Arguments:

- **env**: A `fitr.environments.Graph`
-

QLearner.Qmax

```
fitr.agents.value_functions.Qmax(self, x)
```

Return maximal action value for given state

$$\max_{u_i} Q(\mathbf{x}, u_i) = \max_{\mathbf{u}'} \mathbf{u}'^\top \mathbf{Q}\mathbf{x}$$

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector

Returns:

Scalar value of the maximal action value at the given state

QLearner.Qmean

```
fitr.agents.value_functions.Qmean(self, x)
```

Return mean action value for given state

$$Mean(Q(\mathbf{x}, :)) = \frac{1}{|\mathcal{U}|} \mathbf{1}^\top \mathbf{Q}\mathbf{x}$$

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector

Returns:

Scalar value of the maximal action value at the given state

QLearner.Qx

```
fitr.agents.value_functions.Qx(self, x)
```


Compute action values for a given state

$$Q(\mathbf{x}, :) = \mathbf{Q}\mathbf{x}$$

Arguments:

- **x**: `ndarray((nstates,))` one-hot state vector

Returns:

`ndarray((nactions,))` vector of values for actions in the given state

QLearner.Vx

`fitr.agents.value_functions.Vx(self, x)`

QLearner.uQx

`fitr.agents.value_functions.uQx(self, u, x)`

QLearner.update

`fitr.agents.value_functions.update(self, x, u, r, x_, u_)`

SARSA Learner

`fitr.agents.value_functions.SARSA Learner()`

A general value function object.

A value function here is task specific and consists of several attributes:

- **nstates**: The number of states in the task, $|\mathcal{X}|$
- **nactions**: Number of actions in the task, $|\mathcal{U}|$

- V : State value function $\mathbf{v} = \mathcal{V}(\mathbf{x})$
- Q : State-action value function $\mathbf{Q} = \mathcal{Q}(\mathbf{x}, \mathbf{u})$
- `etrace`: An eligibility trace (optional)

Note that in general we rely on matrix-vector notation for value functions, rather than function notation. Vectors in the mathematical typesetting are by default column vectors.

Arguments:

- `env`: A `fitr.environments.Graph`
-

SARSA Learner.Qmax

`fitr.agents.value_functions.Qmax(self, x)`

Return maximal action value for given state

$$\max_{u_i} Q(\mathbf{x}, u_i) = \max_{\mathbf{u}'} \mathbf{u}'^\top \mathbf{Q} \mathbf{x}$$

Arguments:

- `x`: `ndarray((nstates,))` one-hot state vector

Returns:

Scalar value of the maximal action value at the given state

SARSA Learner.Qmean

`fitr.agents.value_functions.Qmean(self, x)`

Return mean action value for given state

$$\text{Mean}(Q(\mathbf{x}, :)) = \frac{1}{|\mathcal{U}|} \mathbf{1}^\top \mathbf{Q} \mathbf{x}$$

Arguments:

- `x`: `ndarray((nstates,))` one-hot state vector

Returns:

Scalar value of the maximal action value at the given state

SARSA Learner.Qx

```
fitr.agents.value_functions.Qx(self, x)
```

Compute action values for a given state

$$Q(\mathbf{x}, :) = \mathbf{Qx}$$

Arguments:

- `x`: `ndarray((nstates,))` one-hot state vector

Returns:

`ndarray((nactions,))` vector of values for actions in the given state

SARSA Learner.Vx

```
fitr.agents.value_functions.Vx(self, x)
```

SARSA Learner.uQx

```
fitr.agents.value_functions.uQx(self, u, x)
```

SARSA Learner.update

```
fitr.agents.value_functions.update(self, x, u, r, x_, u_)
```

Agent

```
fitr.agents.agents.Agent()
```

Base class for synthetic RL agents

Arguments:

meta : List of metadata of arbitrary type. e.g. labels, covariates, etc. params
 : List of parameters for the agent. Should be filled for specific agent.

Agent.reset_trace

```
fitr.agents.agents.reset_trace(self, x, u=None)
```

For agents with eligibility traces, this resets the eligibility trace (for episodic tasks)

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector
 - **u**: ndarray((nactions,)) one-hot action vector (optional)
-

BanditAgent

```
fitr.agents.agents.BanditAgent()
```

A base class for agents in bandit tasks (i.e. with one step).

This mainly has implications for generating data

BanditAgent.generate__data

```
fitr.agents.agents.generate_data(self, ntrials)
```

BanditAgent.reset__trace

```
fitr.agents.agents.reset_trace(self, x, u=None)
```

For agents with eligibility traces, this resets the eligibility trace (for episodic tasks)

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector
 - **u**: ndarray((nactions,)) one-hot action vector (optional)
-

MDPAgent

```
fitr.agents.agents.MDPAgent()
```

A base class for agents that operate on MDPs.

This mainly has implications for generating data

MDPAgent.generate__data

```
fitr.agents.agents.generate_data(self, ntrials)
```

MDPAgent.reset__trace

```
fitr.agents.agents.reset_trace(self, x, u=None)
```

For agents with eligibility traces, this resets the eligibility trace (for episodic tasks)

Arguments:

- `x`: `ndarray((nstates,))` one-hot state vector
 - `u`: `ndarray((nactions,))` one-hot action vector (optional)
-

RandomBanditAgent

`fitr.agents.agents.RandomBanditAgent()`

An agent that simply selects random actions at each trial

RandomBanditAgent.action

`fitr.agents.agents.action(self, state)`

RandomBanditAgent.generate__data

`fitr.agents.agents.generate_data(self, ntrials)`

RandomBanditAgent.learning

`fitr.agents.agents.learning(self, state, action, reward, next_state, next_action)`

RandomBanditAgent.reset__trace

`fitr.agents.agents.reset_trace(self, x, u=None)`

For agents with eligibility traces, this resets the eligibility trace (for episodic tasks)

Arguments:

- `x`: `ndarray((nstates,))` one-hot state vector
 - `u`: `ndarray((nactions,))` one-hot action vector (optional)
-

RandomMDPAgent

```
fitr.agents.agents.RandomMDPAgent()
```

An agent that simply selects random actions at each trial

Notes

This has been specified as an `OnPolicyAgent` arbitrarily.

RandomMDPAgent.action

```
fitr.agents.agents.action(self, state)
```

RandomMDPAgent.generate__data

```
fitr.agents.agents.generate_data(self, ntrials)
```

RandomMDPAgent.learning

```
fitr.agents.agents.learning(self, state, action, reward, next_state, next_action)
```

RandomMDPAgent.reset_trace

```
fitr.agents.agents.reset_trace(self, x, u=None)
```

For agents with eligibility traces, this resets the eligibility trace (for episodic tasks)

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector
 - **u**: ndarray((nactions,)) one-hot action vector (optional)
-

SARSA SoftmaxAgent

```
fitr.agents.agents.SARSA SoftmaxAgent()
```

An agent that uses the SARSA learning rule and a softmax policy

SARSA SoftmaxAgent.action

```
fitr.agents.agents.action(self, state)
```

SARSA SoftmaxAgent.generate_data

```
fitr.agents.agents.generate_data(self, ntrials)
```

SARSA SoftmaxAgent.learning

```
fitr.agents.agents.learning(self, state, action, reward, next_state, next_action)
```

SARSA SoftmaxAgent.reset_trace

```
fitr.agents.agents.reset_trace(self, x, u=None)
```

For agents with eligibility traces, this resets the eligibility trace (for episodic tasks)

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector
 - **u**: ndarray((nactions,)) one-hot action vector (optional)
-

QLearningSoftmaxAgent

```
fitr.agents.agents.QLearningSoftmaxAgent()
```

An agent that uses the Q-learning rule and a softmax policy

QLearningSoftmaxAgent.action

```
fitr.agents.agents.action(self, state)
```

QLearningSoftmaxAgent.generate_data

```
fitr.agents.agents.generate_data(self, ntrials)
```

QLearningSoftmaxAgent.learning

```
fitr.agents.agents.learning(self, state, action, reward, next_state, next_action)
```

QLearningSoftmaxAgent.reset_trace

```
fitr.agents.agents.reset_trace(self, x, u=None)
```

For agents with eligibility traces, this resets the eligibility trace (for episodic tasks)

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector
 - **u**: ndarray((nactions,)) one-hot action vector (optional)
-

RWSoftmaxAgent

```
fitr.agents.agents.RWSoftmaxAgent()
```

A base class for agents in bandit tasks (i.e. with one step).

This mainly has implications for generating data

RWSoftmaxAgent.action

```
fitr.agents.agents.action(self, state)
```

RWSoftmaxAgent.generate_data

```
fitr.agents.agents.generate_data(self, ntrials)
```

RWSoftmaxAgent.learning

```
fitr.agents.agents.learning(self, state, action, reward, next_state, next_action)
```

RWSoftmaxAgent.reset__trace

```
fitr.agents.agents.reset_trace(self, x, u=None)
```

For agents with eligibility traces, this resets the eligibility trace (for episodic tasks)

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector
 - **u**: ndarray((nactions,)) one-hot action vector (optional)
-

RWSoftmaxAgentRewardSensitivity

```
fitr.agents.agents.RWSoftmaxAgentRewardSensitivity()
```

A base class for agents in bandit tasks (i.e. with one step).

This mainly has implications for generating data

RWSoftmaxAgentRewardSensitivity.action

```
fitr.agents.agents.action(self, state)
```

RWSoftmaxAgentRewardSensitivity.generate__data

```
fitr.agents.agents.generate_data(self, ntrials)
```

RWSoftmaxAgentRewardSensitivity.learning

```
fitr.agents.agents.learning(self, state, action, reward, next_state, next_action)
```

RWSoftmaxAgentRewardSensitivity.reset_trace

```
fitr.agents.agents.reset_trace(self, x, u=None)
```

For agents with eligibility traces, this resets the eligibility trace (for episodic tasks)

Arguments:

- **x**: ndarray((nstates,)) one-hot state vector
 - **u**: ndarray((nactions,)) one-hot action vector (optional)
-

fitr.utils

Functions used across **fitr**.

softmax

fitr.utils.softmax(x)

Computes the softmax function

$$p(\mathbf{x}) = \frac{e^{\mathbf{x} - \max_i x_i}}{\mathbf{1}^\top e^{\mathbf{x} - \max_i x_i}}$$

Arguments:

- **x**: Softmax logits (`ndarray((N,))`)

Returns:

Vector of probabilities of size `ndarray((N,))`

sigmoid

fitr.utils.sigmoid(x, a_min=-10, a_max=10)

Sigmoid function

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$

Arguments:

- **x**: Vector
- **a_min**: Lower bound at which to clip values of **x**
- **a_max**: Upper bound at which to clip values of **x**

Returns:

Vector between 0 and 1 of size **x.shape**

stable_exp

```
fitr.utils.stable_exp(x, a_min=-10, a_max=10)
```

Clipped exponential function

Avoids overflow by clipping input values.

Arguments:

- **x**: Vector of inputs
- **a_min**: Lower bound at which to clip values of **x**
- **a_max**: Upper bound at which to clip values of **x**

Returns:

Exponentiated values of **x**.

logsumexp

```
fitr.utils.logsumexp(x)
```

Numerically stable logsumexp.

Computed as follows:

$$\max x + \log \sum_x e^{x - \max x}$$

Arguments:

- **x**: 'ndarray(shape=(nactions,))'

Returns:

float

log_loss

```
fitr.utils.log_loss(p, q)
```

Log-loss function.

$$\mathcal{L} = \mathbf{p}^\top \log \mathbf{q} + (1 - \mathbf{p})^\top \log(1 - \mathbf{q})$$

Arguments:

- **p**: Binary vector of true labels `ndarray((nsamples,))`
- **q**: Vector of estimates (between 0 and 1) of type `ndarray((nsamples,))`

Returns:

Scalar log loss
