

SPR Implementation Guide: XML POACK

Version 8.00

Table of Contents

About this Guide	3
Support.....	3
Introduction	4
PO XML – Order Tags	5
Order Header Tags	5
Order Line Detail Tags	14
Appendix A – Sample XML Orders	16
Sample Inbound PO: DropShip 04.....	16
Sample Outbound POACK: DropShip 04.....	17
Sample Inbound PO: Wrap & Label 03	18
Sample Outbound POACK: Wrap & Label 03.....	20
Appendix B - FAQ.....	22
General Questions	22

About this Guide

This guide describes the interactions of the data fields in the SPR XML PO Acknowledgement (POACK) with the SPR Order Management System (OMS).

Support

Call the S.P.Richards Helpdesk at 1.888.763.2615 for SPR EDI technical support.

Introduction

SPR PO XML formats are described by the XSD documentation for the XML PO and POACK. This document addresses frequently asked questions about how the XSDs are implemented. Real PO scenarios are profiled and usage issues are discussed.

PO ACK XML – Order Tags

Each valid order tag or element is listed with an explanation of its function. The order header tags, which apply to the entire order, are listed first. The detail line tags, which apply only to the detail line, are listed last.

Whenever a “default” condition is shown in the following lists, the default action is triggered if no value for the tag or element is received. For example, if an attribute for an element is blank, the default will be used. Likewise, if the element is not sent, the default for that element will be used.

Order Header Tags

<xs:element name="Order" minOccurs="1">

1. <xs:attribute name="EnterpriseCode" use="optional" default="SPR">
An SPR Business Unit must be selected for each order. If the default is selected, the order will be processed by SPR USA.
Options: SPR = SPR USA [Default]
 SPC = SPR Canada
 SPS = Special Order SKU
2. <xs:attribute name="BuyerOrganizationCode" use="required">
A valid SPR account number must be sent with each order. Use the 9-digit SPR account number that should be billed for the order. The format should be “1234567.89”. In addition, leading zeroes for the account number must be sent. For example, “0001234.56” is correct, but “1234.56” is not. For testing purposes only “9999999.99” can be used.
3. <xs:attribute name="EntryType" use="Optional">
Enter the electronic method of data transmission; i. e., AS2, FTP. This used for troubleshooting at SPR.
4. <xs:attribute name="DraftOrderFlag" use="optional" default="N">
If the order is a test order, set this attribute to “Y”. For production orders, do not send this attribute.
5. <xs:attribute name="OrderType" use="optional" default="01">
Select the appropriate order type. The default, “01”, is a regular order, which is a local scheduled delivery on an SPR truck.
Options: 01 = Regular Order (DC to Dealer local delivery on SPR truck)
 02 = 2nd Party Logistics (Prearranged delivery relationship)
 03 = Wrap & Label (Boxed and labeled with the ShipTo address, then delivered locally to Dealer on an SPR truck.)
 04 = Drop Ship (Delivered by a parcel carrier, like UPS or FedEx)
 05 = SPS DropShip (ProductPro/Furniture Advantage DropShip sales order)
 07 = SPS W&L (ProductPro/Furniture Advantage W&L sales order – Cross Dock)
6. <xs:attribute name="ShipNode" use="optional">
Select the DC which should ship the order. Send the SPR DC number. The DC number is required for regular orders and Wrap & Label orders. The DC number is also required for DropShip orders which do not use AutoRoute or Source Complete.

7. `<xs:attribute name="IsShipComplete" use="optional" default="N">`

This flag allows orders to be bumped to additional SPR DCs to complete the order. For DropShip orders, the depth of the bumping is controlled by the ParcelZone attribute. For NON-DropShip orders, the depth of the bumping is controlled by the SprinterDays attribute.

DropShip Options:

Y = Send order to the DC closest to the ShipTo ZIP Code. Do not bump to additional DCs.
 N = Do not use sourcing logic. Send order to SPR DC in ShipNode. [Default]
 C = Source Complete "Complete" option
 Q = Source Complete "Quick" option
 S = Source Complete "Single DC" option

NON-DropShip Options:

Q = Send order to the DC in ShipNode and bump to additional DCs in Sprinter network as required to fill as much of the order as possible.
 N = Send order to the DC in ShipNode. Do not use bump logic.

8. `<xs:attribute name="IsShipSingleNode" use="optional" default="N">`

Not Used

9. `<xs:attribute name="CancelOrderOnBackorder" use="optional" default="N">`

When this flag is set to "Y", the entire order will be cancelled if it is not filled completely.

Options: Y = Cancel all lines on the order if every line not filled completely.
 N = Allow the order to be partially filled if it cannot be filled completely.

10. `<xs:attribute name="EnteredBy" use="optional">`

This field is intended to identify the person that entered the order. It is free-form text, and is used by the Dealer.

11. `<xs:attribute name="CustomerPONo" use="optional">`

Enter the Dealer Purchase Order number.

12. `<xs:attribute name="CustomerEMailID" use="optional">`

Enter the e-mail address of the customer who owns the CustomerPONo.

13. `<xs:attribute name="CustCustPONo" use="optional">`

Enter the Purchase Order number for the end consumer if it is different than the CustomerPONo. Many Dealers have customers who have their own Purchase Order numbers that the Dealer must track.

14. `<xs:attribute name="SCAC" use="optional">`

Not Used; Freight Carrier ID

15. `<xs:attribute name="CarrierAccountNo" use="optional">`

Not Used; FreightCarrier Account Number

16. `<xs:attribute name="Division" use="optional">`

Free-form text name of Dealer's frontend Order Management System

17. `<xs:attribute name="DepartmentCode" use="optional">`

Free-form text name of Dealer's backend Order Management System

<xs:element name="PersonInfoShipTo" minOccurs="0">

1. <xs:attribute name="FirstName" use="required">
Enter the name of the end consumer or Ship-to Company.
2. <xs:attribute name="AddressLine1" use="required">
Enter the first line of the address where the order will be shipped.
3. <xs:attribute name="AddressLine2" use="optional">
As required, enter additional address information.
4. <xs:attribute name="AddressLine3" use="optional">
As required, enter additional address information.
5. <xs:attribute name="City" use="required">
Enter the city where the order will be shipped.
6. <xs:attribute name="State" use="required">
Enter the state where the order will be shipped.
7. <xs:attribute name="ZipCode" use="required">
Enter the ZIP Code where the order will be shipped.
8. <xs:attribute name="Country" use="optional">
Enter the country where the order will be shipped.
9. <xs:attribute name="IsCommercialAddress" use="optional" default="N"> Indicate
if the address where the order will be shipped is a commercial address. Options:
 N = ShipTo address is residential
 Y = ShipTo address is commercial
10. <xs:attribute name="EMailID" use="optional">
Enter the e-mail address of the end consumer. This e-mail address will be used to schedule special order deliveries. Also, in case any delivery issues arise, this e-mail address will be used to resolve them.
11. <xs:attribute name="PersonID" use="optional">
As required, enter the name of the person who is expecting the order.
12. <xs:attribute name="OtherPhone" use="optional">
Enter the phone number of the end consumer. This phone number will be used to schedule special order deliveries.

<xs:element name="PersonInfoContact" minOccurs="0">

1. **<xs:attribute name="FirstName" use="optional">**
Enter the ShipFrom Company name.
2. **<xs:attribute name="AddressLine1" use="optional">**
Enter the ShipFrom address for the order.
3. **<xs:attribute name="AddressLine2" use="optional">**
If required, enter the additional ShipFrom address information.
4. **<xs:attribute name="AddressLine3" use="optional">**
If required, enter the additional ShipFrom address information.
5. **<xs:attribute name="City" use="optional">**
Enter the ShipFrom City.
6. **<xs:attribute name="State" use="optional">**
Enter the ShipFrom state.
7. **<xs:attribute name="ZipCode" use="optional">**
Enter the ShipFrom ZIP Code.
8. **<xs:attribute name="Country" use="optional">**
Enter the ShipFrom country.
9. **<xs:attribute name="EMailID" use="optional">**
Enter the e-mail address of the ShipFrom company.

<xs:element name="Instructions" minOccurs="0">**<xs:element name="Instruction" maxOccurs="2">**

1. **<xs:attribute name="InstructionText" use="optional">**
Enter free text instructions. Prints in the "Comment/Special Instructions" field on the Packing List; but, does not print on label.

<xs:element name="Notes" minOccurs="0">**<xs:element name="Note" maxOccurs="6">**

1. **<xs:attribute name="SequenceNo" use="optional">**
Enter the sequence number for this Header note.
2. **<xs:attribute name="ContactType" use="optional">**
Enter the code which applies to this Header note.
Be aware of the max number of occurrences for this element
Options: C = Header Comment (Pack Slip Comment – MaxOccur for Note element is 6)
L = BOL Comment (B.O.L. Comment – MaxOccur for Note element is 4)
3. **<xs:attribute name="ContactReference" use="optional">**
Not Used
4. **<xs:attribute name="ContactUser" use="optional">**

Not Used

5. `<xs:attribute name="CustomerSatIndicator" use="optional">`
Not Used

6. `<xs:attribute name="NoteText" use="required">`
Enter Header note or comments **(Max NoteText is 50 Characters)**

`<xs:element name="Extn" minOccurs="0">`
`<xs:element name="EXTNSprOrderHeaderList" minOccurs="0">`
`<xs:element name="EXTNSprOrderHeader" minOccurs="0">`

1. `<xs:attribute name="EdiPrefix" use="optional">`
Enter the Dealer code assigned by SPR. This for order identification at SPR only.

2. `<xs:attribute name="ShipMethod" use="optional">`
Specify if this order is a Will Call order.
Options: 00=Ship by Default Method [Default]
01=Will Call

3. `<xs:attribute name="LevelOfServ" use="optional" default="D">`
Not Used

4. `<xs:attribute name="UseSprinters" use="optional" default="">`
Not Used

5. `<xs:attribute name="PricedPackSlip" use="optional" default="D">`
Not Used

6. `<xs:attribute name="CanNonUps" use="optional" default="N">`

DropShip:

If this flag is set to "Y" for a DropShip order, only line items which cannot be shipped via standard parcel carrier will be cancelled. If this flag is set to "N" for a DropShip order, SPR will try to ship all items; however, if an item cannot be shipped by parcel carrier, it will be shipped by LTL truck only to the closest zone. If the destination for the LTL carrier is beyond the closest zone, that line item will be cancelled.

Options: Y = Cancel lines which cannot be shipped via parcel carrier.
N = Ship all items and use LTL carrier as required for closest zone. [Default]

NON-DropShip:

Not used for NON-DropShip orders. For NON-DropShip orders, SPR will ship all items via the Sprinter network on SPR trucks.

7. `<xs:attribute name="ParcelZone" use="optional" default="N">`

Used for DropShip orders only.

This flag is ignored if "IsShipComplete" is set to "N."

Options: Y = Use all zones in ZIP Code table
 N = Do not bump [Default]
 2 = Allow 2 zones
 3 = Allow 3 zones
 4 = Allow 4 zones
 5 = Allow 5 zones
 6 = Allow 6 zones

This flag is used for regular orders and Wrap&Label orders only.

This flag is ignored if "IsShipComplete" is set to "N."

The depth is defined in the Sprinter which is maintained by SPR.

The SPR EDI Group can provide the correct depth for specific order scenarios based on this table.

Options: Q = Bump through full depth. Use entire Sprinter network.
 N = Do not bump [Default]
 2 = Depth 2
 3 = Depth 3
 4 = Depth 4
 5 = Depth 5
 6 = Depth 6

8. `<xs:attribute name="ShowCost" use="optional" default="D">`

Print SPR selling price to Dealer for each line item on Packing List. This option is ignored for DropShip orders. For DropShip orders the Dealer cost cannot be printed on the Packing List.

Options: Y = Show Dealer cost for each line item on Packing List
 N = Packing List will not display Dealer cost [Default]

9. `<xs:attribute name="ShowList" use="optional" default="D">`

Print SPR list price of each line item on Packing List.

Options: Y = Show SPR list price for each line item on Packing List [Default]
 N = Packing List will not display list price.

10. `<xs:attribute name="OneOrder" use="optional" default="D">`

Assign a unique invoice number to each order. The invoice file will show one invoice for each order. The default action will group orders with a common invoice number.

Options: Y = Assign separate invoice number to the order. [Default]
 N = Change invoice number when order type changes.

11. `<xs:attribute name="ListCost" use="optional" default="L">`

Use this flag to identify whether the dollar figure sent in each line item is list price or Dealer unit cost. If the SPR Unit of Measure (UOM) is correctly sent in the order, this flag is ignored. However, if the UOM for the line item is not the standard SPR UOM, this flag is used in the calculation of the correct quantity ordered.

Options: L = The dollar figure sent for the line item is list price. [Default]
 C = The dollar figure sent for the line item is Dealer cost.

12. `<xs:attribute name="StdDescs" use="optional" default="D">`

Use the SPR standard labels descriptions. The standard label text can be customized by placing text in the "Label Text" fields.

Options: Y = Use the SPR standard labels descriptions. [Default]
 N = Use custom label tags.

13. `<xs:attribute name="ShowCntry" use="optional" default="N">`
 Print Country of Origin Code on Packing List?
 Options: Y = Print the country code on Packing List [Default]
 N = Do not print country code
14. `<xs:attribute name="FuturePo" use="optional" default="N">`
 Ship order on the specified future date. If FutureDate is not specified, this attribute is ignored.
 Options: Y = Designate order as a future order.
 N = Not a future order [Default]
15. `<xs:attribute name="FutureDate" use="optional">`
 Send date for the future shipment in the format YYYYMMDD.
16. `<xs:attribute name="Language" use="optional" default="E">`
 Language flag
 Options: E=English [Default]
17. `<xs:attribute name="CurrencyCode" use="optional">`
 Not used
18. `<xs:attribute name="PlacedBy" use="optional">`
 Order placed by Name. Used by Dealer for identification. Printed on packing list, but not on label.
19. `<xs:attribute name="DealerRoute" use="optional">`
 Dealer's route code
20. `<xs:attribute name="DealerRefNo" use="optional">`
 Dealer's delivery reference code
21. `<xs:attribute name="DealerAttn" use="optional">`
 Dealer's delivery "Attention To" text
22. `<xs:attribute name="DealerOrder" use="optional">`
 Dealer assigned customer order number
23. `<xs:attribute name="SplPartnerId" use="optional">`
 Second Party Logistics delivery partner ID
24. `<xs:attribute name="SplRouteCode" use="optional">`
 Second Party Logistics delivery ZIP Code
25. `<xs:attribute name="SplStatMsg" use="optional">`
 Second Party Logistics order status message returned by SPR
 OK = Delivery Dealer & Delivery Route match
 ERR DEALER = Invalid Delivery Dealer
 ERR ROUTE = Invalid Delivery Route
26. `<xs:attribute name="DealerField1" use="optional">`
 Not Used
27. `<xs:attribute name="DealerField2" use="optional">`
 Not Used
28. `<xs:attribute name="DealerField3" use="optional">`
 Not Used
29. `<xs:attribute name="DealerField4" use="optional">`

Not Used

30. `<xs:attribute name="LabelCmmnts1" use="optional">`
Shipping Label Comments 1
31. `<xs:attribute name="LabelCmmnts2" use="optional">`
Shipping Label Comments 2
32. `<xs:attribute name="LabelCmmnts3" use="optional">`
Shipping Label Comments 3
33. `<xs:attribute name="PrintBarcode1" use="optional">`
34. `<xs:attribute name="PrintBarcode2" use="optional">`
35. `<xs:attribute name="PrintBarcode3" use="optional">`
Print Shipping Label Barcode.
Options: Y = Print Barcode on Shipping Label [Default]
 N = Do not print Barcode
36. `<xs:attribute name="BarcodeField1" use="optional">`
37. `<xs:attribute name="BarcodeField2" use="optional">`
38. `<xs:attribute name="BarcodeField3" use="optional">`
Enter the text for the Barcode. The Barcode has a 14 character limit.
39. `<xs:attribute name="BarcodeFormat1" use="optional">`
40. `<xs:attribute name="BarcodeFormat2" use="optional">`
41. `<xs:attribute name="BarcodeFormat3" use="optional">`
Select the format of the specified Barcode.
1 = Code 11
2 = Interleaved 2 of 5
3 = Code 39 (default)
8 = EAN-8
9 = UPC-E
A = Code 93
C = Code 128
E = EAN-13
I = Industrial 2 of 5
J = Standard 2 of 5
K = Codabar
L = LOGMARS
P = Plessey
S = UPC/EAN extensions
U = UPC-A
42. `<xs:attribute name="HumanReadable1" use="optional">`
43. `<xs:attribute name="HumanReadable2" use="optional">`
44. `<xs:attribute name="HumanReadable3" use="optional">`
Print the human readable caption with the Barcode
N = Do not print [Default]
Y = Print text with barcode
X = Do not print on label only. It will print on Packing List.

45. `<xs:attribute name="CheckDigit1" use="optional">`
46. `<xs:attribute name="CheckDigit2" use="optional">`
47. `<xs:attribute name="CheckDigit3" use="optional">`
 Print check digit
 Options: N = Do not print [Default]
 Y = Print text with barcode
48. `<xs:attribute name="LabelCms1Desc" use="optional">`
49. `<xs:attribute name="LabelCms2Desc" use="optional">`
50. `<xs:attribute name="LabelCms3Desc" use="optional">`
 Enter Dealer label comment text
51. `<xs:attribute name="PoNoDesc" use="optional">`
 Label text for the PO number field on the label
52. `<xs:attribute name="RouteDesc" use="optional">`
 Label text for the Route field on the label
53. `<xs:attribute name="RefNoDesc" use="optional">`
 Label text for the Reference Number field on the label
54. `<xs:attribute name="AttnDesc" use="optional">`
 Label text for the Attention field on the label
55. `<xs:attribute name="CntryDesc" use="optional">`
 Label text for the Country field on the label
56. `<xs:attribute name="DealerComp" use="optional">`
 Not Used
57. `<xs:attribute name="ConsumerPhone" use="optional">`
 Consumer phone number
58. `<xs:attribute name="Cp1Type" use="optional">`
59. `<xs:attribute name="Cp1Value" use="optional">`
60. `<xs:attribute name="Cp1Desc" use="optional">`
61. `<xs:attribute name="Cp2Type" use="optional">`
62. `<xs:attribute name="Cp2Value" use="optional">`
63. `<xs:attribute name="Cp2Desc" use="optional">`
64. `<xs:attribute name="Cp3Type" use="optional">`
65. `<xs:attribute name="Cp3Value" use="optional">`
66. `<xs:attribute name="Cp3Desc" use="optional">`
67. `<xs:attribute name="Cp4Type" use="optional">`
68. `<xs:attribute name="Cp4Value" use="optional">`
69. `<xs:attribute name="Cp4Desc" use="optional">`
 Not Used
70. `<xs:attribute name="UseDcAddr" use="optional">`
 Use the SPR shipping DCs address as the order's Ship-From address. The return address is printed on shipping label and Packing List.
 Options: N = Use standard return address [Default]
 Y = SPR DC address will be used as return address. A "Y" selection requires a Dealer company name in the PersonInfoContact:FirstName field. If company name is not included, the standard return address is used.

Order Line Detail Tags

<xs:element name="OrderLines">

<xs:element name="OrderLine" maxOccurs="unbounded">

1. **<xs:attribute name="PrimeLineNo" use="required">**
Line number for this line item
2. **<xs:attribute name="CustomerLinePONo" use="optional">**
Line number from customer's original PO

<xs:element name="OrderLineTranQuantity">

1. **<xs:attribute name="TransactionalUOM" use="required">**
The SPR UOM for the line item SKU must be sent in the inbound order. The SPR SKU is 2 characters, which are always uppercase. Some examples of the SPR UOM are "EA", "DZ", and "BX".
2. **<xs:attribute name="OrderedQty" use="required">**
Quantity ordered for this line item

<xs:element name="Item">

1. **<xs:attribute name="CustomerItem" use="required">**
Item SKU

<xs:element name="Instructions" minOccurs="0">

<xs:element name="Instruction" maxOccurs="2">

1. **<xs:attribute name="InstructionText" use="optional">**
The inbound Line Reference Codes are returned in the Instruction tag. If one Line Reference Code is sent, one Instruction is returned. If two Line Reference Codes are sent, two Instruction tags are returned.

<xs:element name="LinePriceInfo">

1. **<xs:attribute name="RetailPrice" use="Optional">**
Dealer to Consumer Sell Price. Returned only in order ACK. Not printed on Packing List or Label.

<xs:element name="Notes" minOccurs="0">

<xs:element name="Note" maxOccurs="unbounded">

1. **<xs:attribute name="SequenceNo" use="optional">**
Associated line number for this note
2. **<xs:attribute name="ContactType" use="optional">**
Enter the code which applies to this Detail Line note.
Options: C = Detail line Comment
3. **<xs:attribute name="ContactReference" use="optional">**
Not Used
4. **<xs:attribute name="ContactUser" use="optional">**
Not Used
5. **<xs:attribute name="NoteText" use="required">**
Note for this line item (Max NoteText is 50 Characters)

<xs:element name="Extn" minOccurs="0">

<xs:element name="EXTNSprOrderLineList" minOccurs="0">

<xs:element name="EXTNSprOrderLine" minOccurs="0">

1. <xs:attribute name="OkProSubs" use="optional" default="Y">

Allow SPR Proprietary Brand Item Substitutes?

Options: Y = Allow Substitution of SPR Proprietary Brand Items for other Proprietary Brands. [Default]
N = Do Not Substitute for Proprietary Brand Items.

2. <xs:attribute name="OkLikeSubs" use="optional" default="N">

Allow Like Item Substitutes?

Options: Y = Allow Substitution of Like Branded Items.
N = Do Not Substitute for Like Branded Items. [Default]

3. <xs:attribute name="OkFullPacks" use="optional" default="Y">

Allow rounding quantity ordered to Full Packs?

Options: Y = Round-Up Quantities to Full Packs when Ordering less than the Minimum Selling Quantity.
[Default]
N = Do Not Round-Up to Full Packs. Cancel remainder quantity.

4. <xs:attribute name="OkBackorder" use="optional" default="N">

Place Shortages on Back-Order?

Options: Y = Place the portion of the Order Quantity that can not be Shipped on Backorder.
N = Do Not Place Shortages on Back-Order. [Default]

5. <xs:attribute name="OkPartial" use="optional" default="Y">

Allow Shipping Partial Lines?

Options: Y = Allow shipment of partially-filled line items. [Default]
N = Do Not Ship Partial Lines.

6. <xs:attribute name="DealerList" use="optional">

Dealer List price for the line item SKU (Future Use: intended for priced packing list)

7. <xs:attribute name="DealerCost" use="optional">

Dealer Expected Cost for the line item SKU; i.e , Price Dealer Expects to pay.

8. <xs:attribute name="ConsumerUom" use="optional">

Dealer selling UOM

9. <xs:attribute name="TaxRate" use="optional">

Consumer Sales tax rate

10. <xs:attribute name="OrigOrder" use="optional">

This is the Original Request for this P.O. Line?

Options: Y = The Request for this Item is Original Demand
N = The Request was generated by a Re-Order Process

11. <xs:attribute name="OkBrandSubs" use="optional">

Allow SPR Proprietary Brand Item Substitutes for National Branded Items?

Options: Y = Allow Substitution of SPR Proprietary Brand Items for National Brands.
N = Do Not Substitute for Proprietary Brand Items for National Brands. [Default]

12. <xs:attribute name="BuyerItemNo" use="optional">

Not Used

13. <xs:attribute name="PrintDcCommnts" use="optional">

Not Used

14. <xs:attribute name="AckStatus" use="optional">

Acknowledgment status

'A' = accepted
 'B' = backorder at SPR DC or out of stock
 'P' = UOM order partial shipment
 'Q' = UOM order quantity error
 'D' = discontinued by S. P. Richards
 'X' = discontinued by manufacturer
 'U' = unit of measure error
 'I' = invalid entry
 'S' = non UPSable items cancelled
 'E' = Error. Order can not be processed.
 'V' = Vendor Procured Product

15. <xs:attribute name="AckDesc" use="optional">

Acknowledgment description

Text Returned: For this status:

'ACCEPTED' = 'A'
 'ETA=999 DAYS' = 'B', 'P', & 'V'
 'NONE W/MFR' = 'B' & 'P'
 'B/O OR LATE' = 'B' & 'P'
 'NOT STD PACK' = 'P'
 'CALL S.P.R.' = 'B'
 'DISC. BY SPR' = 'D'
 'DISC. BY MFR' = 'X'
 'MIN=99999 XX' = 'Q' & 'U'
 'BAD STOCK #' = 'I'
 'BAD CUST' = 'I'
 'NONUPSCANCEL' = 'S'

Note: AckStatus of 'V' and AckDesc of ETA

CSO & VSO items optional status of 'V' for Vendor Sourced Order needs to be enabled in order to process the order. In order to enable the items you need to contact SPR Helpdesk <sprichards@service-now.com>

Appendix A – Sample XML Orders

Sample Outbound POACK: DropShip 04

```
<?xml version="1.0" encoding="UTF-8" standalone="yes" ?>
<Order EnterpriseCode="SPR" BuyerOrganizationCode="9999999.99" DraftOrderFlag="N"
  OrderType="04" ShipNode="23" IsShipComplete="N" IsShipSingleNode="N"
  CancelOrderOnBackorder="N" CustomerPONo="00124" CustCustPONo="00124"
  EntryType="FTP" OrderNo="38135673">
<PersonInfoShipTo FirstName="John Doe" AddressLine1="123 Main RD" City="BUTLER"
  State="PA" ZipCode="16001" Country="USA" IsCommercialAddress="N" />
<PersonInfoContact FirstName="Department of OP" />
<OrderLines>
<OrderLine PrimeLineNo="1" CustomerLinePONo="1">
<OrderLineTranQuantity TransactionalUOM="EA" OrderedQty="5" />
<Item CustomerItem="TC027900" ManufacturerItem="TC027900" />
<Instructions>
<Instruction InstructionText="237009" />
</Instructions>
<LinePriceInfo UnitPrice="78.21" />
<Extn>
<EXTNSprOrderLineList>
<EXTNSprOrderLine OkProSubs="Y" OkLikeSubs="N" OkFullPacks="Y" OkBackorder="N"
  OkPartial="Y" DealerCost="78.21" QtyShipped="5" QtyBackordered="0" DealerPrice="78.21"
  AckStatus="A" AckDesc="ACCEPTED" />
</EXTNSprOrderLineList>
</Extn>
</OrderLine>
</OrderLines>
<Shipments>
<Shipment>
<ShipmentLines>
<ShipmentLine CustomerItem="TC027900" ManufacturerItem="TC027900" ActualQuantity="1"
  DcQtyOrdrd="5" DcQtyOnBo="0" DcExtAmt="78.21" PickTickNum="09029945" />
<ShipmentLine CustomerItem="TC027900" ManufacturerItem="TC027900" ActualQuantity="4"
  DcQtyOrdrd="5" DcQtyOnBo="1" DcExtAmt="78.21" PickTickNum="38135673" />
</ShipmentLines>
</Shipment>
</Shipments>
<Extn>
<EXTNSprOrderHeaderList>
<EXTNSprOrderHeader ShipMethod="0" LevelOfServ="D" UseSprinters="N" PricedPackSlip="D"
  CanNonUps="N" ParcelZone="Y" ShowCost="N" ShowList="N" OneOrder="Y" ListCost="L"
  StdDescs="Y" ShowCntry="N" FuturePo="N" Language="E" CurrencyCode="USD"
  PoAckStatus="A" MarketSoNum="38135673" SprSoNum="38135673" DealerRoute="S.P. EXP
  (Philadelph" DealerRefNo="MOMS00004608900" DealerAttn="MSG KILGORE"
  DealerOrder="31797" UseDcAddr="N" />
</EXTNSprOrderHeaderList>
</Extn>
</Order>
```

Sample Outbound POACK: Wrap & Label 03

```

<?xml version="1.0" encoding="UTF-8" standalone="yes" ?>
<Order EnterpriseCode="SPR" BuyerOrganizationCode="9999999.99" DraftOrderFlag="N"
  OrderType="03" ShipNode="15" IsShipComplete="Q" IsShipSingleNode="N"
  CancelOrderOnBackorder="N" CustomerPONo="37157" CustCustPONo="37157"
  OrderNo="08381386">
<PersonInfoShipTo FirstName="ABC CO." AddressLine1="123 Main St" AddressLine2="Ste. 230"
  City="San Antonio" State="TX" ZipCode="78258" Country="USA" IsCommercialAddress="Y" />
<PersonInfoContact FirstName="John Dow" AddressLine1="123 Main ST" AddressLine2="Suite
  422" City="Farmers Branch" State="TX" ZipCode="75234" />
<OrderLines>
<OrderLine PrimeLineNo="1" CustomerLinePONo="1">
<OrderLineTranQuantity TransactionalUOM="CT" OrderedQty="2" />
<Item CustomerItem="CCR1003" ManufacturerItem="CCR1003" />
<Instructions>
<Instruction InstructionText="336688" />
  </Instructions>
<LinePriceInfo UnitPrice="8.46" />
<Extn>
<EXTNSprOrderLineList>
<EXTNSprOrderLine OkProSubs="Y" OkLikeSubs="N" OkFullPacks="Y" OkBackorder="N"
  OkPartial="Y" QtyShipped="2" QtyBackordered="0" DealerPrice="8.46" AckStatus="A"
  AckDesc="ACCEPTED" />
  </EXTNSprOrderLineList>
  </Extn>
  </OrderLine>
<OrderLine PrimeLineNo="2" CustomerLinePONo="2">
<OrderLineTranQuantity TransactionalUOM="CT" OrderedQty="1" />
<Item CustomerItem="CCR1000" ManufacturerItem="CCR1000" />
<Instructions>
<Instruction InstructionText="336689" />
  </Instructions>
<LinePriceInfo UnitPrice="8.39" />
<Extn>
<EXTNSprOrderLineList>
<EXTNSprOrderLine OkProSubs="Y" OkLikeSubs="N" OkFullPacks="Y" OkBackorder="N"
  OkPartial="Y" QtyShipped="1" QtyBackordered="0" DealerPrice="8.39" AckStatus="A"
  AckDesc="ACCEPTED" />
  </EXTNSprOrderLineList>
  </Extn>
  </OrderLine>
<OrderLine PrimeLineNo="3" CustomerLinePONo="3">
<OrderLineTranQuantity TransactionalUOM="CT" OrderedQty="3" />
<Item CustomerItem="SPZDIETDRPEPPER" ManufacturerItem="SPZDIETDRPEPPER" />
<Instructions>
<Instruction InstructionText="336690" />
  </Instructions>
<LinePriceInfo UnitPrice="8" />
<Extn>
<EXTNSprOrderLineList>

```

```

<EXTNSprOrderLine OkProSubs="Y" OkLikeSubs="N" OkFullPacks="Y" OkBackorder="N"
  OkPartial="Y" QtyShipped="0" QtyBackordered="3" DealerPrice="8" AckStatus="B"
  AckDesc="NONE W/MFR" />
</EXTNSprOrderLineList>
</Extn>
</OrderLine>
</OrderLines>
<Instructions>
  <Instruction InstructionText="" />
  <Instruction InstructionText="Your business helps employ 3,000 U.S. workers. We sincerely
thank you!" />
</Instructions>
<Notes>
  <Note ContactType="L" NoteText="Test BOL comment 1" />
  <Note ContactType="L" NoteText="Test BOL comment 2" />
  <Note ContactType="L" NoteText="Test BOL comment 3" />
  <Note ContactType="L" NoteText="Test BOL comment 4" />
</Notes>
<Shipments>
<Shipment>
<ShipmentLines>
<ShipmentLine CustomerItem="CCR1003" ManufacturerItem="CCR1003" ActualQuantity="2"
  DcQtyOrdrd="2" DcQtyOnBo="0" DcExtAmt="8.46" PickTickNum="08381386" />
<ShipmentLine CustomerItem="CCR1000" ManufacturerItem="CCR1000" ActualQuantity="1"
  DcQtyOrdrd="1" DcQtyOnBo="0" DcExtAmt="8.39" PickTickNum="08381386" />
</ShipmentLines>
</Shipment>
</Shipments>
<Extn>
<EXTNSprOrderHeaderList>
<EXTNSprOrderHeader ShipMethod="0" LevelOfServ="D" UseSprinters="N" PricedPackSlip="D"
  CanNonUps="9" ParcelZone="Y" ShowCost="N" ShowList="N" OneOrder="Y" ListCost="L"
  StdDescs="D" ShowCntry="N" FuturePo="N" Language="E" CurrencyCode="USD"
  PoAckStatus="A" MarketSoNum="08381386" SprSoNum="08381386" DealerRoute="S.P. Flash
ADOT" DealerRefNo="11/04/2009" DealerAttn="John Doe" DealerOrder="46039"
  UseDcAddr="N" />
</EXTNSprOrderHeaderList>
</Extn>
</Order>

```

Appendix B - FAQ

General Questions

Q. Why should XML be used?

A. XML has become the international standard for EDI transmissions.

Appendix C – Contacts and References

General Questions

Contacts

SPR Customer Support 888-763-2615 770-803-4457 helpdesk@sprich.com
SPR EDI Team edi@sprich.com

References

Description	Filename
1. SPR DCs.pdf	

Author: Brad Wagner	EDI Manager Signature: On File
------------------------	-----------------------------------