

STACKS_WORKFLOW

An integrated workflow to streamline STACKS analyses on RAD/GBS data

About STACKS

The STACKS analysis pipeline (<http://creskolab.uoregon.edu/stacks/>) is the de facto tool for SNP discovery in Genotyping By Sequencing (GBS) and Restriction-site Associated DNA sequencing (RAD) studies when no reference genome is available. Upon starting to use STACKS, it is highly suggested to read the two official STACKS papers. These articles are listed at the bottom of the official page and contain the keyword *Stacks* in their title.

About the STACKS Workflow

This STACKS Workflow aims at making the use of the STACKS pipeline easier and more structured so that people tasked with analysing GBS or RAD data and possessing limited UNIX/Linux experience can jump on the analysis wagon faster. It was developed with the needs of our research group in mind with an emphasis on non-model species studies. We make no claim about its usefulness to other groups or in other contexts, but we still believe it may be of use to some.

The workflow has been tested with version 1.10 and earlier versions of STACKS under Linux (Ubuntu 12.04 to 13.10) and MacOSX.

About the manual

This manual can be found in 3 places:

- Online at: https://github.com/enormandeau/stacks_workflow
- In the **MANUAL.pdf** file found in the base directory of **stacks_workflow**
- In the **README.md** file, also found in the base directory of **stacks_workflow**

The online version is especially nicely formatted. We suggest that you use it or the .pdf version. Using the text version is riskier because of the risk of involuntarily modifying and corrupting the file.

Licence

The STACKS workflow is licensed under the GPL3 license. See the LICENCE file for more details.

Overview of the steps

Step 0 - Install and prepare the workflow
Step 1 - Download raw datafiles (Illumina lanes)
Step 2 - Extract individual data with process_radtags
Step 3 - Rename samples
Step 4 - STACKS pipeline
Step 5 - Filtering the results

The workflow

Step 0 - Install and prepare the workflow

- a) Download and install the most recent version of this workflow
 - From the terminal, run:

```
{bash} cd ~
```

If you have `git` installed, you can do the same faster with:

```
{bash} git clone https://github.com/enormandeu/stacks_workflow
```

Use the extracted or cloned folder as your working directory for the rest of the project. All the commands in this manual are launched from that directory.

- b) Download and install STACKS
 - <http://creskolab.uoregon.edu/stacks/>
 - Unzip the archive
 - From within the STACKS folder, run:

```
{bash} ./configure make sudo make install
```

Step 1 - Download raw datafiles (Illumina lanes)

a) Put them in the **02-raw** folder of the `stacks.workflow` folder

- NOTE: All file names MUST end with **.fastq.gz**

b) Prepare the **lane_info.txt** file automatically

- From the `stacks.workflow` folder, run:

```
{bash} ./00-scripts/01_prepare_lane_info.sh
```

Step 2 - Extract individual data with `process_radtags`

a) Prepare a file named **sample_information.csv** using the same format found in the **example_sample_information.csv** file in the **01-info_files** folder. Also save this file in the **01-info_files** folder. This file will be used to extract the samples and rename the sample files automatically. The first column contains the EXACT name of the data file for the lane of each sample. The second column contains the barcode sequence of each sample. The third column contains the population name of each sample. The fourth column contains the name of the sample (do not include the population name or abbreviation in the sample name). The fifth column contains a number identifying the populations. Columns three and four are treated as text, so they can contain either text or numbers. Other columns can be present after the fifth one and will be ignored. However, it is crucial that the five first columns respect the format in the example file exactly. Be especially careful not to include errors in this file, for example mixing lower and capital letters in population or sample names (e.g.: Pop01 and pop01), since these will be treated as two different populations.

b) Launch `process_radtags` with:

```
{bash} ./00-scripts/02_process_radtags.sh <trimLength> <enzyme>
```

Where:

- `trimLength` = length to trim all the sequences
- `enzyme` = name of enzyme (run **process_radtags**, without options, for a list of the supported enzymes)

Step 3a - Rename samples

- a) To rename and copy the samples, run:

```
{bash} ./00-scripts/03_rename_samples.sh
```

- b) Join samples that should go together

- Go to 04-all_samples and join the .fq files that should go together with the `cat` command
- Remove partial .fq files that have been joined
- Remove individuals with too few sequences if needed (optional)

Step 3b - (Optional) Align reads to a reference genome

- a) Install bwa

- b) Download reference genome to the 01-info_files

- c) Index reference genome, run:

```
{bash} bwa index -p genome -a bwtsw ./01-info_files/<genome  
reference>
```

- d) copy files:

```
{bash} cp genome.* 01-info_files
```

- e) Align samples:

```
{bash} for i in $(ls -1 04-all_samples/*.fq) do name=$(basename  
$i) bwa aln -n 5 -k 3 -t 2 ./01-info_files/genome $i | \ bwa samse  
-r "@RG\tID:'$name'\tSM:'$name'\tPL:Illumina" \ ./01-info_files/genome  
- $i ./04ln-all_samples/$name.sam; \ done
```

Step 4 - STACKS pipeline

- a) Prepare population info file

- To prepare a template of that file, run:

```
{bash} ./00-scripts/04_prepare_population_map_template.sh
```

b) Open the stacks script in the 00-scripts folder and edit the options of the `stacks_*` scripts.

c) Run the STACKS programs, in order:

- `ustacks` (or `pstacks` for reference assisted):

```
{bash} ./00-scripts/stacks_1a_ustacks.sh
```

or (use `pstacks` instead if you have a reference genome):

```
{bash} ./00-scripts/stacks_1b_pstacks.sh
```

- `cstacks`:

```
{bash} ./00-scripts/stacks_2_cstacks.sh
```

- `sstacks`:

```
{bash} ./00-scripts/stacks_3_sstacks.sh
```

- populations or genotypes:

```
{bash} ./00-scripts/stacks_4_populations.sh
```

Step 5 - Filtering the results

- Use `./00-scripts/05_filterStacksSNPs.py` to filter your SNPs. To print the documentation, type:

```
{bash} ./00-scripts/05_filterStacksSNPs.py
```

- Launch the script, example:

```
{bash} ./00-scripts/05_new_filterStacksSNPs.py \ -i 05-stacks/batch_1.sumstats.tsv  
\ -o filtered.tsv \ -P 01-info_files/population_map.txt \ -p 2 -x  
1 -H 0.7 -a 0.05 -A 0 -f -0.3 -F 0.8 -s 10
```

How to cite stacks_workflow

If you use `stacks_workflow` in a publication, you can include the following citation:

- Under redaction