

DS	Session	Sorting	Question Information	Level 1 Challenge 13
Problem Description: Siva has several containers, each with a number of fruits in it. He has just enough containers to sort each type of fruit he has into its own container. Siva wants to sort the fruits using his sort method. Siva wants to perform some number of swap operations such that: Each container contains only fruits of the same type. No two fruits of the same type are located in different containers. Function Description organizingContainers has the following parameter(s): <i>int containers[n][m]</i>: a two dimensional array of integers that represent the number of balls of each color in each container Constraints: $1 \leq q \leq 10$ $1 \leq n \leq 100$ $0 \leq \text{containers}[i][j] \leq 10^9$ Input Format: The first line contains an integer 'q', the number of queries. Each of the next 'q' sets of lines is as follows: The first line contains an integer 'n', the number of containers (rows) and ball types (columns). Each of the next 'n' lines contains 'n' space-separated integers describing row containers[i]. Output Format: For each query, print Possible on a new line if David can satisfy the conditions above for the given matrix. Otherwise, print Impossible.				

▼ Logical Test Cases

Test Case 1
INPUT (STDIN)
2
2
1 1
1 1
2
0 2
1 1
EXPECTED OUTPUT
Possible
Impossible

Test Case 2
INPUT (STDIN)
2
2
2 1
1 2
2
1 2
2 1
EXPECTED OUTPUT
Possible
Possible

▼ Mandatory Test Cases

Test Case 1
KEYWORD
void insertionSort(long int *p, long int n)

Test Case 2
KEYWORD
for(i=0; i<n; i++)

Test Case 3
KEYWORD
while(q--)

▼ Complexity Test Cases

Test Case 1
CYCLOMATIC COMPLEXITY
5

Test Case 2
TOKEN COUNT
450

Test Case 3
NLOC
63