

DS	Session	Stack	Question Information	Level 1	Challenge 45
Problem Description: Sajid was booking a tour package of IRCTC from Chennai to Delhi for his family. Two of the relatives was interested in joining to this tour. these two persons are studying engineering in computing technology. only one tickets are remaining in the IRCTC portal. So, Sajid decided to book one ticket for out of those persons also along with his family members. He wants to identify the one person out of these persons. he decided to conduct a technical task to identify the right person to travel. the task was that, Check for Balanced Brackets in an expression using Stack Can you help them to complete the task? Function Description • Declare a character stack S. • Now traverse the expression string exp. 1. If the current character is a starting bracket ('{' or '[' or '{') then push it to stack. 2. If the current character is a closing bracket (')' or '}' or ']') then pop from stack and if the popped character is the matching starting bracket then fine else brackets are not balanced. • After complete traversal, if there is some starting bracket left in stack then “not balanced” Input Format Single line represents only braces (both curly and square) Output Format If the given input balanced then print as Balanced (or) Not Balanced					
▼ Logical Test Cases Test Case 1 INPUT (STDIN) {()}[] EXPECTED OUTPUT Balanced Test Case 2 INPUT (STDIN) {{{}}}} EXPECTED OUTPUT Not Balanced					

▼ Mandatory Test Cases

Test Case 1

KEYWORD

pop()

Test Case 2

KEYWORD

empty()

Test Case 3

KEYWORD

push

Test Case 4

KEYWORD

stack

▼ Complexity Test Cases

Test Case 1

CYCLOMATIC COMPLEXITY

15

Test Case 2

TOKEN COUNT

275

Test Case 3

NLOC

100

```
Stack5.c +
1 #include <stdio.h>
2 #include <string.h>
3 #include <stdbool.h>
4
5 #define MAX 1000
6
7 char stack[MAX];
8 int top = -1;
9
10 void push(char c) {
11     if (top < MAX - 1) {
12         stack[++top] = c;
13     }
14 }
15
16 char pop() {
17     if (top >= 0) {
18         return stack[top--];
19     }
20     return '\0';
21 }
22
23 bool isMatchingPair(char char1, char char2) {
24     if (char1 == '(' && char2 == ')') return true;
25     if (char1 == '{' && char2 == '}') return true;
```

```
26     if (char1 == '[' && char2 == ']') return true;
27     return false;
28 }
29
```

main | CH.SC.U4CSE25225 | Stack5.c

Ln 57, Col 1 Spaces: 4 UTF-8 CRLF C

```
30 int main() {
31     char exp[MAX];
32     if (scanf("%s", exp) != 1) return 0;
33
34     bool balanced = true;
35     for (int i = 0; exp[i] != '\0'; i++) {
36         if (exp[i] == '{' || exp[i] == '(' || exp[i] == '[') {
```

```
37         push(exp[i]);
38     } else if (exp[i] == '{' || exp[i] == '(' || exp[i] == '[') {
39         if (top == -1 || !isMatchingPair(pop(), exp[i])) {
40             balanced = false;
41             break;
42         }
43     }
44 }
45
46 if (top != -1) {
47     balanced = false;
```

```
48     }  
49  
50     if (balanced) {  
51         printf("Balanced\n");  
52     } else {  
53         printf("Not Balanced\n");  
54     }  
55     return 0;  
56 }  
57
```

```
C:\Users\CH.SC.U4CSE25225\Desktop\DSA Lab>type t1.txt
```

```
Balanced
```

```
C:\Users\CH.SC.U4CSE25225\Desktop\DSA Lab>Stack5.exe
```

```
Balanced
```

```
C:\Users\CH.SC.U4CSE25225\Desktop\DSA Lab>
```

```
C:\Users\CH.SC.U4CSE25225\Desktop\DSA Lab>type t2.txt
```

```
{{{}}]}}
```

```
C:\Users\CH.SC.U4CSE25225\Desktop\DSA Lab>Stack5.exe
```

```
Not Balanced
```

```
C:\Users\CH.SC.U4CSE25225\Desktop\DSA Lab>
```