Test on CSS

ASHOK KUMAR. V
10-12 Batch

what is selectors and give example for simple selectors.

what is Descendant Selector and give examplee for its types?

Answers

Selector:-

* A css selector used to Select the HTML element that use want to style and make it beautifull.

eg:-

```
h1 {
  color.red;
}
<h1> hi </h1>
```

(h1 ← Selector)

Simple selector:-

Simple Selector used to elements like Name, id, Tags and other attributes. To Apply for a Particular element.

Types:-

i) Element Selector
ii) ID Selector
iii) Class Selector
iv) Universal Selector
v) attribute Selector
vi) Grouping selector.

* ~~attributes selector~~

Examples for each selectors:

```
<!Doc Type html>
<html>
<head> <Title> Selectors </Title> </head>
<style>
    .P{
      Color: red;
      }
   .h1,h2,h4{
      background Color: aqua;
      }
   # Para1{
      text-align: Center;
     }
   . Para{
      margin : 20Px;
      Padding : 10Px;
     }
   * {
      font-size: 20Px;
     }
  title {
      Color : blue;
     }
</Style>
```

descendant selector: ( )

* Selects elements at any nesting level.

Eg:

```
div p {
    color: red;
}
```

2. Child selector: (>)

* Selects only direct children.

Eg:

```
div > p {
    color: green;
}
```

3. Adjacent sibling selector: (+)

* Selects the element immediately after another element.

Eg:

```
h1 + p {
    color: orange;
}
```

4. General sibling selector: (~)

* selects all matching siblings that come after an element.

Eg:

```
h1 ~ p {
    color: black;
}
```

```
<body>
<html>
    <h1> Heading 1 </h1>
    <h2> Heading 2 </h2>
    <h3> Heading 3 </h3>

<div>
    <P title = "heading" class = "Para" id = "Para1">
                This is Paragraph 1 </P>
    </P class>
    <P class = "Para" id = "Para2">
                This is Paragraph 2 </P>

</div> </body> </html>.
```

2) ~~Combin~~ Descendant Selector :

* A Descendant Selector selects an element that is inside another element, at any level of nesting.

Examples:

```
<div>
    <P> Hello </P>
    <section>
    <P> welcome </P>
    </section>
</div>
```

* div P selects both <P> elements, because both are descendants of .