09 – Dictionary

vEx. No. : 9.1 Date: 4/5/24

Register No.: 231501024 Name: ASHWIN T

Uncommon words

A sentence is a string of single-space separated words where each word consists only of lowercase letters. A word is uncommon if it appears exactly once in one of the sentences, and does not appear in the other sentence.

Given two sentences s1 and s2, return a list of all the uncommon words. You may return the answer in any order.

PROGRAM

```
s1 = input()
s2 = input()
words1 = s1.split()
words2 = s2.split()

count = {}
for word in words1 + words2:
    if word in count:
        count[word] += 1
    else:
        count[word] = 1

uncommon_words = [word for word in count if count[word] == 1]
print(uncommon_words)
```



Ex. No. : **9.2 Date:** 4/5/24

Register No.: 231501024 Name: ASHWIN T

Sort Dictionary by Values Summation

Give a dictionary with value lists, sort the keys by summation of values in value list.

Input: test_dict = {'Gfg': [6, 7, 4], 'best': [7, 6, 5]}

Output : {'Gfg': 17, 'best': 18}

Explanation : Sorted by sum, and replaced.
Input : test_dict = {'Gfg' : [8,8], 'best' : [5,5]}

Output: {'best': 10, 'Gfg': 16}

Explanation: Sorted by sum, and replaced.

Sample Input:

2

Gfg 6 7 4 Best 7 6 5 Sample Output

Gfg 17 Best 18

For example:

Input	Result
2 Gfg 6 7 4 Best 7 6 5	Gfg 17 Best 18

PROGRAM

```
n=int(input())
l1=[]
12=[]
13=[]
d=dict()
for i in range(n):
  l1=input().split(" ")
  l2.append(l1[0])
  l1.pop(0)
  l3.append(l1)
for j in range(len(l3)):
  sum=0
  for k in 13[j]:
     sum+=int(k)
  13[j]=sum
for i in range(len(l2)):
  d[l2[i]]=l3[i]
dn=dict(sorted(d.items(),key=lambda items:items[1]))
for key, value in dn.items():
  print(f"{key} {value}")
```



Ex. No. : 9.3 Date: 4/5/24

Register No.: 231501024 Name: ASHWIN T

Winner of Election

Given an array of names of candidates in an election. A candidate name in the array represents a vote cast to the candidate. Print the name of candidates received Max vote. If there is tie, print a lexicographically smaller name.

Examples:

Output: John

We have four Candidates with name as 'John', 'Johnny', 'jamie', 'jackie'. The candidates John and Johny get maximum votes. Since John is alphabetically smaller, we print it. Use dictionary to solve the above problem

Sample Input:

10

John

John

Johny

Jamie

Jamie

Johny

-

Jack

Johny

Johny

Jackie

Sample Output:

Johny

For example:

Input	Result
10	Johny
John	
John	
Johny	
Jamie	
Jamie	
Johny	
Jack	
Johny	
Johny	
Jackie	

PROGRAM

```
n=int(input())
l1=[]
d=dict()
for i in range(n):
  l1.append(input())
for j in l1:
  d[j]=l1.count(j)
n1=max(d)
m=d[n1]
d.pop(n1)
n2=max(d)
if(m==d[n2]):
  if(len(n1)<len(n2)):</pre>
     print(n1)
  else:
     print(n2)
else:
  print(n1)
```



v

Ex. No. : 9.4 Date: 4/5/24

Register No.: 231501024 Name: ASHWIN T

Student Record

Create a student dictionary for n students with the student name as key and their test mark assignment mark and lab mark as values. Do the following computations and display the result.

- 1. Identify the student with the highest average score
- 2. Identify the student who as the highest Assignment marks
- 3. Identify the student with the Lowest lab marks
- 4. Identify the student with the lowest average score

Note:

If more than one student has the same score display all the student names Sample input:

4

James 67 89 56

Lalith 89 45 45

Ram 89 89 89

Sita 70 70 70

Sample Output:

Ram

James Ram

Lalith

Lalith

PROGRAM

```
n=int(input())
list1=[]
list2=[]
list3=[]
list4=∏
list5=∏
for i in range(n):
  student_data=input()
  student_input_parts=student_data.split()
  name=student_input_parts[0]
  marks=[int(mark) for mark in student_input_parts[1:]]
  average=(marks[0]+marks[1]+marks[2])/3
  list1.append(name)
  list2.append(marks[0])
  list3.append(marks[1])
  list4.append(marks[2])
  list5.append(average)
l1=∏
for i in range(n):
  if list5[i] == max(list5):
       l1.append(list1[i])
for i in l1:
  print(i,end=' ')
print()
12=[]
for i in range(n):
  if list3[i]==max(list3):
     l2.append(list1[i])
for i in 12:
  print(i,end=' ')
print()
13=[]
for i in range(n):
  if list4[i]==min(list4):
     l3.append(list1[i])
l3.reverse()
for i in 13:
  print(i,end=' ')
print()
14=∏
for i in range(n):
  if list5[i]==min(list5):
       l4.append(list1[i])
for i in 14:
  print(i,end=' ')
```

	Input	Expected	Got	
J L F	4 James 67 89 56 Lalith 89 45 45 Ram 89 89 89 Sita 70 70 70	Ram James Ram Lalith Lalith	Ram James Ram Lalith Lalith	~
F	3 Raja 95 67 90 Aarav 89 90 90 Shadhana 95 95 91	Shadhana Shadhana Aarav Raja Raja	Shadhana Shadhana Aarav Raja Raja	~

Ex. No. : 9.5 Date: 4/5/24

Register No.: 231501024 Name: ASHWIN T

Scramble Score

In the game of Scrabble^{M}, each letter has points associated with it. The total score of a word is the sum of the scores of its letters. More common letters are worth fewer points while less common letters are worth more points.

Write a program that computes and displays the Scrabble^m score for a word. Create a dictionary that maps from letters to point values. Then use the dictionary to compute the score.

A Scrabble^m board includes some squares that multiply the value of a letter or the value of an entire word. We will ignore these squares in this exercise.

The points associated with each letter are shown below:

```
Points Letters
1 A, E, I, L, N, O, R, S, T and U
2 D and G
3 B, C, M and P
4 F, H, V, W and Y
5 K
8 I and X
10 Q and
Z
Sample Input
REC
Sample Output
REC is worth 5 points.
PROGRAM
s=input()
l1=list(s)
d=dict([(1,['A','E','I','L','N','O','R','S','T','U']),(2,['D','G']),(3,['B','C','M','P']),(4,['F','H','V','W','Y']),
(5,['K']),(8,['J','X']),(10,['Q','Z'])])
sum=0
for j in l1:
  for key, values in d.items():
     if j in values:
        sum+=key
print(f"{s} is worth {sum} points.")
```

