

# Deep Learning for Natural Language Processing

Introduction to transfer learning and pre-trained embeddings



UNIVERSITY OF  
GOTHENBURG

---

**CHALMERS**

**WASP** | WALLENBERG AI  
AUTONOMOUS SYSTEMS  
AND SOFTWARE PROGRAM

**Richard Johansson**



`richard.johansson@gu.se`

## recap: embeddings

- in a neural network, an **embedding layer** represents a symbol as a continuous vector

2739  
("cucumber")  $\longrightarrow$   $[0.7, -1.2, \dots, -0.1]$

- we've seen how **word embeddings** are used as the first layer in NLP systems such as categorizers




- so far, we trained the word embeddings **from scratch**

# transfer learning: idea and motivation

- ▶ in **transfer learning**, we try to exploit previously learned knowledge when solving new tasks
- ▶ in practice: after training, we **reuse some part** of the model
- ▶ why? because it can **reduce the need for training data** for the target task
- ▶ commonly used when training ML models for vision tasks


# transfer learning in vision



[source]


# transfer learning in NLP

**this lecture:**




# transfer learning in NLP

**this lecture:**



**later:**



# key challenges for transfer learning

- ▶ learning **generally useful** representations
  - ▶ so we need fairly general training tasks
- ▶ finding **training data**
  - ▶ ideally, an unlimited supply!

# key challenges for transfer learning

- ▶ learning **generally useful** representations
  - ▶ so we need fairly general training tasks
- ▶ finding **training data**
  - ▶ ideally, an unlimited supply!
  - ▶ in NLP, we prefer to use **raw text** (unannotated) for pre-training representations



# predicting contexts

- ▶ all pre-training methods for word embeddings are based on predicting what kind of **context** a word appears in
  - ▶ for instance, the surrounding words
- ▶ easy to generate large amount of training data

|     |       |       |                              |                          |                    |   |                              |  |  |
|-----|-------|-------|------------------------------|--------------------------|--------------------|---|------------------------------|--|--|
| The | quick | brown | fox jumps over the lazy dog. |                          |                    | ➡ | (the, quick)<br>(the, brown) |  |  |
| The | quick | brown | fox                          | jumps over the lazy dog. |                    |   | ➡                            | (quick, the)<br>(quick, brown)<br>(quick, fox) |  |
| The | quick | brown | fox                          | jumps                    | over the lazy dog. |   |                              | ➡  | (brown, the)<br>(brown, quick)<br>(brown, fox)<br>(brown, jumps) |

# justification in terms of linguistic theory

- ▶ *“you shall know a word by the company it keeps”* (Firth, 1957)
- ▶ two words probably have a similar “meaning” if they tend to appear in similar **contexts**
- ▶ the **distributional hypothesis** (Harris, 1954): the distribution of contexts in which a word appears is a good proxy for the “meaning” of that word

example: most frequent verbs near *cake* and *pizza*

- ▶ **cake**: eat, bake, throw, cut, buy, get, decorate, garnish, make, serve, order
- ▶ **pizza**: eat, bake, order, munch, buy, serve, garnish, name, get, make, heat



# so what kinds of “contexts” can we use?

- ▶ surrounding words: rest of today's talk
- ▶ alternatives:
  - ▶ documents (Landauer and Dumais, 1997)
  - ▶ syntax (Padó and Lapata, 2007)





- ▶ images (Lazaridou et al., 2015)



# using word embeddings in NLP applications

- ▶ the pre-trained word embeddings can then be “plugged” into NLP applications



- ▶ how? two alternatives:
  - ▶ let the word embeddings be fixed
  - ▶ **fine-tune** the embeddings for the application

## next lecture clips

- ▶ the SGNS (word2vec) training algorithm
- ▶ evaluation and interpretation
- ▶ more training methods
- ▶ research outlook

# references

- J. Firth. 1957. *Papers in Linguistics 1934–1951*. OUP.
- Z. Harris. 1954. Distributional structure. *Word* 10(23):146–162.
- T. K. Landauer and S. T. Dumais. 1997. A solution to Plato's problem: The latent semantic analysis theory of acquisition, induction and representation of knowledge. *Psychological Review* 104:211–240.
- A. Lazaridou, N. T. Pham, and M. Baroni. 2015. Combining language and vision with a multimodal skipgram model. In *NAACL*.
- S. Padó and M. Lapata. 2007. Dependency-based construction of semantic space models. *Computational Linguistics* 33(2):161–199.