Deep Learning for Natural Language Processing

Recurrent neural networks

Marco Kuhlmann

Department of Computer and Information Science


Linköping University



Recurrent neural networks


- Recurrent neural networks (RNNs) can process variable length sequences of inputs, such as sequences of letters or words.
- For any input sequence, a recurrent neural network is 'unrolled' into a deep feedforward network.
 - Depth is proportional to the length of the sequence.
- In contrast to the situation with deep feedforward networks, all parameters are shared across all positions of the sequence.

RNN, recursive view



$$h_i = H(h_{i-1}, x_i)$$
 $y_i = O(h_{i-1}, x_i)$

RNN, unrolled view



Properties of recurrent neural networks

- The parameters of the model are shared across all positions.

 The number of parameters does not grow with the sequence length.
- The output can be influenced by the entire input seen so far.


 Contrast this with the locality constraint of CNNs.
- The hidden state can be a 'lossy summary' of the input sequence.

 Hopefully, it will encode useful information for the task at hand.

Training recurrent neural networks

- Unrolled recurrent neural networks are just feedforward networks, and can therefore be trained using backpropagation.
 No specialised algorithm necessary!
- This way of training recurrent neural networks is called backpropagation through time.
- Shared weights are updated by summing over the gradients computed for each position.

Common usage patterns for RNNs




encoder

example: text classification

transducer

example: part-of-speech tagging



decoder

example: text generation

Extensions of the basic RNN architecture

- Stacked RNNs are RNNs with several layers, where the outputs of one layer become the inputs of the next.
- **Bidirectional RNNs** combine one RNN that moves forward through the input with another RNN that moves backward.

outputs at each position are concatenated

Bi-RNN embeddings

