

model

Package in package 'DDF'

model
Version 1.0 Phase 1.0 Proposed
cupke created on 3/9/2023. Last modified 3/9/2023

model diagram

Class diagram in package 'model'

model
Version 1.0
cupke created on 3/9/2023. Last modified 3/9/2023




Figure 1: model

Activity

Class in package 'model'

An action, undertaking, or event, which is anticipated to be performed or observed, or was performed or observed, according to the study protocol during the execution of the study.


Activity

Version 1.0 Phase 1.0 Proposed


Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES	
 activityDescription : String Private The textual representation of the study activity.	[Is static True. Containment is Not Specified.]
 activityId : String Private Const	[Is static True. Containment is Not Specified.]
 activityIsConditional : boolean Private	[Is static True. Containment is Not Specified.]
 activityIsConditionalReason : String Private	[Is static True. Containment is Not Specified.]
 activityName : String Private The literal identifier (i.e., distinctive designation) of the clinical study activity.	[Is static True. Containment is Not Specified.]
 activityTimelineId : String Private OK, I'm super-struggling with this one here. If we have instances of activities in a ScheduleTimeline that reference activities, then this means that we should have timelines with one Activity, and one ScheduledActivityInstance with the same definition that both point to ScheduleTimelines. We also may have an Activity that points to a ScheduleTimeline and a ScheduledActivityInstance that points to same Activity, but to a different ScheduleTimeline. This will likely happen...correct? At the surface it seems so. I'm thinking this won't work and that only ScheduledActivityInstances should ever point to a ScheduleTimeline. Also it's possible for an Activity to be the start of more than one ScheduleTimeline, correct? If so, then this can't be a scalar variable. Hence the association defined (1 to 0..*) between Activity objects and ScheduledActivityInstance objects.	[Is static True. Containment is Not Specified.]
 bcCategoryIds : List<String> Private	[Is static True. Containment is Not Specified.]


ATTRIBUTES

 bcSurrogateIds : List<String> Private

[Is static True. Containment is Not Specified.]

 biomedicalConceptIds : List<String> Private

[Is static True. Containment is Not Specified.]


 definedProcedures : List<Procedure> Private

[Is static True. Containment is Not Specified.]

 nextActivityId : String Private

A system identifier assigned to a study activity that occurs immediately after the current study activity.

[Is static True. Containment is Not Specified.]

 previousActivityId : String Private

A system identifier assigned to a study activity that occurs immediately prior to the current study activity.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) Activity

Target: Private definedProcedures (Class)
Procedure

Cardinality: [0..*]


 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign


Target: Private activities (Class) Activity

Cardinality: [0..*]


OPERATIONS














 Activity (activityId : String) : Public











[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 addDefinedProcedure (procedure : Procedure) : void Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getActivityDescription () : String Public

OPERATIONS	
	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getActivityId () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getActivityIsConditional () : boolean Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getActivityIsConditionalReason () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getActivityName () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getActivityTimelineId () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getBcCategoryIds () : List<String> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getBcSurrogateIds () : List<String> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getBiomedicalConceptIds () : List<String> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getDefinedProcedures () : List<Procedure> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getNextActivityId () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getPreviousActivityId () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 removeDefinedProcedure (procedure : Procedure) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setActivityDescription (description : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


OPERATIONS
 setActivityIsConditional (activityIsConditional : boolean) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setActivityIsConditionalReason (activityIsConditionalReason : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setActivityName (activityName : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setActivityTimelineId (activityTimelineId : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcCategoryIds (bcCategoryIds : List<String>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcSurrogateIds (bcSurrogateIds : List<String>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBiomedicalConceptIds (biomedicalConceptIds : List<String>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setDefinedProcedures (definedProcedures : List<Procedure>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setNextActivityId (nextActivityId : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setPreviousActivityId (previousActivityId : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

Address


Class in package 'model'

Address
 Version 1.0 Phase 1.0 Proposed
 cupke created on 3/9/2023. Last modified 3/9/2023


ATTRIBUTES

ATTRIBUTES city : String Private

[Is static True. Containment is Not Specified.]

 country : Code Private


[Is static True. Containment is Not Specified.]

 district : String Private


[Is static True. Containment is Not Specified.]

 line : String Private


[Is static True. Containment is Not Specified.]

 postalCode : String Private

[Is static True. Containment is Not Specified.]

 state : String Private

[Is static True. Containment is Not Specified.]

 text : String Private

[Is static True. Containment is Not Specified.]


ASSOCIATIONS Association (direction: Source -> Destination)

Source: Public (Class) Address


Target: Private country (Class) Code

 Association (direction: Source -> Destination)


Source: Public (Class) Organization












Target: Private organizationLegalAddress (Class)
Address**OPERATIONS** getCity () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getCountry () : Code Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getDistrict () : String Public

OPERATIONS	
	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getLine () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getPostalCode () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getState () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getText () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setCity (city : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setCountry (country : Code) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setDistrict (district : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setLine (line : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setPostalCode (postalCode : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setState (state : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setText (text : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]







AliasCode






Class in package 'model'

An alternative symbol or combination of symbols which is assigned to the members of a collection.

AliasCode
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES	
 aliasCodeId : String Private Const	[Is static True. Containment is Not Specified.]
 standardCode : Code Private	[Is static True. Containment is Not Specified.]
 standardCodeAliases : List<Code> Private	[Is static True. Containment is Not Specified.]

ASSOCIATIONS	
 Association (direction: Source -> Destination)	
Source: Public (Class) AliasCode	Target: Private standardCode (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) AliasCode	Target: Private standardCodeAliases (Class) Code Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) Study	Target: Private studyPhase (Class) AliasCode
 Association (direction: Source -> Destination)	
Source: Public (Class) BiomedicalConcept	Target: Private bcConceptCode (Class) AliasCode
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private studyDesignBlindingScheme (Class) AliasCode
 Association (direction: Source -> Destination)	
Source: Public (Class) BiomedicalConceptProperty	Target: Private bcPropertyConceptCode (Class) AliasCode



OPERATIONS
 AliasCode (aliasCodeId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStandardCode () : Code Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStandardCodeAliases () : List<Code> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStandardCode (standardCode : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStandardCodeAliases (standardCodeAliases : List<Code>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


AnalysisPopulation





Class in package 'model'

A target study population on which an analysis is performed. These may be represented by the entire study population, a subgroup defined by a particular characteristic measured at baseline, or a principal stratum defined by the occurrence (or non-occurrence, depending on context) of a specific intercurrent event. (ICH E9 R1 Addendum)

AnalysisPopulation
Version 1.0 Phase 1.0 Proposed
cupke created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
 analysisPopulationId : String Private Const [Is static True. Containment is Not Specified.]
 populationDescription : String Private The textual representation of the study population for analysis. [Is static True. Containment is Not Specified.]






ASSOCIATIONS
 Association (direction: Source -> Destination) <div> Source: Public (Class) Estimand <div>Target: Private analysisPopulation (Class) AnalysisPopulation</div> </div>

OPERATIONS
 AnalysisPopulation (analysisPopulationId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getAnalysisPopulationId () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getPopulationDescription () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setPopulationDescription (populationDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

BiomedicalConcept

Class in package 'model'

BiomedicalConcept
 Version 1.0 Phase 1.0 Proposed
 cupke created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
 bcConceptCode : AliasCode Private [Is static True. Containment is Not Specified.]
 bcName : String Private [Is static True. Containment is Not Specified.]
 bcProperties : List<BiomedicalConceptProperty> Private [Is static True. Containment is Not Specified.]
 bcReference : String Private [Is static True. Containment is Not Specified.]
 bcSynonyms : List<String> Private [Is static True. Containment is Not Specified.]
 biomedicalConceptId : String Private Const [Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) BiomedicalConcept

Target: Private bcConceptCode (Class) AliasCode

 Association (direction: Source -> Destination)

Source: Public (Class) BiomedicalConcept

Target: Private bcProperties (Class)
BiomedicalConceptProperty
Cardinality: [0..*]

 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private biomedicalConcepts (Class)
BiomedicalConcept
Cardinality: [0..*]

OPERATIONS

 BiomedicalConcept (biomedicalConceptId : String) : Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcConceptCode () : AliasCode Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcName () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcProperties () : List<BiomedicalConceptProperty> Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcReference () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcSynonyms () : List<String> Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBiomedicalConceptId () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]







 setBcConceptCode (bcConceptCode : AliasCode) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS
 setBcName (bcName : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcProperties (bcProperties : List<BiomedicalConceptProperty>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcReference (bcReference : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcSynonyms (bcSynonyms : List<String>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

BiomedicalConceptCategory

Class in package 'model'

BiomedicalConceptCategory
 Version 1.0 Phase 1.0 Proposed
 cupke created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
 bcCategoryChildrenIds : List<String> Private [Is static True. Containment is Not Specified.]
 bcCategoryDescription : String Private [Is static True. Containment is Not Specified.]
 bcCategoryMemberIds : List<String> Private [Is static True. Containment is Not Specified.]
 bcCategoryName : String Private [Is static True. Containment is Not Specified.]
 bcCategoryParentIds : List<String> Private [Is static True. Containment is Not Specified.]
 biomedicalConceptCategoryId : String Private Const [Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private bcCategories (Class)
BiomedicalConceptCategory

Cardinality: [0..*]

OPERATIONS

 BiomedicalConceptCategory (bcCategoryId : String) : Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcCategoryChildrenIds () : List<String> Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


 getBcCategoryDescription () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


 getBcCategoryMemberIds () : List<String> Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


 getBcCategoryName () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcCategoryParentIds () : List<String> Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBiomedicalConceptCategoryId () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


 setBcCategoryChildrenIds (bcCategoryChildrenIds : List<String>) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setBcCategoryDescription (bcCategoryDescription : String) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setBcCategoryMemberIds (bcCategoryMemberIds : List<String>) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setBcCategoryName (bcCategoryName : String) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS

 **setBcCategoryParentIds** (bcCategoryParentIds : List<String>) : void Public
 [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

BiomedicalConceptProperty

Class in package 'model'

BiomedicalConceptProperty
 Version 1.0 Phase 1.0 Proposed
 cupke created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES

 **bcPropertyConceptCode** : AliasCode Private
 [Is static True. Containment is Not Specified.]


 **bcPropertyDatatype** : String Private
 [Is static True. Containment is Not Specified.]

 **bcPropertyEnabled** : boolean Private
 [Is static True. Containment is Not Specified.]

 **bcPropertyId** : String Private Const
 [Is static True. Containment is Not Specified.]

 **bcPropertyName** : String Private
 [Is static True. Containment is Not Specified.]

 **bcPropertyRequired** : boolean Private
 [Is static True. Containment is Not Specified.]

 **bcPropertyResponseCodes** : List<ResponseCode> Private
 [Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) BiomedicalConceptProperty

Target: Private bcPropertyResponseCodes (Class)
 ResponseCode

Cardinality: [0..*]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) BiomedicalConceptProperty

Target: Private bcPropertyConceptCode (Class)
AliasCode

 Association (direction: Source -> Destination)

Source: Public (Class) BiomedicalConcept

Target: Private bcProperties (Class)
BiomedicalConceptProperty
Cardinality: [0..*]

OPERATIONS

 BiomedicalConceptProperty (bcPropertyId : String) : Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcPropertyConceptCode () : AliasCode Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcPropertyDatatype () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcPropertyId () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBcPropertyName () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]




 getBcPropertyResponseCodes () : List<ResponseCode> Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 isBcPropertyEnabled () : boolean Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 isBcPropertyRequired () : boolean Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setBcPropertyConceptCode (bcPropertyConceptCode : AliasCode) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


 setBcPropertyDatatype (bcPropertyDatatype : String) : void Public


OPERATIONS
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcPropertyEnabled (bcPropertyEnabled : boolean) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcPropertyName (bcPropertyName : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcPropertyResponseCodes (bcPropertyResponseCodes : List<ResponseCode>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

BiomedicalConceptSurrogate









Class in package 'model'

BiomedicalConceptSurrogate
 Version 1.0 Phase 1.0 Proposed
 cupke created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
 bcSurrogateDescription : String Private [Is static True. Containment is Not Specified.]
 bcSurrogateId : String Private Const [Is static True. Containment is Not Specified.]
 bcSurrogateName : String Private [Is static True. Containment is Not Specified.]
 bcSurrogateReference : String Private [Is static True. Containment is Not Specified.]

ASSOCIATIONS
 Association (direction: Source -> Destination) <div> <div>Source: Public (Class) StudyDesign</div> <div>Target: Private bcSurrogates (Class) BiomedicalConceptSurrogate Cardinality: [0..*]</div> </div>

OPERATIONS

OPERATIONS
 BiomedicalConceptSurrogate (bcSurrogateId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getBcSurrogateDescription () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getBcSurrogateId () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getBcSurrogateName () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getBcSurrogateReference () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcSurrogateDescription (bcSurrogateDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcSurrogateName (bcSurrogateName : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBcSurrogateReference (bcSurrogateReference : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

Code

Class in package 'model'

A symbol or combination of symbols which is assigned to the members of a collection.

Code


Version 1.0 Phase 1.0 Proposed

Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
 code : String Private The literal value of a code. [Is static True. Containment is Not Specified.]
 codeId : String Private Const


ATTRIBUTES

[Is static True. Containment is Not Specified.]

 codeSystem : String Private


The literal identifier (i.e., distinctive designation) of the system used to assign and/or manage codes.

[Is static True. Containment is Not Specified.]

 codeSystemVersion : String Private

The version of the code system.

[Is static True. Containment is Not Specified.]

 decode : String Private

Standardized or dictionary-derived human readable text associated with a code.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) Objective

Target: Private objectiveLevel (Class) Code

 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private trialType (Class) Code

Cardinality: [0..*]

 Association (direction: Source -> Destination)

Source: Public (Class) StudyArm

Target: Private studyArmType (Class) Code

 Association (direction: Source -> Destination)

Source: Public (Class) Encounter

Target: Private encounterContactModes (Class)
Code

Cardinality: [0..*]

 Association (direction: Source -> Destination)

Source: Public (Class) Study

Target: Private businessTherapeuticAreas (Class)
Code

Cardinality: [0..*]

ASSOCIATIONS	
 Association (direction: Source -> Destination)	
Source: Public (Class) InvestigationalIntervention	Target: Private codes (Class) Code Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) Study	Target: Private studyType (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private interventionModel (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) Timing	Target: Private timingType (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) Timing	Target: Private timingRelativeToFrom (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) Address	Target: Private country (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) Indication	Target: Private codes (Class) Code Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) AliasCode	Target: Private standardCode (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) ResponseCode	Target: Private code (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) Endpoint	Target: Private endpointLevel (Class) Code
 Association (direction: Source -> Destination)	

ASSOCIATIONS	
Source: Public (Class) StudyDesign	Target: Private trialIntentType (Class) Code Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) Procedure	Target: Private procedureCode (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyEpoch	Target: Private studyEpochType (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) Encounter	Target: Private encounterEnvironmentalSetting (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) AliasCode	Target: Private standardCodeAliases (Class) Code Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) Organization	Target: Private organizationType (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyArm	Target: Private studyArmDataOriginType (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private therapeuticAreas (Class) Code Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) Encounter	Target: Private encounterType (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesignPopulation	Target: Private plannedSexOfParticipants (Class) Code

ASSOCIATIONS


Cardinality: [0..*]

 Association (direction: Source -> Destination)


Source: Public (Class) StudyProtocolVersion

Target: Private protocolStatus (Class) Code


OPERATIONS

 Code (codeId : String) : Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getCode () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getCodeId () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getCodeSystem () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getCodeSystemVersion () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getDecode () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setCode (code : String) : void Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setCodeSystem (codeSystem : String) : void Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setCodeSystemVersion (codeSystemVersion : String) : void Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setDecode (decode : String) : void Public





[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

Encounter

Class in package 'model'

Contact between subject/patient and healthcare practitioner/researcher, during which an assessment or activity is performed. Contact may be physical or virtual.

Encounter
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES	
 encounterContactModes : List<Code> Private	<p>The means by which an interaction occurs between the subject/participant and person or entity (e.g., a device).</p> <p>[Is static True. Containment is Not Specified.]</p>
 encounterDescription : String Private	<p>The textual representation of the protocol-defined clinical encounter.</p> <p>[Is static True. Containment is Not Specified.]</p>
 encounterEnvironmentalSetting : Code Private	<p>The environment/setting where the event, intervention, or finding occurred.</p> <p>[Is static True. Containment is Not Specified.]</p>
 encounterId : String Private Const	<p>[Is static True. Containment is Not Specified.]</p>
 encounterName : String Private	<p>The literal identifier (i.e., distinctive designation) for a protocol-defined clinical encounter.</p> <p>[Is static True. Containment is Not Specified.]</p>
 encounterScheduledAtTimingId : String Private	<p>Ok, so now that we have a better understanding of the ScheduleTimeline, we need to think about what encounters should point to. In this case I believe the only relevant information in a Timing object re: Encounters is the window data which is just a string (could be meaningless). When managing patient protocols, encounters begin with some type of event, not a constraint such as a Timing. Encounters are an umbrella concept for a series of events (px, rx, labs, etc..) that a patient encounters during a provider visit. In patient protocols they often involve diagnoses and claims of "conditions"...not to be confused with conditions associated with ScheduledDecisionInstances. Which makes me think that we might not want to overload the term "condition". Anyway, I won't change this to a collection until we've figured out why the pointer exists.</p> <p>[Is static True. Containment is Not Specified.]</p>
 encounterType : Code Private	<p>A characterization or classification of contact between subject/patient and healthcare practitioner/researcher, during which an</p>

ATTRIBUTES


assessment or activity is performed.

[Is static True. Containment is Not Specified.]

 nextEncounterId : String Private


A system identifier assigned to a clinical encounter that occurs immediately after the current clinical encounter.

[Is static True. Containment is Not Specified.]


 previousEncounterId : String Private

A system identifier assigned to a clinical encounter that occurs immediately prior to the current clinical encounter.

[Is static True. Containment is Not Specified.]

 transitionEndRule : TransitionRule Private

[Is static True. Containment is Not Specified.]

 transitionStartRule : TransitionRule Private

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) Encounter

Target: Private transitionEndRule (Class)
TransitionRule

 Association (direction: Source -> Destination)

Source: Public (Class) Encounter

Target: Private encounterContactModes (Class)
Code
Cardinality: [0..*]

 Association (direction: Source -> Destination)

Source: Public (Class) Encounter

Target: Private transitionStartRule (Class)
TransitionRule

 Association (direction: Source -> Destination)

Source: Public (Class) Encounter

Target: Private encounterEnvironmentalSetting
(Class) Code

 Association (direction: Source -> Destination)

ASSOCIATIONS

Source: Public (Class) Encounter

Target: Private encounterType (Class) Code

 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private encounters (Class) Encounter

Cardinality: [0..*]


 Association (direction: Source -> Destination)

Source: Public (Class) StudyEpoch

Target: Private encounters (Class) Encounter

Cardinality: [0..*]


OPERATIONS

 Encounter (encounterId : String) : Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getEncounterContactModes () : List<Code> Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getEncounterDescription () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getEncounterEnvironmentalSetting () : Code Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getEncounterId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getEncounterName () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getEncounterScheduledAtTimingId () : String Public













[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getEncounterType () : Code Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getNextEncounterId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS	
 <code>getPreviousEncounterId () : String Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>getStartRule () : TransitionRule Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>getTransitionEndRule () : TransitionRule Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>getTransitionStartRule () : TransitionRule Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setEncounterContactModes (encounterContactModes : List<Code>) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setEncounterDescription (encounterDescription : String) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setEncounterEnvironmentalSetting (encounterEnvironmentalSetting : Code) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setEncounterName (encounterName : String) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setEncounterScheduledAtTimingId (encounterScheduledAtTimingId : String) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setEncounterType (encounterType : Code) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setNextEncounterId (nextEncounterId : String) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setPreviousEncounterId (previousEncounterId : String) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setTransitionEndRule (transitionEndRule : TransitionRule) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setTransitionStartRule (transitionStartRule : TransitionRule) : void Public</code>	

OPERATIONS


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

Endpoint

Class in package 'model'


A defined variable intended to reflect an outcome of interest that is statistically analyzed to address a particular research question. NOTE: A precise definition of an endpoint typically specifies the type of assessments made, the timing of those assessments, the assessment tools used, and possibly other details, as applicable, such as how multiple assessments within an individual are to be combined. [After BEST Resource]

Endpoint
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
 endpointDescription : String Private

The textual representation of the study endpoint.

[Is static True. Containment is Not Specified.]

 endpointId : String Private Const

[Is static True. Containment is Not Specified.]

 endpointLevel : Code Private

A characterization or classification of the study endpoint that determines its category of importance relative to other study endpoints.

[Is static True. Containment is Not Specified.]

 endpointPurposeDescription : String Private

The textual representation of the study endpoint purpose.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS
 Association (direction: Source -> Destination)


Source: Public (Class) Endpoint









Target: Private endpointLevel (Class) Code

 Association (direction: Source -> Destination)

Source: Public (Class) Objective

Target: Private objectiveEndpoints (Class)
Endpoint

ASSOCIATIONS	
Cardinality: [0..*]	
 Association (direction: Source -> Destination)	
Source: Public (Class) Estimand	Target: Private variableOfInterest (Class) Endpoint







OPERATIONS	
 Endpoint (endpointId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getEndpointDescription () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getEndpointId () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getEndpointLevel () : Code Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getEndpointPurposeDescription () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setEndpointDescription (endpointDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setEndpointLevel (endpointLevel : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setEndpointPurposeDescription (endpointPurposeDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	




Estimand

Class in package 'model'

A precise description of the treatment effect reflecting the clinical question posed by a given clinical trial objective. It summarises at a population level what the outcomes would be in the same patients under different treatment conditions being compared. (ICH E9 R1 Addendum)

Estimand
Version 1.0 Phase 1.0 Proposed

ATTRIBUTES	
 analysisPopulation : AnalysisPopulation Private	[Is static True. Containment is Not Specified.]
 estimandId : String Private Const	[Is static True. Containment is Not Specified.]
 intercurrentEvents : List<IntercurrentEvent> Private	[Is static True. Containment is Not Specified.]
 summaryMeasure : String Private A synopsis of the clinical endpoint of interest within the analysis target study population.	[Is static True. Containment is Not Specified.]
 treatment : InvestigationalIntervention Private	[Is static True. Containment is Not Specified.]
 variableOfInterest : Endpoint Private	[Is static True. Containment is Not Specified.]

ASSOCIATIONS	
 Association (direction: Source -> Destination)	
Source: Public (Class) Estimand	Target: Private intercurrentEvents (Class) IntercurrentEvent Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) Estimand	Target: Private variableOfInterest (Class) Endpoint
 Association (direction: Source -> Destination)	
Source: Public (Class) Estimand	Target: Private analysisPopulation (Class) AnalysisPopulation
 Association (direction: Source -> Destination)	
Source: Public (Class) Estimand	Target: Private treatment (Class) InvestigationalIntervention

ASSOCIATIONS


 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private studyEstimands (Class) Estimand

Cardinality: [0..*]

OPERATIONS

 addIntercurrentEvent (intercurrentEvent : IntercurrentEvent) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 Estimand (estimandId : String) : Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getAnalysisPopulation () : AnalysisPopulation Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


 getEstimandId () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getIntercurrentEvents () : List<IntercurrentEvent> Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getSummaryMeasure () : String Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getTreatment () : InvestigationalIntervention Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]




 getVariableOfInterest () : Endpoint Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 removeIntercurrentEvent (intercurrentEvent : IntercurrentEvent) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setAnalysisPopulation (analysisPopulation : AnalysisPopulation) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setIntercurrentEvents (intercurrentEvents : List<IntercurrentEvent>) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS

-  **setSummaryMeasure** (summaryMeasure : String) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
-  **setTreatment** (treatment : InvestigationalIntervention) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
-  **setVariableOfInterest** (variableOfInterest : Endpoint) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]




Indication

Class in package 'model'

The condition, disease or disorder that the clinical trial is intended to investigate or address.







Indication
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES

-  **codes** : List<Code> Private
A short sequence of characters that represents the disease indication.
[Is static True. Containment is Not Specified.]
-  **indicationDescription** : String Private
The condition, disease or disorder that the clinical trial is intended to investigate or address.
[Is static True. Containment is Not Specified.]
-  **indicationId** : String Private Const
[Is static True. Containment is Not Specified.]

ASSOCIATIONS

-  Association (direction: Source -> Destination)
Source: Public (Class) Indication Target: Private codes (Class) Code
Cardinality: [0..*]
-  Association (direction: Source -> Destination)
Source: Public (Class) StudyDesign Target: Private studyIndications (Class) Indication

ASSOCIATIONS	
	Cardinality: [0..*]
OPERATIONS	
 getCodes () : List<Code> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getIndicationDescription () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getIndicationId () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 Indication (indicationId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setCodes (codes : List<Code>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setIndicationDescription (indicationDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	

IntercurrentEvent

Class in package 'model'

An event(s) occurring after treatment initiation that affects either the interpretation or the existence of the measurements associated with the clinical question of interest. (ICH E9 Addendum on Estimands)

IntercurrentEvent
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023


ATTRIBUTES	
 intercurrentEventDescription : String Private The textual representation of the intercurrent event.	[Is static True. Containment is Not Specified.]
 intercurrentEventId : String Private Const	[Is static True. Containment is Not Specified.]

ATTRIBUTES

 intercurrentEventName : String Private

The literal identifier (i.e., distinctive designation) of the intercurrent event.

[Is static True. Containment is Not Specified.]

 intercurrentEventStrategy : String Private

A textual description of the planned strategy to manage and/or mitigate intercurrent events.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) Estimand


Target: Private intercurrentEvents (Class)
IntercurrentEvent

Cardinality: [0..*]

OPERATIONS

 getIntercurrentEventDescription () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getIntercurrentEventId () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getIntercurrentEventName () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getIntercurrentEventStrategy () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 IntercurrentEvent (intercurrentEventId : String) : Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setIntercurrentEventDescription (intercurrentEventDescription : String) : void Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setIntercurrentEventName (intercurrentEventName : String) : void Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setIntercurrentEventStrategy (intercurrentEventStrategy : String) : void Public

OPERATIONS

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

InvestigationalIntervention

Class in package 'model'


The drug, device, therapy, or process under investigation in a clinical study that is believed to have an effect on outcomes of interest in a study. [After https://grants.nih.gov/grants/policy/faq_clinical_trial_definition.htm#5224] (CDISC-Glossary)

InvestigationalIntervention

Version 1.0 Phase 1.0 Proposed


Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES

 codes : List<Code> Private


A short sequence of characters that represents the investigational intervention.

[Is static True. Containment is Not Specified.]

 interventionDescription : String Private

The textual representation of the study intervention.

[Is static True. Containment is Not Specified.]

 investigationalInterventionId : String Private Const

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) InvestigationalIntervention

Target: Private codes (Class) Code

Cardinality: [0..*]

 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private studyInvestigationalInterventions (Class) InvestigationalIntervention

Cardinality: [0..*]







 Association (direction: Source -> Destination)

Source: Public (Class) Estimand

Target: Private treatment (Class) InvestigationalIntervention

ASSOCIATIONS

OPERATIONS

 <code>getCodes () : List<Code> Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>getInterventionDescription () : String Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>getInvestigationalInterventionId () : String Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>InvestigationalIntervention (investigationalInterventionId : String) : Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setCodes (codes : List<Code>) : void Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setInterventionDescription (interventionDescription : String) : void Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

Objective

Class in package 'model'

The reason for performing a study in terms of the scientific questions to be answered by the analysis of data collected during the study.


Objective
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES

 <code>objectiveDescription : String Private</code> The textual representation of the study objective. (BRIDG) [Is static True. Containment is Not Specified.]
 <code>objectiveEndpoints : List<Endpoint> Private</code> [Is static True. Containment is Not Specified.]
 <code>objectiveId : String Private Const</code>

ATTRIBUTES

[Is static True. Containment is Not Specified.]

 objectiveLevel : Code Private

A characterization or classification of the study endpoint that determines its category of importance relative to other study objectives.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) Objective

Target: Private objectiveLevel (Class) Code

 Association (direction: Source -> Destination)

Source: Public (Class) Objective


Target: Private objectiveEndpoints (Class)
Endpoint
Cardinality: [0..*]

 Association (direction: Source -> Destination)


Source: Public (Class) StudyDesign

Target: Private studyObjectives (Class) Objective
Cardinality: [0..*]


OPERATIONS

 getObjectiveDescription () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getObjectiveEndpoints () : List<Endpoint> Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getObjectiveId () : String Public




[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getObjectiveLevel () : Code Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 Objective (objectiveId : String) : Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]







OPERATIONS
 setObjectiveDescription (objectiveDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setObjectiveEndpoints (objectiveEndpoints : List<Endpoint>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setObjectiveLevel (objectiveLevel : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

Organization

Class in package 'model'

A formalized group of persons or other organizations collected together for a common purpose (such as administrative, legal, political) and the infrastructure to carry out that purpose. (BRIDG)

Organization
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
 organizationId : String Private Const [Is static True. Containment is Not Specified.]
 organizationIdentifier : String Private A unique symbol that establishes identity of the organization. (BRIDG) [Is static True. Containment is Not Specified.]
 organizationIdentifierScheme : String Private The name of the organization that provides the identifier for the entity. [Is static True. Containment is Not Specified.]
 organizationLegalAddress : Address Private [Is static True. Containment is Not Specified.]
 organizationName : String Private A non-unique textual identifier for the organization. (BRIDG) [Is static True. Containment is Not Specified.]
 organizationType : Code Private

ATTRIBUTES

A characterization or classification of the formalized group of persons or other organizations collected together for a common purpose (such as administrative, legal, political) and the infrastructure to carry out that purpose.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) Organization

Target: Private organizationLegalAddress (Class)
Address

 Association (direction: Source -> Destination)

Source: Public (Class) Organization


Target: Private organizationType (Class) Code

 Association (direction: Source -> Destination)


Source: Public (Class) StudyIdentifier

Target: Private studyIdentifierScope (Class)
Organization


OPERATIONS

 getOrganizationId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getOrganizationIdentifier () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getOrganizationIdentifierScheme () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getOrganizationLegalAddress () : Address Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getOrganizationName () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getOrganizationType () : Code Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 Organization (organizationId : String) : Public





OPERATIONS	
	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setOrganizationIdentifier (organizationIdentifier : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setOrganizationIdentifierScheme (organizationIdentifierScheme : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setOrganizationLegalAddress (organizationLegalAddress : Address) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setOrganizationName (organizationName : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setOrganizationType (organizationType : Code) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

Procedure


Class in package 'model'

Any activity performed by manual and/or instrumental means for the purpose of diagnosis, assessment, therapy, prevention, or palliative care.

Procedure
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES	
 procedureCode : Code Private A symbol or combination of symbols which is assigned to medical procedure.	[Is static True. Containment is Not Specified.]
 procedureId : String Private Const	[Is static True. Containment is Not Specified.]
 procedureIsConditional : boolean Private	[Is static True. Containment is Not Specified.]
 procedureIsConditionalReason : String Private	[Is static True. Containment is Not Specified.]

ATTRIBUTES

 procedureType : String Private

A characterization or classification of the study procedure.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) Procedure

Target: Private procedureCode (Class) Code

 Association (direction: Source -> Destination)

Source: Public (Class) Activity


Target: Private definedProcedures (Class)
Procedure

Cardinality: [0..*]


OPERATIONS

 getProcedureCode () : Code Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getProcedureId () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getProcedureIsConditional () : boolean Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getProcedureIsConditionalReason () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getProcedureType () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]




 Procedure (procedureId : String) : Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setProcedureCode (procedureCode : Code) : void Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS




-  **setProcedureIsConditional** (procedureIsConditional : boolean) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
-  **setProcedureIsConditionalReason** (procedureIsConditionalReason : String) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
-  **setProcedureType** (procedureType : String) : void Public
[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

ResponseCode



Class in package 'model'

ResponseCode
Version 1.0 Phase 1.0 Proposed
cupke created on 3/9/2023. Last modified 3/9/2023


ATTRIBUTES






-  **code** : Code Private
[Is static True. Containment is Not Specified.]
-  **responseCodeEnabled** : boolean Private
[Is static True. Containment is Not Specified.]
-  **responseCodeId** : String Private Const
[Is static True. Containment is Not Specified.]

ASSOCIATIONS

-  Association (direction: Source -> Destination)
Source: Public (Class) ResponseCode Target: Private code (Class) Code
-  Association (direction: Source -> Destination)
Source: Public (Class) BiomedicalConceptProperty Target: Private bcPropertyResponseCodes (Class) ResponseCode
Cardinality: [0..*]

OPERATIONS

-  **getCode** () : Code Public


OPERATIONS	
	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>getResponseCodeId () : String Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>isResponseCodeEnabled () : boolean Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>ResponseCode (responseCodeId : String) : Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setCode (code : Code) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setResponseCodeEnabled (responseCodeEnabled : boolean) : void Public</code>	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


ScheduledActivityInstance

Class in package 'model'

The ScheduledActivityInstance class is used to extend the ScheduledInstance class with activity-specific information and behaviors needed for the ScheduleTimeline.




ScheduledActivityInstance
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

OUTGOING STRUCTURAL RELATIONSHIPS	
 Generalization from ScheduledActivityInstance to ScheduledInstance	[Direction is 'Source -> Destination'.]

ATTRIBUTES	
 <code>activityIds : List<String> Private</code>	
<p>This is the list of ID references to Activity definitions. There can be 1 or many. This allows for a simpler mechanism for associating non-sequential tasks that have similar constraints to other sequential tasks to be added to the timeline.</p>	
[Is static True. Containment is Not Specified.]	

OPERATIONS	

OPERATIONS

-  getActivityIds () : List<String> Public
 [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
-  ScheduledActivityInstance (scheduledInstanceId : String , scheduledInstanceType : ScheduledInstanceType) : Public
 [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
-  setActivityIds (activityIds : List<String>) : void Public
 [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


ScheduledDecisionInstance

Class in package 'model'


The ScheduledDecisionInstance class is used to extend the ScheduledInstance class with decision-specific information and behaviors needed for the ScheduleTimeline. Different from other ScheduledInstance extensions, this class will be used for flow-control logic such as branching and looping (cycling).

ScheduledDecisionInstance
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

OUTGOING STRUCTURAL RELATIONSHIPS


-  Generalization from ScheduledDecisionInstance to ScheduledInstance
 [Direction is 'Source -> Destination'.]


ATTRIBUTES

-  conditionAssignments : Map<String, String> Package

 This field maps conditions to their associated scheduled instances For example, if you had a generic condition temperature over 99, there may be 2 conditions in the map: {"greater than 99": "123", "less than or equal to 99": "678"} Always state in terms with conditions that are always true The mapping is valid if the condition is true
 [Is static True. Containment is Not Specified.]

OPERATIONS

-  getConditionAssignments () : Map<String, String> Public

 OR conditionAndScheduledInstanceIdAssignments
 [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
-  ScheduledDecisionInstance (scheduledInstanceId : String , scheduledInstanceType : ScheduledInstanceType) : Public
 [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS

 setConditionAssignments (conditionAssignments : Map<String, String>) : void Public
 [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

ScheduledInstance

Class in package 'model'

The ScheduledInstance abstract class is used by ScheduleTimelines to build a sequence of activities and decisions that will define a schedule.


ScheduledInstance
 Version 1.0 Phase 1.0 Proposed
 Chris Upkes created on 3/9/2023. Last modified 3/9/2023

INCOMING STRUCTURAL RELATIONSHIPS

⇒ Generalization from ScheduledActivityInstance to ScheduledInstance
 [Direction is 'Source -> Destination'.]


⇒ Generalization from ScheduledDecisionInstance to ScheduledInstance
 [Direction is 'Source -> Destination'.]

ATTRIBUTES


 scheduledInstanceEncounterId : String Private

I get this now. You do want to know if the instance is part of an encounter. This field points to the encounter that the activity is taking part of.

[Is static True. Containment is Not Specified.]


 scheduledInstanceId : String Private Const

[Is static True. Containment is Not Specified.]

 scheduledInstanceTimelineId : String Private

This field will have a value if the scheduled instance points to a different timeline


[Is static True. Containment is Not Specified.]

 scheduledInstanceTimings : List<Timing> Private

Ok, I'll add this, but it isn't very useful. You're better off starting at a ScheduleTimeline. In this case, you could have an instance pointing to a large number of Timing objects because it has a large number of scheduling constraints. I like the idea of activities not having any Timing references; just decisions because they are selective. If we must, we may want to consider changing this to be directionally at least...incoming and outgoing?


[Is static True. Containment is Not Specified.]

ATTRIBUTES

 `scheduledInstanceType : ScheduledInstanceType Private Const`


Possible Values: ACTIVITY, DECISION

[Is static True. Containment is Not Specified.]

 `scheduleSequenceNumber : Integer Private`

There has been an ask for sequencing of ScheduledInstance in a ScheduleTimeline. In order to do this, the entire ScheduleTimeline must be constructed with all of the necessary ScheduledInstance, Timing and Exit objects. Once this is complete, a some sequencing process can then annotate the ScheduleTimeline's collection of ScheduleInstance objects and update this field. This is a hard field to name, btw. Is scheduleTimelineScheduledInstanceSequenceNumber manageable?

[Is static True. Containment is Not Specified.]

 `scheduleTimelineExitId : String Private`

In the last version of the model, there was a pointer to an Exit object in the previous version of this class. I'm struggling with this, as the exit is the property of a ScheduleTimeline already. I can understand why we need an entry pointer but not an exit. Is this just a wqy of identifying a final ScheduledInstance in some ScheduleTimeline? Isn't that still the perspective of the timeline? Just trying to name it really shows that I'm trying to point to something that's really something my parent cares about.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) ScheduledInstance

Target: Private scheduledInstanceType
(Enumeration) ScheduledInstanceType

 Association (direction: Source -> Destination)

Source: Public (Class) ScheduledInstance


Target: Private scheduledInstanceTimings (Class)
Timing
Cardinality: [0..*]

 Association (direction: Source -> Destination)













Source: Public (Class) ScheduleTimeline

Target: Private scheduleTimelineInstances (Class)
ScheduledInstance
Cardinality: [0..*]

OPERATIONS

 `getScheduledInstanceEncounterId () : String Public`

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]








OPERATIONS
 getScheduledInstanceId () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getScheduledInstanceTimelineId () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getScheduledInstanceTimings () : List<Timing> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getScheduledInstanceType () : ScheduledInstanceType Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getScheduleSequenceNumber () : Integer Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getScheduleTimelineExitId () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 ScheduledInstance (scheduledInstanceId : String , scheduledInstanceType : ScheduledInstanceType) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setScheduledInstanceEncounterId (scheduledInstanceEncounterId : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setScheduledInstanceTimelineId (scheduledInstanceTimelineId : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setScheduledInstanceTimings (scheduledInstanceTimings : List<Timing>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setScheduleSequenceNumber (scheduleSequenceNumber : Integer) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setScheduleTimelineExitId (scheduleTimelineExitId : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

ScheduleTimeline

Class in package 'model'

regarding TimeLine Entry as a new class name. I feel that TimelineEtry is confusing. If there is a timeline entry, then there must be a timeline. Yet, in the diagram, the two concepts are conflated into the TimelineEntry. I suggest keeping ScheduleTimeline and adding entry attribution as a simple condition field.

ScheduleTimeline
Version 1.0 Phase 1.0 Proposed
cupke created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
<p> entryCondition : String Private</p> <p>Here we again place information at two levels: The ScheduledDecisionInstance and The ScheduleTimeline. If the timeline owns all of the instances then it already has a way to get to a condition on a decision. We should ponder this further.</p> <p style="text-align: right;">[Is static True. Containment is Not Specified.]</p>
<p> scheduleTimelineDescription : String Private</p> <p>A textual description of the timeline. There will likely be numerous timelines in a study and this field provides the context for the particular timeline.</p> <p style="text-align: right;">[Is static True. Containment is Not Specified.]</p>
<p> scheduleTimelineEntryId : String Private</p> <p>If the timeline was due to a condition that was met for traversal from a previous timpoint, then we should have a handle to that timepoint.</p> <p style="text-align: right;">[Is static True. Containment is Not Specified.]</p>
<p> scheduleTimelineExits : List<ScheduleTimelineExit> Private</p> <p>This field represents the Exit object associated with the ScheduleTimeline.</p> <p style="text-align: right;">[Is static True. Containment is Not Specified.]</p>
<p> scheduleTimelineId : String Private Const</p> <p style="text-align: right;">[Is static True. Containment is Not Specified.]</p>
<p> scheduleTimelineInstances : List<ScheduledInstance> Private</p> <p>At this point, this is an unordered list of instances. We might consider more encapsulation by creating a timepointSequence wrapper.</p> <p style="text-align: right;">[Is static True. Containment is Not Specified.]</p>
<p> scheduleTimelineName : String Private</p> <p>This is field provides a name for the timeline</p> <p style="text-align: right;">[Is static True. Containment is Not Specified.]</p>

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) ScheduleTimeline

Target: Private scheduleTimelineExits (Class)
ScheduleTimelineExit

Cardinality: [0..*]

 Association (direction: Source -> Destination)

Source: Public (Class) ScheduleTimeline

Target: Private scheduleTimelineInstances (Class)
ScheduledInstance

Cardinality: [0..*]


 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private studyScheduleTimelines (Class)
ScheduleTimeline

Cardinality: [0..*]

OPERATIONS

 getEntryCondition () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getScheduleTimelineDescription () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getScheduleTimelineEntryId () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getScheduleTimelineExits () : List<ScheduleTimelineExit> Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getScheduleTimelineId () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]







 getScheduleTimelineInstances () : List<ScheduledInstance> Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getScheduleTimelineName () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 ScheduleTimeline (scheduleTimelineId : String) : Public



OPERATIONS	
	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setEntryCondition (entryCondition : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setScheduleTimelineDescription (scheduleTimelineDescription : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setScheduleTimelineEntryId (scheduleTimelineEntryId : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setScheduleTimelineExits (scheduleTimelineScheduleTimelineExits : List<ScheduleTimelineExit>) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setScheduleTimelineInstances (scheduleTimelineInstances : List<ScheduledInstance>) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setScheduleTimelineName (scheduleTimelineName : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

ScheduleTimelineExit

Class in package 'model'

Is just Exit intuitive enough in the model as a concept. Does it exist outside of a ScheduleTimeline? If not, then it's maybe a ScheduleTimelineExit or a TimelineExit?

ScheduleTimelineExit
Version 1.0 Phase 1.0 Proposed
cupke created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES	
 scheduleTimelineExitId : String Private Const	[Is static True. Containment is Not Specified.]
ASSOCIATIONS	
 Association (direction: Source -> Destination)	
Source: Public (Class) ScheduleTimeline	Target: Private scheduleTimelineExits (Class) ScheduleTimelineExit Cardinality: [0..*]

OPERATIONS

 `getScheduleTimelineExitId () : String Public`
 [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 `ScheduleTimelineExit (exitId : String) : Public`
 [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


Study

Class in package 'model'

A clinical study involves research using human volunteers (also called participants) that is intended to add to medical knowledge. There are two main types of clinical studies: clinical trials (also called interventional studies) and observational studies. [[<http://ClinicalTrials.gov>]](CDISC Glossary)

Study
 Version 1.0 Phase 1.0 Proposed
 Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES


 `businessTherapeuticAreas : List<Code> Private`
 A therapeutic area classification based on the structure and operations of the business unit.
 [Is static True. Containment is Not Specified.]




 `studyAcronym : String Private`
 [Is static True. Containment is Not Specified.]





 `studyDesigns : List<StudyDesign> Private`
 [Is static True. Containment is Not Specified.]

 `studyId : UUID Private Const`
 [Is static True. Containment is Not Specified.]

 `studyIdentifiers : List<StudyIdentifier> Private`
 [Is static True. Containment is Not Specified.]

 `studyPhase : AliasCode Private`
 A step in the clinical research and development of a therapy from initial clinical trials to post-approval studies. NOTE: Clinical trials are generally categorized into four (sometimes five) phases. A therapeutic intervention may be evaluated in two or more phases simultaneously in different trials, and some trials may overlap two different phases. [21 CFR section 312.21; After ICH Topic E8 NOTE FOR GUIDANCE ON GENERAL CONSIDERATIONS FOR CLINICAL TRIALS, CPMP/ICH/291/95 March 1998]

ATTRIBUTES	
	[Is static True. Containment is Not Specified.]
 studyProtocolVersions : List<StudyProtocolVersion> Private	[Is static True. Containment is Not Specified.]
 studyRationale : String Private	[Is static True. Containment is Not Specified.]
 studyTitle : String Private The sponsor-defined name of the clinical study.	[Is static True. Containment is Not Specified.]
 studyType : Code Private The nature of the investigation for which study information is being collected. (After clinicaltrials.gov)	[Is static True. Containment is Not Specified.]
 studyVersion : String Private A plan at a particular point in time for a study.	[Is static True. Containment is Not Specified.]

ASSOCIATIONS	
 Association (direction: Source -> Destination)	
Source: Public (Class) Study	Target: Private studyPhase (Class) AliasCode
 Association (direction: Source -> Destination)	
Source: Public (Class) Study	Target: Private studyIdentifiers (Class) StudyIdentifier Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) Study	Target: Private businessTherapeuticAreas (Class) Code Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) Study	Target: Private studyType (Class) Code

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) Study


Target: Private studyProtocolVersions (Class)
StudyProtocolVersion
Cardinality: [0..*]

 Association (direction: Source -> Destination)


Source: Public (Class) Study

Target: Private studyDesigns (Class) StudyDesign
Cardinality: [0..*]

OPERATIONS

 addStudyDesign (studyDesign : StudyDesign) : void Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 addStudyIdentifier (studyIdentifier : StudyIdentifier) : void Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 addStudyProtocolVersion (studyProtocolVersion : StudyProtocolVersion) : void Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getBusinessTherapeuticAreas () : List<Code> Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyAcronym () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyDesigns () : List<StudyDesign> Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyId () : UUID Public















[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyIdentifiers () : List<StudyIdentifier> Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyPhase () : AliasCode Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS	
 getStudyProtocolVersions () : List<StudyProtocolVersion> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyRationale () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyTitle () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyType () : Code Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyVersion () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 removeStudyDesign (studyDesign : StudyDesign) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 removeStudyIdentifier (studyIdentifier : StudyIdentifier) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 removeStudyProtocolVersion (studyProtocolVersion : StudyProtocolVersion) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBusinessTherapeuticAreas (businessTherapeuticAreas : List<Code>) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyAcronym (studyAcronym : String) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyDesigns (studyDesigns : List<StudyDesign>) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyIdentifiers (studyIdentifiers : List<StudyIdentifier>) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyPhase (studyPhase : AliasCode) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyProtocolVersions (studyProtocolVersions : List<StudyProtocolVersion>) : void Public	




OPERATIONS	
	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyRationale (studyRationale : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setStudyTitle (studyTitle : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setStudyType (studyType : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setStudyVersion (studyVersion : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 Study (studyId : UUID) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	

StudyArm


Class in package 'model'

A planned pathway assigned to the subject as they progress through the study, usually referred to by a name that reflects one or more treatments, exposures, and/or controls included in the path.


StudyArm
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES	
 studyArmDataOriginDescription : String Private The textual representation of the study arm data origin. [Is static True. Containment is Not Specified.]	
 studyArmDataOriginType : Code Private A characterization or classification of the study arm with respect to where the study arm data originates. [Is static True. Containment is Not Specified.]	
 studyArmDescription : String Private The textual representation of the study arm. [Is static True. Containment is Not Specified.]	

ATTRIBUTES


 studyArmId : String Private Const

[Is static True. Containment is Not Specified.]

 studyArmName : String Private

The literal identifier (i.e., distinctive designation) of the study arm.

[Is static True. Containment is Not Specified.]

 studyArmType : Code Private

The literal identifier (i.e., distinctive designation) of the study arm type.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) StudyArm

Target: Private studyArmType (Class) Code

 Association (direction: Source -> Destination)

Source: Public (Class) StudyArm

Target: Private studyArmDataOriginType (Class)
Code
 Association (direction: Source -> Destination)


Source: Public (Class) StudyCell

Target: Private studyArm (Class) StudyArm


OPERATIONS

 getStudyArmDataOriginDescription () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyArmDataOriginType () : Code Public









[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyArmDescription () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyArmId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS
 getStudyArmName () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyArmType () : Code Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyArmDataOriginDescription (studyArmDataOriginDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyArmDataOriginType (studyArmDataOriginType : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyArmDescription (studyArmDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyArmName (studyArmName : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyArmType (studyArmType : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 StudyArm (studyArmId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

StudyCell


Class in package 'model'

A partitioning of a study arm into individual pieces, which are associated with an epoch and any number of sequential elements within that epoch.

StudyCell


Version 1.0 Phase 1.0 Proposed

Chris Upkes created on 3/9/2023. Last modified 3/9/2023


ATTRIBUTES
 studyArm : StudyArm Private [Is static True. Containment is Not Specified.]
 studyCellId : String Private Const

ATTRIBUTES

[Is static True. Containment is Not Specified.]

 studyElements : List<StudyElement> Private

[Is static True. Containment is Not Specified.]

 studyEpoch : StudyEpoch Private

[Is static True. Containment is Not Specified.]

ASSOCIATIONS
 Association (direction: Source -> Destination)

Source: Public (Class) StudyCell

Target: Private studyElements (Class)
StudyElement

Cardinality: [0..*]

 Association (direction: Source -> Destination)

Source: Public (Class) StudyCell

Target: Private studyArm (Class) StudyArm

 Association (direction: Source -> Destination)

Source: Public (Class) StudyCell


Target: Private studyEpoch (Class) StudyEpoch

 Association (direction: Source -> Destination)


Source: Public (Class) StudyDesign

Target: Private studyCells (Class) StudyCell
Cardinality: [0..*]**OPERATIONS**
 addStudyElement (studyElement : StudyElement) : void Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyArm () : StudyArm Public







[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyCellId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyElements () : List<StudyElement> Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS
 getStudyEpoch () : StudyEpoch Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 removeStudyElement (studyElement : StudyElement) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyArm (studyArm : StudyArm) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyElements (studyElements : List<StudyElement>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyEpoch (studyEpoch : StudyEpoch) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 StudyCell (studyCellId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]












StudyDesign

Class in package 'model'

A plan detailing how a study will be performed in order to represent the phenomenon under examination, to answer the research questions that have been asked, and informing the statistical approach.

StudyDesign
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
 activities : List<Activity> Private [Is static True. Containment is Not Specified.]
 bcCategories : List<BiomedicalConceptCategory> Private [Is static True. Containment is Not Specified.]
 bcSurrogates : List<BiomedicalConceptSurrogate> Private [Is static True. Containment is Not Specified.]
 biomedicalConcepts : List<BiomedicalConcept> Private

ATTRIBUTES	
	[Is static True. Containment is Not Specified.]
 encounters : List<Encounter> Private	[Is static True. Containment is Not Specified.]
 interventionModel : Code Private The general design of the strategy for assigning interventions to participants in a clinical study. (clinicaltrials.gov)	[Is static True. Containment is Not Specified.]
 studyCells : List<StudyCell> Private	[Is static True. Containment is Not Specified.]
 studyDesignBlindingScheme : AliasCode Private	[Is static True. Containment is Not Specified.]
 studyDesignDescription : String Private The textual representation of the study design.	[Is static True. Containment is Not Specified.]
 studyDesignId : String Private Const	[Is static True. Containment is Not Specified.]
 studyDesignName : String Private The literal identifier (i.e., distinctive designation) of the study design.	[Is static True. Containment is Not Specified.]
 studyDesignRationale : String Private	[Is static True. Containment is Not Specified.]
 studyEstimands : List<Estimand> Private	[Is static True. Containment is Not Specified.]
 studyIndications : List<Indication> Private	[Is static True. Containment is Not Specified.]
 studyInvestigationalInterventions : List<InvestigationalIntervention> Private	[Is static True. Containment is Not Specified.]

ATTRIBUTES

 studyObjectives : List<Objective> Private

[Is static True. Containment is Not Specified.]


 studyPopulations : List<StudyDesignPopulation> Private

[Is static True. Containment is Not Specified.]

 studyScheduleTimelines : List<ScheduleTimeline> Private

This field provides a collection of all of the ScheduleTimeline objects associated with the StudyDesign.

[Is static True. Containment is Not Specified.]

 therapeuticAreas : List<Code> Private

A categorization of a disease, disorder, or other condition based on common characteristics and often associated with a medical specialty focusing on research and development of specific therapeutic interventions for the purpose of treatment and prevention.

[Is static True. Containment is Not Specified.]

 trialIntentType : List<Code> Private

The planned purpose of the therapy, device, or agent under study in the clinical trial.

[Is static True. Containment is Not Specified.]

 trialType : List<Code> Private

The nature of the interventional study for which information is being collected.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private biomedicalConcepts (Class)
BiomedicalConcept
Cardinality: [0..*]

 Association (direction: Source -> Destination)


Source: Public (Class) StudyDesign

Target: Private studyPopulations (Class)
StudyDesignPopulation
Cardinality: [0..*]

 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private trialType (Class) Code

ASSOCIATIONS	
Cardinality: [0..*]	
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private studyCells (Class) StudyCell Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private studyDesignBlindingScheme (Class) AliasCode
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private studyEstimands (Class) Estimand Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private interventionModel (Class) Code
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private studyScheduleTimelines (Class) ScheduleTimeline Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private studyObjectives (Class) Objective Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private bcCategories (Class) BiomedicalConceptCategory Cardinality: [0..*]
 Association (direction: Source -> Destination)	
Source: Public (Class) StudyDesign	Target: Private studyIndications (Class) Indication Cardinality: [0..*]
 Association (direction: Source -> Destination)	

ASSOCIATIONS

Source: Public (Class) StudyDesign

Target: Private trialIntentType (Class) Code
Cardinality: [0..*] Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private bcSurrogates (Class)
BiomedicalConceptSurrogate
Cardinality: [0..*] Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private encounters (Class) Encounter
Cardinality: [0..*] Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private therapeuticAreas (Class) Code
Cardinality: [0..*] Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private activities (Class) Activity
Cardinality: [0..*] Association (direction: Source -> Destination)


Source: Public (Class) StudyDesign

Target: Private studyInvestigationalInterventions
(Class) InvestigationalIntervention
Cardinality: [0..*] Association (direction: Source -> Destination)


Source: Public (Class) Study

Target: Private studyDesigns (Class) StudyDesign
Cardinality: [0..*]















OPERATIONS














 addStudyIndication (indication : Indication) : void Public














[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]







 addStudyInvestigationalIntervention (investigationalIntervention : InvestigationalIntervention) : void Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS	
 addStudyObjective (objective : Objective) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getActivities () : List<Activity> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getBcCategories () : List<BiomedicalConceptCategory> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getBcSurrogates () : List<BiomedicalConceptSurrogate> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getBiomedicalConcepts () : List<BiomedicalConcept> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getEncounters () : List<Encounter> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getInterventionModel () : Code Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyCells () : List<StudyCell> Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyDesignBlindingScheme () : AliasCode Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyDesignDescription () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyDesignId () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyDesignName () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyDesignRationale () : String Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyEstimands () : List<Estimand> Public	

OPERATIONS	
	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyIndications () : List<Indication> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getStudyInvestigationalInterventions () : List<InvestigationalIntervention> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getStudyObjectives () : List<Objective> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getStudyPopulations () : List<StudyDesignPopulation> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getStudyScheduleTimelines () : List<ScheduleTimeline> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getTherapeuticAreas () : List<Code> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getTrialIntentType () : List<Code> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getTrialType () : List<Code> Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 removeStudyIndication (indication : Indication) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 removeStudyInvestigationalIntervention (investigationalIntervention : InvestigationalIntervention) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 removeStudyObjective (objective : Objective) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setActivities (activities : List<Activity>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setBcCategories (bcCategories : List<BiomedicalConceptCategory>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	

OPERATIONS
 setBcSurrogates (bcSurrogates : List<BiomedicalConceptSurrogate>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setBiomedicalConcepts (biomedicalConcepts : List<BiomedicalConcept>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setEncounters (encounters : List<Encounter>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setInterventionModel (interventionModel : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyCells (studyCells : List<StudyCell>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyDesignBlindingScheme (studyDesignBlindingScheme : AliasCode) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyDesignDescription (studyDesignDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyDesignName (studyDesignName : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyDesignRationale (studyDesignRationale : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyEstimands (studyEstimands : List<Estimand>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyIndications (studyIndications : List<Indication>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyInvestigationalInterventions (studyInvestigationalInterventions : List<InvestigationalIntervention>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyObjectives (studyObjectives : List<Objective>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS
 setStudyPopulations (studyStudyDesignPopulations : List<StudyDesignPopulation>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyScheduleTimelines (studyScheduleTimelines : List<ScheduleTimeline>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setTherapeuticAreas (therapeuticAreas : List<Code>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setTrialIntentType (trialIntentType : List<Code>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setTrialType (trialType : List<Code>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 StudyDesign (studyDesignId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

StudyDesignPopulation


Class in package 'model'

The population within the general population to which the study results can be generalized.

StudyDesignPopulation
 Version 1.0 Phase 1.0 Proposed
 cupke created on 3/9/2023. Last modified 3/9/2023


ATTRIBUTES
 plannedMaximumAgeOfParticipants : String Private [Is static True. Containment is Not Specified.]
 plannedMinimumAgeOfParticipants : String Private [Is static True. Containment is Not Specified.]
 plannedNumberOfParticipants : int Private [Is static True. Containment is Not Specified.]
 plannedSexOfParticipants : List<Code> Private [Is static True. Containment is Not Specified.]

ATTRIBUTES

 populationDescription : String Private

The textual representation of the study population.

[Is static True. Containment is Not Specified.]

 studyDesignPopulationId : String Private Const

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesignPopulation

Target: Private plannedSexOfParticipants (Class)
Code

Cardinality: [0..*]

 Association (direction: Source -> Destination)

Source: Public (Class) StudyDesign

Target: Private studyPopulations (Class)
StudyDesignPopulation

Cardinality: [0..*]


OPERATIONS

 getPlannedMaximumAgeOfParticipants () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getPlannedMinimumAgeOfParticipants () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getPlannedNumberOfParticipants () : int Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getPlannedSexOfParticipants () : List<Code> Public







[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getPopulationDescription () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyDesignPopulationId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS
 <code>setPlannedMaximumAgeOfParticipants (plannedMaximumAgeOfParticipants : String) : void Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setPlannedMinimumAgeOfParticipants (plannedMinimumAgeOfParticipants : String) : void Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setPlannedNumberOfParticipants (plannedNumberOfParticipants : int) : void Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setPlannedSexOfParticipants (plannedSexOfParticipants : List<Code>) : void Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>setPopulationDescription (populationDescription : String) : void Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>StudyDesignPopulation (uuid : String) : Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

StudyElement

Class in package 'model'

A basic building block for time within a clinical study comprising the following characteristics: a description of what happens to the subject during the element; a definition of the start of the element; a rule for ending the element.


StudyElement
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
 <code>studyElementDescription : String Private</code> The textual representation of the study design element. [Is static True. Containment is Not Specified.]
 <code>studyElementId : String Private Const</code> element only attributes - these purely describe an element [Is static True. Containment is Not Specified.]
 <code>studyElementName : String Private</code>


ATTRIBUTES

The literal identifier (i.e., distinctive designation) of the study design element.

[Is static True. Containment is Not Specified.]

 transitionEndRule : TransitionRule Private

[Is static True. Containment is Not Specified.]

 transitionStartRule : TransitionRule Private

all elements point to transition rules

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) StudyElement

Target: Private transitionStartRule (Class)
TransitionRule

 Association (direction: Source -> Destination)

Source: Public (Class) StudyElement


Target: Private transitionEndRule (Class)
TransitionRule

 Association (direction: Source -> Destination)

Source: Public (Class) StudyCell

Target: Private studyElements (Class)
StudyElement
Cardinality: [0..*]

OPERATIONS

 getStudyElementDescription () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyElementId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyElementName () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getTransitionEndRule () : TransitionRule Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]




OPERATIONS
 getTransitionStartRule () : TransitionRule Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyElementDescription (studyElementDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyElementName (studyElementName : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setTransitionEndRule (transitionEndRule : TransitionRule) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setTransitionStartRule (transitionStartRule : TransitionRule) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 StudyElement (studyElementId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

StudyEpoch


Class in package 'model'

A named time period defined in the protocol, wherein a study activity is specified and unchanging throughout the interval, to support a study-specific purpose.

StudyEpoch
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023


ATTRIBUTES
 encounters : List<Encounter> Private [Is static True. Containment is Not Specified.]
 nextStudyEpochId : String Private A system identifier assigned to the epoch that occurs immediately after the current epoch. [Is static True. Containment is Not Specified.]
 previousStudyEpochId : String Private A system identifier assigned to the epoch that occurs immediately prior to the current epoch. [Is static True. Containment is Not Specified.]

ATTRIBUTES


 studyEpochDescription : String Private

The textual representation of the study epoch.

[Is static True. Containment is Not Specified.]

 studyEpochId : String Private Const

[Is static True. Containment is Not Specified.]

 studyEpochName : String Private

The literal identifier (i.e., distinctive designation) of the study epoch, i.e., the named time period defined in the protocol, wherein a study activity is specified and unchanging throughout the interval, to support a study-specific purpose.

[Is static True. Containment is Not Specified.]

 studyEpochType : Code Private

A characterization or classification of the study epoch, i.e., the named time period defined in the protocol, wherein a study activity is specified and unchanging throughout the interval, to support a study-specific purpose.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) StudyEpoch

Target: Private studyEpochType (Class) Code

 Association (direction: Source -> Destination)

Source: Public (Class) StudyEpoch


Target: Private encounters (Class) Encounter
Cardinality: [0..*]

 Association (direction: Source -> Destination)

Source: Public (Class) StudyCell

Target: Private studyEpoch (Class) StudyEpoch













OPERATIONS

 getEncounters () : List<Encounter> Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getNextStudyEpochId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS
 getPreviousStudyEpochId () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyEpochDescription () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyEpochId () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyEpochName () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getStudyEpochType () : Code Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setEncounters (encounters : List<Encounter>) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setNextStudyEpochId (nextStudyEpochId : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setPreviousStudyEpochId (previousStudyEpochId : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyEpochDescription (studyEpochDescription : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyEpochName (studyEpochName : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyEpochType (studyEpochType : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 StudyEpoch (studyEpochId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


Class in package 'model'

A sequence of characters used to identify, name, or characterize the study.

StudyIdentifier


Version 1.0 Phase 1.0 Proposed

Chris Upkes created on 3/9/2023. Last modified 3/9/2023


ATTRIBUTES
 studyIdentifier : String Private

A sequence of characters used to identify, name, or characterize the study.

[Is static True. Containment is Not Specified.]

 studyIdentifierId : String Private Const

[Is static True. Containment is Not Specified.]

 studyIdentifierScope : Organization Private


[Is static True. Containment is Not Specified.]

ASSOCIATIONS
 Association (direction: Source -> Destination)


Source: Public (Class) StudyIdentifier

Target: Private studyIdentifierScope (Class)
Organization
 Association (direction: Source -> Destination)


Source: Public (Class) Study

Target: Private studyIdentifiers (Class)
StudyIdentifier
Cardinality: [0..*]**OPERATIONS**
 getStudyIdentifier () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]



 getStudyIdentifierId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getStudyIdentifierScope () : Organization Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setStudyIdentifier (studyIdentifier : String) : void Public






OPERATIONS	
	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setStudyIdentifierScope (studyIdentifierScope : Organization) : void Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 StudyIdentifier (studyIdentifierId : String) : Public	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

StudyProtocolVersion

Class in package 'model'


A plan at a particular point in time for a formal investigation to assess the utility, impact, pharmacological, physiological, and/or psychological effects of a particular treatment, procedure, drug, device, biologic, food product, cosmetic, care plan, or subject characteristic. (BRIDG)

StudyProtocolVersion
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES	
 briefTitle : String Private	
The short descriptive name for the protocol.	[Is static True. Containment is Not Specified.]
 officialTitle : String Private	
The formal descriptive name for the protocol.	[Is static True. Containment is Not Specified.]
 protocolAmendment : String Private	
A written description of a change(s) to, or formal clarification of, a protocol. (ICH E6)	[Is static True. Containment is Not Specified.]
 protocolEffectiveDate : Date Private	
The date and time specifying when the protocol amendment takes effect or becomes operative.	[Is static True. Containment is Not Specified.]
 protocolStatus : Code Private	
A condition of the protocol at a point in time with respect to its state of readiness for implementation.	


ATTRIBUTES

[Is static True. Containment is Not Specified.]

 protocolVersion : String Private


A plan at a particular point in time for a formal investigation to assess the utility, impact, pharmacological, physiological, and/or psychological effects of a particular treatment, procedure, drug, device, biologic, food product, cosmetic, care plan, or subject characteristic. (BRIDG)

[Is static True. Containment is Not Specified.]

 publicTitle : String Private


The descriptive name of the protocol that is intended for the lay public, written in easily understood language.

[Is static True. Containment is Not Specified.]

 scientificTitle : String Private

A more extensive descriptive name of the protocol that is intended for medical professionals, written using medical and scientific language.

[Is static True. Containment is Not Specified.]

 studyProtocolVersionId : String Private Const

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) StudyProtocolVersion


Target: Private protocolStatus (Class) Code

 Association (direction: Source -> Destination)


Source: Public (Class) Study

Target: Private studyProtocolVersions (Class)
StudyProtocolVersion
Cardinality: [0..*]


OPERATIONS














 getBriefTitle () : String Public



[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getOfficialTitle () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getProtocolAmendment () : String Public

OPERATIONS	
	[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getProtocolEffectiveDate () : Date Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getProtocolStatus () : Code Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getProtocolVersion () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getPublicTitle () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getScientificTitle () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 getStudyProtocolVersionId () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setBriefTitle (briefTitle : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setOfficialTitle (officialTitle : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setProtocolAmendment (protocolAmendment : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setProtocolEffectiveDate (protocolEffectiveDate : Date) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setProtocolStatus (protocolStatus : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setProtocolVersion (protocolVersion : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	
 setPublicTitle (publicTitle : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]	






OPERATIONS
 <code>setScientificTitle (scientificTitle : String) : void Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 <code>StudyProtocolVersion (studyProtocolVersionId : String) : Public</code> [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

Timing

Class in package 'model'

The Timing class is used to relate ScheduledInstance objects. In graph, this information would likely sit on relationship that exists between ScheduledInstances. ScheduledInstances have no information regarding their relationships with other ScheduledInstances in a ScheduleTimeline. This is where that information is captured. In a typical GANTT chart, these are the arrows you see between the task boxes that tell us how the work should be sequenced.


Timing
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES
 <code>relativeFromScheduledInstanceId : String Private</code> This field defines the ScheduledInstance object that the timing defines as the anchor. When we define a timing relationship between two ScheduledInstances, one instance is the from and the other is the to in what is essentially a "timing between" constraint. [Is static True. Containment is Not Specified.]
 <code>relativeToScheduledInstanceId : String Private</code> This field defines the ScheduledInstance object that has the timing constraint associated with the anchor instance. This is the instance that has the "timingRelativeToFrom" constraint associated with the fromScheduledInstance object. [Is static True. Containment is Not Specified.]
 <code>timingId : String Private Const</code> [Is static True. Containment is Not Specified.]
 <code>timingRelativeToFrom : Code Private</code> Code values that describe the timing relative to the associated timepoint, I believe. Somewhat unsure here. Values are typical of gant task relationship dependencies. They are: StartToStart, StartToEnd, EndToEnd and EndToStart. [Is static True. Containment is Not Specified.]
 <code>timingType : Code Private</code>

ATTRIBUTES


Code values that describe the type of timing. Valid values include Before, After and Absolute.

[Is static True. Containment is Not Specified.]

 timingValue : String Private

According to the presentation, the value will be provide further context based on the type of the timing. For example, if the timing type is absolute then maybe something like "first dose, day 0" and if the type is Before it could be "1 day before x".

[Is static True. Containment is Not Specified.]

 timingWindow : String Private

Defines window of time associated with the timing. We could either define slack or lead time as two variables to ensure consistency however, this can be inferred along with the timingRelativeToFrom value.

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) Timing

Target: Private timingType (Class) Code

 Association (direction: Source -> Destination)

Source: Public (Class) Timing

Target: Private timingRelativeToFrom (Class) Code


 Association (direction: Source -> Destination)

Source: Public (Class) ScheduledInstance

Target: Private scheduledInstanceTimings (Class)
Timing

Cardinality: [0..*]


OPERATIONS

 getRelativeFromScheduledInstanceId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getRelativeToScheduledInstanceId () : String Public











[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getTimingId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getTimingRelativeToFrom () : Code Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

OPERATIONS
 getTimingType () : Code Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getTimingValue () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 getTimingWindow () : String Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setRelativeFromScheduledInstanceId (relativeFromScheduledInstanceId : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setRelativeToScheduledInstanceId (relativeToScheduledInstanceId : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setTimingRelativeToFrom (timingRelativeToFrom : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setTimingType (timingType : Code) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setTimingValue (timingValue : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 setTimingWindow (timingWindow : String) : void Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]
 Timing (timingId : String) : Public [Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]


TransitionRule

Class in package 'model'

A guide that governs the allocation of subjects to operational options at a discrete decision point or branch (e.g., assignment to a particular arm, discontinuation) within a clinical trial plan.


TransitionRule
Version 1.0 Phase 1.0 Proposed
Chris Upkes created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES

 transitionRuleDescription : String Private

The textual representation of the transition rule.

[Is static True. Containment is Not Specified.]

 transitionRuleId : String Private Const

[Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) Encounter

Target: Private transitionEndRule (Class)
TransitionRule

 Association (direction: Source -> Destination)

Source: Public (Class) StudyElement

Target: Private transitionStartRule (Class)
TransitionRule

 Association (direction: Source -> Destination)

Source: Public (Class) Encounter

Target: Private transitionStartRule (Class)
TransitionRule

 Association (direction: Source -> Destination)

Source: Public (Class) StudyElement

Target: Private transitionEndRule (Class)
TransitionRule


OPERATIONS

 getTransitionRuleDescription () : String Public


[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 getTransitionRuleId () : String Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 setTransitionRuleDescription (transitionRuleDescription : String) : void Public

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

 TransitionRule (ruleId : String) : Public

OPERATIONS

[Is static False. Is abstract False. Is return array False. Is query False. Is synchronized False.]

ScheduledInstanceType

Enumeration in package 'model'

ScheduledInstanceType

Version 1.0 Phase 1.0 Proposed

cupke created on 3/9/2023. Last modified 3/9/2023

ATTRIBUTES

 **ACTIVITY** : Public

[Stereotype is «enum». Is static True. Containment is Not Specified.]

 **DECISION** : Public

[Stereotype is «enum». Is static True. Containment is Not Specified.]

ASSOCIATIONS

 Association (direction: Source -> Destination)

Source: Public (Class) ScheduledInstance

Target: Private scheduledInstanceType
(Enumeration) ScheduledInstanceType