

---

# CS 224N: Assignment 1

RYAN MCMAHON

SUNDAY 29<sup>TH</sup> JANUARY, 2017

---

## Contents

<b>1</b>	<b>Problem 1: Softmax (10 pts)</b>	<b>2</b>
1.1	(a) Softmax Invariance to Constant (5 pts) . . . . .	2
1.2	(b) Softmax Coding (5 pts) . . . . .	2
<b>2</b>	<b>Problem 2: Neural Network Basics (30 pts)</b>	<b>3</b>
2.1	(a) Sigmoid Gradient (3 pts) . . . . .	3
2.2	(b) Softmax Gradient w/ Cross Entropy Loss (3 pts) . . . . .	4
2.3	(c) One Hidden Layer Gradient (6 pts) . . . . .	6
2.4	(d) No. Parameters (2 pts) . . . . .	6
2.5	(e) Sigmoid Activation Code (4 pts) . . . . .	7
2.6	(f) Gradient Check Code (4 pts) . . . . .	7

## Problem 1: Softmax (10 pts)

### 1.1 (a) Softmax Invariance to Constant (5 pts)

Prove that softmax is invariant to constant offsets in the input, that is, for any input vector  $x$  and any constant  $c$ ,  $\text{softmax}(x) = \text{softmax}(x + c)$ , where  $x + c$  means adding the constant  $c$  to every dimension of  $x$ . Remember that

$$\text{softmax}(x)_i = \frac{e^{x_i}}{\sum_j e^{x_j}} \quad (1.1)$$

**Answer:**

We can show that  $\text{softmax}(x) = \text{softmax}(x + c)$  by factoring out  $c$  and canceling:

$$\begin{aligned} \text{softmax}(x + c)_i &= \frac{e^{x_i + c}}{\sum_j e^{x_j + c}} = \frac{e^{x_i} \times e^c}{e^c \times \sum_j e^{x_j}} \\ &= \frac{e^{x_i} \times \cancel{e^c}}{\cancel{e^c} \times \sum_j e^{x_j}} = \text{softmax}(x)_i \end{aligned}$$

### 1.2 (b) Softmax Coding (5 pts)

Given an input matrix of  $N$  rows and  $D$  columns, compute the softmax prediction for each row using the optimization in part (a). Write your implementation in `q1_softmax.py`. You may test by executing `python q1_softmax.py`.

*Note: The provided tests are not exhaustive. Later parts of the assignment will reference this code so it is important to have a correct implementation. Your implementation should also be efficient and vectorized whenever possible (i.e., use numpy matrix operations rather than for loops). A non-vectorized implementation will not receive full credit!*

**Answer:**

See code: `~/code/q1_softmax.py`.

## Problem 2: Neural Network Basics (30 pts)

### 2.1 (a) Sigmoid Gradient (3 pts)

Derive the gradients of the sigmoid function and show that it can be rewritten as a function of the function value (i.e., in some expression where only  $\sigma(x)$ , but not  $x$ , is present). Assume that the input  $x$  is a scalar for this question. Recall, the sigmoid function is

$$\sigma(x) = \frac{1}{1 + e^{-x}} \quad (2.1)$$

**Answer:**

$$\begin{aligned} \sigma(x) &= \frac{1}{1 + e^{-x}} \\ &= \frac{e^x}{1 + e^x} \\ \frac{\partial}{\partial x} \sigma(x) &= \frac{e^x \times (1 + e^x) - (e^x \times e^x)}{(1 + e^x)^2} \\ &= \frac{e^x + \cancel{(e^x \times e^x)} - \cancel{(e^x \times e^x)}}{(1 + e^x)^2} \\ &= \frac{e^x}{(1 + e^x)^2} = \sigma(x) \times (1 - \sigma(x)) \end{aligned}$$

Because  $1 - \sigma(x) = \sigma(-x)$  we can show that:

$$\begin{aligned} \frac{\partial}{\partial x} \sigma(x) &= \frac{e^x}{(1 + e^x)^2} \\ &= \sigma(x) \times \sigma(-x) \\ &= \frac{e^x}{1 + e^x} \times \frac{1}{1 + e^{+x}} \\ &= \frac{e^x}{(1 + e^x)^2} \end{aligned}$$

## 2.2 (b) Softmax Gradient w/ Cross Entropy Loss (3 pts)

Derive the gradient with regard to the inputs of a softmax function when cross entropy loss is used for evaluation, i.e., find the gradients with respect to the softmax input vector  $\theta$ , when the prediction is made by  $\hat{y} = \text{softmax}(\theta)$ . Remember the cross entropy function is

$$CE(y, \hat{y}) = - \sum_i y_i \times \log(\hat{y}_i) \quad (2.2)$$

where  $y$  is the one-hot label vector; and  $\hat{y}$  is the predicted probability vector for all classes. (Hint: you might want to consider the fact many elements of  $y$  are zeros, and assume that only the  $k$ -th dimension of  $y$  is one.)

**Answer:**

Let  $S$  represent the softmax function:

$$\begin{aligned} f_i &= e^{\theta_i} \\ g_i &= \sum_{k=1}^K e^{\theta_k} \\ S_i &= \frac{f_i}{g_i} \\ \frac{\partial S_i}{\partial \theta_j} &= \frac{f'_i g_i - g'_i f_i}{g_i^2} \end{aligned}$$

So if  $i = j$ :

$$\begin{aligned} f'_i &= f_i; \quad g'_i = e^{\theta_j} \\ \frac{\partial S_i}{\partial \theta_j} &= \frac{e^{\theta_i} \sum_k e^{\theta_k} - e^{\theta_j} e^{\theta_i}}{(\sum_k e^{\theta_k})^2} \\ &= \frac{e^{\theta_i}}{\sum_k e^{\theta_k}} \times \frac{\sum_k e^{\theta_k} - e^{\theta_j}}{\sum_k e^{\theta_k}} \\ &= S_i \times (1 - S_i) \end{aligned}$$

And if  $i \neq j$ :

$$\begin{aligned} \frac{\partial S_i}{\partial \theta_j} &= \frac{0 - e^{\theta_j} e^{\theta_i}}{(\sum_k e^{\theta_k})^2} \\ &= - \frac{e^{\theta_j}}{\sum_k e^{\theta_k}} \times \frac{e^{\theta_i}}{\sum_k e^{\theta_k}} \\ &= -S_j \times S_i \end{aligned}$$

We can now use these when operating on our loss function (let  $L$  represent the cross entropy function):

$$\begin{aligned}
\frac{\partial L}{\partial \theta_i} &= - \sum_k y_k \frac{\partial \log S_k}{\partial \theta_i} \\
&= - \sum_k y_k \frac{1}{S_k} \frac{\partial S_k}{\partial \theta_i} \\
&= -y_i(1 - S_i) - \sum_{k \neq i} y_k \frac{1}{S_k} (-S_k \times S_i) \\
&= -y_i(1 - S_i) + \sum_{k \neq i} y_k S_i \\
&= -y_i + y_i S_i + \sum_{k \neq i} y_k S_i \\
&= S_i \left( \sum_k y_k \right) - y_i
\end{aligned}$$

And because we know that  $\sum_k y_k = 1$ :

$$\frac{\partial L}{\partial \theta_i} = S_i - y_i$$

### 2.3 (c) One Hidden Layer Gradient (6 pts)

Derive the gradients with respect to the inputs  $\mathbf{x}$  to a one-hidden-layer neural network (that is, find  $\frac{\partial J}{\partial \mathbf{x}}$  where  $J = CE(\mathbf{y}, \hat{\mathbf{y}})$  is the cost function for the neural network). The neural network employs sigmoid activation function for the hidden layer, and softmax for the output layer. Assume the one-hot label vector is  $\mathbf{y}$ , and cross entropy cost is used. (Feel free to use  $\sigma'(x)$  as the shorthand for sigmoid gradient, and feel free to define any variables whenever you see fit.)

Recall that forward propoagation is as follows

$$\mathbf{h} = \text{sigmoid}(\mathbf{x}\mathbf{W}_1 + \mathbf{b}_1)$$

$$\hat{\mathbf{y}} = \text{softmax}(\mathbf{h}\mathbf{W}_2 + \mathbf{b}_2)$$

**Answer:**

Let  $f_2 = \mathbf{x}\mathbf{W}_1 + \mathbf{b}_1$  and  $f_3 = \mathbf{h}\mathbf{W}_2 + \mathbf{b}_2$ ;

$$\begin{aligned} \frac{\partial J}{\partial f_3} &= \delta_3 = \hat{\mathbf{y}} - \mathbf{y} \\ \frac{\partial J}{\partial f_2} &= \delta_2 = \mathbf{W}_2 \delta_3 \circ \sigma'(f_2) \\ \frac{\partial J}{\partial \mathbf{x}} &= \frac{\partial J}{\partial f_2} \frac{\partial f_2}{\partial \mathbf{x}} \\ &= \delta_2 \frac{\partial f_2}{\partial \mathbf{x}} \\ &= \delta_2 \frac{\partial}{\partial \mathbf{x}} \mathbf{x}\mathbf{W}_1 + \mathbf{b}_1 \\ &= \delta_2 \mathbf{W}_1 \end{aligned}$$

### 2.4 (d) No. Parameters (2 pts)

How many parameters are there in this neural network [from (c) above], assuming the input is  $D_x$ -dimensional, the output is  $D_y$ -dimensional, and there are  $H$  hidden units?

**Answer:**

$$\begin{aligned} n_{W_1} &= D_x \times H \\ n_{b_1} &= H \\ n_{W_2} &= H \times D_y \\ n_{b_2} &= D_y \\ N &= (D_x \times H) + H + (H \times D_y) + D_y \end{aligned}$$

## 2.5 (e) Sigmoid Activation Code (4 pts)

*Fill in the implementation for the sigmoid activation function and its gradient in `q2_sigmoid.py`. Test your implementation using `python q2_sigmoid.py`. Again, thoroughly test your code as the provided tests may not be exhaustive.*

**Answer:**

See code: `~/code/q2_sigmoid.py`.

## 2.6 (f) Gradient Check Code (4 pts)

*To make debugging easier, we will now implement a gradient checker. Fill in the implementation for `gradcheck_naive` in `q2_gradcheck.py`. Test your code using `python q2_gradcheck.py`.*

**Answer:**

See code: `~/code/q2_gradcheck.py`.