



Data analysis on PM_{2.5} exposure factors with environmental and survey data

Presenter: Dr. Ming-Chien Mark Tsou

Research Center for Environmental Changes

Academia Sinica



Outline

Part 1:
PM data
processing

Part 2:
Time-
activity
diary (TAD)
data
processing

Part 3:
Multiple
linear
regression
for exposure
factors

Objectives

- To evaluate important factors of personal PM_{2.5} exposure during **at-home period**
 - Outdoor PM_{2.5} concentration
 - Household exposure sources
 - Ventilations

Part 1:

PM data processing

PM data processing

- From Line 1 to 63
- The same procedures as the PM data processing for GAMM
- To export the PM data obtained from AS-LUNG-O, AS-LUNG-I and AS-LUNG-P for each subject

2020/10/8

HiASAP-2020 AI

	A	B	C	D	E	F	G	H	I	J	K
1	Season	AL_Type	datetime	date	time	sht_t	sht_h	co2	cPM1	cPM2.5	
2	0	2	2018/10/8 00:00	2018/10/8	00:00:00	26.7	71.4	420	14.307	15.182	
3	0	2	2018/10/8 00:00	2018/10/8	00:00:15	26.7	71.4	419	13.708	14.278	
4	0	2	2018/10/8 00:00	2018/10/8	00:00:30	26.7	71.3	417	13.708	14.278	
5	0	2	2018/10/8 00:00	2018/10/8	00:00:45	26.8	71.3	417	13.708	13.826	
6	0	2	2018/10/8 00:01	2018/10/8	00:01:00	26.8	71.2	415	13.708	13.826	
7	0	2	2018/10/8 00:01	2018/10/8	00:01:15	26.8	71.2	414	13.708	13.826	
8	0	2	2018/10/8 00:01	2018/10/8	00:01:30	26.8	71.2	414	13.708	13.826	
9	0	2	2018/10/8 00:01	2018/10/8	00:01:45	26.8	71.2	414	13.109	13.826	
10	0	2	2018/10/8 00:02	2018/10/8	00:02:00	26.8	71.1	414	13.109	13.826	
11	0	2	2018/10/8 00:02	2018/10/8	00:02:15	26.8	71	414	13.109	13.826	

1. To get the data time directly from AS- LUNG data for creating the 5-min intervals

```

65 # To calculate 5-min average PM data for exposure factor (based on ASLUNG time)
66 library('lubridate')
67 date_1<-c(ymd(as.character(ASLUNGt$date)))
68 time<-substr(ASLUNGt$time,1,5)
69 date_2<-paste(date_1,time)
70 mm<-c(as.numeric(substr(date_2,16,16)))
71 mm5<-c()
72 for (l in 1:length(mm)) {
73   if(mm[l]<5){
74     mm5[l]<-"0~4"
75   }else{
76     mm5[l]<-"5~9"
77   }
78 }
79 date_3 <- paste0(substr(date_2,1,15),mm5)
80 date_4<-as.data.frame(table(date_3))

```

	date_3	Freq
1	2018-10-08 00:00~4	20
2	2018-10-08 00:05~9	20
3	2018-10-08 00:10~4	20
4	2018-10-08 00:15~9	20
5	2018-10-08 00:20~4	20
6	2018-10-08 00:25~9	20
7	2018-10-08 00:30~4	20
8	2018-10-08 00:35~9	20
9	2018-10-08 00:40~4	20
10	2018-10-08 00:45~9	20
11	2018-10-08 00:50~4	20
12	2018-10-08 00:55~9	20

There are 20
data between
00:00 to 04:59

2. To calculate the 5-min average PM data

```
81 ALFinal<-data.frame()
82 for(j in 1:dim(date_4)[1]){
83     ALFinal[j,1]<-date_4[j,1]
84     ALFinal[j,2]<-substr(bb[k],10,14)
85     ALFinal[j,3]<-mean(as.numeric(ASLUNGt[which(date_3==date_4[j,1]),1]),na.rm = TRUE) # 0=ho
86     ALFinal[j,4]<-mean(as.numeric(ASLUNGt[which(date_3==date_4[j,1]),2]),na.rm = TRUE) # 1=ou
87     ALFinal[j,5]<-mean(as.numeric(ASLUNGt[which(date_3==date_4[j,1]),6]),na.rm = TRUE)
88     ALFinal[j,6]<-mean(as.numeric(ASLUNGt[which(date_3==date_4[j,1]),7]),na.rm = TRUE)
89     ALFinal[j,7]<-mean(as.numeric(ASLUNGt[which(date_3==date_4[j,1]),9]),na.rm = TRUE)
90     ALFinal[j,8]<-mean(as.numeric(ASLUNGt[which(date_3==date_4[j,1]),10]),na.rm = TRUE)
91     ALFinal[j,9]<-mean(as.numeric(ASLUNGt[which(date_3==date_4[j,1]),8]),na.rm = TRUE)
92     ALFinal[j,10]<-date_4[j,2]
93 }
94 colnames(ALFinal)<-c("Date","S_no","Season","AL_Type","TEM","HUM","PM1","PM2.5","CO2","Freq")
```

To create a variable for the number of data in this 5-min interval

3. To exclude the time with insufficient data (half of default number of data)

```

95 # To exclude the 5-min intervals which contained less than half of expected number of data
96 if(substr(aa1[p],9,9)=="0"){
97     ALFinal2 <- ALFinal[which(ALFinal$Freq>=3),]
98 }else{
99     ALFinal2 <- ALFinal[which(ALFinal$Freq>=10),]
100 }

```







	The default number of data in each 5-min interval
AS-LUNG-O	1x5=5
AS-LUNG-I	4x5=20
AS-LUNG-P	4x5=20

```

101
102 ALFinal2 <- data.frame(subset(ALFinal2,select=c(Date,S_no,Season,AL_Type,TEM,HUM,PM1,PM2.5,CO2)))
103 outputname<-paste0("PM_",substr(bb[k],10,14),"_",Season[i]+1,"_",substr(aa1[p],9,9),"_5 min_ASLUNG_Time.csv")
104 write.csv(ALFinal2,outputname,row.names=FALSE,na="")
105 }

```

4. To export the dataset for 5-min average data for each subject

 PM_LA010_1_I_5 min_ASLUNG_Time
 PM_LA014_1_P_5 min_ASLUNG_Time
 PM_LA001_1_O_5 min_ASLUNG_Time
 PM_LA021_1_O_5 min_ASLUNG_Time
 PM_LA010_1_O_5 min_ASLUNG_Time
 PM_LA020_1_O_5 min_ASLUNG_Time

5-min average PM data combination for all subjects

- From Line 108 to 159
- The same procedures as the PM data processing for GAMM from Line 133 to 184
- To export the final dataset for PM data for exposure factors evaluation

1	Date	Year	Month	Day	Hour	Minute	Minute_3	S_no	Season	AL_Type	TEM	HUM	PM1	PM2.5	CO2
2	2018/10/8 13:11	2018	10	8	13	11	1	LA001	0	3	26.305	78.895	2.95625	3.3784	449.95
3	2018/10/8 13:16	2018	10	8	13	16	1	LA001	0	3	26.71	78.17	2.9818	3.4876	448.05
4	2018/10/8 13:21	2018	10	8	13	21	1	LA001	0	3	27.01	77.315	3.1351	3.6332	440.65
5	2018/10/8 13:26	2018	10	8	13	26	1	LA001	0	3	27.165	76.05	3.1862	3.6332	428.65
6	2018/10/8 13:31	2018	10	8	13	31	2	LA001	0	3	27.38	75.31	3.31395	3.797	426.5
7	2018/10/8 13:36	2018	10	8	13	36	2	LA001	0	3	27.48880	75.78880	3.528220	3.870	507.2770

Part 2:

Time-activity diary (TAD) data processing

TAD raw data

Locations

Ventilations

Activities

Sources

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
1	S_no	Year	Month	Day	Date	WD	Hour	Minute_30	Place1	Place2	Ventilation	Ventilation	Activity1	Activity2	AP1	AP2	AP3	Sensor	
2	LA001	2018	10	8	1	1	13	1	1	0	2	0	10	0	0	0	0	0	
3	LA001	2018	10	8	1	1	13	2	1	0	2	0	10	0	0	0	0	1	
4	LA001	2018	10	8	1	1	14	1	3	0	3	0	3	0	0	0	0	1	
5	LA001	2018	10	8	1	1	14	2	3	0	3	0	3	0	0	0	0	1	
6	LA001	2018	10	8	1	1	15	1	3	0	3	0	3	0	0	0	0	1	
7	LA001	2018	10	8	1	1	15	2	3	0	3	0	3	0	0	0	0	1	
8	LA001	2018	10	8	1	1	16	1	3	0	3	0	3	0	0	0	0	1	
9	LA001	2018	10	8	1	1	16	2	3	0	3	0	3	0	0	0	0	1	
10	LA001	2018	10	8	1	1	17	1	3	0	3	0	3	0	0	0	0	1	
11	LA001	2018	10	8	1	1	17	2	3	0	3	0	3	0	0	0	0	1	
12	LA001	2018	10	8	1	1	18	1	3	0	3	0	3	0	0	0	0	1	
13	LA001	2018	10	8	1	1	18	2	3	0	3	0	3	0	0	0	0	1	
14	LA001	2018	10	8	1	1	19	1	3	0	3	0	3	0	0	0	0	1	
15	LA001	2018	10	8	1	1	19	2	16	0	9	0	2	0	0	0	0	1	
16	LA001	2018	10	8	1	1	20	1	1	0	3	0	8	4	2	0	0	1	
17	LA001	2018	10	8	1	1	20	2	1	0	3	0	10	0	0	0	0	1	
18	LA001	2018	10	8	1	1	21	1	1	0	3	0	9	0	0	0	0	1	

TAD data processing

```
39 ##TAD data processing
40 TAD <- read.csv(paste0(way, "/TAD_Raw.csv"))
```

1. To read the TAD data

2. To create dummy variables by categorizing different locations, ventilations, activities or sources into different groups

```

42 Loc_Home <- c()
43 Loc_In <- c()
44 Loc_Out <- c()
45 Loc_Trans_In <- c()
46 Loc_Trans_Out <- c()
47 Loc_Trans <- c()
48 Loc_In_All <- c()
49 Loc_Out_All <- c()
50 Vent_closed <- c()
51 Vent_opened <- c()
52 Vent_AC <- c()
53 Act_sleep <- c()
54 Act_Commute <- c()
55 Act_work <- c()
56 Act_Cook <- c()
57 Act_worship <- c()
58 Act_Shopping <- c()
59 Act_Exercise <- c()
60 Act_Eat <- c()
61 Act_Bath <- c()
62 Act_Sedentary <- c()
63 Act_Housework <- c()
64 Act_Other <- c()
65 S_Exhaust <- c()
66 S_Cooking <- c()
67 S_ETS <- c()
68 S_Dust <- c()
69 S_Incense <- c()
70 S_MosquitoCoil <- c()
71 S_Aromatic <- c()
72 S_Josspaper <- c()
73 S_OpenedBurning <- c()
74 S_Factory <- c()
75 S_Garbage <- c()
76 S_other <- c()
77 S_Incense_JPaper <- c()

80 for(i in 1:dim(TAD)[1]){
81   ifelse(TAD$Place1[i]==1 | TAD$Place2[i]==1, Loc_Home[i]<-1, Loc_Home[i]<-0)
82   ifelse(TAD$Place1[i]==2 | TAD$Place1[i]==3 | TAD$Place1[i]==4 | TAD$Place1[i]==5 | TAD$Place1[i]==6 | TAD$Place1[i]==7 | TAD$Pla
83   ifelse(TAD$Place1[i]==17 | TAD$Place1[i]==18 | TAD$Place1[i]==19 | TAD$Place1[i]==20 | TAD$Place1[i]==21 | TAD$Place1[i]==22 | TAD$Place1[i]==23 | .
84   ifelse(TAD$Place1[i]==11 | TAD$Place1[i]==12 | TAD$Place1[i]==13 | TAD$Place1[i]==14 | TAD$Place2[i]==11 | TAD$Place2[i]==12 | TAD$Place2[i]==13 | .
85   ifelse(TAD$Place1[i]==9 | TAD$Place1[i]==10 | TAD$Place1[i]==15 | TAD$Place1[i]==62 | TAD$Place2[i]==16 | TAD$Place2[i]==9 | TAI
86   ifelse(TAD$Place1[i]==11 | TAD$Place1[i]==12 | TAD$Place1[i]==13 | TAD$Place1[i]==14 | TAD$Place1[i]==9 | TAD$Place1[i]==10 | TAD$Place1[i]==15 | T
87   ifelse(TAD$Place1[i]==1 | TAD$Place1[i]==2 | TAD$Place1[i]==3 | TAD$Place1[i]==4 | TAD$Place1[i]==5 | TAD$Place1[i]==6 | TAD$Place1[i]==7 | TAD$Pla
88   ifelse(TAD$Place1[i]==16 | TAD$Place1[i]==17 | TAD$Place1[i]==18 | TAD$Place1[i]==19 | TAD$Place1[i]==20 | TAD$Place1[i]==21 | TAD$Place1[i]==22 | .
89   ifelse(TAD$Ventilation1[i]==1 | TAD$Ventilation2[i]==1, Vent_closed[i]<-1, Vent_closed[i]<-0)
90   ifelse(TAD$Ventilation1[i]==2 | TAD$Ventilation1[i]==3 | TAD$Ventilation2[i]==2 | TAD$Ventilation2[i]==3, Vent_opened[i]<-1, Vent_opened[i]<-0)
91   ifelse(TAD$Ventilation1[i]==4 | TAD$Ventilation1[i]==5 | TAD$Ventilation2[i]==4 | TAD$Ventilation2[i]==5, Vent_AC[i]<-1, Vent_AC[i]<-0)
92   ifelse(TAD$Activity1[i]==1 | TAD$Activity2[i]==1, Act_sleep[i]<-1, Act_sleep[i]<-0)
93   ifelse(TAD$Activity1[i]==2 | TAD$Activity2[i]==2, Act_Commute[i]<-1, Act_Commute[i]<-0)
94   ifelse(TAD$Activity1[i]==3 | TAD$Activity2[i]==3, Act_work[i]<-1, Act_work[i]<-0)
95   ifelse(TAD$Activity1[i]==4 | TAD$Activity2[i]==4, Act_Cook[i]<-1, Act_Cook[i]<-0)
96   ifelse(TAD$Activity1[i]==5 | TAD$Activity2[i]==5, Act_worship[i]<-1, Act_worship[i]<-0)
97   ifelse(TAD$Activity1[i]==6 | TAD$Activity2[i]==6, Act_Shopping[i]<-1, Act_Shopping[i]<-0)
98   ifelse(TAD$Activity1[i]==7 | TAD$Activity2[i]==7, Act_Exercise[i]<-1, Act_Exercise[i]<-0)
99   ifelse(TAD$Activity1[i]==8 | TAD$Activity2[i]==8, Act_Eat[i]<-1, Act_Eat[i]<-0)
100  ifelse(TAD$Activity1[i]==9 | TAD$Activity2[i]==9, Act_Bath[i]<-1, Act_Bath[i]<-0)
101  ifelse(TAD$Activity1[i]==10 | TAD$Activity2[i]==10, Act_Sedentary[i]<-1, Act_Sedentary[i]<-0)
102  ifelse(TAD$Activity1[i]==11 | TAD$Activity2[i]==11, Act_Housework[i]<-1, Act_Housework[i]<-0)
103  ifelse(TAD$Activity1[i]==64 | TAD$Activity2[i]==64, Act_Other[i]<-1, Act_Other[i]<-0)
104  ifelse(TAD$AP1[i]==1 | TAD$AP2[i]==1 | TAD$AP3[i]==1, S_Exhaust[i]<-1, S_Exhaust[i]<-0)
105  ifelse(TAD$AP1[i]==2 | TAD$AP2[i]==2 | TAD$AP3[i]==2, S_Cooking[i]<-1, S_Cooking[i]<-0)
106  ifelse(TAD$AP1[i]==3 | TAD$AP2[i]==3 | TAD$AP3[i]==3, S_ETS[i]<-1, S_ETS[i]<-0)
107  ifelse(TAD$AP1[i]==4 | TAD$AP2[i]==4 | TAD$AP3[i]==4, S_Dust[i]<-1, S_Dust[i]<-0)
108  ifelse(TAD$AP1[i]==5 | TAD$AP2[i]==5 | TAD$AP3[i]==5, S_Incense[i]<-1, S_Incense[i]<-0)
109  ifelse(TAD$AP1[i]==6 | TAD$AP2[i]==6 | TAD$AP3[i]==6, S_MosquitoCoil[i]<-1, S_MosquitoCoil[i]<-0)
110  ifelse(TAD$AP1[i]==7 | TAD$AP2[i]==7 | TAD$AP3[i]==7, S_Aromatic[i]<-1, S_Aromatic[i]<-0)
111  ifelse(TAD$AP1[i]==8 | TAD$AP2[i]==8 | TAD$AP3[i]==8, S_Josspaper[i]<-1, S_Josspaper[i]<-0)
112  ifelse(TAD$AP1[i]==9 | TAD$AP2[i]==9 | TAD$AP3[i]==9, S_OpenedBurning[i]<-1, S_OpenedBurning[i]<-0)
113  ifelse(TAD$AP1[i]==10 | TAD$AP2[i]==10 | TAD$AP3[i]==10, S_Factory[i]<-1, S_Factory[i]<-0)
114  ifelse(TAD$AP1[i]==11 | TAD$AP2[i]==11 | TAD$AP3[i]==11, S_Garbage[i]<-1, S_Garbage[i]<-0)
115  ifelse(TAD$AP1[i]==65 | TAD$AP2[i]==65 | TAD$AP3[i]==65, S_other[i]<-1, S_other[i]<-0)
116  ifelse(TAD$AP1[i]==5 | TAD$AP2[i]==5 | TAD$AP3[i]==5 | TAD$AP1[i]==8 | TAD$AP2[i]==8 | TAD$AP3[i]==8, S_Incense_JPaper[i]<-1, S_Incense_JPaper[i]<-0)

```

Dummy variables

- For example:

```

42 Loc_Home <- c()
80 for(i in 1:dim(TAD)[1]){
81   ifelse(TAD$Place1[i]==1 | TAD$Place2[i]==1, Loc_Home[i]<-1, Loc_Home[i]<-0)

```

At home	Loc_Home (the dummy variable)
Yes	1
No	0

A. Location: Please select where you stay most of the time in this specific period.

[Indoor] Space with ceiling, wall or door

1. Home
2. Office, classroom, cram school, etc.
3. Factory (repair car garage, furnishing

[Outdoor] hall, road, outdoors, open ground

16. On the road (walking on the road, waiting for bus or traffic light)
17. Traditional market

```

66 S_Cooking <- c()
105 ifelse(TAD$AP1[i]==2 | TAD$AP2[i]==2 | TAD$AP3[i]==2, S_Cooking[i]<-1, S_Cooking[i]<-0)

```

D. Air quality: Please choose at most two items you have smelled.

1. Exhaust gas from cars or motorcycles.
2. Smoke of lampblack from homes, restaurants and peddlers.
3. Smell from smoking or second-hand smoke.
4. Sweep dust.
5. Incense burning smoke (encircle incense, slender stick of incense, thick

Source of cooking	S_Cooking (the dummy variable)
Yes	1
No	0

Variables for TAD data

You can create variables
according your requirements

Location (microenvironments)		Ventilation	Activities		Sources	
Home	Indoor environments (including transportation)	Window open	Sleeping	Taking bath	Vehicle exhaust	Open burning
Indoor environments		Window closed	Commuting	Sedentary activities	Cooking	Factories
Outdoor environments	Outdoor environments (including transportation)	AC-on	Working	Doing housework	ETS	Garbage
Transportation (indoor)			Cooking	Other	Cleaning/dust	Other
Transportation (outdoor)			Worshipping		Burning of incense	Burning of incense/joss-paper
Transportation (all)			Shopping		Burning of mosquito coil	
			Doing exercise		Aromatic products	
			Eating		Burning of joss-paper	

3. To combine all dummy variables created in Step 2 with subjects' ID and data time

```
119 TADr <- data.frame(subset(TAD,select=c(S_no,Year,Month,Day,Date,WD,Hour,Minute_30)),Loc_Home,Loc_In,Loc_Out,Loc_Trans_In,Loc_Trans_Out,Loc_Trans,
```

4. To group the sources with less frequency (cleaning/dust, burning of mosquito coil, aromatic products, open burning, factories, garbage and other) into “Other” group.

```
121 S_Other2<-c()
122 for(i in 1:dim(TADr)[1]){
123   if(TADr$S_Dust[i]==1|TADr$S_MosquitoCoil[i]==1|TADr$S_Aromatic[i]==1|TADr$S_OpenedBurning[i]==1|TADr$S_Factory[i]==1|TADr$S_Garbage[i]==1|TADr$S_Other[i]==1){
124     S_Other2[i]<-1
125   }else{
126     S_Other2[i]<-0
127   }
128 }
```

5. To create a variable for the time with more than one source

```
130 s_Multiple<-c()
131 for(i in 1:dim(TADr)[1]){
132   if(TADr$S_Exhaust[i]+TADr$S_Cooking[i]+TADr$S_ETS[i]+TADr$S_Incense_JPaper[i]+S_Other2[i]<=1){
133     s_Multiple[i]<-0
134   }else{
135     s_Multiple[i]<-1
136   }
137 }
```

6. To create a variable for the time with no recorded source

```
139 S_None<-c()
140 for(i in 1:dim(TADr)[1]){
141   if(TADr$S_Exhaust[i]==0&TADr$S_Cooking[i]==0&TADr$S_ETS[i]==0&TADr$S_Incense_JPaper[i]==0&S_Other2[i]==0){
142     S_None[i]<-1
143   }else{
144     S_None[i]<-0
145   }
146 }
```


7. To create a dummy variable for ventilations

```
148 Vent_D3_1<-c()
149 for(i in 1:dim(TADr)[1]){
150     if(TADr$Vent_AC[i]==0 & TADr$Vent_Closed[i]==1 & Vent_Opened[i]==0){
151         Vent_D3_1[i]<-1
152     }else{
153         Vent_D3_1[i]<-0
154     }
155 }
156
157 Vent_D3_2<-c()
158 for(i in 1:dim(TADr)[1]){
159     if(TADr$Vent_AC[i]==1 & TADr$Vent_Closed[i]==0 & Vent_Opened[i]==0){
160         Vent_D3_2[i]<-1
161     }else{
162         Vent_D3_2[i]<-0
163     }
164 }
```

	Vent_D3_1	Vent_D3_2
AC-on	0	1
Window closed	1	0
Window open (reference group)	0	0

7. To create a "Season" variable

```

166 Season <- c()
167 for(i in 1:dim(TADr)[1]){
168   if(TADr$Year[i]==2018){
169     Season[i]<-0
170   }else{
171     Season[i]<-1
172   }
173 }

```

8. To combine variables created with TAD data

```

174 TADr <- data.frame(TADr,S_Other2,S_Multiple,S_None,Vent_D3_1,Vent_D3_2)
175
176 write.csv(TADr,file="2020_Training_Course_TAD.csv",row.names=FALSE)
177

```

9. To export the final TAD dataset

1	S_no	Year	Month	Day	Date	WD	Hour	Minute_30	Loc_Hom	Loc_In	Loc_Out	Loc_Trans	Loc_Trans	Loc_T
2	LA001	2018	10	8	1	1	13	1	1	1	0	0	0	
3	LA001	2018	10	8	1	1	13	2	1	1	0	0	0	
4	LA001	2018	10	8	1	1	14	1	0	1	0	0	0	
5	LA001	2018	10	8	1	1	14	2	0	1	0	0	0	

Part 3:

Multiple linear regression for exposure factors



→ You can modify by yourself

1. To remove all objects from current workspace

```
1 # To remove previous memory in R.  
2 rm(list=ls())
```

2. To set the default drive of your data

```
3  
4 location <- "D:/"  
5  
6 # To set the output file  
7 cmd1 <- paste0("setwd('",location,"HiASAP/Exposure_Factor/output'")  
8 eval(parse(text=cmd1))
```

3. To set the path and filename of output file

```
9  
10 outputname <- "Exposure_Factor"
```

4. To create variables for personal PM data

```
12 # To create variables of outdoor, indoor and personal data of ASLUNG
13 PM <- read.csv(paste0(location,"HiASAP/PM/output/PM_5 min_AS Lung_Time_All.csv"))
14 ALP <- PM[which(PM$AL_Type==3),]
15 colnames(ALP)[names(ALP) == c("TEM","HUM","PM1","PM2.5","CO2")]<-c("ALP_TEM","ALP_HUM","ALP_PM1","ALP_PM2.5","ALP_CO2")
16 ALP_2 <- ALP[,c(1:9,11:15)]
```

5. To create variables for indoor PM data

```
18 ALI <- PM[which(PM$AL_Type==2),]
19 colnames(ALI)[names(ALI) == c("TEM","HUM","PM1","PM2.5","CO2")]<-c("ALI_TEM","ALI_HUM","ALI_PM1","ALI_PM2.5","ALI_CO2")
20 ALI_2 <- ALI[,c(2:6,8,11:15)]
```

6. To create variables for outdoor PM data

```
22 ALO <- PM[which(PM$AL_Type==1),]
23 colnames(ALO)[names(ALO) == c("TEM","HUM","PM1","PM2.5","CO2")]<-c("ALO_TEM","ALO_HUM","ALO_PM1","ALO_PM2.5","ALO_CO2")
24 ALO_2 <- ALO[,c(2:6,8,11:15)]
```

7. To merge (1) personal PM, (2) indoor PM , (3) outdoor PM , (4) TAD and (5) meteorological data for multiple linear regression

```
26 # To combine data
27 PMA11 <- data.frame()      (1) Personal PM data      (2) Indoor PM data
28 PMA11 <- merge(ALP_2,ALI_2, by=c("Year","Month","Day","Month","Hour","Minute","S_no"))
29 PMA11 <- merge(PMA11,ALO_2, by=c("Year","Month","Day","Month","Hour","Minute","S_no"))
30                               (3) Outdoor PM data
31 PMA11_2 <- data.frame()                               (4) TAD data
32 TAD <- read.csv(paste0(location,"HiASAP/Questionnaire_TAD/output/2020_Training_Course_TAD.csv"))
33 PMA11_2 <- merge(PMA11,TAD, by=c("Year","Month","Day","Month","Hour","Minute_30","S_no"))
34
35 Meteor <- read.csv(paste0(location,"HiASAP/Meteor/Meteor_Hourly_All.csv"))
36 Meteor <- Meteor[,c(1:4,14)]                               (5) Meteorological data
37 PMfinal <- merge(PMA11_2,Meteor, by=c("Year","Month","Day","Month","Hour"))
38
39 write.csv(PMfinal,file=paste0(outputname,".csv"),row.names=FALSE)
```

8. To select data at no-raining, awake and at-home period

```
41 # To select no-raining, awake and at-home period
42 PMfinal_A_NR_Home <- PMfinal[which(PMfinal$Precp==0 & PMfinal$Act_Sleep==0 & PMfinal$Loc_Home==1),]
43
44 # To determine a final regression model by the stepwise regression method
45 # To remain the variables which you are interested
46 aa <- PMfinal_A_NR_Home[,c(9,13,23,50,51,52,62,63,66,67)]
```

9. To select variables you want to add to the model


- In this case, we select **outdoor PM_{2.5} concentration, source of vehicle exhaust, source of cooking, source of ETS, source of burning incense/joss-paper, other sources** and **dummy variables of ventilation** to the models

Stepwise regression method


- Forward stepwise selection
- Backward stepwise selection
- Both forward and backward selection

Stepwise regression method

Forward stepwise selection example with 5 variables:



Backward stepwise selection example with 5 variables:



Multiple linear regression with stepwise regression method

10. To use the stepwise regression method to select the most important variables

```
48 # To use the stepwise regression method to identify and select the most useful explanatory variables from a list of
49 # several plausible independent variables
50 Final_Model <- step(lm(ALP_PM2.5~., data=aa), direction="both")
51 summary(Final_Model)
```

- Here “ALP_PM2.5~.” means all variates except personal PM_{2.5} concentration are added to the model

AIC: a mathematical method for evaluating how well a model fits the data it was generated from

Results of stepwise regression method

Step: AIC=16315.58

ALP_PM2.5 ~ Season + ALO_PM2.5 + S_Exhaust + S_Cooking + S_Incense_JPaper + S_Other2 + Vent_D3_1 + Vent_D3_2

	Df	Sum of Sq	RSS	AIC
- S_Exhaust	1	2.1	1467950	16314
- S_Cooking	1	72.8	1468020	16314
- Vent_D3_2	1	651.8	1468599	16315
<none>			1467948	16316
- S_Other2	1	1967.8	1469915	16317
- S_Incense_JPaper	1	3697.4	1471645	16320
- Season	1	5321.9	1473269	16323
- Vent_D3_1	1	6632.8	1474580	16325
- ALO_PM2.5	1	27556.5	1495504	16361

① Model 1
(Full model)

Step: AIC=16313.59

ALP_PM2.5 ~ Season + ALO_PM2.5 + S_Cooking + S_Incense_JPaper + S_Other2 + Vent_D3_1 + Vent_D3_2

	Df	Sum of Sq	RSS	AIC
- S_Cooking	1	72.7	1468022	16312
- Vent_D3_2	1	651.0	1468601	16313
<none>			1467950	16314
- S_Other2	1	1972.2	1469922	16315
+ S_Exhaust	1	2.1	1467948	16316
- S_Incense_JPaper	1	3705.2	1471655	16318
- Season	1	5486.5	1473436	16321
- Vent_D3_1	1	6653.0	1474603	16323
- ALO_PM2.5	1	27614.4	1495564	16359

② Model 2

Step: AIC=16311.71

ALP_PM2.5 ~ Season + ALO_PM2.5 + S_Incense_JPaper + S_Other2 + Vent_D3_1 + Vent_D3_2

	Df	Sum of Sq	RSS	AIC
- Vent_D3_2	1	652.2	1468675	16311
<none>			1468022	16312
- S_Other2	1	1954.7	1469977	16313
+ S_Cooking	1	72.7	1467950	16314
+ S_Exhaust	1	2.1	1468020	16314
- S_Incense_JPaper	1	3649.8	1471672	16316
- Season	1	5527.4	1473550	16319
- Vent_D3_1	1	6964.9	1474987	16322
- ALO_PM2.5	1	27811.8	1495834	16358

③ Model 3
Final model

Step: AIC=16310.85

smallest

ALP_PM2.5 ~ Season + ALO_PM2.5 + S_Incense_JPaper + S_Other2 + Vent_D3_1

	Df	Sum of Sq	RSS	AIC
<none>			1468675	16311
+ Vent_D3_2	1	652.2	1468022	16312
- S_Other2	1	1966.8	1470641	16312
+ S_Cooking	1	73.9	1468601	16313
+ S_Exhaust	1	1.4	1468673	16313
- S_Incense_JPaper	1	3023.0	1471698	16314
- Season	1	5732.4	1474407	16319
- Vent_D3_1	1	6915.9	1475591	16321
- ALO_PM2.5	1	27282.4	1495957	16356

④ Model 4

Results of final model

11. To run the final model for personal PM_{2.5} exposure factors evaluation

```
53 # In order to explain the set of dummy variables of trinary variable (window open, window closed and AC-on),
54 # we add the dummy variable of "Vent_D3_2" into the final model
55 Final_Model_2 <- lm(ALP_PM2.5 ~ ALO_PM2.5+S_Incense_JPaper+S_Other2+Vent_D3_1+Vent_D3_2+Season, data = aa)
56 summary(Final_Model_2)
```

Call:

```
lm(formula = ALP_PM2.5 ~ ALO_PM2.5 + S_Incense_JPaper + S_Other2 +  
    Vent_D3_1 + Vent_D3_2 + Season, data = aa)
```

Residuals:

Min	1Q	Median	3Q	Max
-55.32	-9.41	-6.92	-0.77	415.84

Coefficients:

β (coefficients)

SE (standard error)

p value

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	12.45380	1.05795	11.772	< 2e-16 ***
ALO_PM2.5	0.35080	0.05037	6.964	4.18e-12 ***
S_Incense_JPaper	9.41805	3.73313	2.523	0.01170 *
S_Other2	-4.12492	2.23419	-1.846	0.06497 .
Vent_D3_1	-6.78389	1.94656	-3.485	0.00050 ***
Vent_D3_2	-11.19743	10.49940	-1.066	0.28631
Season	3.05936	0.98541	3.105	0.00193 **

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 23.95 on 2560 degrees of freedom

Multiple R-squared: 0.03389, Adjusted R-squared: 0.03162

F-statistic: 14.97 on 6 and 2560 DF, p-value: < 2.2e-16

Partial R² estimation

12. To install (for the first time to use) and load the R packages for partial R² estimation

```
58 # To determine the partial R2 of each independent variable
59 # install.packages("rsq") (only for first time to use)
60 library("rsq")
61
62 Partial_R2 <- rsq.partial(Final_Model_2)
```

13. To calculate the partial R² of each independent variable in the model

```
[1] "Partial R2"
$adjustment
[1] FALSE

$variable
[1] "ALO_PM2.5"          "S_Incense_JPaper" "S_Other2"          "Vent_D3_1"          "Vent_D3_2"          "Season"

$partial.rsq
[1] 0.0185928613 0.0024800368 0.0013297616 0.0047219976 0.0004440941 0.0037510554
```

Results export

```
64 # To print out final model results to txt file
65 sink("Exposure_Factor_Results.txt") # redirect console output to a file
66 print("Stepwise")
67 print(stepAIC(ALP_PM2.5~.,data=aa),direction="both"))
68 print("Final model")
69 print(summary(Final_Model_2))
70 print("Partial R2")
71 print(Partial_R2)
72 sink() # return output to the terminal
```

14. To export results of the final model

Results of personal PM_{2.5} exposure factors evaluation

	Personal PM _{2.5} exposure (µg/m ³)			
Variables	Coefficient	95% CI	Partial R ²	p-value
Outdoor PM _{2.5} concentration (µg/m ³)	0.351	0.252, .450	0.0186	<0.001
Burning of incense/joss-paper	9.42	2.10, 16.7	0.0025	0.012
Other exposure sources	-4.12	-8.50, 0.254	0.0013	0.065
Window-closed	-6.78	-10.6, -2.97	0.0047	<0.001
AC-on	-11.2	-31.8, 9.38	0.0004	0.286
Season	3.06	1.13, 4.99	0.0038	0.002

- Burning of incense/joss-paper had on average the highest 5-min PM_{2.5} increments (9.42 µg/m³) to personal PM_{2.5} exposure.

Thank you for your attention