

ASMC Mobile App - Comprehensive Documentation

A modern React Native mobile application for the Anushaktinagar Sports Management Committee (ASMC), providing members with access to activities, events, hall bookings, and comprehensive membership management features.

Table of Contents

- [Quick Start](#)
- [Architecture Overview](#)
- [Installation & Setup](#)
- [Environment Configuration](#)
- [App Structure](#)
- [State Management](#)
- [API Integration](#)
- [UI Components](#)
- [Authentication & Authorization](#)
- [Features Overview](#)
- [Build & Deployment](#)
- [Development Guidelines](#)
- [Troubleshooting](#)

Quick Start

Prerequisites

- **Node.js:** 18.0.0 or higher
- **React Native CLI:** Latest version
- **Android Studio:** For Android development
- **Java Development Kit (JDK):** Version 11 or higher
- **ASMC API:** Backend server running on port 7055

Local Development Setup

```
# Clone the repository
git clone <repository-url>
cd asmcdae-mobile

# Install dependencies
npm install

# For iOS (if needed)
cd ios && pod install && cd ..

# Start Metro bundler
npm run start:reset

# Run on Android
npm run android
```

```
# Run on iOS (if available)
npm run ios
```

Production Build

```
# Build Android APK
cd android
./gradlew assembleRelease

# Build Android AAB (for Play Store)
./gradlew bundleRelease
```

▯ Architecture Overview

Technology Stack

- **Frontend Framework:** React Native 0.79.5
- **State Management:** React Query (TanStack Query) 5.0.0
- **Navigation:** React Navigation 7.x
- **HTTP Client:** Axios 1.10.0
- **Form Management:** Formik 2.4.6 + Yup 1.6.1
- **UI Components:** Custom components with React Native
- **Storage:** AsyncStorage 2.1.2
- **Icons:** React Native Vector Icons 10.2.0
- **Calendar:** React Native Calendars 1.1313.0
- **Image Handling:** React Native Image Picker 7.1.0
- **WebView:** React Native WebView 13.15.0

Project Structure

```
asmcdae-mobile/
├── android/                # Android-specific files
│   ├── app/                # Android app configuration
│   ├── build.gradle        # Gradle build configuration
│   └── gradle.properties  # Gradle properties
├── assets/                 # Static assets
│   ├── icons/              # App icons and images
│   ├── font/               # Custom fonts
│   └── ic_launcher/        # App launcher icons
├── src/
│   ├── components/         # Reusable UI components
│   │   ├── common/         # Common/shared components
│   │   └── Home/           # Home-specific components
│   ├── containers/         # Screen containers
│   │   ├── Activities/     # Activity management
│   │   ├── Events/         # Event management
│   │   ├── Halls/          # Hall management
│   │   ├── Profile/        # User profile
│   │   └── ...              # Other screens
│   ├── contexts/           # React contexts
│   ├── helpers/            # Utility functions
│   └── hooks/              # Custom React hooks
```

```
|   ├── lib/           # Third-party library configurations
|   ├── routes/        # Navigation configuration
|   └── styles/         # Global styles
├── App.js             # Main app component
├── index.js           # App entry point
└── package.json       # Dependencies and scripts
```

Component Architecture

The mobile app follows a **Container-Component pattern** with React Query integration:

1. **Containers:** Screen-level components with business logic
2. **Components:** Reusable UI components for presentation
3. **Contexts:** Global state management with React Context
4. **Hooks:** Custom hooks for data fetching and state management

Installation & Setup

Environment Configuration

Create a `.env` file in the root directory:

```
# API Configuration
API_BASE_URL=http://localhost:7055/api
API_TIMEOUT=30000

# App Configuration
APP_NAME=ASMC Mobile
APP_VERSION=1.0.0

# Authentication
JWT_STORAGE_KEY=asmc_mobile_token
REFRESH_TOKEN_KEY=asmc_mobile_refresh

# Feature Flags
ENABLE_DEBUG_MODE=true
ENABLE_LOGGING=true
```

Android Setup

1. **Install Android Studio**
2. **Configure Android SDK**
3. **Set up Android Emulator**
4. **Configure Environment Variables:**

```
# Add to ~/.bashrc or ~/.zshrc
export ANDROID_HOME=$HOME/Android/Sdk
export PATH=$PATH:$ANDROID_HOME/emulator
export PATH=$PATH:$ANDROID_HOME/tools
export PATH=$PATH:$ANDROID_HOME/tools/bin
export PATH=$PATH:$ANDROID_HOME/platform-tools
```

Development Scripts

```
# Start Metro bundler
npm start

# Start with cache reset
npm run start:reset

# Run on Android
npm run android

# Run on Android (debug mode)
npm run android:dev

# Debug mode with cache reset
npm run debug

# Run tests
npm test

# Lint code
npm run lint

# React DevTools
npm run devtools
```

□ Environment Configuration

API Configuration

Location: `/src/helpers/constants.js`

```
export const baseUrl = 'http://localhost:7055/api';
export const apiEndpoints = {
  auth: {
    login: '/auth/login',
    logout: '/auth/logout',
    refresh: '/auth/refresh',
    profile: '/auth/profile',
  },
  members: {
    list: '/members',
    profile: '/members/profile',
    update: '/members/update',
  },
  activities: {
    list: '/activities',
    detail: '/activities',
    enroll: '/activities/enroll',
  },
  events: {
    list: '/events',
    detail: '/events',
    register: '/events/register',
  },
}
```

```

    },
    halls: {
      list: '/halls',
      detail: '/halls',
      book: '/halls/book',
    },
    payments: {
      history: '/payments/history',
      process: '/payments/process',
    },
  },
};

```

Axios Configuration

Location: /src/helpers/axios.js

```

import axios from 'axios';
import AsyncStorage from '@react-native-async-storage/async-storage';
import { baseUrl } from '../constants';

const axiosInstance = axios.create({
  baseURL: baseUrl,
  timeout: 30000,
  headers: {
    'Content-Type': 'application/json',
  },
});

// Request interceptor
axiosInstance.interceptors.request.use(
  async (config) => {
    const token = await AsyncStorage.getItem('authToken');
    if (token) {
      config.headers.Authorization = `Bearer ${token}`;
    }
    return config;
  },
  (error) => Promise.reject(error),
);

// Response interceptor
axiosInstance.interceptors.response.use(
  (response) => response,
  async (error) => {
    if (error.response?.status === 401) {
      // Handle token expiration
      await AsyncStorage.removeItem('authToken');
      await AsyncStorage.removeItem('refreshToken');
      // Navigate to login
    }
    return Promise.reject(error);
  },
);

```

```
export default axiosInstance;
```

📁 App Structure

Navigation Structure

The app uses React Navigation with a tab-based navigation system:

Main Tabs

1. **Home** - Dashboard and quick access
2. **Events** - Event listings and registration
3. **Halls** - Hall bookings and information
4. **Activities** - Activity enrollment and management
5. **Profile** - User profile and settings

Stack Navigation

- **Public Stack:** Login, Forgot Password
- **Private Stack:** Main app screens with nested navigation

Screen Components

Core Screens

1. **HomeContainer** (/src/containers/Home/)
 - Dashboard with quick actions
 - Recent activities and events
 - Membership status display
2. **EventsContainer** (/src/containers/Events/)
 - Event listings with filtering
 - Event details and registration
 - Event booking management
3. **ActivitiesContainer** (/src/containers/Activities/)
 - Activity listings and categories
 - Activity enrollment
 - Activity schedules and details
4. **HallsContainer** (/src/containers/Halls/)
 - Hall listings and availability
 - Hall booking system
 - Booking history and management
5. **ProfileContainer** (/src/containers/Profile/)
 - User profile information
 - Settings and preferences
 - Membership details

Supporting Screens

- **LoginContainer** - User authentication
- **ForgotPasswordContainer** - Password recovery

- **EditProfileContainer** - Profile editing
- **ChangePasswordContainer** - Password change
- **PaymentHistoryContainer** - Payment records
- **BookingFormContainer** - Booking forms
- **WebViewContainer** - External web content

Common Components

Location: `/src/components/common/`

Header Component

```
import React from 'react';
import { View, Text, TouchableOpacity } from 'react-native';
import MaterialIcons from 'react-native-vector-icons/MaterialIcons';

const Header = ({ title, showBack, showLogout, showProfile, onBack, onLogout }) => {
  return (
    <View style={styles.header}>
      {showBack && (
        <TouchableOpacity onPress={onBack} style={styles.backButton}>
          <MaterialIcons name="arrow-back" size={24} color="#000" />
        </TouchableOpacity>
      )}
      <Text style={styles.title}>{title}</Text>
      {showLogout && (
        <TouchableOpacity onPress={onLogout} style={styles.logoutButton}>
          <MaterialIcons name="logout" size={24} color="#000" />
        </TouchableOpacity>
      )}
    </View>
  );
};
```

InputField Component

```
import React from 'react';
import { TextInput, View, Text } from 'react-native';

const InputField = ({
  label,
  value,
  onChangeText,
  placeholder,
  secureTextEntry,
  error,
  ...props
}) => {
  return (
    <View style={styles.container}>
      {label && <Text style={styles.label}>{label}</Text>}
      <TextInput
        style={[styles.input, error && styles.inputError]}
        value={value}
        placeholder={placeholder}
        secureTextEntry={secureTextEntry}
        onChangeText={onChangeText}
        error={error}
        {...props}
      />
    </View>
  );
};
```

```

        value={value}
        onChangeText={onChangeText}
        placeholder={placeholder}
        secureTextEntry={secureTextEntry}
        {...props}
      />
      {error && <Text style={styles.errorText}>{error}</Text>}
    </View>
  );
};

```

State Management

React Query Integration

Location: /src/lib/queryClient.js

```

import { QueryClient } from '@tanstack/react-query';

export const queryClient = new QueryClient({
  defaultOptions: {
    queries: {
      staleTime: 5 * 60 * 1000, // 5 minutes
      cacheTime: 10 * 60 * 1000, // 10 minutes
      retry: 2,
      refetchOnWindowFocus: false,
    },
    mutations: {
      retry: 1,
    },
  },
});

```

Authentication Context

Location: /src/contexts/AuthContext.js

```

import React, { createContext, useContext, useReducer, useEffect } from 'react';
import AsyncStorage from '@react-native-async-storage/async-storage';

const AuthContext = createContext();

const initialState = {
  user: null,
  token: null,
  isAuth: false,
  isLoading: true,
};

const authReducer = (state, action) => {
  switch (action.type) {
    case 'LOGIN_SUCCESS':
      return {

```



```

        ...state,
        user: action.payload.user,
        token: action.payload.token,
        isAuth: true,
        isLoading: false,
    };
    case 'LOGOUT':
        return {
            ...state,
            user: null,
            token: null,
            isAuth: false,
            isLoading: false,
        };
    case 'SET_LOADING':
        return {
            ...state,
            isLoading: action.payload,
        };
    default:
        return state;
    }
};

export const AuthProvider = ({ children }) => {
    const [state, dispatch] = useReducer(authReducer, initialState);

    useEffect(() => {
        checkAuthStatus();
    }, []);

    const checkAuthStatus = async () => {
        try {
            const token = await AsyncStorage.getItem('authToken');
            const user = await AsyncStorage.getItem('userData');

            if (token && user) {
                dispatch({
                    type: 'LOGIN_SUCCESS',
                    payload: {
                        token,
                        user: JSON.parse(user),
                    },
                });
            } else {
                dispatch({ type: 'SET_LOADING', payload: false });
            }
        } catch (error) {
            dispatch({ type: 'SET_LOADING', payload: false });
        }
    };
};

```

```

const login = async (credentials) => {
  try {
    dispatch({ type: 'SET_LOADING', payload: true });

    const response = await axiosInstance.post('/auth/login', credentials);
    const { token, user } = response.data;

    await AsyncStorage.setItem('authToken', token);
    await AsyncStorage.setItem('userData', JSON.stringify(user));

    dispatch({
      type: 'LOGIN_SUCCESS',
      payload: { token, user },
    });

    return { success: true };
  } catch (error) {
    dispatch({ type: 'SET_LOADING', payload: false });
    return { success: false, error: error.response?.data?.message };
  }
};

const logout = async () => {
  try {
    await AsyncStorage.removeItem('authToken');
    await AsyncStorage.removeItem('userData');
    dispatch({ type: 'LOGOUT' });
  } catch (error) {
    console.error('Logout error:', error);
  }
};

return (
  <AuthContext.Provider
    value={{
      ...state,
      login,
      logout,
    }}
  >
    {children}
  </AuthContext.Provider>
);
};

export const useAuth = () => {
  const context = useContext(AuthContext);
  if (!context) {
    throw new Error('useAuth must be used within AuthProvider');
  }
  return context;
};

```

Custom Hooks

useActivity Hook

Location: `/src/hooks/useActivity.js`

```
import { useQuery, useMutation, useQueryClient } from '@tanstack/react-query';
import axiosInstance from '../helpers/axios';

export const useActivities = () => {
  return useQuery({
    queryKey: ['activities'],
    queryFn: async () => {
      const response = await axiosInstance.get('/activities');
      return response.data;
    },
  });
};

export const useActivity = (id) => {
  return useQuery({
    queryKey: ['activity', id],
    queryFn: async () => {
      const response = await axiosInstance.get(`/activities/${id}`);
      return response.data;
    },
    enabled: !!id,
  });
};

export const useEnrollActivity = () => {
  const queryClient = useQueryClient();

  return useMutation({
    mutationFn: async (activityId) => {
      const response = await
axiosInstance.post(`/activities/${activityId}/enroll`);
      return response.data;
    },
    onSuccess: () => {
      queryClient.invalidateQueries(['activities']);
      queryClient.invalidateQueries(['enrolled-activities']);
    },
  });
};
```

API Integration

API Service Functions

Location: `/src/helpers/api.js`

```

import axiosInstance from './axios';

export const authAPI = {
  login: (credentials) => axiosInstance.post('/auth/login', credentials),
  logout: () => axiosInstance.post('/auth/logout'),
  refreshToken: (refreshToken) => axiosInstance.post('/auth/refresh', { refreshToken
}),
  getProfile: () => axiosInstance.get('/auth/profile'),
  updateProfile: (data) => axiosInstance.put('/auth/profile', data),
};

export const activitiesAPI = {
  getActivities: (params) => axiosInstance.get('/activities', { params }),
  getActivity: (id) => axiosInstance.get(`/activities/${id}`),
  enrollActivity: (id) => axiosInstance.post(`/activities/${id}/enroll`),
  getEnrolledActivities: () => axiosInstance.get('/activities/enrolled'),
};

export const eventsAPI = {
  getEvents: (params) => axiosInstance.get('/events', { params }),
  getEvent: (id) => axiosInstance.get(`/events/${id}`),
  registerEvent: (id) => axiosInstance.post(`/events/${id}/register`),
  getRegisteredEvents: () => axiosInstance.get('/events/registered'),
};

export const hallsAPI = {
  getHalls: (params) => axiosInstance.get('/halls', { params }),
  getHall: (id) => axiosInstance.get(`/halls/${id}`),
  bookHall: (data) => axiosInstance.post('/halls/book', data),
  getBookedHalls: () => axiosInstance.get('/halls/booked'),
};

export const paymentsAPI = {
  getPaymentHistory: () => axiosInstance.get('/payments/history'),
  processPayment: (data) => axiosInstance.post('/payments/process', data),
};

```

Error Handling

```

import Toast from 'react-native-toast-message';

export const handleAPIError = (error) => {
  const message = error.response?.data?.message || 'An error occurred';

  Toast.show({
    type: 'error',
    text1: 'Error',
    text2: message,
  });
};

export const handleAPISuccess = (message) => {

```

```
    Toast.show({
      type: 'success',
      text1: 'Success',
      text2: message,
    });
  });
};
```

UI Components

Style System

Location: /src/styles/styles.js

```
import { StyleSheet, Dimensions } from 'react-native';

const { width, height } = Dimensions.get('window');

export const colors = {
  primary: '#1976d2',
  secondary: '#dc004e',
  success: '#4caf50',
  warning: '#ff9800',
  error: '#f44336',
  background: '#fafafa',
  surface: 'ffffff',
  text: '#212121',
  textSecondary: '#757575',
  border: '#e0e0e0',
};

export const typography = {
  h1: {
    fontSize: 32,
    fontWeight: 'bold',
    fontFamily: 'PlusJakartaSans-Bold',
  },
  h2: {
    fontSize: 24,
    fontWeight: '600',
    fontFamily: 'PlusJakartaSans-SemiBold',
  },
  h3: {
    fontSize: 20,
    fontWeight: '600',
    fontFamily: 'PlusJakartaSans-SemiBold',
  },
  body: {
    fontSize: 16,
    fontFamily: 'PlusJakartaSans-Regular',
  },
  caption: {
    fontSize: 14,
```

```
        fontFamily: 'PlusJakartaSans-Regular',
    },
};

export const spacing = {
  xs: 4,
  sm: 8,
  md: 16,
  lg: 24,
  xl: 32,
  xxl: 48,
};

export const borderRadius = {
  sm: 4,
  md: 8,
  lg: 12,
  xl: 16,
  round: 50,
};

export default StyleSheet.create({
  container: {
    flex: 1,
    backgroundColor: colors.background,
  },
  loadingContainer: {
    flex: 1,
    justifyContent: 'center',
    alignItems: 'center',
  },
  header: {
    flexDirection: 'row',
    alignItems: 'center',
    justifyContent: 'space-between',
    paddingHorizontal: spacing.md,
    paddingVertical: spacing.sm,
    backgroundColor: colors.surface,
    elevation: 2,
    shadowColor: '#000',
    shadowOffset: { width: 0, height: 2 },
    shadowOpacity: 0.1,
    shadowRadius: 4,
  },
  card: {
    backgroundColor: colors.surface,
    borderRadius: borderRadius.md,
    padding: spacing.md,
    margin: spacing.sm,
    elevation: 2,
    shadowColor: '#000',
    shadowOffset: { width: 0, height: 2 },
```

```

        shadowOpacity: 0.1,
        shadowRadius: 4,
    },
    button: {
        backgroundColor: colors.primary,
        paddingHorizontal: spacing.lg,
        paddingVertical: spacing.md,
        borderRadius: borderRadius.md,
        alignItems: 'center',
    },
    buttonText: {
        color: colors.surface,
        fontSize: 16,
        fontWeight: '600',
        fontFamily: 'PlusJakartaSans-SemiBold',
    },
    input: {
        borderWidth: 1,
        borderColor: colors.border,
        borderRadius: borderRadius.md,
        paddingHorizontal: spacing.md,
        paddingVertical: spacing.sm,
        fontSize: 16,
        fontFamily: 'PlusJakartaSans-Regular',
        backgroundColor: colors.surface,
    },
    inputError: {
        borderColor: colors.error,
    },
    errorText: {
        color: colors.error,
        fontSize: 14,
        fontFamily: 'PlusJakartaSans-Regular',
        marginTop: spacing.xs,
    },
  },
});

```

Custom Components

Card Component

```

import React from 'react';
import { View, Text, TouchableOpacity, Image } from 'react-native';
import styles, { colors, spacing } from '../styles/styles';

const Card = ({ title, description, image, onPress, children }) => {
  return (
    <TouchableOpacity style={styles.card} onPress={onPress}>
      {image && <Image source={{ uri: image }} style={styles.cardImage} />}
      {title && <Text style={styles.cardTitle}>{title}</Text>}
      {description && <Text style={styles.cardDescription}>{description}</Text>}
      {children}
    </TouchableOpacity>
  );
};

```

```

        </TouchableOpacity>
    );
};

```

Loading Component

```

import React from 'react';
import { View, ActivityIndicator, Text } from 'react-native';
import styles from '../../styles/styles';

const Loading = ({ message = 'Loading...', size = 'large' }) => {
    return (
        <View style={styles.loadingContainer}>
            <ActivityIndicator size={size} color="#1976d2" />
            <Text style={styles.loadingText}>{message}</Text>
        </View>
    );
};

```

Authentication & Authorization

Login Flow

```

import React, { useState } from 'react';
import { View, Text, Alert } from 'react-native';
import { useAuth } from '../../contexts/AuthContext';
import { InputField } from '../../components/common/InputField';
import { Button } from '../../components/common/Button';

const LoginScreen = () => {
    const [credentials, setCredentials] = useState({
        email: '',
        password: '',
    });
    const [loading, setLoading] = useState(false);
    const { login } = useAuth();

    const handleLogin = async () => {
        setLoading(true);
        const result = await login(credentials);
        setLoading(false);

        if (!result.success) {
            Alert.alert('Login Failed', result.error);
        }
    };

    return (
        <View style={styles.container}>
            <Text style={styles.title}>Welcome to ASMC</Text>

```



```

        <InputField
          label="Email"
          value={credentials.email}
          onChangeText={({text}) => setCredentials({ ...credentials, email: text
        })}

          placeholder="Enter your email"
          keyboardType="email-address"
          autoCapitalize="none"
        />

        <InputField
          label="Password"
          value={credentials.password}
          onChangeText={({text}) =>
            setCredentials({ ...credentials, password: text })
          }
          placeholder="Enter your password"
          secureTextEntry
        />

        <Button
          title="Login"
          onPress={handleLogin}
          loading={loading}
          disabled={loading}
        />
      </View>
    );
  };

```

Protected Routes

```

import React from 'react';
import { useAuth } from '../contexts/AuthContext';
import LoginScreen from '../containers/Login';

const ProtectedRoute = ({ children }) => {
  const { isAuth, isLoading } = useAuth();

  if (isLoading) {
    return <LoadingScreen />;
  }

  if (!isAuth) {
    return <LoginScreen />;
  }

  return children;
};

```

▮ Features Overview

Core Features

1. User Authentication

- Login/logout functionality
- Password recovery
- Profile management

2. Activities Management

- Browse available activities
- Enroll in activities
- View enrolled activities
- Activity schedules and details

3. Events Management

- Browse upcoming events
- Register for events
- View registered events
- Event details and information

4. Hall Booking System

- Browse available halls
- Book halls for specific dates/times
- View booking history
- Manage existing bookings

5. Payment Integration

- View payment history
- Process payments for activities/events
- Membership fee payments

6. Profile Management

- View and edit profile information
- Change password
- View membership details
- Family member management

Advanced Features

- **Offline Support:** Cached data for offline viewing
- **Push Notifications:** Activity and event reminders
- **Image Upload:** Profile picture and document upload
- **Calendar Integration:** Activity and event scheduling
- **Search and Filtering:** Advanced search capabilities
- **Responsive Design:** Optimized for different screen sizes

□ Build & Deployment

Android Build

Debug Build

```
# Clean and build debug APK
cd android
./gradlew clean
./gradlew assembleDebug

# Install on device
adb install app/build/outputs/apk/debug/app-debug.apk
```

Release Build

```
# Generate signed APK
cd android
./gradlew assembleRelease

# Generate AAB for Play Store
./gradlew bundleRelease
```

Build Configuration

Android App Configuration

Location: android/app/build.gradle

```
android {
    compileSdkVersion 34
    buildToolsVersion "34.0.0"

    defaultConfig {
        applicationId "com.asmc.mobile"
        minSdkVersion 21
        targetSdkVersion 34
        versionCode 1
        versionName "1.0.0"
    }

    signingConfigs {
        release {
            storeFile file('release.keystore')
            storePassword 'your_store_password'
            keyAlias 'your_key_alias'
            keyPassword 'your_key_password'
        }
    }

    buildTypes {
        release {
            signingConfig signingConfigs.release
            minifyEnabled true
            proguardFiles getDefaultProguardFile('proguard-android.txt'), 'proguard-
rules.pro'
        }
    }
}
```

Deployment Checklist

Pre-deployment

- ☐ Update version numbers
- ☐ Test on multiple devices
- ☐ Verify all features work
- ☐ Check API endpoints
- ☐ Review security configurations

Post-deployment

- ☐ Monitor app performance
- ☐ Check crash reports
- ☐ Monitor user feedback
- ☐ Update documentation

Development Guidelines

Code Standards

1. Component Structure

- Use functional components with hooks
- Implement proper prop types
- Follow consistent naming conventions

2. File Organization

- Group related files in folders
- Use descriptive file names
- Maintain consistent import order

3. Styling

- Use StyleSheet for performance
- Follow design system guidelines
- Implement responsive design

4. State Management

- Use React Query for server state
- Use React Context for global state
- Minimize local state usage

Performance Best Practices

1. Image Optimization

- Use appropriate image formats
- Implement lazy loading
- Optimize image sizes

2. Memory Management

- Clean up subscriptions and timers

- Use `React.memo` for expensive components
- Implement proper navigation cleanup

3. Network Optimization

- Implement request caching
- Use pagination for large datasets
- Optimize API calls

Testing Guidelines

```
// Example test structure
import React from 'react';
import { render, fireEvent } from '@testing-library/react-native';
import LoginScreen from '../LoginScreen';

describe('LoginScreen', () => {
  it('renders login form correctly', () => {
    const { getByPlaceholderText, getByText } = render(<LoginScreen />);

    expect(getByPlaceholderText('Enter your email')).toBeTruthy();
    expect(getByPlaceholderText('Enter your password')).toBeTruthy();
    expect(getByText('Login')).toBeTruthy();
  });

  it('handles login submission', () => {
    const { getByPlaceholderText, getByText } = render(<LoginScreen />);

    fireEvent.changeText(
      getByPlaceholderText('Enter your email'),
      'test@example.com',
    );
    fireEvent.changeText(getByPlaceholderText('Enter your password'),
      'password123');
    fireEvent.press(getByText('Login'));

    // Add assertions for login behavior
  });
});
```

❏ Troubleshooting

Common Issues

1. Metro Bundler Issues

Problem: Metro bundler not starting or cache issues

Solution:

```
# Clear Metro cache
npm run start:reset

# Clear npm cache
```

```
npm cache clean --force

# Delete node_modules and reinstall
rm -rf node_modules package-lock.json
npm install
```

2. Android Build Issues

Problem: Gradle build failures

Solution:

```
# Clean Gradle cache
cd android
./gradlew clean

# Update Gradle wrapper
./gradlew wrapper --gradle-version=8.0

# Check Java version
java -version
```

3. API Connection Issues

Problem: Cannot connect to backend API

Solution:

- Check API base URL in constants
- Verify backend server is running
- Check network connectivity
- Review CORS configuration

4. Navigation Issues

Problem: Navigation not working properly

Solution:

- Check React Navigation version compatibility
- Verify navigation structure
- Check for missing dependencies
- Review navigation state management

Debug Tools

React Native Debugger

```
# Install React Native Debugger
npm install -g react-native-debugger

# Start debugger
npm run devtools
```

Flipper Integration

```
# Install Flipper
# Download from https://fbflipper.com/

# Configure in android/app/src/debug/java/
# Add Flipper initialization
```

Logging

```
import { Platform } from 'react-native';

const logger = {
  log: (message, data) => {
    if (__DEV__) {
      console.log(`[${new Date().toISOString()}] ${message}`, data);
    }
  },
  error: (message, error) => {
    if (__DEV__) {
      console.error(`[${new Date().toISOString()}] ${message}`, error);
    }
  },
};
```

Summary

The ASMC Mobile App provides a comprehensive mobile solution for sports management with:

- **Modern React Native Architecture** with React Query for state management
- **Comprehensive Feature Set** including activities, events, hall bookings, and payments
- **Robust Authentication** with JWT token management
- **Optimized Performance** with caching and offline support
- **Production-Ready Build** system for Android deployment
- **Extensive Documentation** for development and maintenance

This mobile application ensures members have easy access to all ASMC services and features on their mobile devices.

Version: 1.0.0

Last Updated: January 2025

Maintainer: ASMC Development Team