

goProfiles: an R package for the Statistical Analysis of Functional Profiles

Alex Sánchez, Jordi Ocaña and Miquel Salicrú

May 21, 2010

1 Introduction

This document presents an introduction to the use of *goProfiles*, an R package for the analysis of lists of genes based on their projection at a given level of the Gene Ontology following the methodology developed by [2, ?].

2 Requirements

To use the package one must have R (2.7 or greater) installed. Bioconductor 2.2 or greater is also needed.

3 Quick start

For the inpatient user the following lines provide a quick and simple example on the use of the package to explore and compare two experimental datasets obtained from two prostate cancer experiments ([4, 1]). Detailed explanations about the computations can be found in the following chapters and in the package help.

The analysis proceeds as follows:

- First a dataset is loaded into memory. This dataset contains several lists of genes, from two different studies, selected as being differentially expressed in prostate cancer. `help(prostateIds)` will provide extra information about the lists of genes.

```
> require(goProfiles)
> data(prostateIds)
```

- Next a functional profile is build for each list. For simplicity it is build for the MF ontology only.

```
> welsh.MF <- basicProfile(welsh01EntrezIDs, onto = "MF",
+   level = 2, orgPackage = "org.Hs.eg.db")
> singh.MF <- basicProfile(singh01EntrezIDs, onto = "MF",
+   level = 2, orgPackage = "org.Hs.eg.db")
> welsh.singh.MF <- mergeProfilesLists(welsh.MF,
+   singh.MF, profNames = c("Welsh", "Singh"))
> printProfiles(welsh.singh.MF, percentage = TRUE)
```

Functional Profile

=====

[1] "MF ontology"

	Description	GOID	Welsh	Singh
7	antioxidant activity	GO:0016209	0.2	0.5
4	binding	GO:0005488	83.3	82.4

1	catalytic activity	GO:0003824	36.5	36.3
8	channel regulator activit...	GO:0016247	0.7	0.9
13	chemoattractant activity...	GO:0042056	0.1	0.3
15	chemorepellent activity...	GO:0045499	0.1	0.0
5	electron carrier activity...	GO:0009055	1.2	2.9
10	enzyme regulator activity...	GO:0030234	5.7	6.0
17	molecular transducer acti...	GO:0060089	11.3	8.6
6	proteasome regulator acti...	GO:0010860	0.0	0.2
2	structural molecule activ...	GO:0005198	8.2	11.6
11	transcription regulator a...	GO:0030528	9.5	8.8
14	translation regulator act...	GO:0045182	0.1	0.3
3	transporter activity	GO:0005215	7.0	7.7

```
> plotProfiles(welsh.MF, aTitle = "Welsh (2001). Prostate cancer data")
```

Welsh (2001). Prostate cancer data. MF ontology




Figure 1: Basic profile for a dataset at the second level of the MF ontology

Changing the parameter `onto` to 'ANY' instead of 'MF' will compute profiles for the three ontologies.

```
> welsh <- basicProfile(welsh01EntrezIDs, onto = "ANY",
+   level = 2, orgPackage = "org.Hs.eg.db")
```

- A visual comparison of profiles can be useful to give hints about the difference between them.
- Finally a numerical comparison of both profiles is performed and its summary is printed. Notice that

```
> plotProfiles(welsh.singh.MF, percentage = T, aTitle = "Welsh vs Singh",
+             legend = T)
```




Figure 2: Comparison between two profiles at the second level of the MF ontology

the comparison rebuilds the profiles, that is the input for the computation are the two lists of genes not the profiles.

```
> compared.welsh.singh.01.MF <- compareGeneLists(welsh01EntrezIDs,
+         singh01EntrezIDs, onto = "MF", level = 2,
+         orgPackage = "org.Hs.eg.db")
> print(compSummary(compared.welsh.singh.01.MF))
```

```
Sqr.Euc.Dist      StdErr      pValue      0.95CI.low
      0.002858      0.001391      0.030000      0.000131
      0.95CI.up
      0.005584
```

- The reason to compare two lists similar studies may be to combine them. In this case what is more meaningful to do is an equivalence test, instead of a difference test as above.

```
> eqws01 <- equivalentGOProfiles(compared.welsh.singh.01.MF,
+         simplify = FALSE)
> print(es <- equivSummary(eqws01))
```

```
Sqr.Euc.Dist      StdErr
      0.002858      0.001391
      pValue      CI.up
      0.000000      0.005146
      d0 Equivalent? (1=yes,0=not)
      0.035000      1.000000
```

4 User guide

This introduction has simply shown the possibilities of the program. A more complete user guide can be found at the program's web site:

<http://estbioinfo.stat.ub.es/pubs/goProfiles-Usersguide.pdf>

References

- [1] Singh Dinesh, , William R Sellers, Philip K. Febbo, Kenneth Ross, Donald G Jackson, Judith Manola, Christine Ladd, Pablo Tamayo, Andrew A Renshaw, Anthony V D'Amico, Jerome P Richie, Eric S Lander, Massimo Loda, Philip W Kantoff, and Todd R Golub. Gene expression correlates of clinical prostate cancer behavior. *Cancer Cell*, 1(2):203–209, 2002.
- [2] A. Sánchez-Pla, M. Salicrú, and J. Ocaña. Statistical methods for the analysis of high-throughput data based on functional profiles derived from the gene ontology. *Journal of Statistical Planning and Inference*, 137(12):3975–3989, 2007
- [3] M. Salicrú, J. Ocaña and A. Sánchez-Pla. Comparison of Gene Lists based on Functional Profiles. *submitted*, 2008.
- [4] J.B. Welsh, Lisa M. Sapinoso, Andrew I. Su, Suzanne G. Kern, Jessica Wang-Rodriguez, Christopher A. Moskaluk-Jr., Henry F. Frierson, and Hampton Garret M. Analysis of gene expression identifies candidate markers and pharmacological targets in prostate cancer. *Cancer Res*, 61:5974–5978, 2001.