



# Bioconductor packages for short read analyses

## Subtitol

Alex Sánchez

Unitat d'Estadística i Bioinformàtica (UEB)

June 8, 2014

# Table of Contents

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

- 1 Introduction
- 2 Infrastructure packages
- 3 Biostrings
- 4 BSgenome
- 5 rtracklayer
- 6 GenomicFeatures
- 7 biomaRt
- 8 genomeIntervals
- 9 GenomicRanges
- 10 Rsamtools
- 11 ShortRead
- 12 Conclusions
- 13 Other interesting packages

# Foreword

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

The “core” packages for integrating NGS data analysis represents a massive structure.

It is under very active development and often different ways exist to achieve one goal.

*e.g RangedData vs. GRanges*

The trunk of this core starts to reach maturity and redundant branches might be pruned.

# Aims

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Introduce all the necessary packages to perform the QA and the pre-processing of NGS rawdata:

**biomaRt**

**rtracklayer**

**Biostrings**

**BSgenome**

**GenomicFeatures**

**GenomicRanges**

**IRanges**

**Rsamtools**

**ShortRead**

# Some necessary complements: Classes in R

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Two kinds: S3 and S4

S3 are old and informal, setting the class attribute is enough to “convert” an object into a class

S4 is an attempt at making R more object oriented

they have specific definitions

they define “fields” called “**slots**”

they can inherit and be inherited from

they can have prototypes, validators

they can be virtual

etc.

Most of the classes described here are of S4 type, except when backward compatibility with the R core required otherwise

More information can be found in the R help page:

[?classRepresentation](#)

# Methods to browse S4 classes

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

(Load the IRanges library to run the following example)

```
> require(IRanges)
> ?Classes
> ?Methods
> getClass("RleList")
```

Virtual Class "RleList" [package "IRanges"]

Slots:

Name:	elementType	elementMetadata	metadata
Class:	character	DataTableORNULL	list

Extends:

Class "AtomicList", directly  
Class "List", by class "AtomicList", distance 2  
Class "Vector", by class "AtomicList", distance 3  
Class "Annotated", by class "AtomicList", distance 4

Known Subclasses: "RleViews", "CompressedRleList", "SimpleRleList"

# Methods to browse S4 classes

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

```
> names(completeSubclasses(getClass("RleList")))

[1] "RleViews"          "CompressedRleList" "SimpleRleList"

> head(showMethods(classes="RleList",printTo=FALSE))

[1] "" "Function \"AIC\":"
[3] " <not an S4 generic function>" ""
[5] "Function \"BIC\":" " <not an S4 generic function>"

> showMethods("values",includeDefs=TRUE)

Function: values (package IRanges)
x="RangedData"
function (x, ...)
{
  .local <- function (x)
    x@values
    .local(x, ...)
}

x="Vector"
function (x, ...)
  elementMetadata(x, ...)
```



# Packages dependencies

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Sometimes packages define the same function resulting in one of the function to be inaccessible anymore.

When this happens, one needs to contact the packages authors for them to find an appropriate solution

In the meanwhile, the hack described on the next slides might help

load the GenomicRanges and the genomeIntervals in that order

# Packages dependencies

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions


Other

For the purpose of the example it is not necessary to understand the actual objects that are created. We'll come back to them later.

Create the necessary object

```
grngs <- GRanges (seqnames=c("chr1","chr2","chr31"),  
  ranges=IRanges(start=c(3,4,1),end=c(7,5,3)),strand=c("+","+","-"),  
  seqlengths=c("chr1"=24,"chr2"=18))
```

# Bottom - up approach



# Infrastructure packages

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## IRanges

Long sequences, compressed and pointer referenced

**Views** on long sequences

Integer overlap tppñs; e.g. interval overlap

Used to define genomic intervals (i.e. RangedData)

## GenomicRanges

Recent

IRanges extension

Adds discontinuous genomic interval sets (useful for gapped alignments)

## genomeIntervals

Not Core

Very similar to IRanges

Extremely efficient at interval calculations; e.g. interval overlap

# Infrastructure Views

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Issue

DNA sequences can be very large (think of the human genome)

Duplicating them in memory is contra-efficient

Therefore the views!

Views is yet another IRanges class

a virtual class for storing set of views (pointers) on a single  
Sequence object

available as RleViews, XStringViews, XIntegerViews,  
XStringSetViews, etc.

it stores the sequence using a “pass-by-reference” semantic and  
associates ranges to select the subsequences

# Infrastructure Running Length Encodings (RLEs)

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Issue

Again, memory is the limit. holding a coverage vector at a single bp resolution is inefficient.

Therefore the concept of RLEs

a common compression technique for piecewise constant data

0 0 0 1 1 1 2 2 3 3 3 ... can be compressed in

0(3), 1(3), 2(2), 3(3),...

it couples values e.g. 0 with a run length i.e. 3

Can be partitioned into RleList, e.g. for storing the coverage of different chromosomes

# Infrastructure methods

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

get the methods for the Rle S4 class

```
f.list <- showMethods(classes="Rle", printTo=FALSE)
```

process the result to extract the function name

```
sapply(strsplit(f.list[grep("Function", f.list)],  
function(l)gsub(' ', '', l[[2]])) This return 111 methods!
```

```
> f.list <- showMethods(classes="Rle", printTo=FALSE)  
> length(sapply(strsplit(f.list[grep("Function",  
+ f.list)], ' '), function(l){gsub('\\ |: ', '', l[[2]])}))
```

```
[1] 111
```

# Infrastructure methods, some examples

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

**Arithmetic**  $+$ ,  $-$ ,  $*$ ,  $'\%\%', \%/ \%, /$

**Compare**  $==$ ,  $>$ ,  $<$ ,  $!=$ ,  $<=$ ,  $>=$

**Logic**  $\&$ ,  $|$

**Math**  $\text{abs}$ ,  $\text{sign}$ ,  $\text{sqrt}$ ,  $\text{ceiling}$ ,  $\text{floor}$ ,  $\text{trunc}$ ,  $\text{cummax}$ ,  $\text{cummin}$ ,  
 $\text{cumprod}$ ,  $\text{cumsum}$ ,  $\log$ ,  $\log_{10}$ ,  $\log_2$ ,  $\log_{1p}$ ,  $\text{acos}$ ,  $\text{acosh}$ ,  $\text{asin}$ ,  
 $\text{asinh}, \dots$

**Math2**  $\text{round}$ ,  $\text{signif}$

**Summary**  $\text{max}$ ,  $\text{min}$ ,  $\text{range}$ ,  $\text{prod}$ ,  $\text{sum}$ ,  $\text{any}$ ,  $\text{all}$



# Looks intimidating

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Still the point is:

whenever you think about a functionality, it probably already exists.

# Example 1: coverage

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Coverage calculation

```
> require("ShortRead")
> fl<-system.file("extdata", "GSM424494_wt_G2_orc_chip_rep1_S288C_14.mapview.txt.gz",
+                 package="EatonEtAlChIPseq")
> aln<-readAligned(fl,type="MAQMapview")
> cover<-coverage(aln);cover
> cover[["S288C_14"]]
> head(runValue(cover[["S288C_14"]]))
> as.integer(cover[["S288C_14"]])
> smoothCover<-round(runmean(cover,75,endrule="constant"))
> class(smoothCover)
> smoothCover
```

# Example 2: slice

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Finding wide regions with elevated coverage

```
> islands<-slice(smoothCover,lower=10)
> islandsWithWidePeaks<- islands[vienMaxs(islands)>=20L &width(islands)>=500L]
> islandsWithWidePeaks
```

# What comes on top of IRanges

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

We've "covered" **IRanges** and it's low level capabilities.

Still, High Throughput methods in biology, especially sequencing, are more about sequences than maths.

Therefore the **Biostrings** package, build on top of IRanges



# Biostrings

All the classes in that package derives from the XString class

```
> require(Biostrings)
> getClass("XString")
```

Virtual Class "XString" [package "Biostrings"]

Slots:

Name:	shared	offset	length	elementMetadata
Class:	SharedRaw	integer	integer	DataTableORNULL

Name:	metadata
Class:	list

Extends:

Class "XRaw", directly  
Class "XVector", by class "XRaw", distance 2  
Class "Vector", by class "XRaw", distance 3  
Class "Annotated", by class "XRaw", distance 4

Known Subclasses: "BString", "DNAString", "RNAString", "AAString"

There are 4 subclasses:

**BString**: store strings without alphabet

**DNAString**: store strings with an DNA alphabet

**RNAString**: store strings with an RNA alphabet

# An DNAString example

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

The **Biostring** package contains many example datasets

```
> data(package="Biostrings")
> data(yeastSEQCHR1)
> class(yeastSEQCHR1)

[1] "character"

> nchar(yeastSEQCHR1)

[1] 230208

> DNAString(yeastSEQCHR1)

230208-letter "DNAString" instance
seq: CCACACCACACCCACACCCACACACCACACCACA...GGTGTGTGGGTGTGGTGTGGGTGTGGTGTGTGTGGG
```

The obtained DNAString is defined by the DNA alphabet

```
> alphabet(DNAString(yeastSEQCHR1))

[1] "A" "C" "G" "T" "M" "R" "W" "S" "Y" "K" "V" "H" "D" "B" "N" "-" "+" "."
```

# The alphabets

## The **Biostring** package implements the possible alphabets

```
> GENETIC_CODE
```

```
TTT TTC TTA TTG TCT TCC TCA TCG TAT TAC TAA TAG TGT TGC TGA TGG CTT CTC CTA CTG
"F"  "F"  "L"  "L"  "S"  "S"  "S"  "S"  "Y"  "Y"  "*"  "*"  "C"  "C"  "*"  "W"  "L"  "L"  "L"  "L"
CCT CCC CCA CCG CAT CAC CAA CAG CGT CGC CGA CGG ATT ATC ATA ATG ACT ACC ACA ACG
"P"  "P"  "P"  "P"  "H"  "H"  "Q"  "Q"  "R"  "R"  "R"  "R"  "I"  "I"  "I"  "M"  "T"  "T"  "T"  "T"
AAT AAC AAA AAG AGT AGC AGA AGG GTT GTC GTA GTG GCT GCC GCA GCG GAT GAC GAA GAG
"N"  "N"  "K"  "K"  "S"  "S"  "R"  "R"  "V"  "V"  "V"  "V"  "A"  "A"  "A"  "A"  "D"  "D"  "E"  "E"
GGT GGC GGA GGG
"G"  "G"  "G"  "G"
```

```
> AMINO_ACID_CODE
```

```
      A      R      N      D      C      Q      E      G      H      I      L      K      M
"Ala" "Arg" "Asn" "Asp" "Cys" "Gln" "Glu" "Gly" "His" "Ile" "Leu" "Lys" "Met"
      F      P      S      T      W      Y      V      U      O      B      Z      X
"Phe" "Pro" "Ser" "Thr" "Trp" "Tyr" "Val" "Sec" "Pyl" "Asx" "Glx" "Xaa"
```

```
> RNA_GENETIC_CODE
```

```
UUU UUC UUA UUG UCU UCC UCA UCG UAU UAC UAA UAG UGU UGC UGA UGG CUU CUC CUA CUG
"F"  "F"  "L"  "L"  "S"  "S"  "S"  "S"  "Y"  "Y"  "*"  "*"  "C"  "C"  "*"  "W"  "L"  "L"  "L"  "L"
CCU CCC CCA CCG CAU CAC CAA CAG CGU CGC CGA CGG AUU AUC AUA AUG ACU ACC ACA ACG
"P"  "P"  "P"  "P"  "H"  "H"  "Q"  "Q"  "R"  "R"  "R"  "R"  "I"  "I"  "I"  "M"  "T"  "T"  "T"  "T"
AAU AAC AAA AAG AGU AGC AGA AGG GUU GUC GUA GUG GCU GCC GCA GCG GAU GAC GAA GAG
"N"  "N"  "K"  "K"  "S"  "S"  "R"  "R"  "V"  "V"  "V"  "V"  "A"  "A"  "A"  "A"  "D"  "D"  "E"  "E"
GGU GGC GGA GGG
"G"  "G"  "G"  "G"
```

```
> IUPAC_CODE_MAP
```

```
      A      C      G      T      M      R      W      S      Y      K      V
"A"    "C"    "G"    "T"    "AC"    "AG"    "AT"    "CG"    "CT"    "GT"    "ACG"
      H      D      B      N
```

# Set of Strings

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## XStrings and subclasses instances can all be grouped into Sets

```
> names(completeSubclasses(getClass("XStringSet")))
```

```
[1] "BStringSet"           "DNAStringSet"
[3] "RNAStringSet"        "AAStringSet"
[5] "QualityScaledXStringSet" "XStringQuality"
[7] "QualityScaledBStringSet" "QualityScaledDNAStringSet"
[9] "QualityScaledRNAStringSet" "QualityScaledAAStringSet"
[11] "QualityScaledBStringSet" "QualityScaledDNAStringSet"
[13] "QualityScaledRNAStringSet" "QualityScaledAAStringSet"
[15] "PhredQuality"         "SolexaQuality"
[17] "IlluminaQuality"
```

Again, there are data examples within the **Biostring** package to play with

```
> data(srPhiX174)
> class(srPhiX174)
```

```
[1] "DNAStringSet"
attr(,"package")
[1] "Biostrings"
```

```
> head(srPhiX174)
```

```
A DNAStringSet instance of length 6
width seq
```

```
[1] 35 GTTATTATACCGTCAAGGACTGTGTGACTATTGAC
[2] 35 GGTGGTTATTATACCGTCAAGGACTGTGTGACTAT
[3] 35 TACCGTCAAGGACTGTGTGACTATTGACGCTCTC
[4] 35 GTACGCCGGCAATAATGTTTATGTTGGTTTCATG
[5] 35 GGTTTCATGGTTTGGTCTAACTTTACCGCTACTAA
[6] 35 GGGCAATAATGTTTATGTTGGTTTCATGGTTTGGT
```



# XString Methods

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Basic utilities

subsequence selection

subseq, Views, narrow (XStringSet, IRanges package)

letter frequencies

alphabetFrequency, dinucleotideFrequency (tri..., oligo...),  
uniqueLetters

letter consensus

consensusMatrix, consensusString

letter transformation

reverse, complement, reverseComplement, translate, chartr

Input/Output

read.DNAStringSet (...B...,...RNA...,...AA..)

write.XStringSet, save.XStringSet

# Xstrings Methods (c'ed)

## Advanced

**alignment utilities:** pairwiseAlignment, stringDist

## string matching

(v)matchPDict ( on a reference or a reference set (v))

(v)matchPDict, (v)countPDict,(v)whichPDict

matchPattern

(v)matchPattern,(v)countPattern, neditStartingAt,

neditEndingAt, (which.) isMatchingStartingAt,

(which.)isMatchingEndingAt

matchPWM(Position Weight Matrix, e.g. for transcription factor binding sites)

matchPWM,countPWM

## Others

matchLRPatterns, trimLRPatterns, matchProbePair

# Example 1: Letter/ alphabet frequencies

## Single-letter frequencies

```
> alphabetFrequency(DNAString(yeastSEQCHR1))
```

	A	C	G	T	M	R	W	S	Y	K	V	H	D
69830	44643	45765	69970	0	0	0	0	0	0	0	0	0	0
	B	N	-	+	.								
0	0	0	0	0	0								

```
> alphabetFrequency(DNAString(yeastSEQCHR1),baseOnly=TRUE)
```

	A	C	G	T	other
69830	44643	45765	69970	0	0

## Multi-letter frequencies

```
> dinucleotideFrequency(DNAString(yeastSEQCHR1))
```

	AA	AC	AG	AT	CA	CC	CG	CT	GA	GC	GG	GT	TA
23947	12493	13621	19769	15224	9218	7089	13112	14478	8910	9438	12938	16181	
	TC	TG	TT										
14021	15617	24151											

```
> head(trinucleotideFrequency(DNAString(yeastSEQCHR1)),20)
```

	AAA	AAC	AAG	AAT	ACA	ACC	ACG	ACT	AGA	AGC	AGG	AGT	ATA	ATC	ATG	ATT
8576	4105	4960	6306	3924	2849	2186	3534	4537	2680	2707	3697	5242	3849	4294	6384	
	CAA	CAC	CAG	CAT												
5147	2722	3091	4264													

```
> head(trinucleotideFrequency(DNAString(yeastSEQCHR1),6),14)
```

# Example 2: String manipulation

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Standard transformations

```
> head(narrow(srPhiX174,1,9))
```

```
A DNAStringSet instance of length 6  
width seq
```

```
[1] 9 GTTATTATA  
[2] 9 GGTGGTTAT  
[3] 9 TACCGTCAA  
[4] 9 GTACGCCGG  
[5] 9 GGTTTCATG  
[6] 9 GGGCAATAA
```

```
> head(reverse(narrow(srPhiX174,1,9)))
```

```
A DNAStringSet instance of length 6  
width seq
```

```
[1] 9 ATATTATTG  
[2] 9 TATTGGTGG  
[3] 9 AACTGCCAT  
[4] 9 GGCCGCATG  
[5] 9 GTACTTTGG  
[6] 9 AATAACGGG
```

```
> head(reverseComplement(narrow(srPhiX174,1,9)))
```

```
A DNAStringSet instance of length 6  
width seq
```

```
[1] 9 TATAATAAC  
[2] 9 ATAACCACC  
[3] 9 TTGACGGTA  
[4] 9 CCGGCGTAC  
[5] 9 CATGAAACC  
[6] 9 TTATTGCCC
```

```
> head(translate(narrow(srPhiX174,1,9)))
```

```
A AAStringSet instance of length 6  
width seq
```

```
[1] 3 VII  
[2] 3 GGY  
[3] 3 YRQ  
[4] 3 VRR  
[5] 3 GFM  
[6] 3 GQ*
```

# Example 2: String manipulation

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Bisulffite transformation

```
> alphabetFrequency(chartr("C","T", DNASTring(yeastSEQCHR1)),baseOnly=TRUE)
```

	A	C	G	T	other
69830		0	45765	114613	0

```
> alphabetFrequency(DNASTring(yeastSEQCHR1),baseOnly=TRUE)
```

	A	C	G	T	other
69830	44643	45765	69970		0

# Example 3: Consensus

## Consensus matrix

```
> snippet<-subseq(head(sort(srPhiX174),5),1,10);snippet
```

```
A DNAStringSet instance of length 5  
width seq
```

```
[1] 10 AAATAATGTT  
[2] 10 AACGTTATAT  
[3] 10 AAGGAATGTG  
[4] 10 AAGGACTGTG  
[5] 10 AAGGACTGTG
```

```
> consensusMatrix(snippet,baseOnly=TRUE)
```

	[,1]	[,2]	[,3]	[,4]	[,5]	[,6]	[,7]	[,8]	[,9]	[,10]
A	5	5	1	0	4	2	1	0	1	0
C	0	0	1	0	0	2	0	0	0	0
G	0	0	3	4	0	0	0	4	0	3
T	0	0	0	1	1	1	4	1	4	2
other	0	0	0	0	0	0	0	0	0	0

## Consensus string

```
> consensusString(snippet)
```

```
[1] "AAGGAMTGTK"
```

```
> consensusString(snippet,ambiguity="N",threshold=0.5)
```

```
[1] "AAGGANTGTG"
```

```
> ?consensusString
```

# Example 4: String Matching

## Match counting

```
> data(phiX174Phage)
> phiX174Phage

A DNASTringSet instance of length 6
      width seq                      names
[1]  5386 GAGTTTTATCGCTTCCATGACGC...ATGATTGGCGTATCCAACCTGCA Genbank
[2]  5386 GAGTTTTATCGCTTCCATGACGC...ATGATTGGCGTATCCAACCTGCA RF70s
[3]  5386 GAGTTTTATCGCTTCCATGACGC...ATGATTGGCGTATCCAACCTGCA SS78
[4]  5386 GAGTTTTATCGCTTCCATGACGC...ATGATTGGCGTATCCAACCTGCA Bull
[5]  5386 GAGTTTTATCGCTTCCATGACGC...ATGATTGGCGTATCCAACCTGCA G97
[6]  5386 GAGTTTTATCGCTTCCATGACGC...ATGATTGGCGTATCCAACCTGCA NEB03

> genome<- phiX174Phage[["NEB03"]]
> negPhiX174<- reverseComplement(srPhiX174)
> posCounts<- countPDict(PDict(srPhiX174),genome)
> negCounts<- countPDict(PDict(negPhiX174),genome)
> table(posCounts,negCounts)

      negCounts
posCounts    0
0      1030
1         83
```

# Example 4: String Matching

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

So we have 1030 reads that do not align either way to the genome and only 83 aligning.

The match locations can be found using:

```
[[2]] IRanges of length 1 start end width [1] 2746 2780 35
```

```
[[3]] IRanges of length 1 start end width [1] 2757 2791 35
```

```
... <80 more elements>
```



# Example 5: Pairwise alignment

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## alignment scores

```
> posScore <- pairwiseAlignment(srPhiX174, genome, type="global-local", scoreOnly=TRUE)
> negScore <- pairwiseAlignment(negPhiX174, genome, type="global-local", scoreOnly=TRUE)
> which(pmin(posScore)<pmin(negScore))
```

```
[1] 932
```

## alignment

```
> pairwiseAlignment(srPhiX174[932],genome,type="global-local")
```

```
Global-Local PairwiseAlignmentsSingleSubject (1 of 1)
pattern: [1] GCAATAACCTTGCGAGTCATTCTTTGATTGGTC
subject: [2804] GCAATAATGTTTATGTTGGTTTCATGG-TTTGGTC
score: -33.31176
```

```
> pairwiseAlignment(negPhiX174[932],genome,type="global-local")
```

```
Global-Local PairwiseAlignmentsSingleSubject (1 of 1)
pattern: [1] GACCAAATCAAAGAAATGACTCGCAAGGTTATTGC
subject: [3666] GACCAAATCAAAGAAATGACTCGCAAGGTTAGTGC
score: 61.4804
```

# What next?

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

We now have seen how to deal with biologically meaningful intervals and objects.

Many organism have been sequenced and their genome is know.

An interface in R to easily acces and manipulate such information would be very useful; this is the **BSgenome** package.

# BSgenome

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

**BSgenome**

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges


Rsamtools

ShortRead

Conclusions

Other

It is not just a data package; it leverages the functionalities introduced in **Biostrings**



# Available genomes

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

**BSgenome**

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Easy to find out

```
> require(BSgenome)
> head(available.genomes())

[1] "BSgenome.Alyrata.JGI.v1"
[2] "BSgenome.Amelliifera.BeeBase.assembly4"
[3] "BSgenome.Amelliifera.UCSC.apiMel2"
[4] "BSgenome.Amelliifera.UCSC.apiMel2.masked"
[5] "BSgenome.Athaliana.TAIR.04232008"
[6] "BSgenome.Athaliana.TAIR.TAIR9"
```

However, large genomes(i.e. human, mouse, ... ) packages might take log to transfer.

# BSgenome Class overview (c'ed)

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Important:

proper S4 class usage ban  
accessing a slot through the  
“@” accessor, except within a  
package scope.

Hence, it is nowhere to be  
seen on the present slide

```
> library(BSgenome.Dmelanogaster.UCSC.dm3)
> # Dmelanogaster@seqs_dir
> #Dmelanogaster@mask_dir      ERROR
> #dir(Dmelanogaster@mask_dir)
```

# BSgenome methods

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

**Sequence selection:** `[[, $`

**Subsequence selection:** `getSeq`

**Accessors:** `length`, `names/seqnames`, `mseqnames`, `seqlengths`,  
`masknames`, `sourceUrl`

**Matching:** all Biostrings methods

**SNPs:** `injectSNPs`, `SNPlocspkgenome`, `SNPcount`, `SNPlocs`

# Sequence information

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## operation that do not load sequences

```
> require(BSgenome.Dmelanogaster.UCSC.dm3)
> head(seqnames(Dmelanogaster))

[1] "chr2L" "chr2R" "chr3L" "chr3R" "chr4"  "chrX"

> head(seqlengths(Dmelanogaster))

      chr2L      chr2R      chr3L      chr3R      chr4      chrX
23011544 21146708 24543557 27905053 1351857 22422827
```

## operation that do

```
> alphabetFrequency(Dmelanogaster[["chr4"]],baseOnly=TRUE)

      A      C      G      T  other
430227 238155 242039 441336    100
```





# Extending Biostrings. Example 1

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Applying the Biostrings matching functions:

```
> exclude<-setdiff(seqnames(Hsapiens),c("chr1","chr2"))  
> vcountPattern("ACYTANCAGT", Hsapiens, fixed=c(pattern=FALSE, subject=TRUE), exclude=exclude)
```

	seqname	strand	count
1	chr1	+	1546
2	chr1	-	1545
3	chr2	+	1722
4	chr2	-	1684

```
> #vmatchPattern("ACYTANCAGT",Hsapiens, fixed=c(pattern=FALSE, subject=TRUE), exclude=exclude)  
> #asRangedData=FALSE)
```

# Example 2

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Using a Pattern Dictionary, e.g. a library of microarray probes

```
> library(hgu95av2probe)
> probes<-DNASTringSet(hgu95av2probe$sequence[1:100])
> probes[1:10]
```

```
      A DNASTringSet instance of length 10
      width seq
[1]    25 TGGCTCCTGCTGAGGTCCCCCTTTCC
[2]    25 GGCTGTGAATTCCTGTACATATTC
[3]    25 GCTTCAATTCCATTATGTTTAAATG
[4]    25 GCCGTTTGACAGAGCATGCTCTGCG
[5]    25 TGACAGAGCATGCTCTGCGTTGTTG
[6]    25 CTCTGCGTTGTTGGTTTACCAGCT
[7]    25 GGTTCACCAGCTTCTGCCCTCACA
[8]    25 TTCTGCCCTCACATGCACAGGGATT
[9]    25 CCTCACATGCACAGGGATTTAACAA
[10]   25 TCCTTGGTACTCTGCCCTCCTGTCA
```

# Example 2

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

```
> counts<-vcountPDict(probes,Hsapiens,exclude=exclude);counts
```

```
DataFrame with 400 rows and 4 columns
```

	seqname	strand	index	count
	<Rle>	<Rle>	<integer>	<Rle>
1	chr1	+	1	0
2	chr1	+	2	0
3	chr1	+	3	0
4	chr1	+	4	0
5	chr1	+	5	0
...	...	...	...	...
396	chr2	-	96	0
397	chr2	-	97	0
398	chr2	-	98	0
399	chr2	-	99	0
400	chr2	-	100	0

```
> #whichMatch<-seqselect(counts$index,counts$count>0);whichMatch No existeix seqselect!!  
> #matchedProbes<- probes[WhichMatch];matchedProbes  
> #matchLocs<-matchPDict(PDict(matchedProbes),Hsapiens$chr2);matchLocs  
> #extractAllMatches(Hsapiens$chr2,matchLocs)
```

# Example 5

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

A new interesting feature is the possibility to inject SNPs!

```
> cat(available.SNPs(),sep="\n")

SNPlocs.Hsapiens.dbSNP.20090506
SNPlocs.Hsapiens.dbSNP.20100427
SNPlocs.Hsapiens.dbSNP.20101109
SNPlocs.Hsapiens.dbSNP.20110815
SNPlocs.Hsapiens.dbSNP.20111119
SNPlocs.Hsapiens.dbSNP.20120608

> library("SNPlocs.Hsapiens.dbSNP.20090506")
> HsWithSNPs<-injectSNPs(Hsapiens,
+   "SNPlocs.Hsapiens.dbSNP.20090506")
>
>
```

# Example 5

```
> HsWithSNPs
```

```
Human genome
```

```
|  
| organism: Homo sapiens (Human)  
| provider: UCSC  
| provider version: hg19  
| release date: Feb. 2009  
| release name: Genome Reference Consortium GRCh37  
| with SNPs injected from package: SNPlocs.Hsapiens.dbSNP.20090506
```

```
|  
| single sequences (see '?seqnames'):
```

```
| chr1 chr2 chr3  
| chr4 chr5 chr6  
| chr7 chr8 chr9  
| chr10 chr11 chr12  
| chr13 chr14 chr15  
| chr16 chr17 chr18  
| chr19 chr20 chr21  
| chr22 chrX chrY  
| chrM chr1_gl000191_random chr1_gl000192_random  
| chr4_ctg9_hap1 chr4_gl000193_random chr4_gl000194_random  
| chr6_apd_hap1 chr6_cox_hap2 chr6_dbb_hap3  
| chr6_mann_hap4 chr6_mcf_hap5 chr6_qb1_hap6  
| chr6_ssto_hap7 chr7_gl000195_random chr8_gl000196_random  
| chr8_gl000197_random chr9_gl000198_random chr9_gl000199_random  
| chr9_gl000200_random chr9_gl000201_random chr11_gl000202_random  
| chr17_ctg5_hap1 chr17_gl000203_random chr17_gl000204_random  
| chr17_gl000205_random chr17_gl000206_random chr18_gl000207_random  
| chr19_gl000208_random chr19_gl000209_random chr21_gl000210_random
```

# What next?

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Now that we can access genomic information, it would be useful to import the related annotation. That's (one of) the purpose of the following packages:

**rtracklayer**

**GenomicFeatures**

**biomaRt**

**genomeIntervals**

**rtracklayer** offers export function too and as already presented, **genomeIntervals** offers interval utilities similar to **IRanges**

# rtracklayer

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

**rtracklayer**

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other


rtracklayer



BSgenome



Biostrings



IRanges

# Methods

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

There are two high level methods

`import`

`export`

Both accept the following formats:

BED: `bed`, `bedGraph`, `bed15`

GFF: `gff1`, `2` and `3`

WIG

`export` works with *RangedData* objects

`import` returns a *RangedData* object or *GRanges* object,  
depending on the `(asRangedData)` boolean argument.



# Methods (c'ed)

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

When exporting

The naming convention of the *RangedData* column names is crucial.

The following column names

**names:** for exporting the feature names

**scores:** for exporting the feature scores

**strand:** for exporting the feature strands


**see** ?export.bed for the complete details

# GenomicFeatures

management of transcript information

using **GenomicRanges**

stored into SQLite databases



# Constructors and Class

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## makeTranscriptDbFromBiomart

## makeTranscriptDbFromUCSC

```
> library(GenomicFeatures)
> head(supportedUCSCTables())
```

	track	subtrack
knownGene	UCSC Genes	<NA>
knownGeneOld3	Old UCSC Genes	<NA>
ccdsGene	CCDS	<NA>
refGene	RefSeq Genes	<NA>
xenoRefGene	Other RefSeq	<NA>
vegaGene	Vega Genes	Vega Protein Genes

```
> mm9KG<-makeTranscriptDbFromUCSC(genome="mm9",tablename="knownGene")
> saveFeatures(mm9KG,file="mm9KG.sqlite")
```

# Constructors and Class

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

```
> mm9KG<-loadFeatures("mm9KG.sqlite")
> mm9KG
```

```
TranscriptDb object:
| Db type: TranscriptDb
| Supporting package: GenomicFeatures
| Data source: UCSC
| Genome: mm9
| Organism: Mus musculus
| UCSC Table: knownGene
| Resource URL: http://genome.ucsc.edu/
| Type of Gene ID: Entrez Gene ID
| Full dataset: yes
| miRBase build ID: NA
| transcript_nrow: 55419
| exon_nrow: 246570
| cds_nrow: 213117
| Db created by: GenomicFeatures package from Bioconductor
| Creation time: 2014-06-06 11:29:23 +0200 (Fri, 06 Jun 2014)
| GenomicFeatures version at creation time: 1.16.0
| RSQLite version at creation time: 0.11.4
| DBSCHEMAVERSION: 1.0
```

# Extractors

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

ungrouped  
transcriptBy  
exonsBy  
intronsByTranscript  
fiveUTRsByTranscript  
threeUTRsByTranscript

# Extractors

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

```
> library(GenomicFeatures)
> txExons<-exonsBy(mm9KG)
> head(txExons)
```

```
GRangesList of length 6:
$1
```

```
GRanges with 8 ranges and 3 metadata columns:
```

	seqnames	ranges	strand	exon_id	exon_name	exon_rank
	<Rle>	<IRanges>	<Rle>	<integer>	<character>	<integer>
[1]	chr1	[4797974, 4798063]	+	1	<NA>	1
[2]	chr1	[4798536, 4798567]	+	2	<NA>	2
[3]	chr1	[4818665, 4818730]	+	3	<NA>	3
[4]	chr1	[4820349, 4820396]	+	4	<NA>	4
[5]	chr1	[4822392, 4822462]	+	5	<NA>	5
[6]	chr1	[4827082, 4827155]	+	6	<NA>	6
[7]	chr1	[4829468, 4829569]	+	7	<NA>	7
[8]	chr1	[4831037, 4832908]	+	9	<NA>	8

```
$2
```

```
GRanges with 9 ranges and 3 metadata columns:
```

	seqnames	ranges	strand	exon_id	exon_name	exon_rank
[1]	chr1	[4797974, 4798063]	+	1	<NA>	1
[2]	chr1	[4798536, 4798567]	+	2	<NA>	2
[3]	chr1	[4818665, 4818730]	+	3	<NA>	3
[4]	chr1	[4820349, 4820396]	+	4	<NA>	4
[5]	chr1	[4822392, 4822462]	+	5	<NA>	5
[6]	chr1	[4827082, 4827155]	+	6	<NA>	6
[7]	chr1	[4829468, 4829569]	+	7	<NA>	7
[8]	chr1	[4831037, 4831213]	+	8	<NA>	8
[9]	chr1	[4835044, 4836816]	+	10	<NA>	9

```
...
```

# Usage

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Overlapping with transcripts

`findOverlaps`

`countOverlaps`

`match`

`%in%`

`subsetByOverlaps`

More about these in the following part about **GenomicRanges**

# biomaRt

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

**biomaRt**

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Side note to get help from within R:

```
vignette("biomaRt",package="biomaRt")
```

biomaRt is an interface to the collection of databases that implements the bioMart software suite:

<http://biomart.org>

allow retrieval of huge datasets from different sources through a common interface

examples are: Ensembl, HapMap, Uniprot, ...



# biomaRt, an example

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Connect the mart database

```
> require(biomaRt)
> ensembl<- useMart("ensembl")
> head(listDatasets(ensembl))
```

	dataset	description
1	oanatinus_gene_ensembl	Ornithorhynchus anatinus genes (OANA5)
2	cporcellus_gene_ensembl	Cavia porcellus genes (cavPor3)
3	gaculeatus_gene_ensembl	Gasterosteus aculeatus genes (BROADS1)
4	lafricana_gene_ensembl	Loxodonta africana genes (loxAfr3)
5	itridecemlineatus_gene_ensembl	Ictidomys tridecemlineatus genes (spetri2)
6	choffmanni_gene_ensembl	Choloepus hoffmanni genes (choHof1)

version
1 OANA5
2 cavPor3
3 BROADS1
4 loxAfr3
5 spetri2
6 choHof1

```
> ensembl<- useMart("ensembl",dataset="dmelanogaster_gene_ensembl")
> head(listAttributes(ensembl))
```

	name	description
1	ensembl_gene_id	Ensembl Gene ID
2	ensembl_transcript_id	Ensembl Transcript ID
3	ensembl_peptide_id	Ensembl Protein ID
4	ensembl_exon_id	Ensembl Exon ID
5	description	Description
6	chromosome_name	Chromosome Name

# biomaRt, an example (c'ed)

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

**biomaRt**

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

query the database

```
> exon.annotation<-getBM(c("ensembl_gene_id","strand",  
+                           "chromosome_name","ensembl_exon_id",  
+                           "exon_chrom_start","exon_chrom_end"),  
+                           mart=ensembl,filters="chromosome_name",  
+                           values="4")
```

convert into a RangedData / Granges

# genomeIntervals

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Similar interval implementation to IRanges

(+) overall faster, gff function more robust to 'incorrect' format

(-) less integrated in R

Two classes:

Genome\_intervals

Genome\_intervals\_stranded

Methods

input

**readGff3**, **getGffAttributes**, parseGffAttributes

intervals utilities

interval\_overlap, **interval\_complement**, interval\_union,  
interval\_intersection

# What next?

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

We have seen how to get genomic sequences and their annotation


For processing NGS data, we are now missing the other half of the workflow: loading and manipulating the actual data. For this, three packages are available.

**GenomicRanges**

**Rsamtools**

**ShortRead**

# GenomicRanges



# Naive approach

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Genomic coordinates consist of  
chromosome  
position  
strand  
additional information  
GC content  
etc.

This can be represented by a `data.frame`  
fine for organism information ( $\sim 100k$  exons,  $20k$  genes)  
not for million of reads

# BIOC representation for intervals with data

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

*RangedData*

used by **rtracklayer**

interval grouped by chromosome/contig

strand unaware

*GRanges*

used by **GenomicFeatures**

intervals not required to be grouped by chromosome/contig

strand aware

*GRangesList* can hold exons with spliced transcripts

# GRanges constructor and slots

starts and ends defined in an *IRanges* object

strand, seqnames (chromosome) and seqlengths (chromosome size) to be provided

```
> grngs<-GRanges(seqnames=c("chr1","chr2","chr1"),
+               ranges=IRanges(start=c(3,4,1),end=c(7,5,3)),
+               strand=c("+","+","-"),seqlengths = c("chr1"=24,"chr2"=18))
> grngs
```

GRanges with 3 ranges and 0 metadata columns:

```
      seqnames      ranges strand
      <Rle> <IRanges> <Rle>
[1]      chr1      [3, 7]      +
[2]      chr2      [4, 5]      +
[3]      chr1      [1, 3]      -
---
```

```
seqlengths:
chr1 chr2
 24  18
```

additional slots can contain mtadata information

```
> getSlots("GRanges")
```

seqnames	ranges	strand	elementMetadata	seqinfo
"Rle"	"IRanges"	"Rle"	"DataFrame"	"Seqinfo"
metadata				
"list"				



# Interval operations

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Intra-interval

flank,resize,shift

Inter-interval

disjoin, gaps, reduce, range

coverage

Between intervals sets

union, intersect, setdiff

punion,pintersectm psetdiff

findOverlaps, countOverlaps, %in%, match

Low Level

start,end,width

# Other functions

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Selecting

seqselect, [

head, tail, window

subset, subsetByOverlaps

```
> grngs[strand(grngs)=="-"]
```

```
GRanges with 1 range and 0 metadata columns:
```

```
      seqnames      ranges strand  
      <Rle> <IRanges> <Rle>  
[1]      chr1      [1, 3]      -  
---
```

```
seqlengths:
```

```
chr1 chr2  
  24  18
```

```
> # seqselect(grngs,strand(grngs)=="-") NO EXISTEIX seqselect
```

# Example 1: Intra-interval

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## shift

```
> grngs
```

```
GRanges with 3 ranges and 0 metadata columns:
```

	seqnames	ranges	strand
	<Rle>	<IRanges>	<Rle>
[1]	chr1	[3, 7]	+
[2]	chr2	[4, 5]	+
[3]	chr1	[1, 3]	-

```
---
```

```
seqlengths:
```

chr1	chr2
24	18

```
> shift(grngs,1)
```

```
GRanges with 3 ranges and 0 metadata columns:
```

	seqnames	ranges	strand
	<Rle>	<IRanges>	<Rle>
[1]	chr1	[4, 8]	+
[2]	chr2	[5, 6]	+
[3]	chr1	[2, 4]	-

```
---
```

```
seqlengths:
```

chr1	chr2
24	18

## resize

```
> resize(grngs,10)
```

```
GRanges with 3 ranges and 0 metadata columns:
```

	seqnames	ranges	strand
	<Rle>	<IRanges>	<Rle>
[1]	chr1	[3, 12]	+
[2]	chr2	[4, 13]	+
[3]	chr1	[1, 3]	-

```
---
```

```
seqlengths:
```

chr1	chr2
24	18

## flank

```
> flank(grngs,2)
```

```
GRanges with 3 ranges and 0 metadata columns:
```

	seqnames	ranges	strand
	<Rle>	<IRanges>	<Rle>
[1]	chr1	[1, 2]	+
[2]	chr2	[2, 3]	+
[3]	chr1	[4, 5]	-

```
---
```

```
seqlengths:
```

chr1	chr2
24	18

# Overlap detection

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

*findOverlap* and *countOverlaps* produce a mapping and a tabulation of interval overlaps, respectively

```
> ol<-findOverlaps(grngs,reduce(grngs))  
> ol
```

Hits of length 3

queryLength: 3

subjectLength: 3

	queryHits	subjectHits
	<integer>	<integer>
1	1	1
2	2	3
3	3	2

# Rsamtools

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

**Rsamtools**



ShortRead

Conclusions


Other

Blue represents the "+" strand, red the "-" strand


Reduce



Gaps



Disjoin



# samtools and Rsamtools

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

**Rsamtools**

ShortRead

Conclusions

Other

## samtools

Data Format: SAM(text) and BAM (binary)

Tools: merge, sort, pileup, view, etc.

## Rsamtools

Reads and represents BAMfiles

high level: readAligned (type=BAM), readPileup

lower level: scanBam, scanBamParam, ScanBamWhat

utilities: countBam, sortBam, indexBam, filterBam,  
scanBamHeader

views: BamViews

# Input

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

readAligned returns an *alignedRead* class

described in the following section on **ShortRead**

scanBam returns a list of list i.e.. one list per column in the SAM file.

qname: a *BStringSet* containing the read id

seq: a *DNAStringSet* containing the read sequence

etc.

The possible fields can be found with scanBamWhat()

```
> require(Rsamtools)
> scanBamWhat()

[1] "qname"      "flag"      "rname"      "strand"     "pos"
[6] "qwidth"    "mapq"      "cigar"      "mrnm"       "mpos"
[11] "isize"     "seq"       "qual"       "groupid"    "mate_status"
```

scanBam is the function called by the **GenomicRanges**  
readGappedAlignments method

# Input (c'ed)

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

The input can be controlled using ScanBamParam  
it has three fields

**which:** *GRanges* selecting references, genomic loci, strand, ...

**flag:** use the SAM flag to selected paired, mapped, etc. reads.

```
> names(formals(scanBamFlag))  
  
[1] "isPaired"                "isProperPair"  
[3] "isUnmappedQuery"         "hasUnmappedMate"  
[5] "isMinusStrand"           "isMateMinusStrand"  
[7] "isFirstMateRead"         "isSecondMateRead"  
[9] "isNotPrimaryRead"        "isNotPassingQualityControls"  
[11] "isDuplicate"             "isValidVendorRead"
```

**what:** fields to retrieve (cf. scanBamWhat)



# GappedAlignments vs AlignedRead

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## *AlignedRead*

reads complete files

include sequence, quality, identifier, etc.

reads are assumed to be ungapped

## *GappedAlignments*

use scanBam

genomic coordinates, 'cigar', covered intervals

Cigar: an RLE; M(match), I (insertion), D (deletion), N (skipped), P (padding), S/H (soft/hard clip)

direct IRanges accessors (sub-setting, narrowing, coverage)

# BamViews

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

**Rsamtools**

ShortRead

Conclusions

Other

Access a set of experiments stored in BAM files  
for example to query a specific loci  
Check the vignette ("leeViews")  
Still very unstable!

# BamViews

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

```
> library(leeBamViews)
> bpaths=dir(system.file("bam",package="leeBamViews"),full=TRUE, patt="bam$")
> gt<- do.call(rbind, strsplit(basename(bpaths),"_"))[,1]
> geno<-substr(gt,1,nchar(gt)-1)
> lane<- substr(gt,nchar(gt),nchar(gt))
> pd=DataFrame(geno=geno, lane=lane, row.names=paste(geno,lane,sep="."))
> bs1=BamViews(bamPaths=bpaths, bamSamples=pd, bamExperiment=list(annotation="org.Sc.sgd.db"))
> bamPaths(bs1)
```

```
isowt.5
"/home/ueb/R/x86_64-pc-linux-gnu-library/3.1/leeBamViews/bam/isowt5_13e.bam"
isowt.6
"/home/ueb/R/x86_64-pc-linux-gnu-library/3.1/leeBamViews/bam/isowt6_13e.bam"
rlp.5
"/home/ueb/R/x86_64-pc-linux-gnu-library/3.1/leeBamViews/bam/rlp5_13e.bam"
rlp.6
"/home/ueb/R/x86_64-pc-linux-gnu-library/3.1/leeBamViews/bam/rlp6_13e.bam"
ssr.1
"/home/ueb/R/x86_64-pc-linux-gnu-library/3.1/leeBamViews/bam/ssr1_13e.bam"
ssr.2
"/home/ueb/R/x86_64-pc-linux-gnu-library/3.1/leeBamViews/bam/ssr2_13e.bam"
xrn.1
"/home/ueb/R/x86_64-pc-linux-gnu-library/3.1/leeBamViews/bam/xrn1_13e.bam"
xrn.2
"/home/ueb/R/x86_64-pc-linux-gnu-library/3.1/leeBamViews/bam/xrn2_13e.bam"
```

# BamViews

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

```
> bamSamples(bs1)
```

```
DataFrame with 8 rows and 2 columns
```

	geno	lane
	<character>	<character>
isowt.5	isowt	5
isowt.6	isowt	6
rlp.5	rlp	5
rlp.6	rlp	6
ssr.1	ssr	1
ssr.2	ssr	2
xrn.1	xrn	1
xrn.2	xrn	2

```
> sel<-GRanges(seqnames="Scchr13",IRanges(start=861250,end=863000),strand="+")
```

```
> # covex=RleList(lapply(bamPaths(bs1),function(x) coverage(readGappedAlignments(x))[[1]]))
```

# ShortRead

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals


GenomicRanges

Rsamtools

**ShortRead**

Conclusions

Other



# ShortRead

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

**ShortRead**

Conclusions

Other

## Input

read most sequence proprietary formats

read fastq

read BAM

## Exploration

contains sequence, quality, id, etc. information

## Manipulation

allow the manipulation of the fields with a limited memory impact

## Quality assessment

offers quality assessment functionalities

# AlignedReadClass

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## The main class to store the read information

```
> require(ShortRead)
> showClass("AlignedRead")
```

Class "AlignedRead" [package "ShortRead"]

Slots:

Name:	chromosome	position	strand	alignQuality
Class:	factor	integer	factor	QualityScore

Name:	alignData	quality	sread	id
Class:	AlignedDataFrame	QualityScore	DNASTringSet	BStringSet

Extends:

Class "ShortReadQ", directly

Class "ShortRead", by class "ShortReadQ", distance 2

Class ".ShortReadBase", by class "ShortReadQ", distance 3

All slots can be accessed through accordingly named accessors

# SRFilterclass

## Useful tools to filter the reads during or after the import

```
> showClass("SRFilter")
```

```
Class "SRFilter" [package "ShortRead"]
```

```
Slots:
```

```
Name:          .Data          name
Class:         function ScalarCharacter
```

```
Extends:
```

```
Class "function", from data part
```

```
Class ".SRUtil", directly
```

```
Class "OptionalFunction", by class "function", distance 2
```

```
Class "PossibleMethod", by class "function", distance 2
```

```
Class "expressionORfunction", by class "function", distance 2
```

```
Class "functionORNULL", by class "function", distance 2
```

## many already implemented

idFilter

chromosomeFilter

positionFilter

strandFilter

etc.



# Other classes

The package implements many classes to hold the different kind of data

```
> getClasses(wher="package:ShortRead")
```

[1] "AlignedDataFrame"	"AlignedRead"	"ArrayIntensity"
[4] "BAMQA"	"BowtieQA"	"ExperimentPath"
[7] "FastqFile"	"FastqFileList"	"FastqFileReader"
[10] "FastqQA"	"FastqQuality"	"FastqSampler"
[13] "FastqSamplerList"	"FastqStreamer"	"FastqStreamerList"
[16] "IntegerQuality"	"Intensity"	"IntensityInfo"
[19] "IntensityMeasure"	"MAQMapQA"	"MatrixQuality"
[22] "NumericQuality"	"QA"	".QA"
[25] ".QA2"	"QAAadapterContamination"	"QACollate"
[28] "QAData"	"QAFastqSource"	"QAFiltered"
[31] "QAFlagged"	"QAFrequentSequence"	"QANucleotideByCycle"
[34] "QANucleotideUse"	"QAQualityByCycle"	"QAQualityUse"
[37] "QAReadQuality"	"QASequenceUse"	"QASource"
[40] "QASummary"	"QualityScore"	".Roche"
[43] "RochePath"	"RocheSet"	"RtaIntensity"
[46] "SFastqQuality"	"ShortRead"	".ShortReadBase"
[49] "ShortReadFile"	"ShortReadQ"	"ShortReadQQA"
[52] "Snapshot"	"SnapshotFunction"	"SnapshotFunctionList"
[55] ".Solexa"	"SolexaExportQA"	"SolexaIntensity"
[58] "SolexaIntensityInfo"	"SolexaPath"	"SolexaRealignQA"
[61] "SolexaSet"	"SpTrellis"	"SRError"
[64] "SRFilter"	"SRFilterResult"	"SRList"
[67] "SRSet"	".SRUtil"	"SRVector"
[70] "SRWarn"	"trellis"	

# Input and accessor examples

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Simple walk through

```
> require("EatonEtAlChIPseq")
> fl<-system.file("extdata","GSM424494_wt_G2_orc_chip_rep1_S288C_14.mapview.txt.gz",package=
> aln<-readAligned(fl,type="MAQMapview");aln
```

```
class: AlignedRead
length: 478774 reads; width: 39 cycles
chromosome: S288C_14 S288C_14 ... S288C_14 S288C_14
position: 2 4 ... 784295 784295
strand: + - ... + +
alignQuality: IntegerQuality
alignData varLabels: nMismatchBestHit mismatchQuality nExactMatch24 nOneMismatch24
```

```
> head(sread(aln))
```

```
      A DNAStringSet instance of length 6
      width seq
[1] 39 CGGCTTTCTGACCGAAATTAAAAAAAAAAAAATGAAATG
[2] 39 GATTTATGAAAGAAATTAAAAAAAAAAAAATGAAATGAA
[3] 39 CTTTCTGACCGAAATTAAAAAAAAAAAAATGAAATGAAA
[4] 39 TTTCTGACCGAAATTAAAAAAAAAAAAATGAAATTGAAAC
[5] 39 TTTATGAAAGAAATTAATAAAAAAAAAAATGAAATGAAAC
[6] 39 TTTCTGAAAGAAATTAAAAAAAAAAAAATGAAATGAAAC
```

# Input and accessor examples

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## with filters

```
> filter<- compose(chromosomeFilter("S288C_14"),positionFilter(min=1,max=1000))
> alnF<-readAligned(fl,type="MAQMapView",filter=filter);alnF

class: AlignedRead
length: 715 reads; width: 39 cycles
chromosome: S288C_14 S288C_14 ... S288C_14 S288C_14
position: 2 4 ... 997 999
strand: + - ... - -
alignQuality: IntegerQuality
alignData varLabels: nMismatchBestHit mismatchQuality nExactMatch24 nOneMismatch24
```



# Manipulation example

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## For example to rename chromosome

```
> chrom<-chromosome(alnF)
> i<-sub("S288C_([[:digit:]]+)", "\\1", levels(chrom));i

[1] "14"

> levels(chrom)

[1] "S288C_14"

> levels(chrom)<-paste("chr",as.roman(i),sep="")
> levels(chrom)

[1] "chrXIV"

> alnF<-renew(alnF,chromosome=chrom);alnF

class: AlignedRead
length: 715 reads; width: 39 cycles
chromosome: chrXIV chrXIV ... chrXIV chrXIV
position: 2 4 ... 997 999
strand: + - ... - -
alignQuality: IntegerQuality
alignData varLabels: nMismatchBestHit mismatchQuality nExactMatch24 nOneMismatch24

>
```

# Quality assessment

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Many functions  
are available in  
**ShortRead** that  
can be used for  
performing QA

```
> f.list<-showMethods(  
+ where="package:ShortRead",  
+ printTo=FALSE)
```

```
> sapply(strsplit(f.list[grep("Function",f.list)],' '),  
+        function(x)x[2])  
  
[1] "alphabet"  
[3] "alphabetFrequency"  
[5] "annTrack"  
[7] "!"  
[9] "[["  
[11] "$"  
[13] "chromosome"  
[15] "coerce"  
[17] "to=\"OptionalFunction\""  
[19] "to=\"OptionalFunction\""  
[21] "countLines"  
[23] "dim"  
[25] "encoding"  
[27] "fac"  
[29] "FastqQuality"  
[31] "FastqStreamerList"  
[33] "files"  
[35] "functions"  
[37] "id"  
[39] "%in%"  
[41] "lapply"  
[43] "names<-"  
[45] "name"  
[47] "pan"  
[49] "phenoData"  
[51] "qa2"  
[53] "qa"  
[55] "read454"  
[57] "readBaseQuality"  
"alphabetByCycle"  
"alphabetScore"  
"append"  
"["  
"$<-"  
"c"  
"clean"  
"to=\"classGeneratorFunction\""  
"to=\"genericFunction\""  
"to=\"genericFunction\""  
"coverage"  
"dustyScore"  
"experimentPath"  
"FastqFileList"  
"FastqSamplerList"  
"FastqStreamer"  
"flag"  
"getTrellis"  
"ignore.strand"  
"laneNames"  
"length"  
"names"  
"narrow"  
"pData"  
"position"  
"QACollate"  
"rbind"  
"readAligned"  
"readFastqQual"
```

# QA example (yet another one...)

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

## Using independent functions

```
> abc<- alphabetByCycle(sread(alnF))  
> abc[1:4,1:12]
```


	cycle											
alphabet	[,1]	[,2]	[,3]	[,4]	[,5]	[,6]	[,7]	[,8]	[,9]	[,10]	[,11]	[,12]
A	239	246	251	236	244	244	223	207	184	212	217	230
C	197	172	180	178	169	194	192	194	202	212	185	182
G	103	88	87	105	89	93	108	101	114	90	103	83
T	176	209	197	196	213	184	192	213	215	201	210	220

```
> abc<-abc[1:4, ]  
> par(mfrow=c(1,2))  
> matplot(t(abc),type="l",lty=rep(1,4))  
> m<-as (quality(alnF),"matrix")  
> plot(colMeans(m),type="b")
```

All these and more are combined into the function: `qa()`

These can then be reported using the `report()` function

# Conclusion





# Conclusion

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

We have seen the two “branches” of the core packages:

the one used to get genomic sequence and annotation

the one used to load and manipulate NGS data

Actually, the cit is not so clear ad the packages of these two branches are interacting at different levels.

They provide numerous functionalities and are getting into a “production” (stable development) state.

Higher level packaages are being developed to wrap these functionalities into more user friendly packages.

# Conclusion

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

If you would start today using these packages:

go for the BAM format

go for GRanges objects

Be on the lookout, especially for the *SummarizedExperiment* class in the **GenomicRanges** package.

It is a concept similar to the *ExpressionSet* class developed for microarray and aims at normalizing the output of NGS experiments within R/Bioconductor

# If we were fast..

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Another couple of package to mention

Rsubread (only on linux)

easyRNASeq (self-promotion)

# Rsubread

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions


Other

a package to align  
short read in R!

If you have a  
session on vuori  
you can try that  
code slightly  
modified in the R  
file to use only  
chromosome 1

```
> ## write the human genome sequences
> writeXStringSet(Reduce(append,
+ lapply(seqnames(Hsapiens),
+ function(nam)
+ {dss<-DNASTringSet(unmasked(Hsapiens[[nam]]))
+ names(dss)<-nam
+ dss})),file="hg19.fa")
> ##create the indexes
> require(Rsubread)
> dir.create("indexes")
> buildindex(basename=file.path("indexes","hg19"),
+           reference="hg19.fa")
> ## align the reads
> supply(dir(pattern="*\\.gz$"),function(fil){
+   ## decompress the files
+   gunzip(fil)
+   ##align
+   align(index=file.path("indexes","hg19"),
+         readfile1=sub("\\.gz$", "",fil),
+         nsubreads=2, TH1=1,
+         output_file=sub("\\.fastq\\.gz$", "\\,sam",fil))
+   ## create bam files
+   asBAM(file=sib("\\.fastq\\.gz$", "\\,sam",fil),
+         destination=sub("\\.fastq\\.gz$", "",fil),
+         indexDestination=TRUE)
+ })
```

# easyRNASeq package



# Replicate comparison

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions


Other

The simplest output is a matrix

Comparing replicates is therefore easy

Can be done automatically if the user  
provides the sample information

GRAFIC



# Normalization

Bioconductor  
packages for  
short read  
analyses

Alex Sánchez

Introduction

Infrastructure  
packages

Biostrings

BSgenome

rtracklayer

GenomicFeatures

biomaRt

genomeIntervals

GenomicRanges

Rsamtools

ShortRead

Conclusions

Other

Three types can be applied

**Reads Per feature Kb per Milion**  
reads in the library

DESeq

based on Negative Binomial

fit a model to correct for the library  
sizes

edgeR

based on Negative Binomial

use a trimmed mean of M-values to  
correct for the library sizes

