

8 — PHY 494: Homework assignment (15 points total)

Due Thursday, March 29, 2018, 11:59pm.

Submission is to your **private GitHub repository**.

Read the following instructions carefully. Ask if anything is unclear.

1. `cd` into your assignment repository (change *YourGitHubUsername* to your GitHub username) and run the update script `./scripts/update.sh` (replace *YourGitHubUsername* with your GitHub username):

```
cd assignments-2018-YourGitHubUsername
bash ./scripts/update.sh
```

It should create three subdirectories¹ `assignment_08/Submission`, `assignment_08/Grade`, and `assignment_08/Work`.

2. You can try out code in the `assignment_08/Work` directory but you don't have to use it if you don't want to. Your grade with comments will appear in `assignment_08/Grade`.
3. Create your solution in `assignment_08/Submission`. Use Git to `git add` files and `git commit` changes.

You can create a PDF, a text file or Jupyter notebook inside the `assignment_08/Submission` directory as well as Python code (if required). **Name your files `hw08.pdf` or `hw08.txt` or `hw08.ipynb`**, depending on how you format your work. Files with code (if requested) should be named exactly as required in the assignment.

4. When you are ready to submit your solution, do a final `git status` to check that you haven't forgotten anything, commit any uncommitted changes, and `git push` to your GitHub repository. Check on *your* GitHub repository web page² that your files were properly submitted.

You can push more updates up until the deadline. Changes after the deadline will not be taken into account for grading.

Homeworks must be legible and intelligible or may otherwise be returned ungraded with 0 points.

8.1 Square-root with Newton's method (15 points)

The square root function³ $q(x)$ can be *defined* by the equation

$$q(x)^2 = x. \quad (1)$$

¹If the script fails, file an issue in the [Issue Tracker for PHY494-assignments-skeleton](#) and just create the directories manually.

²<https://github.com/ASU-CompMethodsPhysics-PHY494/assignments-2018-YourGitHubUsername>

³The symbol $\sqrt{\cdot}$ is commonly used to denote the operation of q , so that $q(x) \equiv \sqrt{x}$. For the following it is more useful to think of the square root as a special function than just a calculation.

The goal is to develop and to implement an **efficient algorithm to compute square roots**.

The defining equation Eq. 1 can be rearranged as

$$q(x)^2 - x = 0 \quad (2)$$

$$q^2 - x = 0 \quad (3)$$

$$f_x(q) = 0 \quad (4)$$

where $f_x(q) = q^2 - x$ is now considered a function of the *variable* q and a given *parameter* x . Finding the square root $q(x)$ amounts to finding the root of $f_x(q)$, i.e., find that value q that makes Eq. 3 true for a given x .

- (a) Use the iterative Newton-Raphson algorithm from the class to implement a function `sqrt(x, tol=1e-6, Nmax=100)` in a module `functions.py` that returns the square root of x to a tolerance of `tol` and uses at a maximum `Nmax` iterations. If `Nmax` is exceeded print a warning message and return `None`.⁴ Your code should guess a good starting value for the Newton-Raphson scheme, e.g., $x/2$.

In the Newton-Raphson scheme you have to calculate the update Δq to q in order to obtain the new best guess for the root

$$q \leftarrow q + \Delta q \quad (5)$$

with

$$\Delta q = -\frac{f_x(q)}{f'_x(q)} \quad (6)$$

In your code you may either use a finite difference scheme to calculate $f'_x(q)$ or (more efficiently), use the *analytical derivative* $f'_x(q) = 2q$ directly.⁵

Your code must produce correct results, as tested with `test_functions.py`.⁶ You can run these tests yourself with

```
pytest -v test_functions.py
```

(in the same directory as your `functions.py`). **[10 points]**

- (b) Show results for $x = 0, 0.456 \times 10^{-8}, 10^{-3}, 0.1, 0.64, 0.99, 1, 5, 9, 12.5, 10^3, 1.2345 \times 10^8$ for a tolerance of 10^{-6} . Put the results in a text file `sqrt.txt`. The results should be arranged so that each line contains x and $q(x)$. **[5 points]**

⁴In your code you may *not* use a library square root function such as `math.sqrt` or `numpy.sqrt` nor taking fractional powers such as `x**0.5` or `numpy.power(x, 0.5)`.

⁵Using the analytical derivatives makes for a handy algorithm to *manually* calculate square roots and indeed this is how Newton came up with the method. The algorithm for computing the square root was also already known to the ancient Babylonians.

⁶Some specific tests are allowed to fail and they are marked with `x` or `xfail` in the test output — this is ok.

Note: You don't have to submit any notebooks or written text for problems (a) and (b). It will be sufficient to submit

- `functions.py`
- `sqrt.txt`