

JAVA APPLICATION DEPLOYMENT IN MINIKUBE

Linux System Setup and Java Installation

```
sudo apt install fontconfig openjdk-17-jre
```

```
java -version
```

Jenkins Installation and Management

```
sudo service jenkins restart
```

```
sudo service jenkins status
```

For installation instructions: [Jenkins Installation Guide](#)

Docker Installation and Commands

```
sudo apt install docker.io -y
```

```
sudo service docker restart
```

```
sudo service docker status
```

```
sudo usermod -aG docker $USER
```

```
# Checking Docker Images and Containers
```

```
docker images
```

```
docker ps
```


```
# Fixing permission issues
```

```
sudo chmod 666 /var/run/docker.sock
```

Docker Compose Installation

```
sudo apt install docker-compose -y
```

```
sudo curl -L "https://github.com/docker/compose/releases/latest/download/docker-compose-$(uname -s)-$(uname -m)" -o /usr/local/bin/docker-compose
```



Kubernetes (K8s) Installation and Commands

Installing kubectl

```
curl -LO https://dl.k8s.io/release/v1.32.0/bin/linux/amd64/kubectl
```

```
sudo install -o root -g root -m 0755 kubectl /usr/local/bin/kubectl
```

```
chmod +x kubectl
```

```
mkdir -p ~/.local/bin
```

```
mv ./kubectl ~/.local/bin/kubectl
```

```
kubectl version --client
```

More details: [Install kubectl](#)

Installing Minikube

```
curl -LO https://github.com/kubernetes/minikube/releases/latest/download/minikube-linux-amd64
```

```
sudo install minikube-linux-amd64 /usr/local/bin/minikube && rm minikube-linux-amd64
```

```
minikube start
```

```
minikube status
```

Kubernetes Commands

Pod Management

Create a pod

```
kubectl run my-pod --image=nginx --port=80
```

View all pods

```
kubectl get pods
```

```
kubectl get pods -A
```

```
kubectl get pods -n kube-system
```

View pod details

```
describe pod <pod-name>
```

```
kubectl logs <pod-name>
```

```
kubectl exec <pod-name> -- <command>
```

YAML Configuration for a Pod

```
apiVersion: v1
```

```
kind: Pod
```

```
metadata:
```

```
  name: my-pod
```

```
  labels:
```

```
    app: my-web-app
```

```
    type: backend
```

```
spec:
```

```
  containers:
```

```
    - name: nginx-container
```

```
      image: nginx
```

```
      ports:
```

```
        - containerPort: 80
```

ReplicaSet Management

Create a ReplicaSet

```
kubectl create -f rs-test.yml
```

```
kubectl apply -f rs-test.yml
```

View ReplicaSets

```
kubectl get replicaset
```

```
kubectl get rs -o wide
```

Scale a ReplicaSet

```
kubectl scale replicaset <replicaset-name> --replicas=<desired-replica-count>
```

Delete a ReplicaSet

```
kubectl delete rs <replicaset-name>
```

```
kubectl delete -f rs-test.yml
```

ReplicaSet YAML Configuration

```
apiVersion: apps/v1
```

```
kind: ReplicaSet
```

```
metadata:
```

```
  name: my-rs
```

```
  labels:
```

```
    name: my-rs
```

```
spec:
```

```
  replicas: 4
```

```
  selector:
```

```
    matchLabels:
```

```
      apptype: web-backend
```

```
  template:
```

```
    metadata:
```

```
labels:
  apptype: web-backend
spec:
  containers:
  - name: my-app
    image: nginx
    ports:
    - containerPort: 8080
```

Deployment Management

Create a deployment

```
kubectl create deployment webnginx2 --image=nginx:latest --replicas=1
```

View deployments

```
kubectl get deployments
```

```
kubectl describe deploy <deployment-name>
```

Scale a deployment

```
kubectl scale deploy <deployment-name> --replicas=<desired-replica-count>
```

Delete a deployment

```
kubectl delete deploy <deployment-name>
```

```
kubectl delete -f web-deploy.yml
```

Deployment YAML Configuration

```
apiVersion: apps/v1
```

```
kind: Deployment
```

```
metadata:
```

```
  name: my-deploy
```

```
  labels:
```

```
    name: my-deploy
```

```
spec:
  replicas: 4
  selector:
    matchLabels:
      apptype: web-backend
  strategy:
    type: RollingUpdate
  template:
    metadata:
      labels:
        apptype: web-backend
    spec:
      containers:
        - name: my-app
          image: nginx
          ports:
            - containerPort: 7070
```

Service Management

View services

```
kubectl get svc
```

Create a service from YAML

```
kubectl create -f service.yml
```

Delete a service

```
kubectl delete svc <service-name>
```

Service YAML Configuration

```
apiVersion: v1
```

```
kind: Service
```

```
metadata:
  name: my-service
  labels:
    app: my-service
spec:
  type: NodePort
  ports:
    - port: 9000
      targetPort: 8080
      nodePort: 30002
  selector:
    apptype: web-backend
```

Namespace Management

Create a namespace

```
kubectl create namespace <namespace-name>
```

```
kubectl create ns my-bank
```

View namespaces

```
kubectl get ns
```

Switch to a namespace

```
kubectl config set-context --current --namespace=<namespace-name>
```

Automation using Jenkins push image from github to docker hub using jenkins automation:

The image shows a screenshot of a GitHub repository named 'webapp' by user 'ASWINPRABUSIVA'. The repository is public and has 1 branch and 0 tags. The commit history shows several updates to files like .mvn, src/main/webapp, target, .gitattributes, Dockerfile, jenkinsfile, and pom.xml. The Jenkinsfile is visible in the commit history, showing a pipeline for building and pushing the Docker image to Docker Hub.

The Jenkinsfile content is as follows:

```
1 pipeline {
2   agent any
3   tools {maven "maven"}
4   stages {
5     stage('SCM') {
6       steps {
7         git branch: 'main', url: 'https://github.com/ASWINPRABUSIVA/webapp.git'
8       }
9     }
10    stage('Build') {
11      steps {
12        sh 'mvn clean package'
13      }
14    }
15    stage('build to images') {
16      steps {
17        script {
18          sh 'docker build -t aswinprabusiva/webapp1 .'
19        }
20      }
21    }
22    stage('push to hub') {
23      steps {
24        script {
25          withDockerRegistry(credentialsId: 'docker_cred', toolName: 'docker', url: 'https://index.docker.io/v1/') {
26            sh 'docker push aswinprabusiva/webapp1'
27          }
28        }
29      }
30    }
31  }
32 }
```


Kubernetes Docker Jenkins SetDashboard [jenkins]

localhost:8080

Jenkins

aswinprabu log out

Dashboard

+ New Item

Build History

Project Relationship

Check File Fingerprint

Manage Jenkins

My Views

Build Queue

No builds in the queue.

Build Executor Status

(0 of 2 executors busy)

All

S	W	Name ↓	Last Success	Last Failure	Last Duration	
☁	☀	maven	N/A	N/A	N/A	▶
✔	☁	mvn	1 day 16 hr #10	1 day 16 hr #7	50 sec	▶
☁	☀	pipeline	N/A	N/A	N/A	▶

Icon: S M L

...

REST APIJenkins 2.492.2

Git

Repositories ?

Repository URL ?

https://github.com/ASWINPRABUSIVA/webapp



Credentials ?

ASWINPRABUSIVA/***** (github_crd)

+ Add

Advanced ▾

21-03-2025 09:26



Minikube installation and mysql:

[illegible]

Kubernetes, Namespace:

```

saran@FingerGripPC:~$ kubectl get pod
NAME                READY   STATUS    RESTARTS   AGE
my-deploy-6fc494dbf6-4mh4f    0/1     ErrImagePull    0           57s
saran@FingerGripPC:~$ kubectl delete all --all
pod "my-deploy-6fc494dbf6-4mh4f" deleted
service "kubernetes" deleted
service "my-service" deleted
deployment.apps "my-deploy" deleted
saran@FingerGripPC:~$ kubectl apply -f deployment.yml
deployment.apps/my-deploy created
service/my-service created
saran@FingerGripPC:~$ kubectl get pod
NAME                READY   STATUS    RESTARTS   AGE
my-deploy-6fc494dbf6-grn4n    1/1     Running      0           5s
saran@FingerGripPC:~$ kubectl get deploy
NAME                READY   UP-TO-DATE   AVAILABLE   AGE
my-deploy            1/1      1             1           12s
saran@FingerGripPC:~$ minikube service my-service

```

NAMESPACE	NAME	TARGET PORT	URL
default	my-service	8000	http://192.168.49.2:30007

```

* Starting tunnel for service my-service.

```

NAMESPACE	NAME	TARGET PORT	URL
default	my-service		http://127.0.0.1:43609

```

* Opening service default/my-service in default browser...
* http://127.0.0.1:43609
! Because you are using a Docker driver on linux, the terminal needs to be open to run it.
*C* Stopping tunnel for service my-service.
saran@FingerGripPC:~$ curl http://192.168.49.2:30007/maven-web-app
saran@FingerGripPC:~$ curl http://192.168.49.2:30007/maven-web-app/
<html>
<body>
<h2>Hello World!</h2>
</body>
</html>
saran@FingerGripPC:~$

```

Dashboard >

+ New Item

📅 Build History

👤 Project Relationship

🔍 Check File Fingerprint

⚙️ Manage Jenkins

📁 My Views

Build Queue

No builds in the queue.

Build Executor Status

(0 of 2 executors busy)

All

+

S	W	Name	Last Success	Last Failure	Last Duration
🟢	☁	javaapplication	21 hr #9	21 hr #8	46 sec
⋮	☀	maven	N/A	N/A	N/A
🟢	☁	mvn	2 days 21 hr #10	2 days 21 hr #7	50 sec
⋮	☀	pipeline	N/A	N/A	N/A

Icons: S M L

Add description

REST API Jenkins 2.492.2

Dashboard > javaapplication > Configuration

Configure

⚙️ General

🕒 Triggers

📜 Pipeline

🔧 Advanced

Define your Pipeline using Groovy directly or pull it from source control.

Definition

Pipeline script

Script ?

```
1 pipeline {
2   agent any
3   tools { maven "maven" }
4   stages {
5     stage('SCM') {
6       steps {
7         git branch: 'main', url: 'https://github.com/ASWINPRABUSIVA/webapp.git'
8       }
9     }
10    stage('Build-clean') {
11      steps {
12        sh 'mvn clean'
13      }
14    }
15    stage('Build-validate') {
16      steps {
17        sh 'mvn validate'
18      }
19    }
20    stage('Build-com') {
21      steps {
22        sh 'mvn compile'
23      }
24    }
25    stage('Build-test') {
26      steps {
27        sh 'mvn test'
28      }
29    }
30    stage('Build-pac') {
31      steps {
32        sh 'mvn package'
33      }
34    }
35    stage('Build to images') {
36      steps {
37        script {
38          sh 'docker build -t aswinprabusiva/webapp1 .'
39        }
40      }
41    }
42  }
43 }
```

Save

Apply

Dashboard > javaapplication > Configuration

Configure

General

Triggers

Pipeline

Advanced

```
12      sh 'mvn clean'
13    }
14  }
15  stage('Build-validate') {
16    steps {
17      sh 'mvn validate'
18    }
19  }
20  stage('Build-com') {
21    steps {
22      sh 'mvn compile'
23    }
24  }
25  stage('Build-test') {
26    steps {
27      sh 'mvn test'
28    }
29  }
30  stage('Build-pac') {
31    steps {
32      sh 'mvn package'
33    }
34  }
35  stage('Build to images') {
36    steps {
37      script {
38        sh 'docker build -t aswinprabusiva/webappl .'
39      }
40    }
41  }
42  stage('Push to hub') {
43    steps {
44      script {
45        withDockerRegistry(credentialsId: 'docker_cred', toolName: 'docker', url: 'https://index.docker.io/v1/') {
46          sh 'docker push aswinprabusiva/webappl'
47        }
48      }
49    }
50  }
51  stage('Deploy to Kubernetes') {
52    steps {
53      withKubeConfig(caCertificate: '', clusterName: 'minikube', contextName: 'minikube', credentialsId: 'minikube_cred', name: 'minikube') {
54        sh 'kubectl apply -f dep.yml --validate=false'
55      }
56    }
57  }
58 }
59 }
60 }
```

Save Apply

Dashboard > javaapplication >

Status

Changes

Build Now

Configure

Delete Pipeline

Full Stage View

Stages

Rename

Pipeline Syntax

✓ javaapplication

Add description

Stage View

Average stage times:
(full run time: ~46s)

	Declarative: Tool Install	SCM	Build- clean	Build- validate	Build- com	Build- test	Build- pac	Build to images	Push to hub	Deploy to Kubernetes
1602	101ms	6s	2s	1s	2s	2s	2s	3s	23s	558ms
1557	188ms	1s	2s	1s	2s	2s	2s	3s	1 min 7s	1s failed

Permalinks

- Last build (#9), 21 hr ago
- Last stable build (#9), 21 hr ago
- Last successful build (#9), 21 hr ago
- Last failed build (#8), 21 hr ago
- Last unsuccessful build (#8), 21 hr ago

BUILDS

Filter

March 21, 2025

✓ #9 10:32 AM

✗ #8 10:27 AM

Output:

