

Data Handling: Import, Cleaning and Visualisation

Exercise/Workshop 3: Programming with Data

Ulrich Matter

24/10/2021

Exercises

Exercise A: Write a Sum Function

In the lecture on Programming with Data, we have discussed the most basic programming concepts in R. Among other things, you have learned how we can use for-loops to sum up numbers stored in a numeric vector.

1. Use the code example in the respective lecture notes and the following empty function construct to implement a function that takes a numeric vector as input and returns the sum of the vector's elements.

```
my_sum <-  
  function(x){  
  
  }
```

2. Define the vector `numbers = c(1, 2, 3)`. Then, compare your function `my_sum()` with the `sum()` function (the pre-implemented sum function in R) when using `numbers` as the input argument: Do you get the same output for `my_sum(numbers)` and `sum(numbers)`?

Exercise B: Robustness and Warnings

1. Once you have implemented and successfully tested `my_sum()`, call your function with the following vector as input. What happens?

```
numbers2 <- c("1", "2", "3")
```

2. Why do we get an error? Investigate by comparing the vector `numbers` from Exercise A with the new vector `numbers2`. Hint: the functions `str()` and `class()` might help you.
3. Extend your `my_sum()` function with a control statement that checks whether the input is of the right class for the function to work (Hint: `class(x)!="numeric"`). The goal is to make the function more robust to wrong input. That is, if the input is wrong, issue a warning but don't break down with an error. Use the following code for the warning message:

```
warning("Wrong input! This function only accepts numeric or integer values!")
```

4. Test your enhanced sum function with the two input vectors `numbers` and `numbers2`.

Exercise C: Standard Deviation Function

1. During the lecture on Programming with Data we have step-by-step implemented our own R function to compute the mean. Now implement an R function called `my_sd` that computes the standard deviation, defined as: $SD = \sqrt{\frac{1}{N-1} \sum_{i=1}^N (x_i - \bar{x})^2}$. Hint: revisit the math operators section in the notes on the first exercise session.
2. Test your implementation by comparing its output with the already implemented `sd()` function.

Additional Exercises (not exam-relevant)

Exercise D: Standard Error Function

Building on the function written in Exercise C, implement a function to compute (the estimate of) the sample mean standard error as defined here: $SE_{\bar{x}} = \frac{SD}{\sqrt{n}}$. Hint: the idea is to use your own implementation (in Exercise C) to compute SD as a first step of your standard error function.

Exercises C and D should illustrate how you can approach more complex problems by breaking them up in smaller problems and addressing each of these step-by-step. That is, when looking at the problem of computing $SE_{\bar{x}} = \frac{SD}{\sqrt{n}}$, you see that computing SD is a part of the overall problem, which can be addressed separately.

Exercise E: T-test

Implement a function for the one-sample t-test: $t = \frac{\bar{x} - \mu_0}{\frac{SE}{\sqrt{n}}}$.