



impure device: $\alpha = (d^2I/dV^2)/(2K_0)$, original and denoised. Lines: solid confirmed, dashed single-half (+V), dotted tentative (+V)


impure 11_12 L = 2.00 mm, K0 = 2.77e-05 A V⁻²




impure 11_21 L = 2.00 mm, K0 = 2.77e-05 A V⁻²




impure 11_22 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 12_13 L = 2.00 mm, K0 = 2.77e-05 A V⁻²



impure 12_21 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 12_22 L = 2.00 mm, K0 = 2.77e-05 A V⁻²




wavenumber, +V axis (cm^{-1})

impure device: $\alpha = (d^2I/dV^2)/(2K_0)$, original and denoised. Lines: solid confirmed, dashed single-half (+V), dotted tentative (+V)


impure 12_23 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 13_14 L = 2.00 mm, K0 = 2.77e-05 A V⁻²




impure 13_22 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 13_23 L = 2.00 mm, K0 = 2.77e-05 A V⁻²



impure 13_24 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 14_23 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




wavenumber, +V axis (cm⁻¹)

impure device: $\alpha = (d^2I/dV^2)/(2K_0)$, original and denoised. Lines: solid confirmed, dashed single-half (+V), dotted tentative (+V)


impure 14_24 L = 2.00 mm, $K_0 = 2.77\text{e-}05 \text{ A V}^{-2}$




impure 21_22 L = 2.00 mm, $K_0 = 2.77\text{e-}05 \text{ A V}^{-2}$




impure 21_31 L = 2.00 mm, $K_0 = 2.77\text{e-}05 \text{ A V}^{-2}$




impure 21_32 L = 2.83 mm, $K_0 = 1.96\text{e-}05 \text{ A V}^{-2}$



impure 22_23 L = 2.00 mm, $K_0 = 2.77\text{e-}05 \text{ A V}^{-2}$




impure 22_31 L = 2.83 mm, $K_0 = 1.96\text{e-}05 \text{ A V}^{-2}$




wavenumber, +V axis (cm^{-1})

impure device: $\alpha = (d^2I/dV^2)/(2K_0)$, original and denoised. Lines: solid confirmed, dashed single-half (+V), dotted tentative (+V)


impure 22_32 L = 2.00 mm, K0 = 2.77e-05 A V⁻²




impure 22_33 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 23_24 L = 2.00 mm, K0 = 2.77e-05 A V⁻²




impure 23_32 L = 2.83 mm, K0 = 1.96e-05 A V⁻²



impure 23_33 L = 2.00 mm, K0 = 2.77e-05 A V⁻²




impure 23_34 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




wavenumber, +V axis (cm⁻¹)

impure device: $\alpha = (d^2I/dV^2)/(2K_0)$, original and denoised. Lines: solid confirmed, dashed single-half (+V), dotted tentative (+V)


impure 24_33 L = 2.83 mm, $K_0 = 1.96e-05 \text{ A V}^{-2}$




impure 24_34 L = 2.00 mm, $K_0 = 2.77e-05 \text{ A V}^{-2}$




impure 31_32 L = 2.00 mm, $K_0 = 2.77e-05 \text{ A V}^{-2}$




impure 31_41 L = 2.00 mm, $K_0 = 2.77e-05 \text{ A V}^{-2}$



impure 31_42 L = 2.83 mm, $K_0 = 1.96e-05 \text{ A V}^{-2}$




impure 32_33 L = 2.00 mm, $K_0 = 2.77e-05 \text{ A V}^{-2}$




wavenumber, +V axis (cm^{-1})

impure device: $\alpha = (d^2I/dV^2)/(2K_0)$, original and denoised. Lines: solid confirmed, dashed single-half (+V), dotted tentative (+V)


impure 32_41 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 32_42 L = 2.00 mm, K0 = 2.77e-05 A V⁻²




impure 32_43 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 33_34 L = 2.00 mm, K0 = 2.77e-05 A V⁻²



impure 33_42 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 33_43 L = 2.00 mm, K0 = 2.77e-05 A V⁻²




wavenumber, +V axis (cm⁻¹)

impure device: $\alpha = (d^2I/dV^2)/(2K_0)$, original and denoised. Lines: solid confirmed, dashed single-half (+V), dotted tentative (+V)


impure 33_44 L = 2.83 mm, $K_0 = 1.96\text{e-}05 \text{ A V}^{-2}$




impure 34_43 L = 2.83 mm, $K_0 = 1.96\text{e-}05 \text{ A V}^{-2}$




impure 34_44 L = 2.00 mm, $K_0 = 2.77\text{e-}05 \text{ A V}^{-2}$




impure 41_42 L = 2.00 mm, $K_0 = 2.77\text{e-}05 \text{ A V}^{-2}$



impure 41_51 L = 2.00 mm, $K_0 = 2.77\text{e-}05 \text{ A V}^{-2}$




impure 41_52 L = 2.83 mm, $K_0 = 1.96\text{e-}05 \text{ A V}^{-2}$




wavenumber, +V axis (cm^{-1})

impure device: $\alpha = (d^2I/dV^2)/(2K_0)$, original and denoised. Lines: solid confirmed, dashed single-half (+V), dotted tentative (+V)


impure 42_43 L = 2.00 mm, $K_0 = 2.77\text{e-}05 \text{ A V}^{-2}$




impure 42_51 L = 2.83 mm, $K_0 = 1.96\text{e-}05 \text{ A V}^{-2}$




impure 42_52 L = 2.00 mm, $K_0 = 2.77\text{e-}05 \text{ A V}^{-2}$




impure 42_53 L = 2.83 mm, $K_0 = 1.96\text{e-}05 \text{ A V}^{-2}$



impure 43_44 L = 2.00 mm, $K_0 = 2.77\text{e-}05 \text{ A V}^{-2}$




impure 43_52 L = 2.83 mm, $K_0 = 1.96\text{e-}05 \text{ A V}^{-2}$




wavenumber, +V axis (cm^{-1})

impure device: $\alpha = (d^2I/dV^2)/(2K_0)$, original and denoised. Lines: solid confirmed, dashed single-half (+V), dotted tentative (+V)


impure 43_53 L = 2.00 mm, K0 = 2.77e-05 A V⁻²




impure 43_54 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 44_53 L = 2.83 mm, K0 = 1.96e-05 A V⁻²




impure 44_54 L = 2.00 mm, K0 = 2.77e-05 A V⁻²



impure 51_52 L = 2.00 mm, K0 = 2.77e-05 A V⁻²



impure 52_53 L = 2.00 mm, K0 = 2.77e-05 A V⁻²



wavenumber, +V axis (cm^{-1})

impure device: $\alpha = (d^2I/dV^2)/(2K_0)$, original and denoised. Lines: solid confirmed, dashed single-half (+V), dotted tentative (+V)
impure 53_54 L = 2.00 mm, K0 = 2.77e-05 A V⁻²

