# Inheritance implements IS A

```
☐ Fields
#include "employee.h"
                                        #include "manager.h"
                                                                                           name payRate
using namespace std;
                                        using namespace std;
|Employee::Employee(string theName, float thePayRate)

	☐ Methods

                                                                                           © Employee
                                                                                           @ getName
                                        Manager::Manager(string theName,
 name = theName;
                                                                                           float thePayRate,
 payRate = thePayRate;
                                                      int bonusMult)
                                          : Employee(theName, thePayRate), bonusMult(bonusMult)
|string Employee::getName() const
                                                                                            public
 return name;
                                                                                          Manager
                                                                                          → Employee
                                       ]float Manager::pay(float hoursWorked) const

☐ Fields

|float Employee::pay(float hoursWorked) const

    bonusMult

                                         return bonusMult*(Employee::pay(hoursWorked));
                                                                                         ■ Methods
 return hoursWorked * payRate;
                                                                                           ⊚ pay
                                                                       #include "employee.h"
class Employee {
                                                                        class Manager : public Employee {
public:
                                                                        public:
  Employee(std::string theName, float thePayRate);
                                                                          Manager(std::string theName,
                                                                                      float thePayRate,
  std::string getName() const;
                                                                                      int bonusMult);
  float pay(float hoursWorked) const;
                                                                       float pay(float hoursWorked) const;
protected:
  std::string name;
                                                                        protected:
  float payRate;
                                                                          int bonusMult;
};
```

**Employee** 

Manager inherits all base class members and data

#### Calling base class

Manager must call base class if needed See constructor IL Employee::pay(hoursworked) (Scope it)

Pay is in 2 places do not even need pay in manager, but may want to change how pay works override pay to get diff behavior
Or just use base implementation (code reuse).

You must scope or get infinite recursion (remove Employee:: in manager) If do not call base class employee in constructor. Compiler will attempt to create default constructor to call, if base does not have one will not compile.

Demo remove employee IL from manager

Do not need to call base class in destructor, compiler handles it.

#### **Protected:**

Way for derived classes to get at innards of base class (member vars and functions) without exposing implementation details to world. Why? Without it no derived class can get at base class members

In general, it's a good idea to prefer less inheritance. Use containment wherever possible, and inheritance only in the specific situations in which it's needed. Large inheritance hierarchies in general, and deep ones in particular, are confusing to understand and therefore difficult to maintain. Inheritance is a design-time decision and trades off a lot of runtime flexibility.

Start here 10/22/15 Start on virtyual next time

#### Virtual:

```
void outputPay(Employee *pEmp) {
    // Assume all employees worked 40 hours this period.
    cout << "For Employee:" << endl;
    cout << "Name: " << pEmp->getName() << endl;
    cout << "Pay: " << pEmp->pay(40.0) << endl;
}</pre>
```

As long as not virtual;

Will always call employee::pay() will never go to most derived class Unless you make it virtual in header of where virtual starts, every class derived therafter is virtual by default; AS A COURTESY TO FUTURE DEVELOPERS PUT VIRTUAL IN ALL DERIVED CLASSES

Does it with a V-Table

Human true get truel do Homan Shift Nexus 5 make Call() Professor Scallion LdoScullStuffe) Ldo Prof Sheff() larger releger heiserdy hoder is to marrien watch mywortch; Wexus 5 my News 5; shout don't mbase to want cause desired to de lovo? get frue () { return my watch. get tome () } change carreet
to sculture from fullion
derive from fullion make Call () { return my Nexus S. make Call(); } change eller do Keith Stoff OS m base class break Kerth class de proffs heff(): 3

## **Composition:**

When an object posseses something
I have a watch
I have a Nexus5

### Which to Use:

Think of composition as a **has a** relationship. A car "has an" engine, a person "has a" name, etc. Think of inheritance as an **is a** relationship. A car "is a" vehicle, a person "is a" mammal, etc.