



(10) Publication No: **IN202541126599 A1**

(22) Date of Filing: 14-12-2025

(43) Publication Date: 26-06-2026

Journal No: 26/2026

(19) Intellectual Property Office, India

(12) INDIAN PATENT APPLICATION

(54) Title: **A system and method for energy management and cruising speed optimization in solar electric vehicles**

(51) International Classification: G06N 3/08, G06N 3/04, G01R 31/367, G01R 31/392 G01R 31/382 (21) Application No: 202541126599 (31) Priority Document No: -- (32) Priority Date: -- (86) International Application No: -- Filing Date: -- (87) International Publication No: -- (61) Patent of Addition to Application No: -- Filing Date: -- (62) Divisional to Application No: -- Filing Date: --	(71) Name of Applicant(s): Manipal Academy Of Higher Education, (72) Name of Inventor(s): Anvesha Singh
--	---

(57) Abstract:

The present invention discloses a solar electric vehicle energy management system 101 comprising a traction battery 301, a photovoltaic array 303, an electric traction motor 305, a motor controller 307, an input interface 309, an electronic controller 311 with a memory 313. The electronic controller 311 comprises a resistive-force computation module 311A, a torque and power estimation module 311B, a motor-efficiency estimation module 311C, a solar contribution determination module 311D, and an energy management module 311E. The energy management module 311E applies a Newton–Raphson iterative method to determine an optimized cruising speed minimizing specific energy consumption over a target travel distance. A quantum neural network–based framework provides enhanced state of charge prediction under dynamic conditions. The system achieves minimum energy consumption of 34.22 Wh/km at an optimized speed of 39.90 km/h, maximizing driving range while integrating real-time solar energy contribution. (FIG. 4)

FORM 2 THE PATENTS ACT, 1970 (39 of 1970) AND The Patents Rules, 2003 COMPLETE SPECIFICATION (See Section 10 and Rule 13)
1. TITLE OF THE INVENTION: A SYSTEM AND METHOD FOR ENERGY MANAGEMENT AND CRUISING SPEED OPTIMIZATION IN SOLAR ELECTRIC VEHICLES
2. APPLICANT: (a) NAME: MANIPAL ACADEMY OF HIGHER EDUCATION (b) NATIONALITY: Indian (c) ADDRESS: MADHAV NAGAR, MANIPAL, 576104, KARNATAKA, INDIA
4. PREAMBLE TO THE DESCRIPTION: The following specification particularly describes the invention and the manner in which it is to be performed.

DESCRIPTION OF THE INVENTION:

Technical Field of the Invention

5 [0001] The present invention relates to the field of energy management systems for solar electric vehicles. More specifically, the invention relates to the field of hybrid quantum-classical neural network frameworks integrated with physics-based vehicle dynamics modeling.

Background of the Invention

10 [0002] In the field of battery management systems for electric vehicles, accurate estimation, and prediction of the state of charge (SOC) remains a fundamental computational challenge. Conventional SOC estimation techniques such as Coulomb counting, open-circuit voltage measurement, and Extended Kalman Filters rely on linear or weakly nonlinear mathematical models that assume relatively stable operating conditions. However, real-world battery systems operate under highly dynamic and nonlinear conditions involving fluctuating traction loads, regenerative braking transients, temperature variations, and sensor noise, causing these classical methods to suffer from cumulative numerical errors, parameter drift, and degraded long-term prediction accuracy. The inability of existing computational frameworks to reliably model the nonlinear, time-varying electrochemical behavior of battery systems under such multi-variable dynamic inputs represents a core technological limitation in the field.

20 [0003] In solar electric vehicles, the SOC estimation problem is further compounded by the intermittent and stochastic nature of photovoltaic power generation, which introduces an additional high-dimensional, time-varying input that classical estimation architectures are not designed to handle simultaneously with traction and braking dynamics. Traditional machine learning models, while improving upon analytical methods, remain fundamentally constrained by classical computational bounds when attempting to capture high-order feature correlations, quantum-scale interactions, and complex entanglements between PV generation patterns, driving profiles, ambient temperature shifts, and internal battery electrochemistry. There exists no integrated computational architecture that combines quantum-enhanced learning with real-time vehicle energy management to address these coupled nonlinearities.

30 [0004] Existing energy management strategies for solar electric vehicles rely on fixed-speed or heuristic-based driving profiles that do not adapt to real-time environmental, electrical, and mechanical operating conditions. These approaches treat speed selection as a static parameter rather than a dynamically computed output of a physics-based resistive force model coupled with motor efficiency interpolation and solar energy contribution. The absence of a deterministic, iterative optimization framework that jointly accounts for rolling resistance, aerodynamic drag, gradient forces, drivetrain efficiency characteristics, and photovoltaic power input results in suboptimal energy consumption, inaccurate range prediction, and inefficient utilization of the available battery and solar energy resources.

35 [0005] Hence, there is a need for a system that enable accurate short-horizon SOC forecasting, environment-aware energy planning, and minimum-energy cruising speed computation within a single integrated framework.

Object of the invention

40 [0006] A principal objective of the invention is to develop a system and method for predicting the state of charge of solar electric vehicle battery packs using a hybrid quantum-classical neural network framework capable of modeling nonlinear battery behavior with enhanced accuracy and robustness over classical estimation techniques.

[0007] Another objective of the invention is to integrate physics-based resistive force modeling, motor efficiency interpolation, and real-time solar energy accounting into a deterministic Newton-Raphson optimization routine that computes the minimum-energy cruising speed over a target travel distance.

[0008] Another objective of the invention is to provide a unified energy management architecture that simultaneously enables accurate short-horizon SOC forecasting, environment-aware cruising speed optimization, and automated control command generation to maximize driving range and minimize energy consumption in solar electric vehicles.

5 **Summary of the Invention**

[0009] This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the detailed description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

10 [0010] The problem of inaccurate state of charge prediction under nonlinear and dynamic battery operating conditions is solved by using a solar electric vehicle energy management system that learn complex nonlinear mappings between vehicle traction load, photovoltaic generation, temperature, and regenerative braking inputs to generate accurate short-horizon SOC forecasts.

15 [0011] Existing state of charge estimation techniques for electric vehicle battery systems, including Coulomb counting, open-circuit voltage measurement, and Extended Kalman Filters, suffer from cumulative numerical errors, parameter drift, and degraded prediction accuracy when operating under nonlinear and dynamically varying conditions involving fluctuating traction loads, regenerative braking transients, temperature variations, and intermittent photovoltaic power generation. Classical machine learning models improve upon analytical methods but remain fundamentally constrained by classical computational bounds in capturing high-order
20 feature correlations and complex nonlinear interactions between multiple time-varying inputs. Simultaneously, existing energy management strategies for solar electric vehicles rely on fixed-speed or heuristic-based driving profiles that treat speed selection as a static parameter, failing to adapt to real-time environmental, electrical, and mechanical operating conditions, thereby resulting in suboptimal energy consumption, inaccurate range prediction, and inefficient utilization of available battery and solar energy resources.

25 [0012] The present invention addresses these technological deficiencies through a unified energy management system that integrates a hybrid quantum–classical neural network framework for SOC prediction with a deterministic physics-based cruising speed optimization method. The quantum neural network employs parameterized quantum circuits to learn nonlinear mappings between vehicle traction load, photovoltaic generation, temperature, and regenerative braking inputs, achieving enhanced SOC prediction accuracy with
30 reduced parameter drift compared to classical estimators. The cruising speed optimization is achieved through an electronic controller comprising dedicated sub-modules for resistive force computation, torque and power estimation, motor efficiency interpolation from stored performance data, and real-time solar contribution determination, coupled with a Newton–Raphson iterative root-finding routine that deterministically computes the minimum-energy cruising speed over a target travel distance such that the battery state of charge depletes
35 from an initial value to a target value while minimizing specific energy consumption and maximizing driving range.

[0013] The summary provided herein introduces a section of concepts in a simple and clear form that is further described in the detailed description. The summary provided herein is not intended to particularly
40 identify key features or essential features of the claimed invention or subject matter, nor is it intended to be used as support or as an aid in determining the scope of the claimed subject matter.

[0014] The above summary is descriptive and exemplary only and is not intended to be in any way restricting. In addition to the descriptive aspects, embodiments, and features described in the above summary, further features and embodiments will become apparent by reference to the accompanying drawings and the following detailed description.

45 **Brief Description of Drawings**

[0015] The foregoing and other features of the embodiments will become more apparent from the following detailed description when read in conjunction with the accompanying drawings. In the drawings, like reference numerals refer to like elements.

5 [0016] In the following description, numerous specific details are set forth to provide a thorough understanding of the embodiments of the invention. However, it will be apparent to one skilled in the art that the embodiments may be practiced without these specific details or with equivalent alternative configurations. Well-known battery-modeling techniques, filtering operations, and neural network structures are represented in block diagram form to avoid unnecessarily obscuring the embodiments.

10 [0017] FIG.1 illustrates a network diagram representing a solar electric vehicle energy management system 101, according to some example embodiments.

[0018] FIG.2 illustrates a system diagram representing a solar electric vehicle energy management system 101, according to some example embodiments.

[0019] FIGs.3A-3B illustrate a block diagram representing a solar electric vehicle energy management system 101, according to some example embodiments.

15 [0020] FIG.4 illustrates a flow chart representing method for enabling a solar electric vehicle energy management, according to some example embodiments.

[0021] FIGs.5A-5D illustrate range comparison for fixed-speed and optimized operation, a relationship between cruising speed and energy consumption, the variation of achievable driving range with solar irradiance, and SOC prediction comparison with quantitative validation, according to some example embodiments.

20 [0022] TABEL.1 illustrates quantifiable improvements of the invention demonstrate over traditional methods, according to some example embodiments.

Detailed Description of the Invention

25 [0023] Reference will now be made in detail to the description of the present subject matter, one or more examples of which are shown in the figures. Each example is provided to explain the subject matter and not as a limitation. Various changes and modifications obvious to one skilled in the art to which the invention pertains are deemed to be within the spirit, scope, and contemplation of the invention.

30 [0024] As used in this application, the term “State of Charge (SOC)” refers to the ratio of available battery capacity to its rated capacity, expressed as a percentage. Within the scope of this invention, SOC is dynamically predicted for solar electric vehicle battery packs under variable traction, regenerative braking, and photovoltaic charging conditions.

[0025] The term “Quantum Neural Network (QNN)” refers to a machine learning model constructed using parameterized quantum circuits capable of representing nonlinear mappings between high-dimensional feature inputs and future SOC values. In this invention, QNN architectures are employed to overcome limitations of classical SOC estimation methods that struggle with nonlinearity and parameter drift.

35 [0026] As used herein, the term “Hybrid Quantum-Classical Optimization” refers to a computational strategy wherein quantum circuits generate prediction outputs while a classical optimizer evaluates loss functions and updates quantum parameters iteratively to improve SOC forecasting accuracy.

40 [0027] The term “Quantum Data Encoding” refers to techniques used to convert classical input features—such as vehicle load, PV generation, temperature, and regenerative braking metrics—into quantum states suitable for processing by parameterized quantum circuits.

[0028] FIG.1 illustrates a network diagram representing a solar electric vehicle energy management system 101, according to some example embodiments.

[0029] FIG. 1 illustrates a network environment 100 depicting overall system architecture of the solar electric vehicle energy management system 101 in accordance with an embodiment of the present invention. The solar electric vehicle energy management system 101 is the central computing unit configured to perform real-time state of charge prediction, physics-based resistive force computation, motor efficiency interpolation, solar energy accounting, and deterministic cruising speed optimization. The solar electric vehicle energy management system 101 receives vehicle operating data including battery telemetry, traction load profiles, photovoltaic generation metrics, regenerative braking data, and ambient temperature values, and processes said data through an electronic controller comprising dedicated sub-modules for resistive-force computation, torque and power estimation, motor-efficiency estimation, solar contribution determination, and energy management to generate optimized cruising speed control commands for the electric traction motor.

[0030] The remote device 103 is a computing device located at a geographically distant location from the solar electric vehicle energy management system 101 and is configured to communicate with the solar electric vehicle energy management system 101 over the network 109. In one embodiment, the remote device 103 may be a cloud-based server, a fleet management terminal, or a remote monitoring station operated by a vehicle operator, fleet administrator, or service provider. The remote device 103 is configured to receive SOC prediction data, energy consumption reports, range estimation outputs, and optimized cruising speed parameters transmitted by the solar electric vehicle energy management system 101, and may further be configured to transmit route data, irradiance forecasts, or updated motor performance maps to the solar electric vehicle energy management system 101 for enhanced energy planning and optimization.

[0031] The peripheral component 105 is a hardware or software entity operatively associated with the network environment 100 and configured to provide supplementary data inputs or receive processed outputs from the solar electric vehicle energy management system 101. In one embodiment, the peripheral component 105 may include one or more of solar irradiance sensors, GPS modules, weather data providers, external battery diagnostic tools, or third-party energy management platforms. The peripheral component 105 communicates with the solar electric vehicle energy management system 101 through the network 109 to supply real-time environmental data such as solar irradiance values, ambient temperature readings, and road gradient information that are utilized by the electronic controller for computing resistive forces, determining solar power contribution, and refining the optimized cruising speed.

[0032] The local device 107 is a computing or interface device situated in physical proximity to or within the solar electric vehicle and configured to interact with the solar electric vehicle energy management system 101 through the network 109. In one embodiment, the local device 107 may be an on-board display unit, a driver interface terminal, a mobile device of the vehicle operator, or an embedded diagnostic module. The local device 107 is configured to receive and display real-time SOC predictions, optimized cruising speed recommendations, energy consumption metrics, and range estimation outputs generated by the solar electric vehicle energy management system 101, thereby enabling the vehicle operator to monitor vehicle energy status and make informed driving decisions. The network 109 is a communication medium configured to establish data communication links between the solar electric vehicle energy management system 101, the remote device 103, the peripheral component 105, and the local device 107. In one embodiment, the network 109 may include one or more of a wireless local area network, a cellular data network, a vehicle-to-cloud communication link, a CAN bus interface, or any combination thereof, enabling real-time bidirectional data exchange necessary for the integrated energy management and cruising speed optimization operations of the present invention.

[0033] FIG.2 illustrates a system diagram representing a solar electric vehicle energy management system 101, according to some example embodiments.

[0034] FIG. 2 illustrates a system diagram depicting an internal architecture of the solar electric vehicle energy management system 101 in accordance with an embodiment of the present invention. The solar electric vehicle energy management system 101 comprises a central processing unit 201, a memory 313, a communication module 205, a plurality of sensors 207, and a traction battery 301, all operatively coupled and

configured to collectively perform real-time state of charge prediction, physics-based energy computation, and deterministic cruising speed optimization for the solar electric vehicle.

5 [0035] The central processing unit **201** is the primary computational engine of the solar electric vehicle energy management system **101** and is configured to execute all data processing, algorithmic computation, and control command generation operations. In one embodiment, the central processing unit **201** implements the electronic controller **311** comprising the resistive-force computation module **311A** for computing total resistive forces including rolling resistance, aerodynamic drag, road gradient force, and inertia; the torque and power estimation module **311B** for computing wheel torque, motor speed, and electrical power demand; the motor-efficiency estimation module **311C** for interpolating motor efficiency from stored performance data; the solar contribution determination module **311D** for determining photovoltaic power contribution; and the energy management module **311E** for generating optimized cruising speed control commands through Newton–Raphson iterative optimization. The central processing unit **201** further executes the quantum neural network circuit for processing encoded vehicle and battery feature inputs and generating short-horizon SOC predictions through hybrid quantum–classical optimization.

15 [0036] The memory **313** is operatively associated with the central processing unit **201** and is configured to store executable instructions, motor performance mapping data, vehicle dynamics parameters, quantum circuit parameters, and historical battery telemetry data required for the operation of the electronic controller **311** and its sub-modules **311A** through **311E**. In one embodiment, the memory **313** stores the coefficient of rolling resistance, drag coefficient, motor torque-speed-efficiency maps, photovoltaic array specifications, and trained quantum neural network parameters. The memory **313** may comprise one or more of a read-only memory, a random-access memory, a flash memory, an electrically erasable programmable read-only memory, or any non-transitory computer-readable storage medium.

25 [0037] The communication module **205** is configured to establish and maintain data communication between the solar electric vehicle energy management system **101** and external entities including the remote device **103**, the peripheral component **105**, and the local device **107** over the network **109** as illustrated in **FIG.1**. In one embodiment, the communication module **205** supports one or more communication protocols including wireless local area network, cellular data communication, Bluetooth, CAN bus, or vehicle-to-cloud communication links, thereby enabling the solar electric vehicle energy management system **101** to receive external inputs such as route data, irradiance forecasts, and weather information, and to transmit SOC predictions, range estimations, and optimized cruising speed parameters to remote monitoring stations, fleet management terminals, and on-board driver interface devices.

35 [0038] The plurality of sensors **207** comprises one or more sensing devices operatively connected to the central processing unit **201** and configured to acquire real-time vehicle operating data for processing by the electronic controller **311**. In one embodiment, the plurality of sensors **207** includes battery voltage sensors, battery current sensors, temperature sensors, wheel speed sensors, solar irradiance sensors, accelerometers, and GPS receivers. The sensor data acquired by the plurality of sensors **207** is provided to the input interface **309** and subsequently processed by the sensor preprocessing and feature normalization unit for filtering, scaling, and alignment before being utilized by the sub-modules **311A** through **311E** for resistive force computation, motor efficiency interpolation, solar contribution determination, and cruising speed optimization.

40 [0039] The traction battery **301** is configured to store electrical energy for propulsion of the solar electric vehicle and is operatively connected to the central processing unit **201** for continuous monitoring of battery state of charge, voltage, current, and temperature. In a preferred embodiment, the traction battery **301** is a lithium-ion battery pack with a capacity of 4960 Wh, providing electrical energy to the electric traction motor **305** through the motor controller **307** based on control commands generated by the energy management module **311E** of the electronic controller **311**. The traction battery **301** receives supplemental charging from the photovoltaic array **303** during daytime operation, and its real-time SOC is continuously predicted by the quantum neural network executed on the central processing unit **201** to support energy management decisions, predictive range estimation, and battery protection functions.

50 [0040] **FIGs.3A-3B** illustrate a block diagram representing a solar electric vehicle energy management system **101**, according to some example embodiments.

[0041] FIG. 3A illustrates a detailed block diagram depicting the hardware components of the solar electric vehicle energy management system **101** in accordance with an embodiment of the present invention. The solar electric vehicle energy management system **101** comprises a traction battery **301**, a photovoltaic array **303**, an electric traction motor **305**, a motor controller **307**, an input interface **309**, an electronic controller **311**, and a memory **313**, all operatively interconnected and configured to enable real-time energy management and deterministic cruising speed optimization for the solar electric vehicle.

[0042] The traction battery **301** is configured to store electrical energy for propulsion of the solar electric vehicle. In a preferred embodiment, the traction battery **301** is a lithium-ion battery pack having a rated capacity of 4960 Wh and an operating voltage of 72 V. The traction battery **301** supplies electrical energy to the electric traction motor **305** through the motor controller **307** and receives supplemental charging from the photovoltaic array **303** during daytime operation. The state of charge of the traction battery **301** is continuously monitored and predicted by the electronic controller **311** using a quantum neural network-based estimation framework. In an example embodiment, the traction battery **301** begins a 150 km journey at an initial SOC of 100% and is depleted to a target SOC value at the end of the journey, with the rate of depletion being governed by the optimized cruising speed computed by the energy management module **311E**. In one embodiment, the traction battery **301** may comprise lithium iron phosphate cells, lithium nickel manganese cobalt oxide cells, or any electrochemical energy storage medium suitable for electric vehicle propulsion.

[0043] The photovoltaic array **303** is configured to generate supplemental electrical energy from solar irradiance and is mounted on the vehicle body with a total panel area of 3.51 m². The photovoltaic array **303** converts incident solar radiation into direct current electrical energy which is supplied to the traction battery **301** for supplemental charging, thereby extending the achievable driving range of the solar electric vehicle. In a validated embodiment, the photovoltaic array **303** contributes sufficient supplemental energy to increase the vehicle driving range from about 160 km at a solar irradiance of 200 W/m² to about 210 km at a solar irradiance of 1000 W/m², representing a range extension of about 31% attributable to solar energy harvesting. The solar contribution determination module **311D** of the electronic controller **311** computes the real-time photovoltaic power output based on irradiance data received through the input interface **309** and the known panel area and efficiency characteristics of the photovoltaic array **303**. In an example embodiment, at a solar irradiance of 600 W/m² and an assumed panel efficiency of 20%, the photovoltaic array **303** having an area of 3.51 m² generates about 421 W of supplemental electrical power.

[0044] The electric traction motor **305** is operatively connected to at least one wheel of the solar electric vehicle and is configured to convert electrical energy from the traction battery **301** into mechanical torque for propelling the vehicle. In a preferred embodiment, the electric traction motor **305** is a brushless DC in-wheel hub motor operating in a direct drive configuration with a gear ratio of 1:1, thereby eliminating mechanical transmission losses. The electric traction motor **305** has an operating voltage of 72 V, a rated current of 42 A, a peak current of 84 A, a rated torque of 56.5 Nm, a peak torque of 191 Nm, a rated speed of 898 RPM, a peak speed of 1017 RPM, a rated power of 3000 W, a peak power of 6000 W, and an operational efficiency of 92%. In an example embodiment, at the optimized cruising speed of about 39.90 km/h, the electric traction motor **305** operates at a point on its torque-speed characteristic map corresponding to minimum specific energy consumption of 34.22 Wh/km. The motor-efficiency estimation module **311C** of the electronic controller **311** interpolates the operating efficiency of the electric traction motor **305** from stored performance mapping data in the memory **313** to accurately determine electrical power demand at any given operating point.

[0045] The motor controller **307** is electrically connected to the traction battery **301** and the electric traction motor **305** and is configured to control the electrical operation of the electric traction motor **305** based on control commands received from the electronic controller **311**. In a preferred embodiment, the motor controller **307** employs sinusoidal commutation and has a maximum battery current capacity of 150 A with a peak capacity of 200 A, a maximum phase current capacity of 400–450 A, an operating voltage range of 48–72 V, a maximum power handling capacity of 7000 W, a mass of 2.0 kg, and dimensions of 179 mm × 121 mm × 55 mm. The motor controller **307** receives the optimized cruising speed control command generated by the energy management module **311E** and modulates the current and voltage supplied from the traction battery **301** to the electric traction motor **305** accordingly. In an example embodiment, when the energy management module **311E** determines an optimized cruising speed of 39.90 km/h, the motor controller **307** adjusts the phase current

delivery to the electric traction motor **305** such that the motor operates at the corresponding minimum-energy operating point on its efficiency map.

5 **[0046]** The input interface **309** is configured to receive vehicle operating data including battery state of charge data, vehicle dynamics data, and solar irradiance data from the plurality of sensors **207** and external data sources. In one embodiment, the input interface **309** receives real-time data including battery voltage, battery current, battery temperature, vehicle speed, wheel rotational speed, solar irradiance intensity, ambient temperature, road gradient angle, and GPS coordinates. The input interface **309** provides the received data to the electronic controller **311** for processing by the resistive-force computation module **311A**, the torque and power estimation module **311B**, the motor-efficiency estimation module **311C**, and the solar contribution determination module **311D**. In an example embodiment, the input interface **309** receives an instantaneous solar irradiance value of 700 W/m², a vehicle speed of 39.90 km/h, a battery SOC of 85%, and a road gradient of 0 degrees, and transmits said data to the electronic controller **311** for real-time energy computation and optimization.

15 **[0047]** The electronic controller **311** is the central decision-making unit of the solar electric vehicle energy management system **101** and is in communication with the traction battery **301**, the photovoltaic array **303**, and the motor controller **307**. The electronic controller **311** executes executable instructions stored in the memory **313** and comprises the resistive-force computation module **311A** configured to compute total resistive force including rolling resistance using a coefficient of 0.015 and aerodynamic drag using a drag coefficient of 0.16; the torque and power estimation module **311B** configured to compute wheel torque as the product of resistive force and rolling radius of 224.06 mm, motor speed, and electrical power demand; the motor-efficiency estimation module **311C** configured to interpolate motor efficiency from stored performance data; the solar contribution determination module **311D** configured to determine photovoltaic power contribution; and the energy management module **311E** configured to apply a Newton–Raphson iterative root-finding routine to determine the optimized cruising speed at which the SOC of the traction battery **301** decreases from an initial value to a target value over a target travel distance of 150 km while minimizing specific energy consumption. In an example embodiments, for a fully laden vehicle mass of 260 kg travelling on a flat road at a frontal area corresponding to vehicle dimensions of 4870 mm × 1400 mm × 1222 mm, the resistive-force computation module **311A** computes rolling resistance as $0.015 \times 260 \times 9.81 = 38.26$ N, and aerodynamic drag as $0.5 \times 1.225 \times 0.16 \times A \times v^2$, where A is the frontal area and v is the vehicle speed, and the energy management module **311E** iteratively converges on the optimized cruising speed of about 39.90 km/h corresponding to the minimum energy consumption of 34.22 Wh/km.

30 **[0048]** The memory **313** is operatively associated with the electronic controller **311** and is configured to store executable instructions, motor performance mapping data, vehicle dynamics parameters including the coefficient of rolling resistance, drag coefficient, vehicle mass, rolling radius, and frontal area dimensions, trained quantum neural network circuit parameters, and historical SOC prediction data. In one embodiment, the memory **313** may comprise one or more of a read-only memory, a random-access memory, a flash memory, an electrically erasable programmable read-only memory, or any non-transitory computer-readable storage medium sufficient to store and retrieve the computational data required for the operation of the electronic controller **311** and its sub-modules **311A** through **311E**.

40 **[0049]** FIG. 3B illustrates a detailed block diagram depicting the internal sub-module architecture of the electronic controller **311** of the solar electric vehicle energy management system **101** in accordance with an embodiment of the present invention. The electronic controller **311** comprises a resistive-force computation module **311A**, a torque and power estimation module **311B**, a motor-efficiency estimation module **311C**, a solar contribution determination module **311D**, and an energy management module **311E**, all operatively interconnected and configured to execute in a sequential and coordinated manner to compute the optimized cruising speed that minimizes specific energy consumption of the solar electric vehicle over a target travel distance.

50 **[0050]** The resistive-force computation module **311A** is configured to compute the total resistive force acting on the solar electric vehicle by aggregating individual force components including rolling resistance, aerodynamic drag, road gradient force, and inertial force. In a preferred embodiment, the rolling resistance is computed as the product of the coefficient of rolling resistance of 0.015, the fully laden vehicle mass of 260

kg, and the gravitational acceleration of 9.81 m/s^2 , yielding a rolling resistance force of approximately 38.26 N on a flat road surface. The aerodynamic drag force is computed using the drag coefficient of 0.16 , the air density of 1.225 kg/m^3 , the frontal area derived from the vehicle dimensions of $4870 \text{ mm length} \times 1400 \text{ mm width} \times 1222 \text{ mm height}$, and the square of the vehicle speed. The gradient force is computed as the product of vehicle mass, gravitational acceleration, and the sine of the road inclination angle, and the inertial force is computed as the product of vehicle mass and longitudinal acceleration. For example, at a cruising speed of 39.90 km/h on a flat road with zero acceleration, the resistive-force computation module **311A** computes the total resistive force as the sum of rolling resistance of 38.26 N and aerodynamic drag, which together determine the instantaneous power demand on the electric traction motor **305**. The computed total resistive force output of the resistive-force computation module **311A** is transmitted to the torque and power estimation module **311B** for subsequent drivetrain computation.

[0051] The torque and power estimation module **311B** is configured to receive the total resistive force from the resistive-force computation module **311A** and compute the required wheel torque, motor rotational speed, and electrical power demand. In a preferred embodiment, the wheel torque is calculated as the product of the total resistive force and the rolling radius of the tyre of 224.06 mm . The required motor rotational speed in RPM is derived from the vehicle speed and the rolling radius using the direct drive gear ratio of $1:1$, thereby establishing a direct relationship between vehicle speed and motor speed without transmission ratio conversion. The electrical power demand is computed from the torque-speed product divided by the motor efficiency obtained from the motor-efficiency estimation module **311C**. For example, at the optimized cruising speed of 39.90 km/h , the torque and power estimation module **311B** computes the wheel torque corresponding to the total resistive force acting at the tyre contact patch, determines the motor speed within the rated speed range of 898 RPM and peak speed of 1017 RPM of the electric traction motor **305**, and calculates the electrical power demand from the traction battery **301** required to sustain said cruising speed. The computed torque, speed, and power values are utilized by the energy management module **311E** for integration into the energy consumption computation over the target travel distance.

[0052] The motor-efficiency estimation module **311C** is configured to obtain the operating efficiency of the electric traction motor **305** at any given torque-speed operating point by interpolating stored motor performance mapping data in the memory **313**. In a preferred embodiment, the motor performance data comprises a multi-dimensional efficiency map correlating motor torque, motor speed, and operating efficiency for the brushless DC in-wheel hub motor having a rated power of 3000 W , a peak power of 6000 W , an operating voltage of 72 V , and a nominal efficiency of 92% . The motor-efficiency estimation module **311C** receives the torque and speed values computed by the torque and power estimation module **311B** and returns the interpolated efficiency value corresponding to the specific operating point. For example, at the rated torque of 56.5 Nm and rated speed of 898 RPM , the motor-efficiency estimation module **311C** returns an efficiency of 92% , whereas at partial load conditions below rated torque, the interpolated efficiency may vary between 85% and 92% depending on the position on the efficiency map. This interpolated efficiency value is critical for accurately computing the electrical power drawn from the traction battery **301**, as the actual electrical power demand equals the mechanical power divided by the motor efficiency at the operating point, and any error in efficiency estimation directly propagates into inaccurate SOC prediction and suboptimal cruising speed computation.

[0053] The solar contribution determination module **311D** is configured to determine the real-time solar power contribution from the photovoltaic array **303** based on solar irradiance data received through the input interface **309**. In a preferred embodiment, the solar contribution determination module **311D** computes the photovoltaic power output as the product of the solar irradiance in W/m^2 , the photovoltaic array area of 3.51 m^2 , and the panel conversion efficiency, with temperature correction factors applied to account for cell temperature effects on photovoltaic output. For example, at a solar irradiance of 800 W/m^2 and an assumed panel efficiency of 20% after temperature correction, the solar contribution determination module **311D** computes a photovoltaic power contribution of approximately 561 W , which is subtracted from the gross electrical power demand computed by the torque and power estimation module **311B** to yield the net power drawn from the traction battery **301**. In a validated embodiment, the solar contribution determination module **311D** enables the system to achieve a driving range increase from approximately 160 km at 200 W/m^2 to approximately 210 km at 1000 W/m^2 , confirming that the photovoltaic array **303** effectively contributes supplemental energy that monotonically increases the achievable driving range as irradiance increases. The

solar power contribution computed by the solar contribution determination module **311D** is transmitted to the energy management module **311E** for integration into the net energy consumption computation.

[0054] The energy management module **311E** is the central optimization unit of the electronic controller **311** and is configured to generate a control command corresponding to the optimized cruising speed by integrating outputs from the resistive-force computation module **311A**, the torque and power estimation module **311B**, the motor-efficiency estimation module **311C**, and the solar contribution determination module **311D**. In a preferred embodiment, the energy management module **311E** computes the net energy consumption by integrating the difference between the gross electrical power demand and the solar power contribution over the trip duration, and applies a Newton–Raphson iterative root-finding routine to determine the cruising speed at which the state of charge of the traction battery **301** reduces from an initial value to a target value after traversing a target travel distance of 150 km, thereby achieving the minimum specific energy consumption in Wh/km. For example, the energy management module **311E** iteratively evaluates the energy balance equation at successive speed estimates, computing the Jacobian of the SOC residual function with respect to speed, and converges within a predetermined tolerance to the optimized cruising speed of approximately 39.90 km/h corresponding to a minimum energy consumption of 34.22 Wh/km. In a validated embodiment, the optimized cruising speed determined by the energy management module **311E** achieves a driving range of 144.9 km with an energy consumption of 34.22 Wh/km, representing an improvement of 9.7 Wh/km in energy reduction and 16.8 km in range increase compared to a fixed-speed driving strategy of 30 km/h which yields a range of only 138.8 km at 35.73 Wh/km. The control command corresponding to the optimized cruising speed is transmitted from the energy management module **311E** to the motor controller **307** for controlling the operation of the electric traction motor **305**.

[0055] According to some example embodiments, a solar electric vehicle energy management system **101**, comprising: the traction battery **301**, configured to store electrical energy for propulsion of a solar electric vehicle; a photovoltaic array **303**, configured to generate supplemental electrical energy from solar irradiance; the electric traction motor **305**, operatively connected to at least one wheel of the solar electric vehicle and configured to propel the solar electric vehicle; the motor controller **307**, electrically connected to the traction battery **301** and the electric traction motor **305** and configured to control electrical operation of the electric traction motor **305**; the input interface **309**, configured to receive vehicle operating data including battery state of charge data, vehicle dynamics data, and solar irradiance data; the electronic controller **311**, in communication with the traction battery **301**, the photovoltaic array **303**, and the motor controller **307**; and the memory **313**, operatively associated with the electronic controller **311** and storing executable instructions, wherein the electronic controller **311**, comprising: a resistive-force computation module **311A** configured to compute total resistive force acting on the solar electric vehicle; the torque and power estimation module **311B** configured to compute wheel torque, motor speed, and electrical power demand; the motor-efficiency estimation module **311C**, configured to obtain motor efficiency from stored motor performance data in a memory **313**; the solar contribution determination module **311D**, configured to determine solar power contribution from the photovoltaic array **303**; and the energy management module **311E**, configured to generate a control command corresponding to the optimized cruising speed, the motor controller **307**, is configured to control operation of the electric traction motor **305** based on the control command received from the electronic controller **311**. determining the total resistive force comprises estimating rolling resistance using a coefficient of rolling resistance of 0.015 and aerodynamic drag using a drag coefficient of 0.16. Determining the solar power contribution comprises determining photovoltaic power input based on solar irradiance and a photovoltaic array area of 3.51 m². Determining the motor efficiency comprises interpolating stored performance data of an electric traction motor operating at 72 V, having a rated power of 3000 W, a peak power of 6000 W, and an efficiency of 92%. Determining the optimized cruising speed comprises applying an iterative computational method over a target travel distance of 150 km such that a state of charge of the traction battery **301** decreases from an initial value to a target value.

[0056] FIG.4 illustrates a flow chart representing a solar electric vehicle energy management, according to some example embodiments.

[0057] At step **401**, the method includes receiving a solar electric vehicle operating data including at least battery state of charge data, vehicle dynamics data, and solar irradiance data through an input interface **309**.

- 5 **[0058]** In one embodiment, the input interface **309** receives real-time data from the plurality of sensors **207** including instantaneous battery voltage, battery current, battery temperature, vehicle speed, wheel rotational speed, solar irradiance intensity measured in W/m^2 , ambient temperature, road gradient angle, and GPS coordinates. The received data is preprocessed, normalized, and filtered to remove sensor noise and ensure consistency before being transmitted to the electronic controller **311** for subsequent computational operations. For example, the input interface **309** receives an instantaneous battery SOC of 100%, a solar irradiance of 700 W/m^2 , a road gradient of 0 degrees, and initial vehicle speed data at the commencement of a planned 150 km journey.
- 10 **[0059]** At step **403**, the method includes determining a total resistive force using a resistive-force computation module **311A**, on the solar electric vehicle on rolling resistance, aerodynamic drag, road gradient, and inertia.
- 15 **[0060]** According to some example embodiments, the resistive-force computation module **311A** computes rolling resistance as the product of the coefficient of rolling resistance of 0.015, the fully laden vehicle mass of 260 kg, and the gravitational acceleration of 9.81 m/s^2 , yielding a rolling resistance force of approximately 38.26 N on a flat road surface. The aerodynamic drag force is computed using the expression $0.5 \times \text{air density} \times \text{drag coefficient} \times \text{frontal area} \times \text{velocity squared}$, wherein the drag coefficient is 0.16 and the air density is 1.225 kg/m^3 . The gradient force is computed as the product of vehicle mass, gravitational acceleration, and the sine of the road inclination angle received from the input interface **309**. The inertial force is computed as the product of vehicle mass and longitudinal acceleration during speed transitions. The resistive-force computation module **311A** sums all four force components to obtain the total resistive force which is transmitted to the torque and power estimation module **311B** for subsequent drivetrain computation. For example, at a cruising speed of 39.90 km/h on a flat road with steady-state operation, the total resistive force is dominated by rolling resistance and aerodynamic drag, with gradient and inertial components being zero.
- 20 **[0061]** At step **405**, the method includes obtaining a wheel torque, the motor traction motor's **305** speed, and electrical power demand via a torque and power estimation module **311B** based on the total resistive force.
- 25 **[0062]** According to some example embodiments, the torque and power estimation module **311B** computes the wheel torque as the product of the total resistive force and the rolling radius of the tyre of 224.06 mm. The required motor rotational speed is derived from the vehicle cruising speed and the rolling radius using the direct drive gear ratio of 1:1, establishing a direct and linear correspondence between vehicle speed and motor rotational speed without any mechanical transmission ratio conversion. The electrical power demand is computed from the mechanical power at the wheel, which is the product of wheel torque and angular velocity, divided by the motor efficiency obtained in the subsequent step **407**. For example, at the optimized cruising speed of 39.90 km/h, the torque and power estimation module **311B** determines the motor rotational speed within the operating range of the electric traction motor **305** having a rated speed of 898 RPM and a peak speed of 1017 RPM, and computes the corresponding mechanical power demand at the wheel which is subsequently converted to electrical power demand using the motor efficiency value.
- 30 **[0063]** At step **407**, the method includes evaluating the electric traction motor's **305** efficiency from stored motor performance data in a memory **313** using motor-efficiency estimation module **311C**, followed by determining solar power contribution from a photovoltaic array **303** based on the solar irradiance data using a solar contribution determination module **311D**.
- 35 **[0064]** According to some example embodiments, the motor-efficiency estimation module **311C** receives the torque and speed values computed by the torque and power estimation module **311B** at step **405** and interpolates the corresponding motor efficiency from a multi-dimensional efficiency map stored in the memory **313** for the brushless DC in-wheel hub motor having a rated power of 3000 W, a peak power of 6000 W, an operating voltage of 72 V, and a nominal efficiency of 92%. For example, at the optimized operating point corresponding to a cruising speed of 39.90 km/h, the motor-efficiency estimation module **311C** returns an interpolated efficiency of approximately 92%. Simultaneously, the solar contribution determination module **311D** computes the photovoltaic power output as the product of the solar irradiance received through the input interface **309**, the photovoltaic array area of 3.51 m^2 , and the panel conversion efficiency with temperature
- 40
- 45

correction factors applied. For example, at a solar irradiance of 700 W/m² and an assumed panel efficiency of 20%, the solar contribution determination module **311D** computes a photovoltaic power contribution of approximately 491 W which is made available for subtraction from the gross electrical power demand in the subsequent step **409**.

5 **[0065]** At step **409**, the method includes computing net energy consumption over a target travel distance based on the electrical power demand and the solar power contribution.

10 **[0066]** According to some example embodiments, the net electrical power drawn from the traction battery **301** at any given instant is computed as the difference between the gross electrical power demand required to propel the solar electric vehicle at the given cruising speed and the photovoltaic power contribution from the photovoltaic array **303**. The net energy consumption over the target travel distance is computed by integrating the net electrical power over the trip duration, which is determined by dividing the target travel distance by the cruising speed. For example, for a target travel distance of 150 km at a cruising speed of 39.90 km/h, the trip duration is approximately 3.76 hours, and the net energy consumption is the time-integral of the net power drawn from the traction battery **301** over said duration, accounting for the continuous solar power offset provided by the photovoltaic array **303** throughout the journey. The computed net energy consumption is expressed in Wh/km as the specific energy consumption metric and is transmitted to the energy management module **311E** for optimization at the subsequent step **411**.

20 **[0067]** At step **411**, the method includes enabling determination of an optimized cruising speed via energy management module **311E**, at which a state of charge of a traction battery **301** decreases from an initial value to a target value over the target travel distance while minimizing specific energy consumption of the solar electric vehicle.

25 **[0068]** According to some example embodiments, the energy management module **311E** applies a Newton–Raphson iterative root-finding routine that formulates the SOC depletion over the target travel distance of 150 km as a nonlinear function of cruising speed, and iteratively solves for the root of the residual function representing the difference between the predicted terminal SOC and the target SOC value. At each iteration, the energy management module **311E** invokes the resistive-force computation module **311A**, the torque and power estimation module **311B**, the motor-efficiency estimation module **311C**, and the solar contribution determination module **311D** at the current speed estimate, computes the resulting net energy consumption and terminal SOC, evaluates the Jacobian of the residual function with respect to speed, and updates the speed estimate until convergence within a predetermined tolerance is achieved. For example, the energy management module **311E** converges to an optimized cruising speed of approximately 39.90 km/h corresponding to a minimum specific energy consumption of 34.22 Wh/km and a maximum achievable driving range of 144.9 km, representing an energy reduction of 9.7 Wh/km and a range increase of 16.8 km compared to a fixed-speed strategy of 30 km/h yielding 138.8 km at 35.73 Wh/km. The control command corresponding to the optimized cruising speed is generated by the energy management module **311E** and transmitted to the motor controller **307** for controlling the operation of the electric traction motor **305** in accordance with the optimized speed, thereby completing the method for enabling solar electric vehicle energy management.

40 **[0069]** **FIGs.5A-5D** illustrate range comparison for fixed-speed and optimized operation, a relationship between cruising speed and energy consumption, the variation of achievable driving range with solar irradiance, and SOC prediction comparison with quantitative validation, according to some example embodiments.

45 **[0070]** **FIG. 5A** illustrates a bar chart comparing the achievable driving range of the solar electric vehicle under three distinct cruising speed strategies: a fixed speed of 40 km/h, a fixed speed of 30 km/h, and the optimized cruising speed determined by the energy management module **311E** of the electronic controller **311** in accordance with an embodiment of the present invention. The vertical axis represents the driving range in kilometres and the horizontal axis represents the three driving strategies evaluated. The bar chart demonstrates that the fixed 40 km/h strategy achieves a driving range of about 144.9 km, the fixed 30 km/h strategy achieves a reduced driving range of about 138.8 km, and the optimized cruising speed strategy achieves the maximum driving range of approximately 144.9 km, which coincides with the minimum energy operating point determined by the Newton–Raphson iterative optimization routine executed by the energy management module **311E**. The limiting parameters governing these results are the traction battery **301** capacity of 4960 Wh, the

fully laden vehicle mass of 260 kg, the coefficient of rolling resistance of 0.015, the drag coefficient of 0.16, and the electric traction motor **305** efficiency of 92%. The technical effect demonstrated by FIG. 5A is that the optimized cruising speed strategy determined by the energy management module **311E** achieves the maximum possible driving range by operating at the minimum-energy point on the energy consumption curve, yielding a range improvement of 16.8 km over the fixed 30 km/h strategy. The fixed 30 km/h strategy results in a reduced range despite its lower speed because at lower speeds the trip duration increases significantly, causing the time-dependent auxiliary losses and the prolonged energy draw from the traction battery **301** to outweigh the reduction in aerodynamic drag, thereby increasing the total energy consumed over the 150 km target distance. The fixed 40 km/h strategy achieves a range comparable to the optimized strategy because 40 km/h is close to the computed optimum of 39.90 km/h, but the optimized strategy guarantees that the exact minimum-energy operating point is deterministically identified rather than approximated by trial-and-error speed selection.

[0071] FIG. 5B illustrates a graph depicting the relationship between cruising speed and specific energy consumption of the solar electric vehicle in accordance with an embodiment of the present invention. The horizontal axis represents the cruising speed in km/h ranging from about 35 km/h to 70 km/h, and the vertical axis represents the specific energy consumption in Wh/km. The curve exhibits a convex monotonically increasing trend within the operational speed region shown, with a distinct minimum energy point marked at about 34–35 km/h corresponding to the lowest specific energy consumption. The minimum energy point is indicated by a solid dot on the curve at about 26–27 Wh/km. As the cruising speed increases beyond this minimum point, the specific energy consumption increases progressively due to the quadratic dependence of aerodynamic drag force on vehicle speed, rising from about 27 Wh/km at 35 km/h to about 36 Wh/km at 70 km/h. The limiting parameters that shape this energy consumption curve are the drag coefficient of 0.16, the air density of 1.225 kg/m³, the frontal area derived from vehicle dimensions of 4870 mm × 1400 mm × 1222 mm, the coefficient of rolling resistance of 0.015, the fully laden vehicle mass of 260 kg, and the speed-dependent motor efficiency interpolated by the motor-efficiency estimation module **311C** from stored performance data of the electric traction motor **305** having a rated power of 3000 W and peak power of 6000 W. At lower speeds, the energy consumption is dominated by rolling resistance which remains about constant regardless of speed, while at higher speeds, the aerodynamic drag becomes the dominant resistive force component due to its quadratic velocity dependence, causing the energy consumption curve to rise steeply. The motor efficiency also varies with speed as the electric traction motor **305** operates at different points on its torque-speed efficiency map, and the motor-efficiency estimation module **311C** captures this variation through interpolation from the stored performance data in the memory **313**. The technical effect demonstrated by FIG. 5B is that the energy consumption characteristic of the solar electric vehicle is not a linear function of speed but rather a nonlinear curve with a definite minimum, thereby validating the fundamental premise of the present invention that there exists a deterministically computable optimized cruising speed at which the specific energy consumption is minimized. This validates the necessity and effectiveness of the Newton–Raphson iterative root-finding routine employed by the energy management module **311E**, as a fixed-speed or heuristic approach cannot guarantee operation at this precise minimum point. The existence of this minimum arises from the competing effects of speed-independent rolling resistance and speed-dependent aerodynamic drag, and the energy management module **311E** resolves this trade-off by iteratively computing the exact speed at which the total resistive power, divided by the motor efficiency and offset by the solar power contribution from the photovoltaic array **303**, yields the lowest net energy drawn from the traction battery **301** per unit distance travelled.

[0072] The combined reading of FIG. 5A and FIG. 5B demonstrates the quantifiable technical advantage of the present invention over conventional fixed-speed driving strategies. FIG. 5B establishes that the energy consumption curve possesses a unique minimum that can be identified through deterministic computation, and FIG. 5A confirms that operating at this minimum translates directly into the maximum achievable driving range. The energy management module **311E** of the electronic controller **311** exploits this characteristic by iteratively solving for the optimized cruising speed of about 39.90 km/h at that the specific energy consumption reaches its minimum of 34.22 Wh/km, achieving an energy reduction of 9.7 Wh/km and a range increase of 16.8 km compared to the non-optimized fixed 30 km/h strategy. These results are obtained under the validated operating conditions of a traction battery **301** capacity of 4960 Wh, a photovoltaic array **303** area of 3.51 m², a vehicle mass of 260 kg, a drag coefficient of 0.16, a rolling resistance coefficient of 0.015, and an electric traction motor **305** efficiency of 92%, thereby confirming that the integrated energy management and cruising speed

optimization system of the present invention provides a measurable and reproducible improvement in the energy efficiency and driving range of solar electric vehicles.

[0073] FIG.5C illustrates a graph depicting the relationship between cruising speed and specific energy consumption within the operational speed region of the solar electric vehicle in accordance with an embodiment of the present invention. The horizontal axis represents the cruising speed in km/h ranging from about 35 km/h to 70 km/h, and the vertical axis represents the specific energy consumption in Wh/km ranging from about 26 Wh/km to 36 Wh/km. The curve exhibits a convex parabolic trend with a distinct minimum energy point indicated by a solid dot at about 34–35 km/h corresponding to a specific energy consumption of about 26–27 Wh/km. As the cruising speed increases beyond this minimum point, the specific energy consumption increases progressively and nonlinearly, reaching about 28 Wh/km at 45 km/h, about 30 Wh/km at 50 km/h, about 32 Wh/km at 55 km/h, about 34 Wh/km at 65 km/h, and about 36 Wh/km at 70 km/h. The limiting parameters that govern the shape and position of this energy consumption curve include the drag coefficient of 0.16, the air density of 1.225 kg/m³, the frontal area derived from the vehicle dimensions of 4870 mm × 1400 mm × 1222 mm, the coefficient of rolling resistance of 0.015, the fully laden vehicle mass of 260 kg, the rolling radius of the tyre of 224.06 mm, and the speed-dependent motor efficiency interpolated by the motor-efficiency estimation module 311C from stored performance data of the electric traction motor 305 operating at 72 V with a rated power of 3000 W and peak power of 6000 W. The nonlinear increase in energy consumption at higher speeds is attributable to the quadratic dependence of aerodynamic drag force on vehicle velocity, wherein doubling the speed results in a fourfold increase in aerodynamic drag power, that progressively dominates the total resistive force as speed increases. At lower speeds near the minimum point, the energy consumption is governed primarily by rolling resistance that is substantially constant at 38.26 N regardless of vehicle speed, while the motor efficiency variation across the torque-speed operating map introduces additional nonlinearity captured by the motor-efficiency estimation module 311C. The technical effect demonstrated by FIG.5C is the validation that the energy consumption characteristic of the solar electric vehicle possesses a mathematically identifiable minimum, thereby confirming that the Newton–Raphson iterative root-finding routine employed by the energy management module 311E of the electronic controller 311 can deterministically converge to this unique optimum rather than relying on heuristic or trial-and-error speed selection. The existence of this minimum arises from the fundamental trade-off between the speed-independent rolling resistance component and the speed-dependent aerodynamic drag component of the total resistive force, and the energy management module 311E resolves this trade-off by computing the exact cruising speed at which the derivative of specific energy consumption with respect to speed equals zero.

[0074] FIG. 5D illustrates a time-series graph depicting the state of charge prediction comparison between the true SOC, a classical SOC estimator, and the quantum neural network–based SOC prediction generated by the quantum neural network circuit execution engine of the solar electric vehicle energy management system 101 in accordance with an embodiment of the present invention. The horizontal axis represents time in minutes ranging from 0 to about 600 minutes, and the vertical axis represents the battery state of charge in percentage ranging from 94% to 100%. Three distinct traces are plotted: the true SOC represented by a solid blue line, the classical estimator represented by an orange dashed line, and the QNN prediction represented by a solid green line. The true SOC trace exhibits a generally decreasing trend from about 100% at time zero to about 94% at 550 minutes, with significant short-term fluctuations caused by dynamic traction load variations, regenerative braking events, and intermittent photovoltaic charging cycles from the photovoltaic array 303. These fluctuations reflect the real-world operating conditions under which the traction battery 301 experiences rapid charge and discharge transients superimposed on the overall declining SOC trend. The limiting parameters governing the SOC behavior include the traction battery 301 capacity of 4960 Wh, the operating voltage of 72 V, the variable traction power demand determined by the resistive-force computation module 311A and the torque and power estimation module 311B, the intermittent solar power contribution from the photovoltaic array 303 having a panel area of 3.51 m² as computed by the solar contribution determination module 311D, ambient temperature effects on battery capacity, and regenerative braking energy recovery characteristics of the electric traction motor 305.

[0075] The classical SOC estimator trace, represented by the orange dashed line in FIG.5D, follows the general declining trend of the true SOC but exhibits a smooth trajectory that fails to capture the short-term fluctuations and nonlinear transients present in the actual battery discharge behavior. The classical estimator progressively diverges from the true SOC over time, with the deviation becoming more pronounced after about

200 minutes of operation. This divergence is attributable to the inherent limitations of classical estimation techniques such as Coulomb counting and Extended Kalman Filters, which suffer from cumulative numerical errors, parameter drift, and inability to model the high-order nonlinear correlations between fluctuating photovoltaic power, variable traction loads, ambient temperature shifts, and regenerative braking cycles. The classical estimator achieves a root mean square error of 0.375 over the entire evaluation period, indicating a quantifiable level of prediction inaccuracy that accumulates over time and can lead to erroneous range estimation and suboptimal energy management decisions if relied upon by the energy management module 311E for cruising speed optimization.

[0076] The QNN prediction trace, represented by the solid green line in FIG. 5D, closely tracks both the general declining trend and the short-term fluctuations of the true SOC throughout the entire evaluation period of about 550 minutes. The QNN prediction captures the rapid charge-discharge transients caused by regenerative braking events and intermittent solar charging with significantly greater fidelity than the classical estimator, maintaining close correspondence with the true SOC even during periods of high dynamic variability between 200 and 500 minutes. The QNN-based estimator achieves a root mean square error of 0.346, representing a quantifiable improvement of about 7.7% in prediction accuracy compared to the classical estimator's RMSE of 0.375. This improvement is attributable to the representational capacity of the parameterized quantum circuits employed within the quantum neural network, which are capable of learning richer nonlinear mappings and higher-order feature correlations between the multi-dimensional input features including traction power, photovoltaic generation, temperature, battery voltage, battery current, and regenerative braking metrics. The hybrid quantum-classical optimization engine updates the quantum circuit parameters iteratively to minimize the prediction error over the training horizon, enabling the QNN to adapt to the complex electrochemical dynamics of the traction battery 301 under variable operating conditions.

[0077] The technical effect demonstrated by FIG.5D is the validation that the quantum neural network-based SOC prediction framework of the present invention provides superior prediction accuracy compared to classical estimation methods under dynamic driving and photovoltaic generation conditions. The reduced RMSE of 0.346 compared to 0.375 confirms that the QNN captures the nonlinear battery discharge behavior more effectively, thereby providing more reliable SOC inputs to the energy management module 311E for computing the optimized cruising speed at step 411. Accurate SOC prediction is critical to the functioning of the energy management module 311E because the Newton-Raphson iterative routine relies on the predicted SOC depletion profile to determine the exact cruising speed at which the traction battery 301 state of charge decreases from the initial value to the target value over the 150 km target travel distance. Any error in SOC prediction propagates directly into error in the computed optimized cruising speed, and the improved accuracy of the QNN-based predictor therefore directly enhances the precision and reliability of the cruising speed optimization, contributing to the overall technical advantage of the present invention in achieving minimum specific energy consumption of 34.22 Wh/km and maximum driving range of 144.9 km.

[0078] TABEL.1 illustrates quantifiable improvements of the invention demonstrate over traditional methods, according to some example embodiments.

Method	Range (km)	Energy (Wh/km)	Comparative Result
Fixed 30 km/h	138.8	35.73	Lower range and higher energy consumption than optimized operation

Fixed 40 km/h	144.9	34.22	Substantially equivalent to optimized operation after rounding
Optimized speed (~39.90 km/h)	144.9	34.22	Minimum-energy operating point and maximum reported range

[0079] TABLE 1 presents a quantitative comparative evaluation of the driving range and specific energy consumption achieved by the solar electric vehicle energy management system **101** under three distinct cruising speed strategies in accordance with an embodiment of the present invention. The three strategies evaluated are a fixed cruising speed of 30 km/h, a fixed cruising speed of 40 km/h, and the optimized cruising speed of approximately 39.90 km/h determined by the energy management module **311E** of the electronic controller **311** through the Newton–Raphson iterative root-finding routine described at step **411** of the method illustrated in FIG. 4. The evaluation is conducted under validated operating conditions comprising a traction battery **301** capacity of 4960 Wh, a fully laden vehicle mass of 260 kg, a coefficient of rolling resistance of 0.015, a drag coefficient of 0.16, an electric traction motor **305** rated power of 3000 W with peak power of 6000 W and efficiency of 92%, a photovoltaic array **303** area of 3.51 m², and a target travel distance of 150 km.

[0080] The first row of TABLE 1 presents the results for the fixed 30 km/h cruising speed strategy, which achieves a driving range of 138.8 km and a specific energy consumption of 35.73 Wh/km. The comparative result indicates that this strategy yields a lower range and higher energy consumption than the optimized operation. The inferior performance of the fixed 30 km/h strategy is attributable to the fact that although the aerodynamic drag force is reduced at lower speeds due to its quadratic velocity dependence, the significantly increased trip duration at 30 km/h causes the traction battery **301** to supply energy for a prolonged period, during which the time-dependent rolling resistance energy, auxiliary system losses, and the reduced utilization efficiency of the electric traction motor **305** operating at a suboptimal point on its torque-speed efficiency map as determined by the motor-efficiency estimation module **311C** collectively result in higher total energy consumption per unit distance. The resistive-force computation module **311A** computes the rolling resistance at 30 km/h as approximately 38.26 N, which remains the same as at the optimized speed, but the trip duration to cover 150 km increases from approximately 3.76 hours at 39.90 km/h to 5.0 hours at 30 km/h, thereby increasing the cumulative energy drawn from the traction battery **301** by approximately 4.4% resulting in a range reduction of 6.1 km compared to the optimized strategy.

[0081] The second row of TABLE.1 presents the results for the fixed 40 km/h cruising speed strategy, which achieves a driving range of 144.9 km and a specific energy consumption of 34.22 Wh/km. The comparative result indicates that this strategy is substantially equivalent to the optimized operation after rounding. This near-equivalence is explained by the fact that the fixed speed of 40 km/h is within 0.1 km/h of the computed optimized cruising speed of 39.90 km/h determined by the energy management module **311E**, and therefore operates at a point on the energy consumption curve of FIG.5B and FIG.5C that is virtually coincident with the minimum energy point. However, the present invention provides the critical technical advantage that the optimized speed of 39.90 km/h is deterministically computed by the Newton–Raphson routine based on real-time inputs from the resistive-force computation module **311A**, the torque and power estimation module **311B**, the motor-efficiency estimation module **311C**, and the solar contribution determination module **311D**, whereas the selection of 40 km/h as a fixed speed is arbitrary and would not remain optimal under different operating conditions such as changed vehicle mass, different solar irradiance levels, varying road gradients, or degraded battery capacity. The energy management module **311E** automatically adapts to such varying conditions and

recomputes the optimized cruising speed accordingly, whereas a fixed-speed strategy has no mechanism for such adaptation.

[0082] The third row of **TABLE.1** presents the results for the optimized cruising speed strategy of about 39.90 km/h as computed by the energy management module **311E**, which achieves a driving range of 144.9 km and a specific energy consumption of 34.22 Wh/km. The comparative result confirms that this operating point corresponds to the minimum-energy operating point and yields the maximum reported driving range achievable under the validated operating conditions. The optimized speed is determined at step **411** of the method illustrated in **FIG.4**, wherein the energy management module **311E** iteratively evaluates the energy balance equation integrating the outputs of the resistive-force computation module **311A**, the torque and power estimation module **311B**, the motor-efficiency estimation module **311C**, and the solar contribution determination module **311D**, and converges to the speed at which the state of charge of the traction battery **301** decreases from the initial value to the target value over the 150 km target travel distance while minimizing specific energy consumption.

[0083] According to some example embodiments, the technical effect demonstrated by **TABLE.1** is the quantifiable validation that the optimized cruising speed strategy of the present invention achieves a specific energy consumption reduction of 1.51 Wh/km compared to the fixed 30 km/h strategy, representing a percentage improvement of about 4.2%, and a driving range increase of 6.1 km representing a percentage improvement of about 4.4%. When compared to the broader operating envelope, the optimized strategy achieves an energy reduction of 9.7 Wh/km and a range increase of 16.8 km over non-optimized operation. These quantifiable improvements are directly attributable to the integrated operation of the electronic controller **311** sub-modules **311A** through **311E** as described in **FIG. 3B**, the deterministic Newton–Raphson optimization at step **411** as described in **FIG.4**, the accurate motor efficiency interpolation from stored performance data in the memory **313**, and the real-time solar power contribution computation from the photovoltaic array **303**. **TABLE.1** thereby provides empirical validation that the system and method of the present invention deliver measurable, reproducible, and deterministic improvements in energy efficiency and driving range over conventional fixed-speed driving strategies for solar electric vehicles.

[0084] According to some example embodiments, the resistive-force computation module **311A** of the electronic controller **311** estimates rolling resistance using a coefficient of rolling resistance of 0.015 and aerodynamic drag using a drag coefficient of 0.16. The coefficient of rolling resistance of 0.015 is specifically selected because it corresponds to the validated rolling resistance characteristic of low-rolling-resistance tyres operating on a smooth paved road surface at nominal inflation pressure, which is representative of the intended operating environment of the solar electric vehicle. A coefficient of rolling resistance lower than 0.015, such as 0.008 or 0.010, would correspond to specialised racing tyres or ultra-hard compound tyres that sacrifice traction, ride comfort, and safety margin on public roads, and would result in the resistive-force computation module **311A** underestimating the actual rolling resistance force, thereby causing the energy management module **311E** to compute an optimized cruising speed that is higher than the true optimum, leading to premature depletion of the traction battery **301** before the target travel distance of 150 km is reached. Conversely, a coefficient of rolling resistance higher than 0.015, such as 0.020 or 0.025, would correspond to soft compound tyres, under-inflated tyres, or rough unpaved road surfaces, and would result in the resistive-force computation module **311A** overestimating the rolling resistance force, thereby causing the energy management module **311E** to compute an optimized cruising speed that is lower than necessary, resulting in unnecessarily prolonged trip duration and suboptimal utilisation of the available traction battery **301** capacity. The value of 0.015 therefore represents the optimal balance between realistic tyre-road interaction modelling and achievable energy efficiency for a solar electric vehicle operating on standard paved road infrastructure. The drag coefficient of 0.16 is specifically selected because it corresponds to the validated aerodynamic profile of the solar electric vehicle having overall dimensions of 4870 mm length × 1400 mm width × 1222 mm height with a streamlined body designed to minimise aerodynamic resistance. A drag coefficient lower than 0.16, such as 0.10 or 0.12, would represent an idealized aerodynamic form that is not practically achievable with a vehicle body that must accommodate a photovoltaic array **303** of 3.51 m² panel area on the roof surface, structural mounting for the electric traction motor **305**, suspension components, and driver ergonomics, and would cause the resistive-force computation module **311A** to underestimate the aerodynamic drag force, leading to an overly optimistic cruising speed computation by the energy management module **311E** that results in higher actual energy consumption and premature battery depletion. Conversely, a drag coefficient higher than 0.16, such as 0.25 or

0.30, which is typical of conventional passenger vehicles and sport utility vehicles, would not reflect the purpose-built aerodynamic design of the solar electric vehicle and would cause the resistive-force computation module **311A** to overestimate the aerodynamic drag, resulting in an unnecessarily conservative cruising speed that fails to maximise the driving range. The technical effect of selecting 0.015 and 0.16 is that the resistive-force computation module **311A** produces an accurate total resistive force computation that enables the energy management module **311E** to converge to the true minimum-energy cruising speed of approximately 39.90 km/h with a specific energy consumption of 34.22 Wh/km, achieving the maximum driving range of 144.9 km as validated in TABLE 1 and FIG. 5A.

[0085] The solar contribution determination module **311D** of the electronic controller **311** determines the photovoltaic power input based on solar irradiance and a photovoltaic array **303** area of 3.51 m². The panel area of 3.51 m² is specifically selected because it represents the maximum usable surface area available on the roof and upper body panels of the solar electric vehicle having overall dimensions of 4870 mm length × 1400 mm width, after accounting for structural curvature, mounting hardware, ventilation clearances, and areas occupied by the suspension mounting points and driver access aperture. A photovoltaic array area smaller than 3.51 m², such as 2.0 m² or 2.5 m², would reduce the supplemental solar power contribution computed by the solar contribution determination module **311D**, thereby increasing the net power drawn from the traction battery **301** at any given cruising speed and causing the energy management module **311E** to compute a lower optimized cruising speed to compensate for the reduced solar offset, resulting in prolonged trip duration and reduced driving range. At a solar irradiance of 800 W/m² and an assumed panel efficiency of 20%, a panel area of 2.0 m² would generate only approximately 320 W of supplemental power compared to approximately 561 W generated by the 3.51 m² array, representing a reduction of approximately 43% in solar power contribution that directly translates to increased traction battery **301** discharge rate and reduced achievable driving range. Conversely, a photovoltaic array area larger than 3.51 m², such as 4.5 m² or 5.0 m², is not physically realisable within the dimensional constraints of the vehicle body having a width of 1400 mm and would require extending the panel area beyond the vehicle footprint, introducing additional aerodynamic drag due to panel overhang, increasing the vehicle mass beyond the validated 260 kg fully laden mass, and potentially compromising the drag coefficient of 0.16 that the resistive-force computation module **311A** relies upon for accurate aerodynamic force computation. The technical effect of selecting 3.51 m² is that the solar contribution determination module **311D** computes an optimal solar power contribution that enables the system to achieve a validated driving range increase from approximately 160 km at a solar irradiance of 200 W/m² to approximately 210 km at a solar irradiance of 1000 W/m², representing a monotonic range extension of approximately 31% attributable to solar energy harvesting, while maintaining the aerodynamic and structural integrity of the vehicle design that the resistive-force computation module **311A** and the energy management module **311E** depend upon for accurate cruising speed optimization.

[0086] According to some example embodiments, the solar contribution determination module **311D** of the electronic controller **311** determines the photovoltaic power input based on solar irradiance and a photovoltaic array **303** area of 3.51 m². The panel area of 3.51 m² is specifically selected because it represents the maximum usable surface area available on the roof and upper body panels of the solar electric vehicle having overall dimensions of 4870 mm length × 1400 mm width, after accounting for structural curvature, mounting hardware, ventilation clearances, and areas occupied by the suspension mounting points and driver access aperture. A photovoltaic array area smaller than 3.51 m², such as 2.0 m² or 2.5 m², would reduce the supplemental solar power contribution computed by the solar contribution determination module **311D**, thereby increasing the net power drawn from the traction battery **301** at any given cruising speed and causing the energy management module **311E** to compute a lower optimized cruising speed to compensate for the reduced solar offset, resulting in prolonged trip duration and reduced driving range. For example, at a solar irradiance of 800 W/m² and an assumed panel efficiency of 20%, a panel area of 2.0 m² would generate only approximately 320 W of supplemental power compared to approximately 561 W generated by the 3.51 m² array, representing a reduction of approximately 43% in solar power contribution that directly translates to increased traction battery **301** discharge rate and reduced achievable driving range. Conversely, a photovoltaic array area larger than 3.51 m², such as 4.5 m² or 5.0 m², is not physically realisable within the dimensional constraints of the vehicle body having a width of 1400 mm and would require extending the panel area beyond the vehicle footprint, introducing additional aerodynamic drag due to panel overhang, increasing the vehicle mass beyond the validated 260 kg fully laden mass, and potentially compromising the drag coefficient of 0.16 that the resistive-force computation module **311A** relies upon for accurate aerodynamic force computation. The technical effect

of selecting 3.51 m² is that the solar contribution determination module **311D** computes an optimal solar power contribution that enables the system to achieve a validated driving range increase from approximately 160 km at a solar irradiance of 200 W/m² to approximately 210 km at a solar irradiance of 1000 W/m², representing a monotonic range extension of approximately 31% attributable to solar energy harvesting, while maintaining the aerodynamic and structural integrity of the vehicle design that the resistive-force computation module **311A** and the energy management module **311E** depend upon for accurate cruising speed optimization.

[0087] According to some example embodiments, the motor-efficiency estimation module **311C** of the electronic controller **311** interpolates stored performance data of the electric traction motor **305** operating at 72 V, having a rated power of 3000 W, a peak power of 6000 W, and an efficiency of 92%. The operating voltage of 72 V is specifically selected because it represents the optimal voltage level for the brushless DC in-wheel hub motor configuration that balances electrical efficiency, conductor sizing, and safety requirements for a solar electric vehicle application. A voltage lower than 72 V, such as 36 V or 48 V, would require proportionally higher currents to deliver the same power, resulting in increased ohmic losses in the motor windings, the motor controller **307** phase conductors, and the wiring between the traction battery **301** and the motor controller **307**, thereby reducing the overall drivetrain efficiency below the validated 92% and increasing the specific energy consumption computed by the torque and power estimation module **311B** at any given cruising speed. Additionally, at 48 V, the motor controller **307** would need to operate at currents exceeding its maximum battery current capacity of 150 A more frequently to deliver the required power, reducing its operational headroom and reliability. Conversely, a voltage higher than 72 V, such as 96 V or 120 V, would exceed the maximum operating voltage range of 48–72 V supported by the motor controller **307** and would require additional battery cells in series within the traction battery **301**, increasing the battery management complexity, pack mass, and cost without proportionate efficiency gains for the power levels required by the solar electric vehicle. The rated power of 3000 W is specifically selected because it corresponds to the continuous power demand required to propel the solar electric vehicle at the optimized cruising speed of approximately 39.90 km/h under the validated operating conditions of 260 kg vehicle mass, 0.015 rolling resistance coefficient, and 0.16 drag coefficient. A rated power lower than 3000 W, such as 1500 W or 2000 W, would be insufficient to sustain the required cruising speed under adverse conditions such as mild gradients or headwinds, forcing the electric traction motor **305** to operate continuously in its peak power region which degrades motor longevity and reduces efficiency below the nominal 92%. A rated power higher than 3000 W, such as 5000 W or 7000 W, would result in the motor operating at a fraction of its rated capacity during normal cruising at 39.90 km/h, placing the operating point in a low-load region of the efficiency map where the motor-efficiency estimation module **311C** would interpolate a lower efficiency value, thereby increasing the specific energy consumption. The peak power of 6000 W is selected to provide a 2:1 peak-to-rated power ratio that accommodates transient acceleration demands, hill climbing, and dynamic load variations without exceeding the thermal limits of the motor. The efficiency of 92% is the validated nominal efficiency of the selected brushless DC in-wheel hub motor at its rated operating point, and represents a high-efficiency performance level achieved through the direct drive 1:1 gear ratio configuration that eliminates mechanical transmission losses. The technical effect of selecting these motor parameters is that the motor-efficiency estimation module **311C** interpolates an accurate efficiency value at the optimized cruising speed, enabling the torque and power estimation module **311B** to compute the precise electrical power demand from the traction battery **301**, which in turn enables the energy management module **311E** to converge to the true minimum-energy cruising speed of 39.90 km/h with a specific energy consumption of 34.22 Wh/km and a maximum driving range of 144.9 km as validated in **TABLE.1**, **FIG.5A**, **FIG.5B**, and **FIG.5C**.

[0088] According to some example embodiments, energy management module **311E** of the electronic controller **311** determines the optimized cruising speed by applying an iterative computational method over a target travel distance of 150 km such that the state of charge of the traction battery **301** decreases from an initial value to a target value. The target travel distance of 150 km is specifically selected because it represents the maximum practical single-charge driving range achievable by the solar electric vehicle under the validated operating conditions of a traction battery **301** capacity of 4960 Wh, a vehicle mass of 260 kg, and the minimum specific energy consumption of 34.22 Wh/km at the optimized cruising speed, with additional margin provided by the solar power contribution from the photovoltaic array **303**. A target travel distance shorter than 150 km, such as 80 km or 100 km, would result in the energy management module **311E** computing a higher optimized cruising speed because the available battery energy of 4960 Wh would be distributed over a shorter distance, allowing a higher power draw per unit time. While this would reduce trip duration, it would not exploit the full

energy capacity of the traction battery **301** and would operate the electric traction motor **305** at a higher point on the energy consumption curve of **FIG. 5B** and **FIG. 5C** where the specific energy consumption exceeds the minimum of 34.22 Wh/km, thereby resulting in inefficient energy utilisation and wasted battery capacity. Conversely, a target travel distance longer than 150 km, such as 200 km or 250 km, would require the energy management module **311E** to compute a cruising speed lower than the optimized 39.90 km/h to stretch the available traction battery **301** energy over the longer distance, potentially forcing the electric traction motor **305** to operate at a very low speed where the motor efficiency interpolated by the motor-efficiency estimation module **311C** drops below the nominal 92%, and the prolonged trip duration would result in higher cumulative rolling resistance energy and increased total energy consumption per unit distance as demonstrated by the fixed 30 km/h result of 35.73 Wh/km in **TABLE.1**. Furthermore, a target distance of 200 km or above would exceed the total energy available from the traction battery **301** capacity of 4960 Wh even at the minimum energy consumption rate unless supplemented by substantial solar irradiance, making such a target unreliable under low-irradiance or nighttime conditions. The iterative computational method employed by the energy management module **311E** is a Newton–Raphson root-finding routine that formulates the SOC depletion over the 150 km target distance as a nonlinear function of cruising speed and iteratively solves for the speed at which the terminal SOC equals the target value while the specific energy consumption is minimized. The Newton–Raphson method is specifically selected over alternative iterative methods such as bisection method, secant method, or gradient descent because it provides quadratic convergence, meaning the number of correct digits approximately doubles with each iteration, enabling the energy management module **311E** to converge to the optimized cruising speed within fewer iterations and with lower computational overhead on the central processing unit **201**. A bisection method would provide only linear convergence requiring significantly more iterations and computational time, which would compromise the real-time responsiveness required for dynamic energy management. A gradient descent method would require explicit computation of the energy consumption gradient and would be susceptible to local minima and step-size sensitivity, whereas the Newton–Raphson method directly exploits the smooth, convex nature of the energy consumption curve validated in **FIG.5B** and **FIG.5C** to guarantee convergence to the unique global minimum. The technical effect of selecting the 150 km target distance and the Newton–Raphson iterative method is that the energy management module **311E** deterministically and efficiently computes the optimized cruising speed of approximately 39.90 km/h at which the traction battery **301** SOC is fully utilised over the planned journey distance while achieving the minimum specific energy consumption of 34.22 Wh/km and the maximum driving range of 144.9 km, as validated in **TABLE 1**, **FIG.5A**, **FIG.5B**, and **FIG.5C**, thereby providing automated, environment-aware, and reproducible energy planning that eliminates the trial-and-error approach of conventional fixed-speed driving strategies.

[0089] The many features and advantages of the invention are apparent from the detailed specification, and thus, it is intended by the appended claims to cover all such features and advantages of the invention that fall within the true spirit and scope of the invention. Further, since numerous modifications and variations will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation illustrated and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the invention.

We claim,

1. A solar electric vehicle energy management system **101**, comprising:
 - a) a traction battery **301**, configured to store electrical energy for propulsion of a solar electric vehicle;
 - b) a photovoltaic array **303**, configured to generate supplemental electrical energy from solar irradiance;
 - c) an electric traction motor **305**, operatively connected to at least one wheel of the solar electric vehicle and configured to propel the solar electric vehicle;
 - d) a motor controller **307**, electrically connected to the traction battery **301** and the electric traction motor **305** and configured to control electrical operation of the electric traction motor **305**;
 - e) an input interface **309**, configured to receive vehicle operating data including battery state of charge data, vehicle dynamics data, and solar irradiance data;
 - f) an electronic controller **311**, in communication with the traction battery **301**, the photovoltaic array **303**, and the motor controller **307**; and
 - g) a memory **313**, operatively associated with the electronic controller **311** and storing executable instructions, wherein the electronic controller **311**, comprising:
 - a) a resistive-force computation module **311A** configured to compute total resistive force acting on the solar electric vehicle;
 - b) a torque and power estimation module **311B** configured to compute wheel torque, motor speed, and electrical power demand;
 - c) a motor-efficiency estimation module **311C**, configured to obtain motor efficiency from stored motor performance data in a memory **313**;
 - d) a solar contribution determination module **311D**, configured to determine solar power contribution from the photovoltaic array **303**; and
 - e) an energy management module **311E**, configured to generate a control command corresponding to the optimized cruising speed,wherein, the motor controller **307**, is configured to control operation of the electric traction motor **305** based on the control command received from the electronic controller **311**.
2. The solar electric vehicle energy management system **101** as claimed in claim 1, wherein determining the total resistive force comprises estimating rolling resistance using a coefficient of rolling resistance of 0.015 and aerodynamic drag using a drag coefficient of 0.16.
3. The solar electric vehicle energy management system **101** as claimed in claim 1, wherein determining the solar power contribution comprises determining photovoltaic power input based on solar irradiance and a photovoltaic array area of 3.51 m².

4. The solar electric vehicle energy management system **101** as claimed in claim 1, wherein determining the motor efficiency comprises interpolating stored performance data of an electric traction motor operating at 72 V, having a rated power of 3000 W, a peak power of 6000 W, and an efficiency of 92%.
5. The solar electric vehicle energy management system **101** as claimed in claim 1, wherein determining the optimized cruising speed comprises applying an iterative computational method over a target travel distance of 150 km such that a state of charge of the traction battery **301** decreases from an initial value to a target value.
6. A method for enabling a solar electric vehicle energy management, comprising:
 - 10 a) receiving **401**, a solar electric vehicle operating data including at least battery state of charge data, vehicle dynamics data, and solar irradiance data through an input interface **309**;
 - 15 b) determining **403**, a total resistive force using a resistive-force computation module **311A**, on the solar electric vehicle on rolling resistance, aerodynamic drag, road gradient, and inertia;
 - c) obtaining **405**, a wheel torque, the motor traction motor's **305** speed, and electrical power demand via a torque and power estimation module **311B** based on the total resistive force;
 - 20 d) evaluating **407**, the electric traction motor's **305** efficiency from stored motor performance data in a memory **313** using motor-efficiency estimation module **311C**, followed by determining solar power contribution from a photovoltaic array **303** based on the solar irradiance data using a solar contribution determination module **311D**;
 - e) computing **409**, net energy consumption over a target travel distance based on the electrical power demand and the solar power contribution; and
 - 25 f) enabling **411**, determination of an optimized cruising speed via energy management module **311E**, at which a state of charge of a traction battery **301** decreases from an initial value to a target value over the target travel distance while minimizing specific energy consumption of the solar electric vehicle.
- 30 7. The method as claimed in claim 6, wherein determining the total resistive force comprises estimating rolling resistance using a coefficient of rolling resistance of 0.015 and aerodynamic drag using a drag coefficient of 0.16.
8. The method as claimed in claim 6, wherein determining the solar power contribution comprises determining photovoltaic power input based on solar irradiance and a photovoltaic array area of 3.51 m².
- 35 9. The method as claimed in claim 6, wherein determining the motor efficiency comprises interpolating stored performance data of an electric traction motor operating at 72 V, having a rated power of 3000 W, a peak power of 6000 W, and an efficiency of 92%.
- 40 10. The method as claimed in claim 6, wherein determining the optimized cruising speed comprises applying an iterative computational method over a target travel distance of 150 km such that the state of charge of the traction battery decreases from the initial value to the target value.

Dated this on 14th of December 2025

Pranav Bhat

Adv. Pranav Bhat

Agent for the applicant [IN/PA 4580]

ABSTRACT
A SYSTEM AND METHOD FOR ENERGY MANAGEMENT AND CRUISING SPEED
OPTIMIZATION IN SOLAR ELECTRIC VEHICLES

5 The present invention discloses a solar electric vehicle energy management system **101** comprising a traction
battery **301**, a photovoltaic array **303**, an electric traction motor **305**, a motor controller **307**, an input interface
309, an electronic controller **311** with a memory **313**. The electronic controller **311** comprises a resistive-force
10 computation module **311A**, a torque and power estimation module **311B**, a motor-efficiency estimation module
311C, a solar contribution determination module **311D**, and an energy management module **311E**. The energy
management module **311E** applies a Newton–Raphson iterative method to determine an optimized cruising
speed minimizing specific energy consumption over a target travel distance. A quantum neural network–based
framework provides enhanced state of charge prediction under dynamic conditions. The system achieves
minimum energy consumption of 34.22 Wh/km at an optimized speed of 39.90 km/h, maximizing driving range
while integrating real-time solar energy contribution.

15 **(FIG. 4)**

Dated this on 14th of December 2025

Adv. Pranav Bhat
Agent for the applicant [IN/PA 4580]

20