

Instructions

Follow the instructions and get all the user stories below to pass to finish the project. Create your database by logging in to psql with `psql --username=freecodecamp --dbname=postgres`. You can query the database in your script with `psql --username=freecodecamp --dbname=salon -c "SQL QUERY HERE"`, add more flags if you need to. Be sure to get creative, and have fun!

Don't forget to connect to your database to add tables after you create it

Hints:

- The tests check the script output so don't use `clear` or other commands which might erase it
- See `examples.txt` for example output of a passing script
- The tests may add data to your database, feel free to delete it

Notes:

If you leave your virtual machine, your database may not be saved. You can make a dump of it by entering `pg_dump -cC --inserts -U freecodecamp salon > salon.sql` in a bash terminal (not the psql one). It will save the commands to rebuild your database in `salon.sql`. The file will be located where the command was entered. If it's anything inside the `project` folder, the file will be saved in the VM. You can rebuild the database by entering `psql -U postgres < salon.sql` in a terminal where the `.sql` file is.

If you are saving your progress on [freeCodeCamp.org](https://www.freecodecamp.org), after getting all the tests to pass, follow the instructions above to save a dump of your database. Save the `salon.sql` file, as well as the final version of your `salon.sh` file, in a public repository and submit the URL to it on [freeCodeCamp.org](https://www.freecodecamp.org).

Complete the tasks below

- You should create a database named `salon`
- You should connect to your database, then create tables named `customers`, `appointments`, and `services`
- Each table should have a primary key column that automatically increments
- Each primary key column should follow the naming convention, `table_name_id`. For example, the `customers` table should have a `customer_id` key. Note that there's no `s` at the end of `customer`
- Your `appointments` table should have a `customer_id` foreign key that references the `customer_id` column from the `customers` table
- Your `appointments` table should have a `service_id` foreign key that references the `service_id` column from the `services` table
- Your `customers` table should have `phone` that must be unique
- Your `customers` and `services` tables should have a `name` column
- Your `appointments` table should have a `time` column
- You should have at least three rows in your `services` table for the different services you offer
- You should create a script file named `salon.sh` in the `project` folder
- Your script file should have a "shebang" that uses bash when the file is executed (use `#!/bin/bash`)
- Your script file should have executable permissions
- You should not use the `clear` command in your script
- You should display a numbered list of the services you offer before the first prompt for input, each with the format `#) <service>`. For example, `1) cut`, where `1` is the `service_id`

- If you pick a service that doesn't exist, you should be shown the same list of services again
- Your script should prompt users to enter a `service_id`, phone number, a name if they aren't already a customer, and a time. You should use `read` to read these inputs into variables named `SERVICE_ID_SELECTED`, `CUSTOMER_PHONE`, `CUSTOMER_NAME`, and `SERVICE_TIME`
- If a phone number entered doesn't exist, you should get the customer's name and enter it and the phone number into the `customers` table
- You can create a row in the `appointments` table by running your script and entering `1`, `555-555-5555`, `Fabio`, `10:30` at each request for input if that phone number isn't in the `customers` table. The row should have the `customer_id` for that customer, and the `service_id` for the service entered
- You can create another row in the `appointments` table by running your script and entering `2`, `555-555-5555`, `11am` at each request for input if that phone number is already in the `customers` table. The row should have the `customer_id` for that customer, and the `service_id` for the service entered
- After an appointment is successfully added, you should output the message `I have put you down for a <service> at <time>, <name>.` For example, if the user chooses `cut` as the service, `10:30` is entered for the time, and their name is `Fabio` in the database the output would be `I have put your down for a cut at 10:30, Fabio.`