

# Contents

1	Basic	1
1.1	Increase Stack	1
1.2	Default	1
2	Data Structure	
2.1	Heavy Light Decomposition	1
2.2	Bigint	2
2.3	Leftist Heap	3
2.4	Treap	3
2.5	Unordered Hash Function	4
3	Graph	
3.1	Tarjan	4
3.2	Kosaraju Scc	4
3.3	SW Min Cut	4
3.4	Dinic	5
3.5	Cost Flow	5
3.6	Isap	5
3.7	2 Com Flow	6
3.8	DMST With Sol	7
3.9	Maximum Clique	7
3.10	Minimum Mean Cycle	8
3.11	Kuhn Munkress	8
3.12	Simple Graph Matching	8
3.13	Bipartite Matching	9
4	Math	9
4.1	Simplex	9
4.2	Ax+by=gcd	10
4.3	Fast Fourier Transform	10
4.4	Pollard Rho	10
4.5	Polygen	10
4.6	Gauss Elimination	11
4.7	Mod Utils	11
4.8	Ntt	11
4.9	Chinese Remainder	12
4.10	Primes	12
4.11	Miller Rabin	12
5	Geometry	13
5.1	Half Plane Intersection	13
5.2	KD Tree	14
5.3	Minimum Covering Circle	14
5.4	Minkowski Sum	15
5.5	Convex Hull	15
5.6	Intersection Of Two Circles	15
5.7	Intersection Of Two Lines	15
5.8	Point Operators	16
6	Stringology	16
6.1	AC Automata	16
6.2	SAM	16
6.3	Palindrome	16
6.4	Z Value	17
6.5	Smallest Rotation	17
6.6	Suffix Array	17
6.7	Sais	17
7	Problems	18
7.1	Orange Protection	18
7.2	Max Tangent	19
7.3	Cot4	19

## 1 Basic

### 1.1 Increase Stack

```

1 //stack resize
1 asm( "mov %0,%esp\n" ::"g"(mem+100000000) );
1 //change esp to rsp if 64-bit system
2
3 //stack resize (linux)
3 #include <sys/resource.h>
4 void increase_stack_size() {
4     const rlim_t ks = 64*1024*1024;
4     struct rlimit rl;
4     int res=getrlimit(RLIMIT_STACK, &rl);
5     if(res==0){
5         if(rl.rlim_cur<ks){
5             rl.rlim_cur=ks;
6             res=setrlimit(RLIMIT_STACK, &rl);
7         }
8     }
9 }

```

### 1.2 Default

```

9 #include<bits/stdc++.h>
9 #include<unistd.h>
10 using namespace std;
10 #define FZ(n) memset((n),0,sizeof(n))
10 #define FMO(n) memset((n),-1,sizeof(n))
11 #define F first
11 #define S second
11 #define PB push_back
12 #define ALL(x) begin(x),end(x)
12 #define SZ(x) ((int)(x).size())
13 #define IOS ios_base::sync_with_stdio(0); cin.tie(0)
14 template<typename A, typename B>
14 ostream& operator <<(ostream &s, const pair<A,B> &p) {
15     return s<<"("<<p.first<<","<<p.second<<")";
16 }
16 template<typename T>
16 ostream& operator <<(ostream &s, const vector<T> &c) {
16     s<<"[";
16     for (auto it : c) s << it << " ";
16     s<<"]";
16     return s;
17 }
17 // Let's Fight!
18 int main() {
18     return 0;
19 }

```

## 2 Data Structure

### 2.1 Heavy Light Decomposition

```

// only one segment tree / no 0/1 base issue
// getPathSeg return the segment in order u->v
// fa[root] = root
typedef pair<int,int> pii;

int N,fa[MXN],belong[MXN],dep[MXN],sz[MXN],que[MXN];
int step,line[MXN],stPt[MXN],edPt[MXN];
vector<int> E[MXN], chain[MXN];

void DFS(int u){
    vector<int> &c = chain[belong[u]];
    for (int i=c.size()-1; i>=0; i--){
        int v = c[i];
        stPt[v] = step;
        line[step++] = v;
    }
    for (int i=0; i<(int)c.size(); i++){
        u = c[i];
        for (auto v : E[u]){

```

```

    if (fa[u] == v || (i && v == c[i-1])) continue;
    DFS(v);
}
edPt[u] = step-1;
}
}
void build_chain(int st){
    int fr,bk;
    fr=bk=0; que[bk++] = 1; fa[st]=st; dep[st]=0;
    while (fr < bk){
        int u=que[fr++];
        for (auto v : E[u]){
            if (v == fa[u]) continue;
            que[bk++] = v;
            dep[v] = dep[u]+1;
            fa[v] = u;
        }
    }
    for (int i=bk-1,u,pos; i>=0; i--){
        u = que[i]; sz[u] = 1; pos = -1;
        for (auto v : E[u]){
            if (v == fa[u]) continue;
            sz[u] += sz[v];
            if (pos== -1 || sz[v]>sz[pos]) pos=v;
        }
        if (pos == -1) belong[u] = u;
        else belong[u] = belong[pos];
        chain[belong[u]].PB(u);
    }
    step = 0;
    DFS(st);
}
int getLCA(int u, int v){
    while (belong[u] != belong[v]){
        int a = chain[belong[u]].back();
        int b = chain[belong[v]].back();
        if (dep[a] > dep[b]) u = fa[a];
        else v = fa[b];
    }
    return sz[u] >= sz[v] ? u : v;
}
vector<pii> getPathSeg(int u, int v){
    vector<pii> ret1,ret2;
    while (belong[u] != belong[v]){
        int a = chain[belong[u]].back();
        int b = chain[belong[v]].back();
        if (dep[a] > dep[b]){
            ret1.PB({stPt[a],stPt[u]});
            u = fa[a];
        } else {
            ret2.PB({stPt[b],stPt[v]});
            v = fa[b];
        }
    }
    if (dep[u] > dep[v]) swap(u,v);
    ret1.PB({stPt[u],stPt[v]});
    reverse(ret2.begin(), ret2.end());
    ret1.insert(ret1.end(),ret2.begin(),ret2.end());
    return ret1;
}
// Usage
void build(){
    build_chain(1); //change root
    init(0,step,0); //init segment tree
}
int get_answer(int u, int v){
    int ret = -2147483647;
    vector<pii> vec = getPathSeg(u,v);
    for (auto it : vec)
        ; // check answer with segment [it.F, it.S]
    return ret;
}
}

```

## 2.2 Bigint

```

struct Bigint{
    static const int LEN = 60;
    static const int BIGMOD = 100000;

    int s;

```

```

    int vl, v[LEN];
    // vector<int> v;
    Bigint() : s(1) { vl = 0; }
    Bigint(long long a) {
        s = 1; vl = 0;
        if (a < 0) { s = -1; a = -a; }
        while (a) {
            push_back(a % BIGMOD);
            a /= BIGMOD;
        }
    }
    Bigint(string str) {
        s = 1; vl = 0;
        int stPos = 0, num = 0;
        if (!str.empty() && str[0] == '-') {
            stPos = 1;
            s = -1;
        }
        for (int i=SZ(str)-1, q=1; i>=stPos; i--) {
            num += (str[i] - '0') * q;
            if ((q *= 10) >= BIGMOD) {
                push_back(num);
                num = 0; q = 1;
            }
        }
        if (num) push_back(num);
    }

    int len() const {
        return vl;
        // return SZ(v);
    }
    bool empty() const { return len() == 0; }
    void push_back(int x) {
        v[vl++] = x;
        // v.PB(x);
    }
    void pop_back() {
        vl--;
        // v.pop_back();
    }
    int back() const {
        return v[vl-1];
        // return v.back();
    }
    void n() {
        while (!empty() && !back()) pop_back();
    }
    void resize(int nl) {
        vl = nl;
        fill(v, v+vl, 0);
        // v.resize(nl);
        // fill(ALL(v), 0);
    }

    void print() const {
        if (empty()) { putchar('0'); return; }
        if (s == -1) putchar('-');
        printf("%d", back());
        for (int i=len()-2; i>=0; i--) printf("%.4d",v[i]);
    }
    friend ostream& operator << (ostream& out,
        const Bigint &a) {
        if (a.empty()) { out << "0"; return out; }
        if (a.s == -1) out << "-";
        out << a.back();
        for (int i=a.len()-2; i>=0; i--) {
            char str[10];
            snprintf(str, 5, "%.4d", a.v[i]);
            out << str;
        }
        return out;
    }

    int cp3(const Bigint &b) const {
        if (s != b.s) return s > b.s;
        if (s == -1) return -(this->cp3(-b));
        if (len() != b.len()) return len()>b.len()?1:-1;
        for (int i=len()-1; i>=0; i--)
            if (v[i]!=b.v[i]) return v[i]>b.v[i]?1:-1;
        return 0;
    }
}

```

```

bool operator < (const Bigint &b) const { return cp3(b)
    ==-1; }
bool operator == (const Bigint &b) const { return cp3(b)
    ==0; }
bool operator > (const Bigint &b) const { return cp3(b)
    ==1; }

Bigint operator - () const {
    Bigint r = (*this);
    r.s = -r.s;
    return r;
}
Bigint operator + (const Bigint &b) const {
    if (s == -1) return -((*this)+(-b));
    if (b.s == -1) return (*this)-(-b);
    Bigint r;
    int nl = max(len(), b.len());
    r.resize(nl + 1);
    for (int i=0; i<nl; i++) {
        if (i < len()) r.v[i] += v[i];
        if (i < b.len()) r.v[i] += b.v[i];
        if (r.v[i] >= BIGMOD) {
            r.v[i+1] += r.v[i] / BIGMOD;
            r.v[i] %= BIGMOD;
        }
    }
    r.n();
    return r;
}
Bigint operator - (const Bigint &b) const {
    if (s == -1) return -((*this)-(-b));
    if (b.s == -1) return (*this)+(-b);
    if ((*this) < b) return -(b-(*this));
    Bigint r;
    r.resize(len());
    for (int i=0; i<len(); i++) {
        r.v[i] += v[i];
        if (i < b.len()) r.v[i] -= b.v[i];
        if (r.v[i] < 0) {
            r.v[i] += BIGMOD;
            r.v[i+1]--;
        }
    }
    r.n();
    return r;
}
Bigint operator * (const Bigint &b) {
    Bigint r;
    r.resize(len() + b.len() + 1);
    r.s = s * b.s;
    for (int i=0; i<len(); i++) {
        for (int j=0; j<b.len(); j++) {
            r.v[i+j] += v[i] * b.v[j];
            if (r.v[i+j] >= BIGMOD) {
                r.v[i+j+1] += r.v[i+j] / BIGMOD;
                r.v[i+j] %= BIGMOD;
            }
        }
    }
    r.n();
    return r;
}
Bigint operator / (const Bigint &b) {
    Bigint r;
    r.resize(max(1, len()-b.len()+1));
    int oriS = s;
    Bigint b2 = b; // b2 = abs(b)
    s = b2.s = r.s = 1;
    for (int i=r.len()-1; i>=0; i--) {
        int d=0, u=BIGMOD-1;
        while(d<u) {
            int m = (d+u+1)>>1;
            r.v[i] = m;
            if ((r*b2) > (*this)) u = m-1;
            else d = m;
        }
        r.v[i] = d;
    }
    s = oriS;
    r.s = s * b.s;
    r.n();
    return r;
}

```

```

}
Bigint operator % (const Bigint &b) {
    return (*this)-(*this)/b*b;
}
};

```

## 2.3 Leftist Heap

```

const int MAXSIZE = 10000;

struct Node{
    int num,lc,rc;
    Node () : num(0), lc(-1), rc(-1) {}
    Node (int _v) : num(_v), lc(-1), rc(-1) {}
}tree[MAXSIZE];

int merge(int x, int y){
    if (x == -1) return y;
    if (y == -1) return x;
    if (tree[x].num < tree[y].num)
        swap(x, y);
    tree[x].rc = merge(tree[x].rc, y);
    swap(tree[x].lc, tree[x].rc);
    return x;
}

/* Usage
merge: root = merge(x, y)
delmin: root = merge(root.lc, root.rc)
*/

```

## 2.4 Treap

```

struct Node{
    int pri,num,cnt,lc,rc;
    Node () : pri(-1), num(0), cnt(0), lc(0), rc(0) {}
    Node (int _num){
        pri = (rand()<<15) + rand();
        num = _num;
        cnt = 1;
        lc = rc = 0;
    }
}tree[MX];

int nMem;

int get_rand(){
    return (rand()<<15) + rand();
}
int get_node(){
    tree[nMem] = Node();
    if (nMem >= MX) while(1);
    return nMem++;
}
void upd_node(int rt){
    if (!rt) return;
    int lc=tree[rt].lc;
    int rc=tree[rt].rc;
    tree[rt].cnt = tree[lc].cnt + tree[rc].cnt + 1;
}
int merge(int a, int b){
    if (!a) return b;
    if (!b) return a;
    int res=0;
    if (tree[a].pri > tree[b].pri){
        res = a; //get_node();
        tree[res] = tree[a];
        tree[res].rc = merge(tree[res].rc,b);
    } else {
        res = b; //get_node();
        tree[res] = tree[b];
        tree[res].lc = merge(a,tree[res].lc);
    }
    upd_node(res);
    return res;
}
pair<int,int> split(int a, int k){
    if (k == 0) return {0,a};
}

```

```

if (k == tree[a].cnt) return {a,0};
int lc=tree[a].lc, rc=tree[a].rc;
pair<int,int> res;
int np=a; //get_node();
//tree[np] = tree[a];
if (tree[lc].cnt >= k){
    res = split(lc,k);
    tree[np].lc = res.S;
    res.S = np;
} else {
    res = split(rc,k-tree[lc].cnt-1);
    tree[np].rc = res.F;
    res.F = np;
}
upd_node(res.F);
upd_node(res.S);
return res;
}

```

## 2.5 Unordered Hash Function

```

struct Key {
    int first,second;
    Key () {}
    Key (int _x, int _y) : first(_x), second(_y) {}
    bool operator == (const Key &b) const {
        return tie(F,S) == tie(b.F,b.S);
    }
};
struct KeyHasher {
    size_t operator()(const Key& k) const {
        return k.first + k.second*1000000;
    }
};
typedef unordered_map<Key,int,KeyHasher> map_t;

int main(int argc, char** argv){
    map_t mp;
    for (int i=0; i<10; i++)
        mp[Key(i,0)] = i+1;
    for (int i=0; i<10; i++)
        printf("%d\n", mp[Key(i,0)]);

    return 0;
}

```

## 3 Graph

### 3.1 Tarjan

```

const int MAXV = 101000;

int V, E;
vector<int> el[MAXV];
int dfn[MAXV], low[MAXV], did;
bool ins[MAXV];
stack<int> st;
int scc[MAXV], scn;

void tarjan(int u){
    cout << u << endl;
    dfn[u] = low[u] = ++did;
    st.push(u); ins[u] = true;

    for(int i=0; i<(int)el[u].size(); i++){
        int v = el[u][i];
        if(!dfn[v]){
            tarjan(v);
            low[u] = min(low[u], low[v]);
        } else if(ins[v]){
            low[u] = min(low[u], dfn[v]);
        }
    }

    if(dfn[u] == low[u]){

```

```

int v;
do{
    v = st.top();
    st.pop();
    scc[v] = scn;
    ins[v] = false;
}while(v != u);
scn ++;
}
}

void calcscc(){
    did = scn = 0;
    for(int i=0; i<V; i++){
        if(!dfn[i]) tarjan(i);
    }
}

```

### 3.2 Kosaraju Scc

```

struct Scc{
    int n, nScc, vst[MXN], bln[MXN];
    vector<int> E[MXN], rE[MXN], vec;
    void init(int _n){
        n = _n;
        for (int i=0; i<MXN; i++){
            E[i].clear();
            rE[i].clear();
        }
    }
    void add_edge(int u, int v){
        E[u].PB(v);
        rE[v].PB(u);
    }
    void DFS(int u){
        vst[u]=1;
        for (auto v : E[u])
            if (!vst[v]) DFS(v);
        vec.PB(u);
    }
    void rDFS(int u){
        vst[u] = 1;
        bln[u] = nScc;
        for (auto v : rE[u])
            if (!vst[v]) rDFS(v);
    }
    void solve(){
        nScc = 0;
        vec.clear();
        FZ(vst);
        for (int i=0; i<n; i++)
            if (!vst[i]) DFS(i);
        reverse(vec.begin(),vec.end());
        FZ(vst);
        for (auto v : vec){
            if (!vst[v]){
                rDFS(v);
                nScc++;
            }
        }
    }
};

```

### 3.3 SW Min Cut

```

struct SW{ // O(V^3)
    static const int MXN = 514;
    int n,vst[MXN],del[MXN];
    int edge[MXN][MXN],wei[MXN];
    void init(int _n){
        n = _n;
        FZ(edge);
        FZ(del);
    }
    void add_edge(int u, int v, int w){
        edge[u][v] += w;
        edge[v][u] += w;
    }
}

```

```

void search(int &s, int &t){
    FZ(vst); FZ(wei);
    s = t = -1;
    while (true){
        int mx=-1, cur=0;
        for (int i=0; i<n; i++){
            if (!del[i] && !vst[i] && mx<wei[i])
                cur = i, mx = wei[i];
        }
        if (mx == -1) break;
        vst[cur] = 1;
        s = t;
        t = cur;
        for (int i=0; i<n; i++){
            if (!vst[i] && !del[i]) wei[i] += edge[cur][i];
        }
    }
    int solve(){
        int res = 2147483647;
        for (int i=0, x=y; i<n-1; i++){
            search(x,y);
            res = min(res,wei[y]);
            del[y] = 1;
            for (int j=0; j<n; j++){
                edge[x][j] = (edge[j][x] += edge[y][j]);
            }
        }
        return res;
    }
}
}graph;

```

### 3.4 Dinic

```

struct Dinic{
    static const int MXN = 10000;
    struct Edge{ int v,f,re; };
    int n,s,t,level[MXN];
    vector<Edge> E[MXN];
    void init(int _n, int _s, int _t){
        n = _n; s = _s; t = _t;
        for (int i=0; i<n; i++) E[i].clear();
    }
    void add_edge(int u, int v, int f){
        E[u].PB({v,f,SZ(E[v])});
        E[v].PB({u,0,SZ(E[u])-1});
    }
    bool BFS(){
        FMO(level);
        queue<int> que;
        que.push(s);
        level[s] = 0;
        while (!que.empty()){
            int u = que.front(); que.pop();
            for (auto it : E[u]){
                if (it.f > 0 && level[it.v] == -1){
                    level[it.v] = level[u]+1;
                    que.push(it.v);
                }
            }
        }
        return level[t] != -1;
    }
    int DFS(int u, int nf){
        if (u == t) return nf;
        int res = 0;
        for (auto &it : E[u]){
            if (it.f > 0 && level[it.v] == level[u]+1){
                int tf = DFS(it.v, min(nf,it.f));
                res += tf; nf -= tf; it.f -= tf;
                E[it.v][it.re].f += tf;
                if (nf == 0) return res;
            }
        }
        if (!res) level[u] = -1;
        return res;
    }
    int flow(int res=0){
        while (BFS())
            res += DFS(s,2147483647);
        return res;
    }
}
}flow;

```

### 3.5 Cost Flow

```

typedef pair<long long, long long> pll;
struct CostFlow {
    static const int MXN = 205;
    static const long long INF = 102938475610293847LL;
    struct Edge {
        int v, r;
        long long f, c;
    };
    int n, s, t, prv[MXN], prvL[MXN], inq[MXN];
    long long dis[MXN], fl, cost;
    vector<Edge> E[MXN];
    void init(int _n, int _s, int _t) {
        n = _n; s = _s; t = _t;
        for (int i=0; i<n; i++) E[i].clear();
        fl = cost = 0;
    }
    void add_edge(int u, int v, long long f, long long c) {
        E[u].PB({v, SZ(E[v]), f, c});
        E[v].PB({u, SZ(E[u])-1, 0, -c});
    }
    pll flow() {
        while (true) {
            for (int i=0; i<n; i++) {
                dis[i] = INF;
                inq[i] = 0;
            }
            dis[s] = 0;
            queue<int> que;
            que.push(s);
            while (!que.empty()) {
                int u = que.front(); que.pop();
                inq[u] = 0;
                for (int i=0; i<SZ(E[u]); i++) {
                    int v = E[u][i].v;
                    long long w = E[u][i].c;
                    if (E[u][i].f > 0 && dis[v] > dis[u] + w) {
                        prv[v] = u; prvL[v] = i;
                        dis[v] = dis[u] + w;
                        if (!inq[v]) {
                            inq[v] = 1;
                            que.push(v);
                        }
                    }
                }
            }
            if (dis[t] == INF) break;
            long long tf = INF;
            for (int v=t; v!=s; v=u) {
                int u=prv[v], l=prvL[v];
                tf = min(tf, E[u][l].f);
            }
            for (int v=t; v!=s; v=u) {
                int u=prv[v], l=prvL[v];
                E[u][l].f -= tf;
                E[v][E[u][l].r].f += tf;
            }
            cost += tf * dis[t];
            fl += tf;
        }
        return {fl, cost};
    }
}
}flow;

```

### 3.6 Isap

```

struct Isap{
    static const int MXN = 10000;
    struct Edge{ int v,f,re; };
    int n,s,t,h[MXN],gap[MXN];
    vector<Edge> E[MXN];
    void init(int _n, int _s, int _t){
        n = _n; s = _s; t = _t;
        for (int i=0; i<n; i++) E[i].clear();
    }
    void add_edge(int u, int v, int f){
        E[u].PB({v,f,SZ(E[v])});
    }
}

```

```

    E[v].PB({u,0,SZ(E[u])-1});
}
int DFS(int u, int nf, int res=0){
    if (u == t) return nf;
    for (auto &it : E[u]){
        if (h[u]==h[it.v]+1 && it.f>0){
            int tf = DFS(it.v,min(nf,it.f));
            res += tf; nf -= tf; it.f -= tf;
            E[it.v][it.re].f += tf;
            if (nf == 0) return res;
        }
    }
    if (nf){
        if (--gap[h[u]] == 0) h[s]=n;
        gap[++h[u]]++;
    }
    return res;
}
int flow(int res=0){
    FZ(h); FZ(gap);
    gap[0] = n;
    while (h[s] < n) res += DFS(s,2147483647);
    return res;
}
}flow;

```

### 3.7 2 Com Flow

```

const int MAXN = 64;
const int INF = 1029384756;

int N;
int s1, s2, t1, t2, d1, d2, S, T;
int edge[MAXN][MAXN];
int cap[MAXN][MAXN];

int h[MAXN], gap[MAXN];
bool vis[MAXN];

int isap(int v, int f)
{
    if(v == T)return f;

    if(vis[v])return 0;
    vis[v] = true;

    for(int i=0; i<N+2; i++)
    {
        if(cap[v][i] <= 0)continue;
        if(h[i] != h[v] - 1)continue;
        int res = isap(i, min(cap[v][i], f));
        if(res > 0)
        {
            cap[v][i] -= res;
            cap[i][v] += res;
            return res;
        }
    }

    gap[h[v]]--;
    if(gap[h[v]] <= 0)h[S] = N + 4;
    h[v]++;
    gap[h[v]]++;

    return 0;
}

int get_flow()
{
    for(int i=0; i<MAXN; i++)
    {
        h[i] = gap[i] = 0;
    }
    gap[0] = N + 2;

    int flow = 0;

    while(h[S] <= N + 3)
    {
        for(int i=0; i<N+2; i++)

```

```

        {
            vis[i] = false;
        }

        int df = isap(S, INF);
        flow += df;
    }

    return flow;
}

int main()
{
    ios_base::sync_with_stdio(0);

    int TT;
    cin>>TT;
    while(TT--){
        cin>>N;
        cin>>s1>>t1>>d1>>s2>>t2>>d2;

        for(int i=0; i<MAXN; i++)
        {
            for(int j=0; j<MAXN; j++)
            {
                edge[i][j] = 0;
            }
        }

        for(int i=0; i<N; i++)
        {
            string s;
            cin>>s;
            for(int j=0; j<N; j++)
            {
                if(s[j] == 'X')edge[i][j] = 0;
                else if(s[j] == 'O')edge[i][j] = 1;
                else if(s[j] == 'N')edge[i][j] = INF;
            }
        }

        int ans = 0;

        S = N;
        T = N + 1;

        //first
        for(int i=0; i<MAXN; i++)
        {
            for(int j=0; j<MAXN; j++)
            {
                cap[i][j] = edge[i][j];
            }
        }

        cap[S][s1] = cap[t1][T] = d1;
        cap[S][s2] = cap[t2][T] = d2;

        ans = get_flow();

        //second
        for(int i=0; i<MAXN; i++)
        {
            for(int j=0; j<MAXN; j++)
            {
                cap[i][j] = edge[i][j];
            }
        }

        cap[S][s1] = cap[t1][T] = d1;
        cap[S][t2] = cap[s2][T] = d2;

        ans = min(ans, get_flow());

        cout<<(ans == d1 + d2 ? "Yes" : "No")<<endl;
    }

    return 0;
}

```

### 3.8 DMST With Sol

```

const int INF = 1029384756;

struct edge_t{
    int u,v,w;
    set< pair<int,int> > add, sub;
    edge_t() : u(-1), v(-1), w(0) {}
    edge_t(int _u, int _v, int _w) {
        u = _u; v = _v; w = _w;
        add.insert({u, v});
    }
    edge_t& operator += (const edge_t& obj) {
        w += obj.w;
        FOR (it, obj.add) {
            if (!sub.count(*it)) add.insert(*it);
            else sub.erase(*it);
        }
        FOR (it, obj.sub) {
            if (!add.count(*it)) sub.insert(*it);
            else add.erase(*it);
        }
        return *this;
    }
    edge_t& operator -= (const edge_t& obj) {
        w -= obj.w;
        FOR (it, obj.sub) {
            if (!sub.count(*it)) add.insert(*it);
            else sub.erase(*it);
        }
        for (auto it : obj.add) {
            if (!add.count(it)) sub.insert(it);
            else add.erase(it);
        }
        return *this;
    }
} eg[MXN*MXN], prv[MXN], EDGE_INF(-1,-1,INF);
int N,M;
int cid, incyc[MXN], contracted[MXN];
vector<int> E[MXN];

edge_t dmst(int rt){
    edge_t cost;
    for (int i=0; i<N; i++){
        contracted[i] = incyc[i] = 0;
        prv[i] = EDGE_INF;
    }
    cid = 0;
    int u,v;
    while (true){
        for (v=0; v<N; v++){
            if (v != rt && !contracted[v] && prv[v].w == INF)
                break;
        }
        if (v >= N) break; // end
        for (int i=0; i<M; i++){
            if (eg[i].v == v && eg[i].w < prv[v].w)
                prv[v] = eg[i];
        }
        if (prv[v].w == INF) // not connected
            return EDGE_INF;
        cost += prv[v];
        for (u=prv[v].u; u!=v && u!=-1; u=prv[u].u);
        if (u == -1) continue;
        incyc[v] = ++cid;
        for (u=prv[v].u; u!=v; u=prv[u].u){
            contracted[u] = 1;
            incyc[u] = cid;
        }
        for (int i=0; i<M; i++){
            if (incyc[eg[i].u] != cid && incyc[eg[i].v] == cid){
                eg[i] -= prv[eg[i].v];
            }
        }
        for (int i=0; i<M; i++){
            if (incyc[eg[i].u] == cid) eg[i].u = v;
            if (incyc[eg[i].v] == cid) eg[i].v = v;
            if (eg[i].u == eg[i].v) eg[i--] = eg[--M];
        }
        for (int i=0; i<N; i++){

```

```

            if (contracted[i]) continue;
            if (prv[i].u>=0 && incyc[prv[i].u] == cid)
                prv[i].u = v;
        }
        prv[v] = EDGE_INF;
    }
    return cost;
}

void solve(){
    edge_t cost = dmst(0);
    for (auto it : cost.add){ // find a solution
        E[it.F].PB(it.S);
        prv[it.S] = edge_t(it.F,it.S,0);
    }
}

```

### 3.9 Maximum Clique

```

class MaxClique {
public:
    static const int MV = 210;

    int V;
    int el[MV][MV/30+1];
    int dp[MV];
    int ans;
    int s[MV][MV/30+1];
    vector<int> sol;

    void init(int v) {
        V = v; ans = 0;
        FZ(el); FZ(dp);
    }

    /* Zero Base */
    void addEdge(int u, int v) {
        if(u > v) swap(u, v);
        if(u == v) return;
        el[u][v/32] |= (1<<(v%32));
    }

    bool dfs(int v, int k) {
        int c = 0, d = 0;
        for(int i=0; i<(V+31)/32; i++) {
            s[k][i] = el[v][i];
            if(k != 1) s[k][i] &= s[k-1][i];
            c += __builtin_popcount(s[k][i]);
        }
        if(c == 0) {
            if(k > ans) {
                ans = k;
                sol.clear();
                sol.push_back(v);
                return 1;
            }
            return 0;
        }
        for(int i=0; i<(V+31)/32; i++) {
            for(int a = s[k][i]; a; a >> 1) {
                if(k + (c-d) <= ans) return 0;
                int lb = a&(-a), lg = 0;
                a ^= lb;
                while(lb!=1) {
                    lb = (unsigned int)(lb) >> 1;
                    lg++;
                }
                int u = i*32 + lg;
                if(k + dp[u] <= ans) return 0;
                if(dfs(u, k+1)) {
                    sol.push_back(v);
                    return 1;
                }
            }
        }
        return 0;
    }

    int solve() {
        for(int i=V-1; i>=0; i--) {

```

```

        dfs(i, 1);
        dp[i] = ans;
    }
    return ans;
}
};

```

### 3.10 Minimum Mean Cycle

```

/* minimum mean cycle */
const int MAXE = 1805;
const int MAXN = 35;
const double inf = 1029384756;
const double eps = 1e-6;
struct Edge {
    int v,u;
    double c;
};
int n,m,prv[MAXN][MAXN], prve[MAXN][MAXN], vst[MAXN];
Edge e[MAXE];
vector<int> edgeID, cycle, rho;
double d[MAXN][MAXN];
inline void bellman_ford() {
    for(int i=0; i<n; i++) d[0][i]=0;
    for(int i=0; i<n; i++) {
        fill(d[i+1], d[i+1]+n, inf);
        for(int j=0; j<m; j++) {
            int v = e[j].v, u = e[j].u;
            if(d[i][v]<inf && d[i+1][u]>d[i][v]+e[j].c) {
                d[i+1][u] = d[i][v]+e[j].c;
                prv[i+1][u] = v;
                prve[i+1][u] = j;
            }
        }
    }
}
double karp_mmc() {
    // returns inf if no cycle, mmc otherwise
    double mmc=inf;
    int st = -1;
    bellman_ford();
    for(int i=0; i<n; i++) {
        double avg=-inf;
        for(int k=0; k<n; k++) {
            if(d[n][i]<inf-eps) avg=max(avg,(d[n][i]-d[k][i])/(n-k));
            else avg=max(avg,inf);
        }
        if (avg < mmc) tie(mmc, st) = tie(avg, i);
    }
    FZ(vst); edgeID.clear(); cycle.clear(); rho.clear();
    for (int i=n; !vst[st]; st=prv[i--][st]) {
        vst[st]++;
        edgeID.PB(prve[i][st]);
        rho.PB(st);
    }
    while (vst[st] != 2) {
        int v = rho.back(); rho.pop_back();
        cycle.PB(v);
        vst[v]++;
    }
    reverse(ALL(edgeID));
    edgeID.resize(SZ(cycle));
    return mmc;
}

```

### 3.11 Kuhn Munkres

```

struct KM{
    // Maximum Bipartite Weighted Matching (Perfect Match)
    static const int MXN = 650;
    static const int INF = 2147483647; // long long
    int n,match[MXN],vx[MXN],vy[MXN];
    int edge[MXN][MXN],lx[MXN],ly[MXN],slack[MXN];
    // ^^^ long long
    void init(int _n){
        n = _n;
        for (int i=0; i<n; i++)

```

```

        for (int j=0; j<n; j++)
            edge[i][j] = 0;
    }
    void add_edge(int x, int y, int w){ // long long
        edge[x][y] = w;
    }
    bool DFS(int x){
        vx[x] = 1;
        for (int y=0; y<n; y++){
            if (vy[y]) continue;
            if (lx[x]+ly[y] > edge[x][y]){
                slack[y] = min(slack[y], lx[x]+ly[y]-edge[x][y]);
            }
        } else {
            vy[y] = 1;
            if (match[y] == -1 || DFS(match[y])){
                match[y] = x;
                return true;
            }
        }
    }
    return false;
}
int solve(){
    fill(match,match+n,-1);
    fill(lx,lx+n,-INF);
    fill(ly,ly+n,0);
    for (int i=0; i<n; i++){
        for (int j=0; j<n; j++){
            lx[i] = max(lx[i], edge[i][j]);
        }
        for (int i=0; i<n; i++){
            fill(slack,slack+n,INF);
            while (true){
                fill(vx,vx+n,0);
                fill(vy,vy+n,0);
                if ( DFS(i) ) break;
                int d = INF; // long long
                for (int j=0; j<n; j++){
                    if (!vy[j]) d = min(d, slack[j]);
                }
                for (int j=0; j<n; j++){
                    if (vx[j]) lx[j] -= d;
                    if (vy[j]) ly[j] += d;
                    else slack[j] -= d;
                }
            }
        }
        int res=0;
        for (int i=0; i<n; i++){
            res += edge[match[i]][i];
        }
        return res;
    }
}graph;

```

### 3.12 Simple Graph Matching

```

struct GenMatch { // 1-base
    static const int MAXN = 250;
    int V;
    bool el[MAXN][MAXN];
    int pr[MAXN];
    bool inq[MAXN],inp[MAXN],inb[MAXN];
    queue<int> qe;
    int st,ed;
    int nb;
    int bk[MAXN],djs[MAXN];
    int ans;
    void init(int _V) {
        V = _V;
        FZ(el); FZ(pr);
        FZ(inq); FZ(inp); FZ(inb);
        FZ(bk); FZ(djs);
        ans = 0;
    }
    void add_edge(int u, int v) {
        el[u][v] = el[v][u] = 1;
    }
    int lca(int u,int v) {
        memset(inp,0,sizeof(inp));
        while(1) {
            u = djs[u];

```



```

    inp[u] = true;
    if(u == st) break;
    u = bk[pr[u]];
}
while(1) {
    v = djs[v];
    if(inp[v]) return v;
    v = bk[pr[v]];
}
return v;
}
void upd(int u) {
    int v;
    while(djs[u] != nb) {
        v = pr[u];
        inb[djs[u]] = inb[djs[v]] = true;
        u = bk[v];
        if(djs[u] != nb) bk[u] = v;
    }
}
void blo(int u, int v) {
    nb = lca(u, v);
    memset(inb, 0, sizeof(inb));
    upd(u); upd(v);
    if(djs[u] != nb) bk[u] = v;
    if(djs[v] != nb) bk[v] = u;
    for(int tu = 1; tu <= V; tu++)
        if(inb[djs[tu]]) {
            djs[tu] = nb;
            if(!inq[tu]) {
                qe.push(tu);
                inq[tu] = 1;
            }
        }
}
void flow() {
    memset(inq, false, sizeof(inq));
    memset(bk, 0, sizeof(bk));
    for(int i = 1; i <= V; i++)
        djs[i] = i;

    while(qe.size()) qe.pop();
    qe.push(st);
    inq[st] = 1;
    ed = 0;
    while(qe.size()) {
        int u = qe.front(); qe.pop();
        for(int v = 1; v <= V; v++)
            if(el[u][v] && (djs[u] != djs[v]) && (pr[u] != v)) {
                if((v == st) || ((pr[v] > 0) && bk[pr[v]] > 0))
                    blo(u, v);
                else if(bk[v] == 0) {
                    bk[v] = u;
                    if(pr[v] > 0) {
                        if(!inq[pr[v]]) qe.push(pr[v]);
                    } else {
                        ed = v;
                        return;
                    }
                }
            }
    }
}
void aug() {
    int u, v, w;
    u = ed;
    while(u > 0) {
        v = bk[u];
        w = pr[v];
        pr[v] = u;
        pr[u] = v;
        u = w;
    }
}
int solve() {
    memset(pr, 0, sizeof(pr));
    for(int u = 1; u <= V; u++)
        if(pr[u] == 0) {
            st = u;
            flow();

```

```

        if(ed > 0) {
            aug();
            ans++;
        }
    }
    return ans;
}
};

int main() {
    gp.init(V);
    for(int i=0; i<E; i++) {
        int u, v;
        cin >> u >> v;
        gp.edge(u, v);
    }
    cout << gp.solve() << endl;
}

```

### 3.13 Bipartite Matching

```

bool DFS(int u) {
    for (auto v : E[u]) {
        if (!vst[v]) {
            vst[v] = 1;
            if (match[v] == -1 || DFS(match[v])) {
                match[v] = u; match[u] = v;
                return true;
            }
        }
    }
    return false;
}

int DoMatch(int res=0) {
    memset(match, -1, sizeof(match));
    for (int i=1; i<=N; i++) {
        if (match[i] == -1) {
            memset(vst, 0, sizeof(vst));
            DFS(i);
        }
    }
    for (int i=1; i<=N; i++)
        if (match[i] != -1) res++;
    return res;
}

```

## 4 Math

### 4.1 Simplex

```

const int maxn = 111;
const int maxm = 111;
const double eps = 1E-10;

double a[maxn][maxm], b[maxn], c[maxm], d[maxn][maxm];
double x[maxm];
int ix[maxn + maxm]; // !!! array all indexed from 0
// max{cx} subject to {Ax<=b, x>=0}
// n: constraints, m: vars !!!
// x[] is the optimal solution vector
//
// usage :
// value = simplex(a, b, c, N, M);
double simplex(double a[maxn][maxm], double b[maxn],
               double c[maxm], int n, int m) {
    ++m;
    int r = n, s = m - 1;
    memset(d, 0, sizeof(d));
    for (int i = 0; i < n + m; ++i) ix[i] = i;
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m - 1; ++j) d[i][j] = -a[i][j];
        d[i][m - 1] = 1;
        d[i][m] = b[i];
        if (d[r][m] > d[i][m]) r = i;
    }
}

```

```

for (int j = 0; j < m - 1; ++j) d[n][j] = c[j];
d[n + 1][m - 1] = -1;
for (double dd;; ) {
    if (r < n) {
        int t = ix[s]; ix[s] = ix[r + m]; ix[r + m] = t;
        d[r][s] = 1.0 / d[r][s];
        for (int j = 0; j <= m; ++j) if (j != s) d[r][j] *= -d[r][s];
        for (int i = 0; i <= n + 1; ++i) if (i != r) {
            for (int j = 0; j <= m; ++j) if (j != s) d[i][j] += d[r][j] * d[i][s];
            d[i][s] *= d[r][s];
        }
    }
    r = -1; s = -1;
    for (int j = 0; j < m; ++j) if (s < 0 || ix[s] > ix[j]) {
        if (d[n + 1][j] > eps || (d[n + 1][j] > -eps && d[n][j] > eps)) s = j;
    }
    if (s < 0) break;
    for (int i = 0; i < n; ++i) if (d[i][s] < -eps) {
        if (r < 0 || (dd = d[r][m] / d[r][s] - d[i][m] / d[i][s]) < -eps || (dd < eps && ix[r + m] > ix[i + m])) r = i;
    }
    if (r < 0) return -1; // not bounded
}
if (d[n + 1][m] < -eps) return -1; // not executable
double ans = 0;
for(int i=0; i<m; i++) x[i] = 0;
for (int i = m; i < n + m; ++i) { // the missing enumerated x[i] = 0
    if (ix[i] < m - 1) {
        ans += d[i - m][m] * c[ix[i]];
        x[ix[i]] = d[i - m][m];
    }
}
return ans;
}

```

## 4.2 $Ax+by=gcd$

```

typedef pair<int, int> pii;
pii gcd(int a, int b){
    if(b == 0) return make_pair(1, 0);
    else{
        int p = a / b;
        pii q = gcd(b, a % b);
        return make_pair(q.second, q.first - q.second * p);
    }
}

```

## 4.3 Fast Fourier Transform

```

// const int MAXN = 262144;
// (must be 2^k)

typedef long double ld;
typedef complex<ld> cplx;
const ld PI = acosl(-1);
const cplx I(0, 1);

cplx omega[MAXN+1];
void pre_fft()
{
    for(int i=0; i<=MAXN; i++)
        omega[i] = exp(i * 2 * PI / MAXN * I);
}
void fft(int n, cplx a[], bool inv=false)
{
    int basic = MAXN / n;

```

```

int theta = basic;
for (int m = n; m >= 2; m >>= 1) {
    int mh = m >> 1;
    for (int i = 0; i < mh; i++) {
        cplx w = omega[inv ? MAXN - (i * theta % MAXN) : i * theta % MAXN];
        for (int j = i; j < n; j += m) {
            int k = j + mh;
            cplx x = a[j] - a[k];
            a[j] += a[k];
            a[k] = w * x;
        }
    }
    theta = (theta * 2) % MAXN;
}
int i = 0;
for (int j = 1; j < n - 1; j++) {
    for (int k = n >> 1; k > (i ^ k); k >>= 1);
    if (j < i) swap(a[i], a[j]);
}
if (inv)
    for (i = 0; i < n; i++)
        a[i] /= n;
}

```

## 4.4 Pollard Rho

```

/* pollard rho */
// does not work when n is prime
long long modit(long long x, long long mod) {
    if(x >= mod) x -= mod;
    //if(x < 0) x += mod;
    return x;
}
long long mult(long long x, long long y, long long mod) {
    long long s = 0, m = x % mod;
    while(y) {
        if(y & 1) s = modit(s + m, mod);
        y >>= 1;
        m = modit(m + m, mod);
    }
    return s;
}
long long f(long long x, long long mod) {
    return modit(mult(x, x, mod) + 1, mod);
}
long long pollard_rho(long long n) {
    long long x, x2;
    if(!(n & 1)) return 2;
    //x = x2 = randll() % n;
    x = x2 = 2;
    while(1) {
        x = f(x, n); x2 = f(f(x2, n), n);
        long long d = __gcd(abs(x - x2), n);
        if(d != 1 && d != n) return d;
    }
}

```

## 4.5 Polygen

```

class PolynomialGenerator {
    /* for a nth-order polynomial f(x), *
    * given f(0), f(1), ..., f(n) *
    * express f(x) as sigma_i {c_i * C(x, i)} */
public:
    int n;
    vector<long long> coef;
    // initialize and calculate f(x), vector _fx should be
    // filled with f(0) to f(n)
    PolynomialGenerator(int _n, vector<long long> _fx) : n(_n), coef(_fx) {
        for(int i=0; i<n; i++)
            for(int j=n; j>i; j--)
                coef[j] -= coef[j-1];
    }
    // evaluate f(x), runs in O(n)

```

```

long long eval(int x) {
    long long m=1,ret=0;
    for(int i=0;i<=n;i++) {
        ret+=coef[i]*m;
        m=m*(x-i)/(i+1);
    }
    return ret;
};

```

#### 4.6 Gauss Elimination

```

const int MAX = 300;
const double EPS = 1e-8;

double mat[MAX][MAX];
void Gauss(int n) {
    for(int i=0; i<n; i++) {
        bool ok = 0;
        for(int j=i; j<n; j++) {
            if(fabs(mat[j][i]) > EPS) {
                swap(mat[j], mat[i]);
                ok = 1;
                break;
            }
        }
        if(!ok) continue;

        double fs = mat[i][i];
        for(int j=i+1; j<n; j++) {
            double r = mat[j][i] / fs;
            for(int k=i; k<n; k++) {
                mat[j][k] -= mat[i][k] * r;
            }
        }
    }
}

```

#### 4.7 Mod Utils

```

// _fd(a,b) floor(a/b).
// _rd(a,m) a-floor(a/m)*m.
// _pv(a,m,r) largest x s.t x<=a && x%m == r.
// _nx(a,m,r) smallest x s.t x>=a && x%m == r.
// _ct(a,b,m,r) |A| , A = { x : a<=x<=b && x%m == r }.

int _fd(int a,int b){ return a<0?(-~a/b-1):a/b; }
int _rd(int a,int m){ return a-_fd(a,m)*m; }
int _pv(int a,int m,int r)
{
    r=(r%m+m)%m;
    return _fd(a-r,m)*m+r;
}
int _nt(int a,int m,int r)
{
    m=abs(m);
    r=(r%m+m)%m;
    return _fd(a-r-1,m)*m+r+m;
}
int _ct(int a,int b,int m,int r)
{
    m=abs(m);
    a=_nt(a,m,r);
    b=_pv(b,m,r);
    return (a>b)?0:((b-a+m)/m);
}

```

#### 4.8 Ntt

```

int P=605028353,root=3,MAXNUM=262144;
// Remember coefficient are mod P
/*
p=a*2^n+1
n 2^n      p      a      root
5 32      97      3      5
6 64     193      3      5

```

```

7 128      257      2      3
8 256      257      1      3
9 512      7681     15     17
10 1024     12289    12     11
11 2048     12289    6      11
12 4096     12289    3      11
13 8192     40961    5      3
14 16384    65537    4      3
15 32768    65537    2      3
16 65536    65537    1      3
17 131072   786433   6     10
18 262144   786433   3     10 (605028353,
    2308, 3)
19 524288   5767169  11     3
20 1048576  7340033   7      3
21 2097152  23068673  11     3
22 4194304  104857601 25     3
23 8388608  167772161  20     3
24 16777216 167772161  10     3
25 33554432 167772161  5      3 (1107296257, 33,
    10)
26 67108864 469762049  7      3
27 134217728 2013265921 15     31
*/
int bigmod(long long a,int b){
    if(b==0)return 1;
    return (bigmod((a*a)%P,b/2)*(b%2?a:1ll))%P;
}
int inv(int a,int b){
    if(a==1)return 1;
    return (((long long)(a-inv(b%a,a))*b+1)/a)%b;
}
std::vector<long long> ps(MAXNUM);
std::vector<int> rev(MAXNUM);
struct poly{
    std::vector<unsigned int> co;
    int n;//polynomial degree = n
    poly(int d){n=d;co.resize(n+1,0);}
    void trans2(int NN){
        int r=0,st,N;
        unsigned int a,b;
        while((1<<r)<(NN>>1))++r;
        for(N=2;N<=NN;N<=1,--r){
            for(st=0;st<NN;st+=N){
                int i,ss=st+(N>>1);
                for(i=(N>>1)-1;i>=0;--i){
                    a=co[st+i]; b=(ps[i<<r]*co[ss+i])%P;
                    co[st+i]=a+b; if(co[st+i]>=P)co[st+i]-=P;
                    co[ss+i]=a+b; if(co[ss+i]>=P)co[ss+i]-=P;
                }
            }
        }
    }
    void trans1(int NN){
        int r=0,st,N;
        unsigned int a,b;
        for(N=NN;N>1;N>=1,++r){
            for(st=0;st<NN;st+=N){
                int i,ss=st+(N>>1);
                for(i=(N>>1)-1;i>=0;--i){
                    a=co[st+i]; b=co[ss+i];
                    co[st+i]=a+b; if(co[st+i]>=P)co[st+i]-=P;
                    co[ss+i]=((a+b)*ps[i<<r])%P;
                }
            }
        }
    }
}
poly operator*(const poly& _b)const{
    poly a=*this,b=_b;
    int k=n+b.n,i,N=1;
    while(N<=k)N*=2;
    a.co.resize(N,0); b.co.resize(N,0);
    int r=bigmod(root,(P-1)/N),Ni=inv(N,P);
    ps[0]=1;
    for(i=1;i<N;++i)ps[i]=(ps[i-1]*r)%P;
    a.trans1(N);b.trans1(N);
    for(i=0;i<N;++i)a.co[i]=((long long)a.co[i]*b.co[i]
    )%P;
    r=inv(r,P);
    for(i=1;i<N/2;++i)std::swap(ps[i],ps[N-i]);
    a.trans2(N);
}

```

```

    for(i=0;i<N;++i)a.co[i]=((long long)a.co[i]*Ni)%P;
    a.n=n+_b.n; return a;
}
};

```

## 4.9 Chinese Remainder

```

int pfn; // number of distinct prime factors
int pf[MAXNUM]; // prime factor powers
int rem[MAXNUM]; // corresponding remainder
int pm[MAXNUM];
inline void generate_primes() {
    int i,j;
    pnum=1;
    prime[0]=2;
    for(i=3;i<MAXVAL;i+=2) {
        if(nprime[i]) continue;
        prime[pnum++]=i;
        for(j=i*i;j<MAXVAL;j+=i) nprime[j]=1;
    }
}
inline int inverse(int x,int p) {
    int q,tmp,a=x,b=p;
    int a0=1,a1=0,b0=0,b1=1;
    while(b) {
        q=a/b; tmp=b; b=a-b*q; a=tmp;
        tmp=b0; b0=a0-b0*q; a0=tmp;
        tmp=b1; b1=a1-b1*q; a1=tmp;
    }
    return a0;
}
inline void decompose_mod() {
    int i,p,t=mod;
    pfn=0;
    for(i=0;i<pnum&&prime[i]<=t;i++) {
        p=prime[i];
        if(t%p==0) {
            pf[pfn]=1;
            while(t%p==0) {
                t/=p;
                pf[pfn]*=p;
            }
            pfn++;
        }
        if(t>1) pf[pfn++]=t;
    }
}
inline int chinese_remainder() {
    int i,m,s=0;
    for(i=0;i<pfn;i++) {
        m=mod/pf[i];
        pm[i]=(long long)m*inverse(m,pf[i])%mod;
        s=(s+(long long)pm[i]*rem[i])%mod;
    }
    return s;
}

```

## 4.10 Primes

```

/*
* 12721
* 13331
* 14341
* 75577
* 123457
* 222557
* 556679
* 999983
* 1097774749
* 1076767633
* 100102021
* 999997771
* 1001010013
* 1000512343
* 987654361
* 999991231
* 999888733
* 98789101

```

```

* 987777733
* 999991921
* 1010101333
* 1010102101
* 1000000000039
* 100000000000037
* 2305843009213693951
* 4611686018427387847
* 9223372036854775783
* 18446744073709551557
*/

```

```

int mu[MX],p_tbl[MX];
vector<int> primes;
void sieve() {
    mu[1] = p_tbl[1] = 1;
    for (int i=2; i<MX; i++) {
        if (!p_tbl[i]) {
            p_tbl[i] = i;
            primes.PB(i);
            mu[i] = -1;
        }
        for (auto p : primes) {
            int x = i*p;
            if (x >= M) break;
            p_tbl[x] = p;
            mu[x] = -mu[i];
            if (i%p==0) {
                mu[x] = 0;
                break;
            }
        }
    }
}
vector<int> factor(int x) {
    vector<int> fac{1};
    while (x > 1) {
        int fn=SZ(fac), p=p_tbl[x], pos=0;
        while (x%p == 0) {
            x /= p;
            for (int i=0; i<fn; i++)
                fac.PB(fac[pos++]*p);
        }
        return fac;
    }
}

```

## 4.11 Miller Rabin

```

// n < 4,759,123,141      3 : 2, 7, 61
// n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
// n < 3,474,749,660,383  6 : primes <= 13
// n < 3,825,123,056,546,413,051  9 : primes <= 23
long long power(long long x,long long p,long long mod){
    long long s=1,m=x;
    while(p) {
        if(p&1) s=mult(s,m,mod);
        p>>=1;
        m=mult(m,m,mod);
    }
    return s;
}
bool witness(long long a,long long n,long long u,int t)
{
    long long x=power(a,u,n);
    for(int i=0;i<t;i++) {
        long long nx=mult(x,x,n);
        if(nx==1&&x!=1&&x!=n-1) return 1;
        x=nx;
    }
    return x!=1;
}
bool miller_rabin(long long n,int s=100) {
    // iterate s times of witness on n
    // return 1 if prime, 0 otherwise
    if(n<2) return 0;
    if(!(n&1)) return n==2;
    long long u=n-1;
    int t=0;

```

```
// n-1 = u*2^t
while(u&1) {
    u>>=1;
    t++;
}
while(s--) {
    long long a=randll()%(n-1)+1;
    if(witness(a,n,u,t)) return 0;
}
return 1;
}
```

## 5 Geometry

### 5.1 Half Plane Intersection

```
#include<bits/stdc++.h>

using namespace std;

#define PB push_back
#define _x first
#define _y second

const int MXL = 5000;
const double EPS = 1e-8;

typedef pair<double, double> pdd;
typedef pair<pdd, pdd> Line;

pdd operator + (const pdd p1, const pdd p2){
    return pdd(p1._x + p2._x, p1._y + p2._y);
}

pdd operator - (const pdd p1, const pdd p2){
    return pdd(p1._x - p2._x, p1._y - p2._y);
}

pdd operator * (const double c, const pdd p){
    return pdd(p._x * c, p._y * c);
}

double operator % (const pdd p1, const pdd p2){
    return p1._x * p2._y - p2._x * p1._y;
}

vector<Line> lnlst;
double atn[MXL];

bool lncmp(int l1, int l2){
    return atn[l1] < atn[l2];
}

pdd interPnt(pdd p1, pdd p2, pdd q1, pdd q2){
    double f1 = (p2 - p1) % (q1 - p1);
    double f2 = (p2 - p1) % (p1 - q2);
    double f = (f1 + f2);

    if(fabs(f) < EPS) return pdd(nan(""), nan(""));

    return (f2 / f) * q1 + (f1 / f) * q2;
}

deque<Line> dq;

void halfPlaneInter(){
    int n = lnlst.size();
    vector<int> stlst;
    for(int i=0; i<n; i++){
        stlst.PB(i);
        pdd d = lnlst[i].second - lnlst[i].first;
        atn[i] = atan2(d._y, d._x);
    }
    sort(stlst.begin(), stlst.end(), lncmp);
    vector<Line> lst;

    for(int i=0; i<n; i++){
```

```
if(i) {
    int j = i-1;
    Line l1 = lnlst[stlst[i]];
    Line lj = lnlst[stlst[j]];
    pdd di = l1.second - l1.first;
    pdd dj = lj.second - lj.first;
    if(fabs(di%dj) < EPS){
        if(di % (lj.second - lj.first) < 0) {
            lst.pop_back();
        }else continue;
    }
}
lst.PB(lnlst[stlst[i]]);
}

dq.PB(lst[0]);
dq.PB(lst[1]);
for(int i=2; i<n; i++){
    int dsz = dq.size();
    Line l1 = lst[i];
    while(dsz >= 2){
        Line l1 = dq[dsz-1];
        Line l2 = dq[dsz-2];

        pdd it12 = interPnt(l1.first, l1.second, l2.first,
            l2.second);

        if((l1.second - l1.first) % (it12 - l1.first) < 0){
            dq.pop_back();
            dsz--;
        } else break;
    }

    while(dsz >= 2){
        Line l1 = dq[0];
        Line l2 = dq[1];

        pdd it12 = interPnt(l1.first, l1.second, l2.first,
            l2.second);

        if((l1.second - l1.first) % (it12 - l1.first) < 0){
            dq.pop_front();
            dsz--;
        } else break;
    }

    Line l1 = dq[dsz - 1];
    if(!std::isnan(interPnt(l1.first, l1.second, l1.first,
        l1.second)._x)){
        dq.PB(l1);
    }
}

int dsz = dq.size();
while(dsz >= 2){
    Line l1 = dq[dsz - 1];
    Line l2 = dq[dsz - 2];
    Line l = dq[0];
    pdd it12 = interPnt(l1.first, l1.second, l2.first,
        l2.second);
    if(std::isnan(it12._x)) {
        dq.pop_back();
        dq.pop_back();
        dsz -= 2;
    } else if((l1.second - l1.first) % (it12 - l1.first) <
        0){
        dq.pop_back();
        dsz--;
    } else break;
}
}

int main(){
    int N;
    cin >> N;
    for(int i=0; i<N; i++){
        double x1, x2, y1, y2;
        cin >> x1 >> y1 >> x2 >> y2;
        lnlst.PB({pdd(x1, y1), pdd(x2, y2)});
    }
}
```

```

}

halfPlaneInter();

int dsz = dq.size();
cout << dsz << endl;
for(int i=0; i<dsz; i++){
    int j = (i+1) % dsz;
    pdd it = interPnt(dq[i].first, dq[i].second, dq[j].first, dq[j].second);
    cout << it._x << ' ' << it._y << endl;
}
}

```

## 5.2 KD Tree

```

const INF = 11000000000;

class NODE{ public:
    int x,y,x1,x2,y1,y2;
    int i,f;
    NODE *L,*R;
};

inline long long dis(NODE& a,NODE& b){
    long long dx=a.x-b.x;
    long long dy=a.y-b.y;
    return dx*dx+dy*dy;
}

NODE node[100000];
bool cmpx(const NODE& a,const NODE& b){ return a.x<b.x; }
bool cmpy(const NODE& a,const NODE& b){ return a.y<b.y; }

NODE* KDTree(int L,int R,int dep){
    if(L>R) return 0;
    int M=(L+R)/2;
    if(dep%2==0){
        nth_element(node+L,node+M,node+R+1,cmpx);
        node[M].f=0;
    }else{
        nth_element(node+L,node+M,node+R+1,cmpy);
        node[M].f=1;
    }
    node[M].x1=node[M].x2=node[M].x;
    node[M].y1=node[M].y2=node[M].y;
    node[M].L=KDTree(L,M-1,dep+1);
    if(node[M].L){
        node[M].x1=min(node[M].x1,node[M].L->x1);
        node[M].x2=max(node[M].x2,node[M].L->x2);
        node[M].y1=min(node[M].y1,node[M].L->y1);
        node[M].y2=max(node[M].y2,node[M].L->y2);
    }
    node[M].R=KDTree(M+1,R,dep+1);
    if(node[M].R){
        node[M].x1=min(node[M].x1,node[M].R->x1);
        node[M].x2=max(node[M].x2,node[M].R->x2);
        node[M].y1=min(node[M].y1,node[M].R->y1);
        node[M].y2=max(node[M].y2,node[M].R->y2);
    }
    return node+M;
}

inline int touch(NODE* r,int x,int y,long long d){
    long long d2;
    d2 = (long long)(sqrt(d)+1);
    if(x<r->x1-d2 || x>r->x2+d2 || y<r->y1-d2 || y>r->y2+d2)
        return 0;
    return 1;
}

void nearest(NODE* r,int z,long long &md){
    if(!r || !touch(r,node[z].x,node[z].y,md)) return;
    long long d;
    if(node[z].i!=r->i){
        d=dis(*r,node[z]);
        if(d<md) md=d;
    }
    if(r->f==0){
        if(node[z].x<r->x){
            nearest(r->L,z,md);

```

```

            nearest(r->R,z,md);
        }else{
            nearest(r->R,z,md);
            nearest(r->L,z,md);
        }
    }else{
        if(node[z].y<r->y){
            nearest(r->L,z,md);
            nearest(r->R,z,md);
        }else{
            nearest(r->R,z,md);
            nearest(r->L,z,md);
        }
    }
}

int main(){
    int TT,n,i;
    long long d;
    NODE* root;
    scanf("%d",&TT);
    while(TT--){
        scanf("%d",&n);
        for(i=0;i<n;i++){
            scanf("%d %d",&node[i].x,&node[i].y);
            node[i].i=i;
        }
        root=KDTree(0,n-1,0);
        for(i=0;i<n;i++){
            d=9000000000000000000LL;
            nearest(root,i,d);
            ans[node[i].i]=d;
        }
    }
}

```

## 5.3 Minimum Covering Circle

```

struct Mcc{
    // return pair of center and r^2
    static const int MAXN = 1000100;
    int n;
    pdd p[MAXN],cen;
    double r2;

    void init(int _n, pdd _p[]){
        n = _n;
        memcpy(p,_p,sizeof(pdd)*n);
    }

    double sqr(double a){ return a*a; }
    double abs2(pdd a){ return a.x*a.x+a.y*a.y; }
    pdd center(pdd p0, pdd p1, pdd p2) {
        pdd a = p1-p0;
        pdd b = p2-p0;
        double c1=abs2(a)*0.5;
        double c2=abs2(b)*0.5;
        double d = a.x*b.y - a.y*b.x;
        double x = p0.x + (c1 * b.y - c2 * a.y) / d;
        double y = p0.y + (a.x * c2 - b.x * c1) / d;
        return pdd(x,y);
    }

    pair<pdd,double> solve(){
        random_shuffle(p,p+n);
        r2=0;
        for (int i=0; i<n; i++){
            if (abs2(cen-p[i]) <= r2) continue;
            cen = p[i];
            r2 = 0;
            for (int j=0; j<i; j++){
                if (abs2(cen-p[j]) <= r2) continue;
                cen = 0.5 * (p[i]+p[j]);
                r2 = abs2(cen-p[j]);
                for (int k=0; k<j; k++){
                    if (abs2(cen-p[k]) <= r2) continue;
                    cen = center(p[i],p[j],p[k]);
                    r2 = abs2(cen-p[k]);
                }
            }
        }
        return {cen,r2};
    }
}

```

```

    }
}mcc;

```

## 5.4 Minkowski Sum

```

/* convex hull Minkowski Sum */
#define INF 1000000000000000LL
class PT{ public:
    long long x,y;
    int POS(){
        if(y==0) return x>0?0:1;
        return y>0?0:1;
    }
};
PT pt[300000],qt[300000],rt[300000];
long long Lx,Rx;
int dn,un;
inline bool cmp(PT a,PT b){
    int pa=a.POS(),pb=b.POS();
    if(pa==pb) return (a^b)>0;
    return pa<pb;
}
int minkowskiSum(int n,int m){
    int i,j,r,p,q,fi,fj;
    for(i=1,p=0;i<n;i++){
        if(pt[i].y<pt[p].y || (pt[i].y==pt[p].y && pt[i].x<
            pt[p].x)) p=i; }
    for(i=1,q=0;i<m;i++){
        if(qt[i].y<qt[q].y || (qt[i].y==qt[q].y && qt[i].x<
            qt[q].x)) q=i; }
    rt[0]=pt[p]+qt[q];
    r=1; i=p; j=q; fi=fj=0;
    while(1){
        if((fj&&j==q) || ((!fi||i!=p) && cmp(pt[(p+1)%n]-pt[
            p],qt[(q+1)%m]-qt[q]))){
            rt[r]=rt[r-1]+pt[(p+1)%n]-pt[p];
            p=(p+1)%n;
            fi=1;
        }else{
            rt[r]=rt[r-1]+qt[(q+1)%m]-qt[q];
            q=(q+1)%m;
            fj=1;
        }
        if(r<=1 || ((rt[r]-rt[r-1])^(rt[r-1]-rt[r-2]))!=0)
            r++;
        else rt[r-1]=rt[r];
        if(i==p && j==q) break;
    }
    return r-1;
}
void initInConvex(int n){
    int i,p,q;
    long long Ly,Ry;
    Lx=INF; Rx=-INF;
    for(i=0;i<n;i++){
        if(pt[i].x<Lx) Lx=pt[i].x;
        if(pt[i].x>Rx) Rx=pt[i].x;
    }
    Ly=Ry=INF;
    for(i=0;i<n;i++){
        if(pt[i].x==Lx && pt[i].y<Ly){ Ly=pt[i].y; p=i; }
        if(pt[i].x==Rx && pt[i].y<Ry){ Ry=pt[i].y; q=i; }
    }
    for(dn=0,i=p;i!=q;i=(i+1)%n){ qt[dn++]=pt[i]; }
    qt[dn]=pt[q]; Ly=Ry=-INF;
    for(i=0;i<n;i++){
        if(pt[i].x==Lx && pt[i].y>Ly){ Ly=pt[i].y; p=i; }
        if(pt[i].x==Rx && pt[i].y>Ry){ Ry=pt[i].y; q=i; }
    }
    for(un=0,i=p;i!=q;i=(i+n-1)%n){ rt[un++]=pt[i]; }
    rt[un]=pt[q];
}
inline int inConvex(PT p){
    int L,R,M;
    if(p.x<Lx || p.x>Rx) return 0;
    L=0;R=dn;
    while(L<R-1){ M=(L+R)/2;
        if(p.x<qt[M].x) R=M; else L=M; }

```

```

        if(tri(qt[L],qt[R],p)<0) return 0;
        L=0;R=un;
        while(L<R-1){ M=(L+R)/2;
            if(p.x<rt[M].x) R=M; else L=M; }
        if(tri(rt[L],rt[R],p)>0) return 0;
        return 1;
    }
}
int main(){
    int n,m,i;
    PT p;
    scanf("%d",&n);
    for(i=0;i<n;i++) scanf("%I64d %I64d",&pt[i].x,&pt[i].
        y);
    scanf("%d",&m);
    for(i=0;i<m;i++) scanf("%I64d %I64d",&qt[i].x,&qt[i].
        y);
    n=minkowskiSum(n,m);
    for(i=0;i<n;i++) pt[i]=rt[i];
    scanf("%d",&m);
    for(i=0;i<m;i++) scanf("%I64d %I64d",&qt[i].x,&qt[i].
        y);
    n=minkowskiSum(n,m);
    for(i=0;i<n;i++) pt[i]=rt[i];
    initInConvex(n);
    scanf("%d",&m);
    for(i=0;i<m;i++){
        scanf("%I64d %I64d",&p.x,&p.y);
        p.x*=3; p.y*=3;
        puts(inConvex(p)?"YES":"NO");
    }
}

```

## 5.5 Convex Hull

```

double cross(pdd o, pdd a, pdd b){
    return (a-o) % (b-o);
}
vector<pdd> convex_hull(vector<pdd> pt){
    sort(pt.begin(),pt.end());
    int top=0;
    vector<pdd> stk(2*pt.size());
    for (int i=0; i<(int)pt.size(); i++){
        while (top >= 2 && cross(stk[top-2],stk[top-1],pt[i]
            ]) <= 0)
            top--;
        stk[top++] = pt[i];
    }
    for (int i=pt.size()-2, t=top+1; i>=0; i--){
        while (top >= t && cross(stk[top-2],stk[top-1],pt[i]
            ]) <= 0)
            top--;
        stk[top++] = pt[i];
    }
    stk.resize(top-1);
    return stk;
}

```

## 5.6 Intersection Of Two Circles

```

vector<pdd> interCircle(pdd o1, double r1, pdd o2,
    double r2) {
    ld d2 = (o1 - o2) * (o1 - o2);
    ld d = sqrt(d2);
    if (d > r1+r2) return {};
    pdd u = 0.5*(o1+o2) + ((r2*r2-r1*r1)/(2*d2))*(o1-o2);
    double A = sqrt((r1+r2+d) * (r1-r2+d) * (r1+r2-d) *
        (-r1+r2+d));
    pdd v = A / (2*d2) * pdd(o1.S-o2.S, -o1.F+o2.F);
    return {u+v, u-v};
}

```

## 5.7 Intersection Of Two Lines

```

#include<bits/stdc++.h>
using namespace std;

```



```
const double EPS = 1e-9;

pdd interPnt(pdd p1, pdd p2, pdd q1, pdd q2){
    double f1 = (p2 - p1) % (q1 - p1);
    double f2 = (p2 - p1) % (p1 - q2);
    double f = (f1 + f2);

    if(fabs(f) < EPS) return pdd(nan(""), nan(""));

    return (f2 / f) * q1 + (f1 / f) * q2;
}
```

## 5.8 Point Operators

```
#include<bits/stdc++.h>
using namespace std;

#define _x first
#define _y second
typedef pair<double, double> pdd;

pdd operator + (const pdd p1, const pdd p2){
    return pdd(p1._x + p2._x, p1._y + p2._y);
}
pdd operator - (const pdd p1, const pdd p2){
    return pdd(p1._x - p2._x, p1._y - p2._y);
}

pdd operator * (const double c, const pdd p){
    return pdd(p._x * c, p._y * c);
}
pdd operator - (const pdd p){
    return (-1.0) * p;
}

double operator * (const pdd p1, const pdd p2){
    return p1._x * p2._x + p1._y * p2._y;
}

double operator % (const pdd p1, const pdd p2){
    return p1._x * p2._y - p2._x * p1._y;
}
```

## 6 Stringology

### 6.1 AC Automata

```
struct ACautomata{
    struct Node{
        int cnt,dp;
        Node *go[26], *fail;
        Node(){
            cnt = 0;
            dp = -1;
            memset(go,0,sizeof(go));
            fail = 0;
        }
    };

    Node *root, pool[1048576];
    int nMem;

    Node* new_Node(){
        pool[nMem] = Node();
        return &pool[nMem++];
    }

    void init(){
        nMem = 0;
        root = new_Node();
    }

    void add(const string &str){
        insert(root,str,0);
    }

    void insert(Node *cur, const string &str, int pos){
        if (pos >= (int)str.size()){
            cur->cnt++;
            return;
        }
    }
```

```
int c = str[pos]-'a';
if (cur->go[c] == 0){
    cur->go[c] = new_Node();
}
insert(cur->go[c],str,pos+1);
}

void make_fail(){
    queue<Node*> que;
    que.push(root);
    while (!que.empty()){
        Node* fr=que.front();
        que.pop();
        for (int i=0; i<26; i++){
            if (fr->go[i]){
                Node *ptr = fr->fail;
                while (ptr && !ptr->go[i]) ptr = ptr->fail;
                if (!ptr) fr->go[i]->fail = root;
                else fr->go[i]->fail = ptr->go[i];
                que.push(fr->go[i]);
            }
        }
    }
};
```

### 6.2 SAM

```
// par : fail link
// val : a topological order ( useful for DP )
// go[x] : automata edge ( x is integer in [0,26) )

struct SAM{
    struct State{
        int par, go[26], val;
        State () : par(0), val(0){ FZ(go); }
        State (int _val) : par(0), val(_val){ FZ(go); }
    };
    vector<State> vec;
    int root, tail;

    void init(int arr[], int len){
        vec.resize(2);
        vec[0] = vec[1] = State(0);
        root = tail = 1;
        for (int i=0; i<len; i++){
            extend(arr[i]);
        }

        void extend(int w){
            int p = tail, np = vec.size();
            vec.PB(State(vec[p].val+1));
            for ( ; p && vec[p].go[w]==0; p=vec[p].par)
                vec[p].go[w] = np;
            if (p == 0){
                vec[np].par = root;
            } else {
                if (vec[vec[p].go[w]].val == vec[p].val+1){
                    vec[np].par = vec[p].go[w];
                } else {
                    int q = vec[p].go[w], r = vec.size();
                    vec.PB(vec[q]);
                    vec[r].val = vec[p].val+1;
                    vec[q].par = vec[np].par = r;
                    for ( ; p && vec[p].go[w] == q; p=vec[p].par)
                        vec[p].go[w] = r;
                }
            }
            tail = np;
        }
    };
};
```

### 6.3 Palindrome

```
const int MAX = 1000;
int len;
char ip[MAX];
char op[MAX*2];
int zv[MAX*2];
```



```

int main(){
    cin >> ip;
    len = strlen(ip);

    int l2 = len*2 - 1;
    for(int i=0; i<l2; i++){
        if(i&1) op[i] = '@';
        else op[i] = ip[i/2];
    }
    int l=0, r=0;
    zv[0] = 1;

    for(int i=1; i<l2; i++){
        if( i > r ){
            l = r = i;
            while( l>0 && r<l2-1 && op[l-1] == op[r+1] ){
                l --;
                r ++;
            }
            zv[i] = (r-l+1);
        }else{
            int md = (l+r)/2;
            int j = md + md - i;
            zv[i] = zv[j];
            int q = zv[i] / 2;
            int nr = i + q;
            if( nr == r ){
                l = i + i - r;

                while( l>0 && r<l2-1 && op[l-1] == op[r+1] ){
                    l --;
                    r ++;
                }
                zv[i] = r - l + 1;
            }else if( nr > r ){
                zv[i] = (r - i) * 2 + 1;
            }
        }
    }

    return 0;
}

```

## 6.4 Z Value

```

char s[MAXLEN];
int len,z[MAXLEN];
void Z_value() {
    int i,j,left,right;
    left=right=0; z[0]=len;
    for(i=1;i<len;i++) {
        j=max(min(z[i-left],right-i),0);
        for(;i+j<len&&s[i+j]==s[j];j++);
        z[i]=j;
        if(i+z[i]>right) {
            right=i+z[i];
            left=i;
        }
    }
}

```

## 6.5 Smallest Rotation

```

string mcp(string s){
    int n = s.length();
    s += s;
    int i=0, j=1, k=0;
    while (j<n && k<n){
        if (s[i+k] == s[j+k]) k++;
        else {
            if (s[i+k] < s[j+k]) {
                j += k + 1;
            } else {
                i = j;
                j = max(j+1, j+k);
            }
        }
        k = 0;
    }
}

```

```

    }
}
return s.substr(i, n);
}

```

## 6.6 Suffix Array

```

const int MAX = 1020304;
int ct[MAX], he[MAX], rk[MAX], sa[MAX], tsa[MAX], tp[
MAX][2];

void suffix_array(char *ip){
    int len = strlen(ip);
    int alp = 256;

    memset(ct, 0, sizeof(ct));
    for(int i=0;i<len;i++) ct[ip[i]+1]++;
    for(int i=1;i<alp;i++) ct[i]+=ct[i-1];
    for(int i=0;i<len;i++) rk[i]=ct[ip[i]];

    for(int i=1;i<len;i*=2){
        for(int j=0;j<len;j++){
            if(j+i>=len) tp[j][1]=0;
            else tp[j][1]=rk[j+i]+1;

            tp[j][0]=rk[j];
        }
        memset(ct, 0, sizeof(ct));
        for(int j=0;j<len;j++) ct[tp[j][1]+1]++;
        for(int j=1;j<len+2;j++) ct[j]+=ct[j-1];
        for(int j=0;j<len;j++) tsa[ct[tp[j][1]]+=j];

        memset(ct, 0, sizeof(ct));
        for(int j=0;j<len;j++) ct[tp[j][0]+1]++;
        for(int j=1;j<len+1;j++) ct[j]+=ct[j-1];
        for(int j=0;j<len;j++) sa[ct[tp[tsa[j]][0]]+=j]=tsa[
j];

        rk[sa[0]]=0;
        for(int j=1;j<len;j++){
            if( tp[sa[j]][0] == tp[sa[j-1]][0] &&
                tp[sa[j]][1] == tp[sa[j-1]][1] )
                rk[sa[j]] = rk[sa[j-1]];
            else
                rk[sa[j]] = j;
        }
    }

    for(int i=0,h=0;i<len;i++){
        if(rk[i]==0) h=0;
        else{
            int j=sa[rk[i]-1];
            h=max(0,h-1);
            for(;ip[i+h]==ip[j+h];h++);
        }
        he[rk[i]]=h;
    }
}

```

## 6.7 Sais

```

struct SA{
#define REP(i,n) for ( int i=0; i<int(n); i++ )
#define REP1(i,a,b) for ( int i=(a); i<=int(b); i++ )
    static const int MXN = 300010;
    bool _t[MXN*2];
    int _s[MXN*2], _sa[MXN*2], _c[MXN*2], x[MXN], _p[
MXN], _q[MXN*2], hei[MXN], r[MXN];
    int operator [] (int i){ return _sa[i]; }
    void build(int *s, int n, int m){
        memcpy(_s, s, sizeof(int) * n);
        sais(_s, _sa, _p, _q, _t, _c, n, m);
        mkhei(n);
    }
    void mkhei(int n){
        REP(i,n) r[_sa[i]] = i;
        hei[0] = 0;
    }
}

```

```

    REP(i,n) if(r[i]) {
        int ans = i>0 ? max(hei[r[i-1]] - 1, 0) : 0;
        while(_s[i+ans] == _s[_sa[r[i]-1]+ans]) ans++;
        hei[r[i]] = ans;
    }
}
void sais(int *s, int *sa, int *p, int *q, bool *t, int *c, int n, int z){
    bool uniq = t[n-1] = true, neq;
    int nn = 0, nmzx = -1, *nsa = sa + n, *ns = s + n, lst = -1;
#define MS0(x,n) memset((x),0,n*sizeof(*(x)))
#define MAGIC(XD) MS0(sa, n); \
    memcpy(x, c, sizeof(int) * z); \
    XD; \
    memcpy(x + 1, c, sizeof(int) * (z - 1)); \
    REP(i,n) if(sa[i] && !t[sa[i]-1]) sa[x[s[sa[i]-1]]++] = sa[i]-1; \
    memcpy(x, c, sizeof(int) * z); \
    for(int i = n - 1; i >= 0; i--) if(sa[i] && t[sa[i]-1]) sa[--x[s[sa[i]-1]]] = sa[i]-1;
    MS0(c, z);
    REP(i,n) uniq &= ++c[s[i]] < 2;
    REP(i,z-1) c[i+1] += c[i];
    if (uniq) { REP(i,n) sa[--c[s[i]]] = i; return; }
    for(int i = n - 2; i >= 0; i--) t[i] = (s[i]==s[i+1] ? t[i+1] : s[i]<s[i+1]);
    MAGIC(REP1(i,1,n-1) if(t[i] && !t[i-1]) sa[--x[s[i]]]=p[q[i]=nn++]=i);
    REP(i, n) if (sa[i] && t[sa[i]] && !t[sa[i]-1]) {
        neq=lst<0||memcmp(s+sa[i],s+lst,(p[q[sa[i]]+1]-sa[i])*sizeof(int));
        ns[q[lst=sa[i]]]=nmzx+=neq;
    }
    sais(ns, nsa, p + nn, q + n, t + n, c + z, nn, nmzx + 1);
    MAGIC(for(int i = nn - 1; i >= 0; i--) sa[--x[p[nsa[i]]]] = p[nsa[i]]);
}
}
}
sa;

void suffix_array(int* ip, int len) {
    // should padding a zero in the back
    // s is int array, n is array length
    // s[0..n-1] != 0, and s[n] = 0
    // resulting SA will be length n+1
    ip[len++] = 0;
    sa.build(ip, len, 128);
    // original 1-base
    for (int i=0; i<l; i++) {
        hei[i] = sa.hei[i + 1];
        sa[i] = sa._sa[i + 1];
    }
}
}

```

## 7 Problems

### 7.1 Orange Protection

```

/*
 * Given a Tree and the power of every node.
 * Each Node can protect the nodes whose distance <=
 *   cover[i] with it
 * output the number of each node that it can protect.
 */
const int MXN = 100005;

int cover[MXN], ans[MXN];
int N, ok[MXN];
int fr,bk,que[MXN],vst[MXN],dis[MXN],fa[MXN],sz[MXN];
vector<int> E[MXN];

int bit[MXN];
int lb(int a){ return a & -a; }

```

```

void reset_bit(int st){
    for (int i = st+1; i < MXN; i+=lb(i))
        bit[i] = 0;
}
void update(int st){
    for (int i = st+1; i < MXN; i+=lb(i))
        bit[i]++;
}
int query(int st, int ret = 0){
    for (int i = st+1; i > 0; i-=lb(i))
        ret += bit[i];
    return ret;
}

void BFS(int st){
    fr = bk = 0;
    que[bk++] = st;
    vst[st] = 1;
    dis[st] = 0;
    while (fr < bk){
        int u = que[fr++];
        for (auto v : E[u]){
            if (!ok[v] || vst[v]) continue;
            vst[v] = 1;
            dis[v] = dis[u] + 1;
            fa[v] = u;
            que[bk++] = v;
        }
    }
    for (int i=0; i<bk; i++)
        vst[que[i]] = 0;
}

int find_centroid(int st){
    int ret=-1, cnt=MXN+100;
    BFS(st);
    for (int i = bk-1; i>=0; i--){
        int u = que[i], mx = 0;
        sz[u] = 1;
        for (auto v : E[u]){
            if (!ok[v] || v == fa[u]) continue;
            sz[u] += sz[v];
            mx = max(mx, sz[v]);
        }
        mx = max(mx, bk-sz[u]);
        if (mx < cnt){
            ret = u;
            cnt = mx;
        }
    }
    return ret;
}

void solve(int u){
    int root = find_centroid(u);
    ok[root] = 0;
    for (auto v : E[root])
        if (ok[v]) solve(v);

    for (auto v : E[root]){
        if (!ok[v]) continue;
        BFS(v);
        for (int i=0; i<bk; i++){
            dis[que[i]]++;
            update(dis[que[i]]);
        }
        for (int i=0; i<bk; i++){
            int it = que[i];
            ans[it] -= query(cover[it] - dis[it]);
        }
        for (int i=0; i<bk; i++)
            reset_bit(dis[que[i]]);
    }
    BFS(root);
    for (int i=0; i<bk; i++) update(dis[que[i]]);
    for (int i=0; i<bk; i++){
        int v = que[i];
        ans[v] += query(cover[v] - dis[v]);
    }
    for (int i=0; i<bk; i++) reset_bit(dis[que[i]]);

    ok[root] = 1;
}

```

```

int main(int argc, char** argv){
    scanf("%d", &N);
    for (int i=0; i<N; i++){
        scanf("%d", &cover[i]);
        cover[i] = min(cover[i], N);
    }
    for (int i=0,u,v; i<N-1; i++){
        scanf("%d%d", &u, &v);
        u--; v--;
        E[u].PB(v);
        E[v].PB(u);
    }
    fill(ok,ok+N,1);
    FZ(vst); FZ(ans); FZ(bit);
    solve(0);
    for (int i=0; i<N; i++){
        printf("%d\n", ans[i]);
    }
    return 0;
}

```

## 7.2 Max Tangent

```

typedef long long LL;
const int MAXN = 100010;
struct Coord{
    LL x, y;
    Coord operator - (Coord ag) const{
        Coord res;
        res.x = x - ag.x;
        res.y = y - ag.y;
        return res;
    }
}sum[MAXN], pnt[MAXN], ans, calc;

inline bool cross(Coord a, Coord b, Coord c){
    return (c.y - a.y) * (c.x - b.x) > (c.x - a.x) * (c.y - b.y);
}

int main(){
    int n, l, np, st, ed, now;
    scanf("%d %d\n", &n, &l);
    sum[0].x = sum[0].y = np = st = ed = 0;
    for (int i = 1, v; i <= n; i++){
        scanf("%d", &v);
        sum[i].y = sum[i-1].y + v;
        sum[i].x = i;
    }
    ans.x = now = 1;
    ans.y = -1;
    for (int i = 0; i <= n - l; i++){
        while (np > 1 && cross(pnt[np-2], pnt[np-1], sum[i]))
            np--;
        if (np < now && np != 0) now = np;
        pnt[np++] = sum[i];
        while (now < np && !cross(pnt[now-1], pnt[now], sum[i+l]))
            now++;
        calc = sum[i+l] - pnt[now-1];
        if (ans.y * calc.x < ans.x * calc.y){
            ans = calc;
            st = pnt[now-1].x;
            ed = i + l;
        }
    }
    double res = (sum[ed].y - sum[st].y) / (sum[ed].x - sum[st].x);
    printf("%f\n", res);
    return 0;
}

```

## 7.3 Cot4

```

#include <bits/stdc++.h>
using namespace std;
#define FZ(n) memset((n),0,sizeof(n))

```

```

#define FMO(n) memset((n),-1,sizeof(n))
#define MC(n,m) memcpy((n),(m),sizeof(n))
#define F first
#define S second
#define MP make_pair
#define PB push_back
#define FOR(x,y) for(__typeof(y.begin())x=y.begin();x!=y.end();x++)
#define IOS ios_base::sync_with_stdio(0)

#ifdef ONLINE_JUDGE
#define FILEIO(name) \
freopen(name".in", "r", stdin); \
freopen(name".out", "w", stdout);
#else
#define FILEIO(name)
#endif
// Let's Fight!

typedef long long LL;

const int MXN = 130005;
const int MX = 300005;
const int HASH = 12721;
const int MOD = 999997771;
const int LOG = 17;
struct query_t{
    int ti,sj,id;
};
struct tTree_t{
    int tp, prvID, prvID2;
    char ch;
    int l,r,len;
}tTree[MXN];
vector<int> E[MXN];
vector<query_t> q[MXN];

int sa[MXN],rk[MXN],rk2[MXN],fa[LOG][MXN],sCh[MXN],
    cmpLv;
pair<int,int> azRange[30];
int N,nq;
int tID,sID;
int ans[MXN];

inline int getRank(int id){
    if (id == 0) return 0;
    if (id >= sID) while(1);
    return rk[id];
}

bool comp0(int a, int b){
    return sCh[a] < sCh[b];
}

bool comp1(int a, int b){
    if (getRank(a) == getRank(b)){
        return getRank(fa[cmpLv][a]) < getRank(fa[cmpLv][b]);
    }
    return getRank(a) < getRank(b);
}

void suffix_array(){
    sCh[1] = 0;
    for (int i=1; i<sID; i++){
        sa[i] = i;
        rk[i] = sCh[i];
    }
    sort(sa+1,sa+sID,comp0);
    cmpLv = 0;
    for (int len = 1; len < MXN; len <= 1){
        sort(sa+1,sa+sID,comp1);
        int r = 1;
        rk2[sa[1]] = r;
        for (int i=2; i<sID; i++){
            if (comp1(sa[i-1],sa[i])){
                rk2[sa[i]] = ++r;
            } else {
                rk2[sa[i]] = r;
            }
        }
        for (int i=1; i<sID; i++){
            rk[i] = rk2[i];
        }
        cmpLv++;
    }
}

```

```

    }
}

void init(){
    nq = 0;
    tID = 2;
    sID = 2;
    FZ(fa);
}

int trash;
void input(){
    init();
    trash = scanf("%d", &N);
    for (int i=0; i<N; i++){
        int cmd;
        trash = scanf("%d", &cmd);
        if (cmd == 1){
            int prvID;
            char str[10];
            trash = scanf("%d%s", &prvID, str);
            E[prvID].PB(sID);
            fa[0][sID] = prvID;
            sCh[sID] = str[0];
            sID++;
        } else if (cmd == 2){
            int dir;
            int prvID;
            char str[5];
            trash = scanf("%d%d%s", &dir,&prvID,str);
            if (dir == 0){
                tTree[tID].tp = 0;
                tTree[tID].prvID = prvID;
                tTree[tID++].ch = str[0];
            } else {
                tTree[tID].tp = 1;
                tTree[tID].prvID = prvID;
                tTree[tID++].ch = str[0];
            }
        } else if (cmd == 3){
            int a,b;
            trash = scanf("%d%d", &a, &b);
            tTree[tID].tp = 2;
            tTree[tID].prvID = a;
            tTree[tID++].prvID2 = b;
        } else if (cmd == 4){
            int ti,sj;
            trash = scanf("%d%d", &ti, &sj);
            q[sj].PB((query_t){ti,sj,nq});
            nq++;
        }
    }
}

int moveUP(int u, int len){
    for (int i=0; i<LOG && len; i++){
        if (len & (1<<i)){
            len -= 1<<i;
            u = fa[i][u];
        }
    }
    return u;
}

int getL(int l, int r, int up, int cp){
    if (l == r) return l;
    while (l < r){
        int mid = (l+r) / 2;
        int id = moveUP(sa[mid],up);
        if (cp <= rk[id])
            r = mid;
        else
            l = mid+1;
    }
    return l;
}

int getR(int l, int r, int up, int cp){
    if (l == r) return l;
    while (l < r){
        int mid = (l+r) / 2;
        int id = moveUP(sa[mid],up);
        if (cp < rk[id])
            r = mid;
        else
            l = mid+1;
    }
}

```

```

    }
    return l;
}

void prvSolve(){
    for (int i=1; i<LOG; i++){
        for (int j=1; j<sID; j++){
            fa[i][j] = fa[i-1][fa[i-1][j]];
        }
    }
    suffix_array();
    for (int i=0; i<30; i++){
        azRange[i] = MP(sID,0);
    }
    for (int i=1; i<sID; i++){
        if (sa[i] == 1) continue;
        int ch = sCh[sa[i]] - 'a';
        azRange[ch].F = min(azRange[ch].F,i);
        azRange[ch].S = max(azRange[ch].S,i);
    }
    for (int i=0; i<30; i++){
        azRange[i].S++;
        if (azRange[i].S == 1){
            azRange[i].F = azRange[i].S = sID;
        }
    }

    tTree[1].len = 0;
    tTree[1].l = 1;
    tTree[1].r = sID;
    for (int i=2; i<tID; i++){
        int id1 = tTree[i].prvID;
        int id2 = tTree[i].prvID2;
        if (tTree[i].tp == 0){
            tTree[i].len = tTree[id1].len + 1;
            int up = tTree[id1].len;
            char ch = tTree[i].ch;
            int l,r;
            l = tTree[id1].l;
            r = tTree[id1].r;
            if (l == r){
                tTree[i].l = tTree[i].r = l;
            } else {
                while (l < r){
                    int mid = (l+r)/2;
                    int id = moveUP(sa[mid],up);
                    if (ch <= sCh[id])
                        r = mid;
                    else
                        l = mid+1;
                }
                tTree[i].l = l;
            }

            l = tTree[id1].l;
            r = tTree[id1].r;
            while (l < r){
                int mid = (l+r)/2;
                int id = moveUP(sa[mid],up);
                if (ch < sCh[id])
                    r = mid;
                else
                    l = mid+1;
            }

            tTree[i].r = r;
        }
        else if (tTree[i].tp == 1){
            tTree[i].len = tTree[id1].len + 1;
            int ch = tTree[i].ch;
            int l = azRange[ch-'a'].F;
            int r = azRange[ch-'a'].S;
            if (id1 == 1){
                tTree[i].l = l;
                tTree[i].r = r;
            } else {
                tTree[i].l = getL(l,r,1,tTree[id1].l);
                tTree[i].r = getR(l,r,1,tTree[id1].r-1);
            }
        }
        else if (tTree[i].tp == 2){
            tTree[i].len = tTree[id1].len + tTree[id2].len;
            tTree[i].len = min(tTree[i].len,100005);
            if (tTree[i].len < 100000){
                int up = tTree[id2].len;
                int l = tTree[id2].l;
            }
        }
    }
}

```

```

        int r = tTree[id2].r;
        tTree[i].l = getL(l,r,up,tTree[id1].l);
        tTree[i].r = getR(l,r,up,tTree[id1].r-1);
    } else {
        tTree[i].l = tTree[i].r = sID-1;
    }
}
}
}
int bit[MXN];
int lb(int a){ return a & -a; }
void update(int st, int v){
    for (int i=st; i<sID; i+=lb(i))
        bit[i] += v;
}
int query(int st){
    int res = 0;
    for (int i=st; i>0; i-=lb(i))
        res += bit[i];
    return res;
}
void DFS(int u){
    update(rk[u],1);
    FOR(it,q[u]){
        int id = it->ti;
        if (tTree[id].len == 0 || tTree[id].len > 100000)
            ans[it->id] = 0;
        else
            ans[it->id] = query(tTree[id].r-1) - query(tTree[
                id].l-1);
    }
    FOR(it,E[u])
        DFS(*it);
    update(rk[u],-1);
}
void solve(){
    DFS(1);
    for (int i=0; i<nq; i++)
        printf("%d\n", ans[i]);
}
int main(){
    input();
    prvSolve();
    solve();

    return 0;
}

```