

ORACLE

# E-Business Suite Database Migration using XTTS

Sanjit Behera  
Oracle Cloud Lift Services


Copyright © 2023, Oracle and/or its affiliates | Public



# Architecture

High level steps for Full XTTS

## Transportable Tablespace Procedure



## Introduction

- ❑ XTTS stands for cross platform transportable tablespace.
- ✓ This presentation covers the steps needed to use Cross Platform Transportable Tablespaces using XTTS scripts with RMAN incremental backups to migrate data between systems that have different endian formats.
- ✓ We can use XTTS in 2 ways:
  - a. Full XTTS
  - b. Incremental XTTS
- ✓ Full XTTS
  - Copy all datafiles from the source to the destination in downtime mode.
  - Export metadata in source instance.
  - Convert the endian formats in target instance.
  - Import the metadata in target instance.
- ✓ Incremental XTTS
  - Take Level0 (L0) backup and copy to the destination.
  - Keep series of incremental backups.
  - Take final backups during downtime.
  - Export metadata in source instance with same final backup downtime.
  - Restore L0, apply incremental backups including final backup.
  - Import the metadata in target instance.

## Pre-requisites

- ✓ The source database must be in ARCHIVELOG mode.
- ✓ Minimum version for source and destination is 11.2.0.4.
- ✓ The Oracle version of source must be lower or equal to destination.
- ✓ This method does NOT support Windows as either source or destination.
- ✓ The source database's COMPATIBLE parameter must not be greater than the destination database's COMPATIBLE parameter.
- ✓ RMAN on the source system must not have default channel configured to type SBT.
- ✓ RMAN on the source system must not have DEVICE TYPE DISK configured with COMPRESSED.
- ✓ RMAN on the source system must not have BACKUP TYPE TO COPY. The source must have BACKUP TYPE TO BACKUPSET.

## Incremental XTTS Steps

### 1. Initial setup

- a. Provision the target database.
- b. In source Identify tablespaces to be transported and check, fix the violations.
- c. Install xttconvert scripts on the source system.
- d. Create necessary directories and configure xtt.properties on the source system.

### 2. Prepare phase (source data remains online)

- a. Run the backup on the source system.
- b. Transfer the backup and xtt script files to the destination system.
- c. Restore the datafiles on the destination system

### 3. Roll Forward phase (source data remains online)

- a. Create an incremental backup.
- b. Transfer incremental backups and res.txt to the destination system.
- c. Apply the incremental backup to the datafile copies on the destination system.
- d. Repeat this phase as many times as necessary.

## Incremental XTTS Steps

### 4. Transport phase (source data is READ ONLY)

- a. Alter source tablespace(s) to READ ONLY in the source database.
- b. Create the final incremental backup of the tablespaces being transported on the source system.
- c. Transfer incremental backups and res.txt to the destination system.
- d. Apply last incremental backup to destination datafiles.

### 5. Run metadata export

- a. Run datapump export on source database.
- b. Transfer the export files to destination server.
- c. Run datapump import on destination server.

## References

- V4 Reduce Transportable Tablespace Downtime using Cross Platform Incremental Backup (Doc ID 2471245.1).
- Oracle E-Business Suite 12.2 Platform Migration from On-Premises to Oracle Cloud Using Transportable Tablespaces with Oracle Database 19c (Doc ID 2725558.1) .
- Oracle E-Business Suite 12.1 Platform Migration from On-Premises to Oracle Cloud Using Transportable Tablespaces with Oracle Database 19c (Doc ID 2725557.1).





# Thank You