



**Rossmoyne Senior High School**

**Semester 1 examination, 2021**

**Question/Answer booklet**

# PHYSICS

## UNIT 1

Please place your student identification label in this box

Student number:

In figures

--	--

--	--	--

--	--	--

In words

---

---

**Circle teacher's name:**

**Cooper**

**Mahabeer**

**Shashikumar**

### Time allowed for this paper

Reading time before commencing work:

ten minutes

Working time:

two hours, 30 minutes

### Materials required/recommended for this paper

*To be provided by the supervisor*

This Question/Answer booklet

Number of additional  
answer booklets used  
(if applicable)

--

### ***To be provided by the candidate***

Standard items: pens (blue/black preferred), pencils (including coloured),  
sharpener, correction fluid/tape, eraser, ruler, highlighters

Special items: up to three non-programmable calculators approved for use in the WACE  
examinations, protractor.

### Important note to candidates

No other items may be taken into the examination room. It is **your** responsibility to ensure that you do not have any unauthorised material. If you have any unauthorised material with you, hand it to the supervisor **before** reading any further.

**STRUCTURE OF THIS PAPER**

Section	Questions	Questions to be attempted	Suggested working time (mins)	Marks available	Percentage of exam
Section One: Short Response	8	8	45	45	30%
Section Two: Problem Solving	6	6	75	75	50%
Section Three: Comprehension	2	2	30	30	20%
Total				<b>150</b>	<b>100</b>

**INSTRUCTIONS TO CANDIDATES**

1. Write your answers in the spaces provided beneath each question. The value of each question is shown following each question.
2. Answers to questions involving calculations should be evaluated and given in decimal form. Final answers should be given to three significant figures and include appropriate units.
3. Questions containing the instruction "**ESTIMATE**" may give insufficient numerical data for their solution. Give final answers to a maximum of two significant figures and include appropriate units.
4. Despite an incorrect result, credit may be obtained for method and working providing these are clearly and legibly set out.
5. Questions containing specific instructions to **show working** should be answered with a complete, logical, clear sequence of reasoning showing how the final answer was arrived at; correct answers which do not show working will not be awarded full marks.
6. Supplementary pages for the use of planning/continuing your answer to a question have been provided at the end of this Question & Answer booklet. If you use these pages to continue an answer, indicate at the original answer where the answer is continued, i.e. give the page number.
7. Extra/spare graphs have also been provided at the end of this Question & Answer booklet.

---

**Section One: Short Response****30% (45 marks)**

This section has 8 questions. Answer **all** questions. Answer the questions in the spaces provided.  
Suggested working time: 45 minutes.

---

**Question 1****(6 marks)**

A  $1.10 \times 10^3 \text{ W}$  electric water heater has an efficiency,  $\eta = 55.0\%$ . The heater raises the temperature of  $10.0 \text{ kg}$  of water from  $20.0^\circ\text{C}$  to  $75.0^\circ\text{C}$ . Calculate the time (in seconds) taken for the electric water heater to complete this task. Show working.

**Question 2****(5 marks)**

A  $135 \text{ g}$  block of aluminium is heated in an oven and placed into an insulated vessel containing  $1.10 \text{ kg}$  of water at  $19.0^\circ\text{C}$ . The final temperature of the aluminium and water mixture was  $35.0^\circ\text{C}$  when they reached thermal equilibrium. Assuming no water boils off, calculate the initial temperature of the aluminium block.

$$C_{\text{AL}} = 900 \text{ J kg}^{-1} \text{ K}^{-1}$$

$$C_{\text{water}} = 4180 \text{ J kg}^{-1} \text{ K}^{-1}$$

**Question 3****(7 marks)**


General power outlets have three points that contact the plug attached to the electrical appliance.

- a) State the potential difference between:  
(3 marks)

Live and neutral: \_\_\_\_\_

Neutral and Earth: \_\_\_\_\_

Earth and Live: \_\_\_\_\_



Fuses are being phased out of household use and being replaced by circuit breakers that perform the same function.



- b) Provide one of the benefits of a circuit breaker over a fuse.

**(1 mark)**


---



---



---



---

The electrical panel in the workshop also has an earth wire leading from all circuits to a long metal rod that is inserted deep into the ground outside the building.



- c) State which hazard this protects the consumer from and explain why a fuse or a circuit breaker cannot protect from this hazard.

**(3 marks)**


---



---



---



---



---




---

### Question 4

**(4 marks)**

Some students conducted an experiment examining methods of heat transfer using the equipment shown below. A glass tube has all air evacuated from its interior creating a vacuum within it. A copper tube filled with water is placed inside the glass tube. The students touch a copper bulb located at the top of the copper tube and notice that after a certain time, it starts to get hotter.



Explain each of the heating processes that occur within the apparatus that cause the students to detect an increase in temperature in the copper bulb.

[illegible]

**Question 5****(7 marks)**

You are provided with four resistors, each of  $2.00\ \Omega$ . Show how to connect them to produce an effective resistance of  $5.00\ \Omega$ .

- a) Draw in the space below, so that points A and B are at either end of the effective resistance. Label the resistors in your diagram R1, R2, R3 ....etc.

**(3 marks)**

The resistor network you have drawn is now constructed and connected correctly to a  $9.00\text{V}$  power supply.

- b) Calculate the voltage drop across each of the resistors and write the value in the table below. If you used fewer than five resistors, leave the unused resistor box(es) blank.

**(4 marks)**

Resistor	Voltage drop (V)
R1	
R2	
R3	
R4	

**Question 6****(6 marks)**

Plutonium-239 is a fissile material used in fast-breeder nuclear reactors. One possible fission reaction involving this radioisotope is shown below. The nuclear reaction is incomplete.



- a) Determine the number of neutrons produced by this fission reaction.

(1 mark)

The masses of the particles involved in this fission reaction are in the table below.

<b>Pu-239</b>	<b>239.052163 u</b>
<b>neutron</b>	<b>1.00866 u</b>
<b>Ba-142</b>	<b>141.916343 u</b>
<b>Sr-93</b>	<b>92.91403 u</b>

- b) Calculate the energy released (in Joules) by this fission reaction.

(5 marks)

\_\_\_\_\_ J

**Question 7****(6 marks)**

A family is worried that their electricity bill has risen considerably over the years and decide to modify their home in an effort to reduce their electricity bill. They currently have sixteen 18.0 W halogen globes in the ceiling which have an electrical efficiency of 36.0%. They decide to replace all the globes with 5.00 W energy efficient LEDs. The household determines that, in an average week, the 16 halogen globes each run for 12.0 hours.

- a) Calculate the energy wasted by the halogen globes in one week.

(3 marks)

\_\_\_\_\_ J

- b) Synergy currently charge an average of 32.0 cents per kW h. Calculate how much money the family would save on their electricity bills each year by replacing the halogen globes with the LEDs.

(3 marks)


\$ \_\_\_\_\_



**Question 8****(4 marks)**

A hospital physicist is working with some radioactive materials. As part of the safety procedures required when handling this material, the physicist wears a badge containing film which reacts to the radiation. The film is placed behind a number of windows where different filters can be placed.

The structure of the badge is below:



After working with the material, the film is developed. It is found that the film behind both the uncovered window and the aluminium window have turned black (ie – has been exposed to some radiation and reacted with it). State which type of radiation could cause the film in **only** these areas to turn black. Explain your answer by commenting on the penetrating properties of alpha, beta and gamma radiation.

---

---

---

---

---

---

---

---

---

---


**END OF SECTION ONE**

**Section Two: Problem Solving****50% (75 marks)**

This section contains 6 questions. Answer **all** questions. Answer the questions in the spaces provided. Suggested working time 75 minutes.

**Question 9****(10 marks)**


A thermistor is a device in which resistance varies with temperature. The characteristics of a particular thermistor are shown in the diagram.



- a) Calculate the current in mA that would flow through the thermistor at  $4.00^{\circ}\text{C}$  if the voltage across it were 2.50 V. Express your answer to 3 significant figures.

**(3 marks)**

This thermistor is now used to control the temperature of a freezer unit of a refrigerator. The circuit is shown below. The switch controlling the freezer switches it on when the voltage across the variable resistor  $R$  is equal to (or greater than) 2.00 V. The freezer unit must turn on when the temperature is  $-2.00\text{ }^{\circ}\text{C}$  or higher.



- b) Calculate the total current in mA required to flow through the circuit when the temperature is  $-2.00\text{ }^{\circ}\text{C}$  in order to meet the required voltage across the resistor.


(4 marks)

- c) Calculate the resistance that the variable resistor needs to have in order achieve this current. (If you could not obtain an answer to part (b), you may use  $I_T = 1.10\text{ mA}$ )

(3 marks)

**Question 10****(14 marks)**

A cell in a circuit supplies electrical energy to other components of a circuit. If the cell has internal resistance, some of the electrical energy produced is wasted due to heating inside the cell. The internal resistance in the cell can be treated as a resistor that is in series with rest of the circuit. As the battery's internal resistance increases, it has said to have gone "flat", as it can no longer provide a suitable EMF to the circuit.



An interesting observation is that as the current through the circuit increases, the EMF provided by the battery decreases. Consider a cell connected to a resistance  $R$ . The cell's EMF is  $E$  and its internal resistance is  $R_i$ . Given Ohm's Law, current can be expressed as:

$$E = IR + IR_i$$

So  $IR = E - IR_i$

Or  $V = E - R_i I$

Students conduct an experiment to test the internal resistance of two 1.5 Volt batteries to determine if they are flat or not. They use a variable resistor to vary the total resistance of the circuit and obtain the following values.

Current (A)	Voltage (V)	
	Battery 1	Battery 2
0.00	1.50	1.50
0.20	1.32	1.45
0.40	1.12	1.40
0.60	0.93	1.36
0.80	0.73	1.32
1.00	0.55	1.25

- a) On the graph on the following page, plot a graph of Voltage vs Current for both batteries. A spare grid is provided on the end of this Question/Answer booklet. If you need to use it, cross out this attempt and clearly indicate that you have redrawn it on the spare page.


**(5 marks)**

- b) Calculate the gradient of both graphs.

**(4 marks)**

- c) Determine the internal resistance of both batteries and state which battery is 'flatter'.

**(2 marks)**



- d) Explain why testing the voltage across a flat 1.50 V battery with a voltmeter might display a voltage of 1.50 V even though it is flat.

(3 marks)

**Question 11****(13 marks)**

Radon-222 (half-life 3.83 days) is a naturally occurring inert gaseous isotope of radon that forms from the alpha decay of radium-226 (half-life  $1.6 \times 10^3$  years). Radium-226 is found in many rocks, building materials and buildings. Because radon-222 is a gas and its decay releases tissue-damaging radiation, it can cause lung cancer when inhaled into the lungs over a prolonged period.

- a) Write the equation for the alpha decay of radium-226 to radon-222. (2 marks)
- b) Radon-222 also undergoes alpha decay. Explain why these alpha particles are so much more dangerous to humans than those released by the parent radium. (3 marks)

A sample of radon-222 was measured to have an initial activity of 1.40 kBq.

- c) Calculate the activity of the sample 2.00 weeks later. (3 marks)

Consider a sample of radon that was trapped in a closed room. A 78.0 kg person stayed in the room for eight hours. In that time their lungs, of mass 2.40 kg absorbed energy released by alpha particles equal to 0.160 J.

- d) Determine the absorbed dose this person could receive. (2 marks)

- e) Determine the maximum dose equivalent of this radiation. (2 marks)

The table below describes the approximate physiological effects of different types of dose equivalents


<b>Whole Body Dose (mSv)</b>	<b>Effect</b>
0 – 100	No observable effect
100 – 1000	Slight to moderate decrease in white blood cell counts
350 - 500	Temporary Sterility women; men
1000- 2000	Significant reduction in blood cell counts, brief nausea and vomiting. Rarely fatal.
2000 – 5000	Radiation sickness - Nausea, vomiting, diarrhoea, hair loss, skin rashes, severe blood damage, bone marrow damaged, hemorrhage, fatalities.
<b>Localised Dose</b>	<b>Effect</b>
0 – 100	No observable effect
100 – 300	Decrease in red blood cell count. Inflammation of tissue
300 - 800	Damage to capillaries and smaller blood vessels.
1000- 2000	Significant hemorrhaging of large blood vessels. Significant tissue atrophy
2000 – 5000	Severe damage to tissues, major hemorrhaging, organ and tissue failure.

Table 1: Physiological Effects of Radiation on an Adult Human

- f) State the physiological effects that the person might receive after being in this room for 8 hours. (1 marks)

**Question 12****(16 marks)**

Consider the following complex circuit diagram below:



- a) Show that that the total resistance of the circuit is  $9.83\ \Omega$ .

(5 marks)

- b) Calculate the voltage drop across the  $2.00\ \Omega$  resistor.

(4 marks)



- 
- c) Calculate the current that flows through the  $8.00\ \Omega$  resistor.

(4 marks)

- d) Explain what would happen to the power drawn by the circuit if the  $3.00\ \Omega$  resistor was removed from the circuit.

(3 marks)

**Question 13****(14 marks)**

The radioisotope most widely used in medicine is an isotope of Technetium, Tc-99. It is employed in some 80% of all nuclear medicine procedures. Tc-99 has almost the ideal characteristics for a nuclear medicine scan. These are:

- It has a half-life of 6 hours.
- It mainly emits gamma rays.
- The chemistry of technetium is so versatile it can form tracers by being incorporated into a range of biologically-active substances that ensure it concentrates in the tissue or organ of interest.

Its logistics also favour its use. Technetium generators – a lead pot enclosing a glass tube containing the radioisotope – are supplied to hospitals from the nuclear reactor where the isotopes are made. They contain molybdenum-99 (Mo-99), with a half-life of 66 hours, which progressively decays to Tc-99. The Tc-99 is washed out of the lead pot by saline solution when it is required. After two weeks or less the generator is returned for recharging.

- a) As stated, Tc-99 is gained from the decay of Mo-99 atoms. Identify the type of decay that occurs in Mo-99 by writing a balanced nuclear equation for this transmutation.

(3 marks)

---

---

---

---

- b) Tc-99 mainly emits gamma rays. This also makes it very useful for medical scans. State two (2) reasons for this.

(2 marks)

---

---

---

---

- c) Explain why the half-life of Tc-99 makes it an ideal radioisotope to use for a medical scan.

(2 marks)

---

---

---

---

---

A 50.0 g sample of solid Tc-99 arrives at a hospital.

- d) Calculate the mass of solid, radioactive Tc-99 that remains after 15 hours. Show working.  
(3 marks)

\_\_\_\_\_ kg

- e) Once the mass of a sample of Tc-99 drops below 5.00 g, a new sample of Tc-99 needs to be brought into the hospital. Calculate how long it will take for this sample of Tc-99 to drop below this mass.  
(4 marks)

**Question 14****(18 marks)**

Lead sinkers used in fishing are made by heating masses of the lead to its melting point and then placing it in a mould to achieve the required shape. The lead is then cooled down and solidified by plunging the sinkers into a cool bucket of water.

In one such example of sinker production, 100.0 g of lead is heated to its melting point of 327.5 °C. While it is at this temperature, the lead is moulded into the required shape and then dropped into a bucket of water at 25.0 °C. The mass of the plastic bucket is 800.0 g and it contains 5.00 L of water.

The extra data required to answer the questions that follow is contained in the table below. Other data can be found in the Formulae and Data booklet if required.

<b>Specific heat capacity of lead</b>	<b>130.0 J kg<sup>-1</sup> °C<sup>-1</sup></b>
<b>Latent heat of fusion of lead</b>	<b>22 900 J kg<sup>-1</sup></b>
<b>Specific heat capacity of the plastic bucket</b>	<b>900.0 J kg<sup>-1</sup> °C<sup>-1</sup></b>
<b>Mass of one (1) litre of water</b>	<b>1.00 kg</b>

The lead, water and the plastic bucket reach thermal equilibrium and achieve a final common temperature of 'T'. For parts a) to d), assume no energy is lost to the surroundings.

- a) Show that the quantity of internal energy lost by the lead as it freezes at its melting point is equal to 2290 J.

**(2 marks)**

- b) Derive an expression (in terms of 'T') for the **total** internal energy lost by the lead as it achieves a final temperature of 'T'.

**(3 marks)**


- 
- c) Derive an expression (in terms of 'T') for the **total** internal energy gained by the water and the plastic bucket as they achieve a final temperature of 'T'.  
(4 marks)

- d) Hence, use the expressions you derived in parts b) and c) to show that the final temperature 'T' is approximately 25 °C.  
(3 marks)

In reality, some thermal energy is lost to the atmosphere by the lead/water/plastic bucket system.

- e) Describe the roles that conduction and convection play in transferring heat from the bucket of water to the air above.

(3 marks)



- f) When calculating the final temperature in part d), heat lost to the atmosphere and surroundings was not included. In words, explain the effect that including this energy loss would have had on this final temperature.

(3 marks)

END OF SECTION TWO

**Section Three: Comprehension****20% (30 Marks)**

This section has **2** questions. Answer both questions and write your answers in the spaces provided.

Suggested working time: 30 minutes.

**Question 15****(16 marks)****Nuclear Astrophysics: Nucleosynthesis in the Universe****From Lepine-Szily and Descouvemont (2012)**

The role of nuclear reactions in our Universe is two-fold: the production of energy and the formation of elements – a process called nucleosynthesis.

The idea of energy production in stars occurring through the nuclear fusion of H-1 and H-2 into He-4 was first raised by A.S. Eddington in 1920.

In 1931, Georges Lemaitre, a Belgian Priest and astrophysicist, proposed the idea of the 'Big Bang' (not the name, however, which was suggested later by Fred Hoyle), based on the evident expansion of the Universe: if projected backwards, this expansion suggested that everything began from a very small region in the past.

After the Big Bang, the first generation of stars was formed from Hydrogen and Helium only. Heavier elements necessary for a carbon-based life were produced by nucleosynthesis in stars. Then the elements absolutely essential for life were made in supernova explosions of massive stars. These processes took place on massively long timescales – billions of years.

In 1939, Hans Bethe established which nuclear reactions could be responsible for the production of He-4 from Hydrogen in the stars. He introduced the mechanism of the proton-proton (pp) chain and the Carbon-Nitrogen-Oxygen (CNO) cycle. C-12 itself is produced by a "triple- $\alpha$ " process (three  $\alpha$ -particles combining in two steps to form C-12).


In 1948, Alpher, Bethe and Gamow proposed that ALL elements could be produced during the Big Bang and subsequent star formation through successive neutron captures and photon emissions.

Relevant to this process of nucleosynthesis and energy production is the concept of nuclear binding energies. Let us consider a nucleus made of  $Z$  protons and  $N$  neutrons (where the mass number  $A = Z + N$ ). The binding energy of this nucleus is defined as the energy required to break this nucleus into ' $A$ ' individual nucleons.

How binding energy per nucleon (in MeV) varies against mass number ( $A$ ) is displayed in Figure 1. This graph illustrates some important information about nuclei and their binding energy.

The behaviour of the nuclear binding energy with ' $A$ ' in Figure 1 shows that for  $A < 56$ , binding energy per nucleon is increased as the mass of isotopes increase; or, in other words, by isotopes 'capturing' another nucleon ( $p$  or  $n$ ) or an  $\alpha$ -particle. This is the origin of fusion reactions occurring in stars and fusion reactors.

In contrast, for masses  $A > 56$ , as the mass of isotopes increases, the binding energy per nucleon decreases. Hence, nuclei can increase their binding energy per nucleon by emitting particles. In this region, many nuclei are unstable and emit  $\alpha$ -particles. Spontaneous fission occurs in the uranium region ( $A > 200$ ).



- a) According to the graph in Figure 1, the isotope with the greatest binding energy per nucleon is Fe-56. Use the data in the table below (and information from your Data Booklet) to show that the binding energy per nucleon for Fe-56 is about 8.6 MeV. Show all working.

(4 marks)

PARTICLE	MASS (u)
Fe-56	55.9349375
Proton	1.00727647
Neutron	1.008665



- b) The isotope Fe-56 is situated in a region on the graph at the beginning of this question called the “Region of very stable nuclides”. The radioisotope U-235 is not located in this region.

i. Use Figure 1 to estimate the binding energy per nucleon (in MeV) for U-235.

(1 mark)

\_\_\_\_\_ MeV

- ii. Compare the binding energy per nucleon values for both U-235 and Fe-56. Use this comparison to explain why Fe-56 can be called a ‘stable nuclide’, while U-235 cannot be called this.

(3 marks)

---

---

---

---

---

---

---

- c) Use the information in the article to briefly describe why isotopes in the region with mass numbers such that  **$A < 56$**  are more likely to undergo **fusion**, while those isotopes with mass numbers such that  **$A > 200$**  are more likely to undergo **fission**.

(2 marks)

---

---

---

---

- d) In your own words, describe the process of ‘nucleosynthesis’.

(2 marks)

---

---

---

---

- e) Like many isotopes in the region  $A > 56$ , the radioisotope Ti-205 is an  $\alpha$ -emitter. Write a balanced nuclear equation for this nuclear decay.  
(2 marks)

- f) The article describes the process whereby the important isotope of Carbon, C-12, is produced by a "triple- $\alpha$ " process (ie, three  $\alpha$ -particles combining in two steps to form C-12).  
In the space below, write **two (2)** balanced nuclear equations illustrating the "triple- $\alpha$ " process.  
(2 marks)

**Question 16****(14 marks)****The Space Shuttle's Thermal Protection System**

The Space Shuttle Orbiter was an amazing technological achievement that remained in service for thirty years between 1976 and 2006. It was the world's first reusable spacecraft.

One of the most visible aspects of the Orbiter was its external tiles (seen above as both black and white in colour). These tiles formed part of the Orbiter's Thermal Protection System (TPS), which worked to protect both the spacecraft and its human occupants from the extreme temperatures created by friction during its re-entry into the Earth's atmosphere.

Early vehicles that had to re-enter the Earth's atmosphere used a variety of techniques to avoid combusting. Two examples included heat sinks that absorbed the enormous heat that would have been absorbed by the vehicle itself and ablative materials that actually ignited, burned and charred as they absorbed the heat created by re-entry.

However, none of these early vehicles were reusable. Hence, the materials used to protect these vehicles were rendered essentially unusable after the space flight. Reusable vehicles posed a different challenge. Scientists figured that a combination of metals and ceramic materials could not only withstand but also survive the high temperatures of re-entry.

In the case of the Orbiter, scientists chose the conventional aluminium for the main body due to its low density and light mass. A TPS that essentially coated the main body with a layer of heat resistant materials was then added to the exterior.

The properties of aluminium demanded that the maximum temperature of the Orbiter's structure remained lower than 175 °C. At this temperature, the aluminium begins to soften and its shape can be permanently distorted by the extreme heat. The temperatures experienced by the Orbiter during re-entry were, however, much higher than the melting point of aluminium (660 °C).

During the 1960's, NASA developed a silica-based insulation material (silicon dioxide). NASA designers constructed tiles made from this material to coat the Orbiter's aluminium body.

The part of the Orbiter that experienced the highest temperatures during re-entry was on the underside of its body. This part of the Orbiter was covered with about 20 000 black High-Temperature Reusable Surface Insulation (or HRSI tiles) made from the silica-based insulation material. These tiles experienced maximum surface temperatures of between 650 °C and 1260 °C.

These tiles have very different thermal properties to the aluminium. Some of these are shown in the table below:

	ALUMINIUM	SILICON DIOXIDE
MELTING POINT	660 °C	1710 °C
SPECIFIC HEAT CAPACITY	900 Jkg <sup>-1</sup> °C <sup>-1</sup>	628 Jkg <sup>-1</sup> °C <sup>-1</sup>
THERMAL CONDUCTIVITY	180 Wm <sup>-1</sup> °C <sup>-1</sup>	0.0485 Wm <sup>-1</sup> °C <sup>-1</sup>

As can be seen from the table, the thermal conductivity of silicon dioxide is vastly lower than that of aluminium. Thermal conductivity (often denoted by 'k') refers to the intrinsic ability of a material to transfer heat by conduction. It is also defined as the amount of heat per unit time (ie, Joules per second), per unit area (in square metres) that can be conducted through a flat surface of unit length or thickness of a given material (ie - per metre), the faces of the plate differing by one unit of temperature (per degree Celsius). Thermal conductivity can be calculated using the equation below:

$$k = \frac{Q}{t} \cdot \frac{L}{A (T_2 - T_1)} \quad (1)$$

where: k = thermal conductivity (Wm<sup>-1</sup>°C<sup>-1</sup>)  
 $Q/t$  = rate of flow of thermal energy (W)  
 L = length or thickness of the conducting material (m)  
 A = surface area of the material (m<sup>2</sup>)  
 $T_2 - T_1$  = temperature difference across the length of the material (°C)

- a) Identify **two (2)** thermal properties that materials used as 'heat sinks' would need to have when protecting a spacecraft during re-entry.

(2marks)

---

---

---

---

---

---

---

---

---

---

- b) Use the particle model to describe what is occurring to aluminium as its temperature increases from below  $175\text{ }^{\circ}\text{C}$  to above its melting point of  $660\text{ }^{\circ}\text{C}$ .

(4 marks)

---

---

---

---

---

---

---

---

A typical HRSI tile has the following specifications:

**mass = 1.02 kg; dimensions = 15 cm x 15 cm; thickness = 2.54 cm**

- c) During re-entry, an HRSI tile will typically experience a temperature gradient of  $1260\text{ }^{\circ}\text{C}$  on its exterior to about  $170\text{ }^{\circ}\text{C}$  on its interior. Using equation (1), determine how much heat energy is passed through the tile every second during re-entry.

(4 marks)

- d) A human can hold a HRSI tile in their bare hands even if it has been raised to temperatures similar to those experienced during re-entry. This certainly could not be done with an aluminium object. Using data from the table, explain why. (3 marks)

---

---

---

---

---

---

---

---

- e) The HRSI tiles are black in colour. Explain why this colour also assists with protecting the aluminium Orbiter body from absorbing excessive amounts of heat. (1 mark)

---

---

---

**END OF EXAMINATION**

Supplementary page

Question number: \_\_\_\_\_

Lined area for writing answers, consisting of multiple horizontal lines.

Question number: \_\_\_\_\_



Question number: \_\_\_\_\_


Supplementary page

Question number: \_\_\_\_\_

---

Supplementary graph page

Question number: \_\_\_\_\_



<b>Section</b>	<b>Qu. N°</b>	<b>Marks Available</b>	<b>Your Mark</b>	<b>Section Total</b>	<b>Section as % of Exam</b>
<b>1</b>	<b>1</b>	<b>6</b>		<b>/45</b>	
	<b>2</b>	<b>5</b>			
	<b>3</b>	<b>7</b>			
	<b>4</b>	<b>4</b>			
	<b>5</b>	<b>7</b>			
	<b>6</b>	<b>6</b>			
	<b>7</b>	<b>6</b>			
	<b>8</b>	<b>4</b>			
<b>2</b>	<b>9</b>	<b>10</b>		<b>/75</b>	
	<b>10</b>	<b>14</b>			
	<b>11</b>	<b>13</b>			
	<b>12</b>	<b>16</b>			
	<b>13</b>	<b>14</b>			
	<b>14</b>	<b>18</b>			
<b>3</b>	<b>15</b>	<b>16</b>		<b>/30</b>	
	<b>16</b>	<b>14</b>			
<b>Total</b>				<b>/150</b>	<b>%</b>