

kirloskar
powergen

25 - 58.5 kVA
**CPCBIV+
COMPLIANT**



**BETTER POWER
FOR A**

limitless

T O M O R R O W

**INDIA'S LARGEST
FLEET OF GENSETS**

An aerial photograph showing a dense green forest on the left and a dark blue river on the right, separated by a narrow path. The text is overlaid on the image.

BETTER POWER
FOR A

limitless

T O M O R R O W



A RICH HERITAGE OF OVER A CENTURY OF ENGINEERING EXCELLENCE.

Kirloskar power generating sets prioritize user experience, delivering exceptional features and benefits. Streamlined installation and enhanced dependability to expedited service, reduced maintenance costs, and optimized performance.


Kirloskar Powergen sets itself apart with groundbreaking engineering that establishes new industry benchmarks.

limitless **POTENTIAL, SUSTAINABLE PRACTICES**

Our state-of-the-art manufacturing facility embodies our commitment to sustainable practices. We partner with nature to power the facility itself, transforming waste into valuable resources. This focus on sustainability inspires both our workforce and surrounding communities.

It's here, where cutting-edge technology meets exceptional skills,
that we engineer solutions to empower limitless possibilities.

Discover our Plant with a
QR Code Scan.



25-58.5kVA TECHNICAL SPECIFICATIONS

Prime Rating at rated rpm (as per ISO8528)		kVA	25	30	40	58.5
		kW	20	24	32	46.8
Genset Model		–	KG4-25WS1	KG4-30WS1	KG4-40WS1	KG4-58.5WS
Frequency		Hz	50			
Power Factor		lagging	0.8			
Voltage		V	230 (1Ø) & 415 (3Ø)		415 (3Ø)	
Governing class (As per ISO 8528 Part-V)		–	G2			
DG set Noise level at 1 meter		dBA	<75 (Genset with canopy)			
Fuel tank capacity (Standard DG set)		Ltrs	50	72	100	165
Weight of genset with canopy (approx.)^	Dry	Kg	770	1025	1165	1460
	Wet (w/o fuel)	Kg	780	1040	1180	1485
Overall dimensions of genset ^	Length	mm	2330	2500	2750	2900
	Width	mm	950	950	1050	1100
	Height	mm	1260	1385	1495	1580
Electrical Battery Start in R Voltage		Volts-DC	12			

ENGINE

Engine Model	-	3R550ETA 4G1	3R1190ENA 4G1	3R1190ETA 4G1	4R810ETA 4G1
Rated output	kW	26.5	31	41.1	54.4
(Prime Continuous rating as per ISO8528-1)	HP	36	42	56	74
No. of cylinder	Number	3	3	3	4
Cubic capacity ²	Ltrs	1.65	3.57	3.57	3.24
Bore x Stroke	mm	86 x 94	110 x 125	110 x 125	96 x 112
Rated Speed	RPM	1500			
Aspiration	NA/TC/TA	TA	NA	TA	TA
Lube Oil change period	hrs.	500			
Lube oil Sump Capacity (max)	Ltrs	5.95	7	7	10
Coolant Capacity	Ltrs	4.9	10	8.3	12.7

ALTERNATOR

Insulation Class	-	Class H			
Alternator Efficiency (at 100% load) 0.8 pf**	%	87.9	88.4	87.9	90.8
Max Voltage Dip at Full Load 0.8 pf lag	-	< 20 %	< 16 %	< 16 %	< 20 %
Max Time to build up rated voltage at Rated RPM	-	< 2 sec, provided engine reach the rated speed			

[^] Tolerances Apply

☎ These Weight are for handling & transportation only

** Efficiency of Alternator as per standards IEC60034-1

Notes

Above specifications are subject to change without prior notice due to continuous technical development.

For intermediate ratings, kindly contact nearest Kirloskar office.

For Site Conditions other than standard operating conditions consult Kirloskar Oil Engines for available prime power.



7 Easy steps for a happy Genset Ownership

- Insist on a load-study
- Select the Genset rating as per the load-study and with sufficient margin for future load expansion
- Apply site-selection guidelines carefully
- Insist on installation in line with Kirloskar guidelines
- Ensure adequate size and proper connection of cables
- Understand the Genset operation & maintenance procedures during commissioning
- Follow routine maintenance protocols through authorised Kirloskar service dealers

Genset kVA 25 to 58.5 kVA Features



Prime rating and Stand-by rating

'Prime power' is designed for Unlimited hours, as compared to 'Emergency stand-by' designed for 200 hours in a year. Prime rated Gensets also permit 10% temporary overloading. Users need to carefully select the Genset rating to meet their requirement. Kirloskar offers Prime power as a standard offer. Contact Kirloskar for stand-by ratings.



No replacement to displacement

Engine capacity (cc) plays a vital role in Genset performance. Higher engine capacity leads to a robust and stable Genset performance.

Higher engine capacity also enables the Genset to respond quickly & positively to sudden load additions.



Best Fluid Efficiency (Fuel)

Kirloskar Gensets offer a unique combination of CPCB norm compliance and enhanced fuel efficiency. Across the range, Kirloskar Gensets offer substantial savings in fuel cost.



O2E Series (Optimal Operating Efficiency):

Genset ratings are selected based on the present load and future expansion. Fuel efficiency of most Gensets is optimized at the full rating of the Genset.

In practice, Gensets rarely get loaded to full capacity. Power demand variations across day & night, weekdays & weekends, summer & winter lead to an average 50-70% loading on Gensets.

Considering this practical situation, Kirloskar has extended fuel efficiency optimization from 100%, right up to 50% of rated load.

Combination of best-in-class fuel efficiency & O2E provides a double advantage.




Exhaust gas recirculation (EGR)

EGR is used to reduce NOx emitted by the engine. By recirculating exhaust gases into the engine's cylinder, a percentage of the air is replaced with CO₂.

It is an effective strategy to control NOx (Nitrogen Oxides) Emissions from diesel engines.

Some part of exhaust gas is recirculated in the combustion chamber. Once mixed, the concentration of the oxygen in the fresh air is reduced and the temperature of the fresh air is increased slightly.



Common Rail Direct Injection System (CRDi):

Common rail diesel injection technology, popularly known as CRDi, provides a significant upgrade over traditional mechanical fuel injection systems. CRDi provides precise fuel control, multiple injections, enhanced performance, lower noise and reduced emissions. High pressure common rail system employed on Kirloskar CPCB IV+ Gensets maximizes fuel atomization, delivering a smooth and smoke free performance. Diesel filters with 'A' class filtration are used for CRDi Engines which enhances the filtration efficiency. Common rail fuel injection system will provide a new level of performance, efficiency, and reliability.



Genset Monitoring at Your Finger Tips

Kirloskar gensets are enabled with Kirloskar remote monitoring system which shares Real Time Genset information and location Services. It can be accessed via mobile device or desktop. Kirloskar remote monitoring system also highlights any parameter which needs special attention. These critical indication alerts are sent to user mobile via text message. It also alerts nearest services dealer in case of any emergency break-down.

KRM Desktop Display



**Ask your Dealer for KRM
login details & password**



On Board Diagnostics

Superior uptime. Genset comes with advanced diagnostic capabilities, this coupled with Kirloskar remote monitoring system provides real time monitoring of performance, emission and service critical parameters this helps for early diagnosis to fix the issues before system breakdown.



State of the art Genset Controller

Kirloskar Genset put the command in your hands. Micro-processor based Genset controllers display a host of genset parameters and put all controls at your fingertips.

Monitoring Features:

- Phase Voltages & Currents, Frequency, Genset kVA, kW, kWh, kVAR, Power Factor
- Lube oil Pressure, Engine Temperature, RPM, Run Hours, Number of starts, Fuel Level, Auto / Manual Stop, Battery charge condition, AMF feature

Diagnostic Features:

- Battery charging failure, Over/Under speed, Over Current, Over/Under Voltage, Over kW, Phase Seq., Phase missing, Mains Under voltage, Low fuel level
- Low Lube oil Pressure, High Engine Temperature, Low/High battery voltage, Low Fuel Level, Over Crank protection, Routine maintenance indicator, Genset Test Facility, Mains Frequency

Optional Features:

- Modbus Communication



KG640C Controller



Peace-of-mind Ownership


Kirloskar Gensets have always been preferred for their robust design and reliability over long usage life. Kirloskar range carries the confidence of well-established and proven engine platforms. For compliance to revised CPCB norms, Kirloskar has carefully selected those technologies which not only retain, but enhance Gensets durability and on-site serviceability.

Thus, Kirloskar Gensets offer you many years of trouble-free performance; backed by the assurance of prompt support. Peace-of-mind driven by product reliability and low cost of ownership.



Alternator Features

Kirloskar Alternator is compact in design, rugged and best in class efficiency. Advanced Digital AVR improves the Voltage regulation and Response time.



Compact footprint

Kirloskar CPCB compliant Gensets are having compact footprint which results in space saving. CPCB compliant technology is upgraded by maintaining the compact footprint of Genset.

Anubandhan IV⁺

Unlock complete care for your CPCB IV+ Diesel Genset



Refuel and Relax

Complete coverage for 5 years or 6000 hours[#]



Complete Range of Gensets

All-inclusive maintenance for gensets from 7.5 to 750 kVA



Optimised (TCO) Cost of Ownership

Considerable savings in maintenance cost over the period of 5 years



24x7 Support

Dependable 24x7 support for prompt resolution of breakdowns and major issues



Flexibility of Subscription

Customized package available at pre-commissioning & post-commissioning of genset



Customised Package

Packages designed as per genset running hours



One-Time Payment

Covers all services and spares for your DG set



Assured Genuine Spares and Services

Usage of Genuine Kirloskar spares serviced by Trained and Certified engineers.

[#] Whichever is earlier




5 YEARS

Extended Warranty^{*}

For 5 critical spare parts

^{*}Condition Apply

Glimpses **CPCB IV+** Genset (25-58.5 kVA)





SHAPING THE FUTURE.
DELIVERING POWER TO OVER 50+ COUNTRIES.

INGENIOUS DESIGN.
UNMATCHED PERFORMANCE.

KIRLOSKAR OIL ENGINES LIMITED
A Kirloskar Group Company

Regd. Office: 13, Laxmanrao Kirloskar Road,
Khadki, Pune, Maharashtra 411 003
INDIA



BETTER POWER
FOR A

limitless
T O M O R R O W



Tel: +91 (20) 2581 0341
Fax: +91 (20) 2581 3208, 2581 0209
Helpline: +91 8806 33 44 33
koel.sales@kirloskar.com

Stamp of
Authorised
Representative

Marks "Kirloskar" along with the suffix, or prefix, "I" as shown and copyright "limitless" are owned Kirloskar Proprietary Limited. and Kirloskar Oil Engines Ltd. is the Permitted User. This Catalog is copyrighted and may not be reproduced in any form not even parts of it, without previous written permission by copyright owners, Kirloskar Oil Engines Ltd. Product improvement is a continuous process. Kindly contact Kirloskar Oil Engines Ltd. for latest information. Images are for illustration purposes only.