

Physics-Informed Neural Networks: A Deep Learning Framework for Solving Forward and Inverse Problems Involving Nonlinear Partial Differential Equations

M. Raissi¹, P. Perdikaris² and G.E. Karniadakis¹

¹*Division of Applied Mathematics, Brown University,
Providence, RI, 02912, USA*

²*Department of Mechanical Engineering and Applied Mechanics,
University of Pennsylvania,
Philadelphia, PA, 19104, USA*

Abstract

We introduce *physics-informed neural networks* – neural networks that are trained to solve supervised learning tasks while respecting any given laws of physics described by general nonlinear partial differential equations. In this work, we present our developments in the context of solving two main classes of problems: data-driven solution and data-driven discovery of partial differential equations. Depending on the nature and arrangement of the available data, we devise two distinct types of algorithms, namely continuous time and discrete time models. The first type of models forms a new family of *data-efficient* spatio-temporal function approximators, while the latter type allows the use of arbitrarily accurate implicit Runge-Kutta time stepping schemes with unlimited number of stages. The effectiveness of the proposed framework is demonstrated through a collection of classical problems in fluids, quantum mechanics, reaction-diffusion systems, and the propagation of nonlinear shallow-water waves.

Keywords: Data-driven scientific computing, Machine learning, Predictive modeling, Runge-Kutta methods, Nonlinear dynamics

1. Introduction

With the explosive growth of available data and computing resources, recent advances in machine learning and data analytics have yielded trans-

Preprint submitted to Journal of Computational Physics

October 26, 2018

4 formative results across diverse scientific disciplines, including image recog-
5 nition [1], cognitive science [2], and genomics [3]. However, more often than
6 not, in the course of analyzing complex physical, biological or engineering
7 systems, the cost of data acquisition is prohibitive, and we are inevitably
8 faced with the challenge of drawing conclusions and making decisions under
9 partial information. In this *small data* regime, the vast majority of state-
10 of-the-art machine learning techniques (e.g., deep/convolutional/recurrent
11 neural networks) are lacking robustness and fail to provide any guarantees
12 of convergence.

13
14 At first sight, the task of training a deep learning algorithm to accurately
15 identify a nonlinear map from a few – potentially very high-dimensional –
16 input and output data pairs seems at best naive. Coming to our rescue, for
17 many cases pertaining to the modeling of physical and biological systems,
18 there exists a vast amount of prior knowledge that is currently not being uti-
19 lized in modern machine learning practice. Let it be the principled physical
20 laws that govern the time-dependent dynamics of a system, or some empir-
21 ically validated rules or other domain expertise, this prior information can
22 act as a regularization agent that constrains the space of admissible solutions
23 to a manageable size (e.g., in incompressible fluid dynamics problems by dis-
24 carding any non realistic flow solutions that violate the conservation of mass
25 principle). In return, encoding such structured information into a learning
26 algorithm results in amplifying the information content of the data that the
27 algorithm sees, enabling it to quickly steer itself towards the right solution
28 and generalize well even when only a few training examples are available.

29
30 The first glimpses of promise for exploiting structured prior information to
31 construct data-efficient and physics-informed learning machines have already
32 been showcased in the recent studies of [4–6]. There, the authors employed
33 Gaussian process regression [7] to devise functional representations that are
34 tailored to a given linear operator, and were able to accurately infer solu-
35 tions and provide uncertainty estimates for several prototype problems in
36 mathematical physics. Extensions to nonlinear problems were proposed in
37 subsequent studies by Raissi *et. al.* [8, 9] in the context of both inference and
38 systems identification. Despite the flexibility and mathematical elegance of
39 Gaussian processes in encoding prior information, the treatment of nonlinear
40 problems introduces two important limitations. First, in [8, 9] the authors
41 had to locally linearize any nonlinear terms in time, thus limiting the applica-

bility of the proposed methods to discrete-time domains and compromising the accuracy of their predictions in strongly nonlinear regimes. Secondly, the Bayesian nature of Gaussian process regression requires certain prior assumptions that may limit the representation capacity of the model and give rise to robustness/brittleness issues, especially for nonlinear problems [10].

2. Problem setup

In this work we take a different approach by employing deep neural networks and leverage their well known capability as universal function approximators [11]. In this setting, we can directly tackle nonlinear problems without the need for committing to any prior assumptions, linearization, or local time-stepping. We exploit recent developments in automatic differentiation [12] – one of the most useful but perhaps under-utilized techniques in scientific computing – to differentiate neural networks with respect to their input coordinates and model parameters to obtain *physics-informed neural networks*. Such neural networks are constrained to respect any symmetries, invariances, or conservation principles originating from the physical laws that govern the observed data, as modeled by general time-dependent and nonlinear partial differential equations. This simple yet powerful construction allows us to tackle a wide range of problems in computational science and introduces a potentially transformative technology leading to the development of new data-efficient and physics-informed learning machines, new classes of numerical solvers for partial differential equations, as well as new data-driven approaches for model inversion and systems identification.

The general aim of this work is to set the foundations for a new paradigm in modeling and computation that enriches deep learning with the long-standing developments in mathematical physics. To this end, our manuscript is divided into two parts that aim to present our developments in the context of two major classes of problems: data-driven solution and data-driven discovery of partial differential equations. All code and data-sets accompanying this manuscript are available on GitHub at <https://github.com/maziarraissi/PINNs>. Throughout this work we have been using relatively simple deep feed-forward neural networks architectures with hyperbolic tangent activation functions and no additional regularization (e.g., L1/L2 penalties, dropout, etc.). Each numerical example in the manuscript is accompanied with a detailed discussion about the neural network architecture we

employed as well as details about its training process (e.g. optimizer, learning rates, etc.). Finally, a comprehensive series of systematic studies that aims to demonstrate the performance of the proposed methods is provided in Appendix A and Appendix B.

In this work, we consider parametrized and nonlinear partial differential equations of the general form

$$u_t + \mathcal{N}[u; \lambda] = 0, \quad x \in \Omega, \quad t \in [0, T], \quad (1)$$

where $u(t, x)$ denotes the latent (hidden) solution, $\mathcal{N}[\cdot; \lambda]$ is a nonlinear operator parametrized by λ , and Ω is a subset of $\mathbb{R}^D$. This setup encapsulates a wide range of problems in mathematical physics including conservation laws, diffusion processes, advection-diffusion-reaction systems, and kinetic equations. As a motivating example, the one dimensional Burgers equation [13] corresponds to the case where $\mathcal{N}[u; \lambda] = \lambda_1 uu_x - \lambda_2 u_{xx}$ and $\lambda = (\lambda_1, \lambda_2)$. Here, the subscripts denote partial differentiation in either time or space. Given noisy measurements of the system, we are interested in the solution of two distinct problems. The first problem is that of inference, filtering and smoothing, or data-driven solutions of partial differential equations [4, 8] which states: *given fixed model parameters λ what can be said about the unknown hidden state $u(t, x)$ of the system?* The second problem is that of learning, system identification, or data-driven discovery of partial differential equations [5, 9, 14] stating: *what are the parameters λ that best describe the observed data?*

3. Data-driven solutions of partial differential equations

Let us start by concentrating on the problem of computing data-driven solutions to partial differential equations (i.e., the first problem outlined above) of the general form

$$u_t + \mathcal{N}[u] = 0, \quad x \in \Omega, \quad t \in [0, T], \quad (2)$$

where $u(t, x)$ denotes the latent (hidden) solution, $\mathcal{N}[\cdot]$ is a nonlinear differential operator, and Ω is a subset of $\mathbb{R}^D$. In sections 3.1 and 3.2, we put forth two distinct types of algorithms, namely continuous and discrete time models, and highlight their properties and performance through the lens of different benchmark problems. In the second part of our study (see section 4), we shift our attention to the problem of data-driven discovery of partial differential equations [5, 9, 14].

111 3.1. Continuous Time Models

112 We define $f(t, x)$ to be given by the left-hand-side of equation (2); i.e.,

$$f := u_t + \mathcal{N}[u], \quad (3)$$

113 and proceed by approximating $u(t, x)$ by a deep neural network. This as-
 114 sumption along with equation (3) result in a *physics-informed neural net-*
 115 *work* $f(t, x)$. This network can be derived by applying the chain rule for
 116 differentiating compositions of functions using automatic differentiation [12],
 117 and has the same parameters as the network representing $u(t, x)$, albeit with
 118 different activation functions due to the action of the differential operator
 119 $\mathcal{N}$. The shared parameters between the neural networks $u(t, x)$ and $f(t, x)$
 120 can be learned by minimizing the mean squared error loss

$$MSE = MSE_u + MSE_f, \quad (4)$$

121 where

$$MSE_u = \frac{1}{N_u} \sum_{i=1}^{N_u} |u(t_u^i, x_u^i) - u^i|^2,$$

122 and

$$MSE_f = \frac{1}{N_f} \sum_{i=1}^{N_f} |f(t_f^i, x_f^i)|^2.$$

123 Here, $\{t_u^i, x_u^i, u^i\}_{i=1}^{N_u}$ denote the initial and boundary training data on $u(t, x)$
 124 and $\{t_f^i, x_f^i\}_{i=1}^{N_f}$ specify the collocations points for $f(t, x)$. The loss MSE_u
 125 corresponds to the initial and boundary data while MSE_f enforces the struc-
 126 ture imposed by equation (2) at a finite set of collocation points. Although
 127 similar ideas for constraining neural networks using physical laws have been
 128 explored in previous studies [15, 16], here we revisit them using modern
 129 computational tools, and apply them to more challenging dynamic problems
 130 described by time-dependent nonlinear partial differential equations.

131

132 Here, we should underline an important distinction between this line of
 133 work and existing approaches in the literature that elaborate on the use of
 134 machine learning in computational physics. The term *physics-informed ma-*
 135 *chine learning* has been also recently used by Wang *et. al.* [17] in the context
 136 of turbulence modeling. Other examples of machine learning approaches for
 137 predictive modeling of physical systems include [18–29]. All these approaches

138 employ machine learning algorithms like support vector machines, random
 139 forests, Gaussian processes, and feed-forward/convolutional/recurrent neural
 140 networks merely as *black-box* tools. As described above, the proposed work
 141 aims to go one step further by revisiting the construction of “custom” activa-
 142 tion and loss functions that are tailored to the underlying differential opera-
 143 tor. This allows us to open the black-box by understanding and appreciating
 144 the key role played by automatic differentiation within the deep learning field.
 145 Automatic differentiation in general, and the back-propagation algorithm in
 146 particular, is currently the dominant approach for training deep models by
 147 taking their derivatives with respect to the parameters (e.g., weights and
 148 biases) of the models. Here, we use the exact same automatic differentiation
 149 techniques, employed by the deep learning community, to physics-inform
 150 neural networks by taking their derivatives with respect to their input co-
 151 ordinates (i.e., space and time) where the physics is described by partial
 152 differential equations. We have empirically observed that this structured ap-
 153 proach introduces a regularization mechanism that allows us to use relatively
 154 simple feed-forward neural network architectures and train them with small
 155 amounts of data. The effectiveness of this simple idea may be related to
 156 the remarks put forth by Lin, Tegmark and Rolnick [30] and raises many
 157 interesting questions to be quantitatively addressed in future research. To
 158 this end, the proposed work draws inspiration from the early contributions of
 159 Psychogios and Ungar [16], Lagaris *et. al.* [15], as well as the contemporary
 160 works of Kondor [31, 32], Hirn [33], and Mallat [34].

161
 162 In all cases pertaining to data-driven solution of partial differential equa-
 163 tions, the total number of training data N_u is relatively small (a few hundred
 164 up to a few thousand points), and we chose to optimize all loss functions using
 165 L-BFGS, a quasi-Newton, full-batch gradient-based optimization algorithm
 166 [35]. For larger data-sets, such as the data-driven model discovery examples
 167 discussed in section 4, a more computationally efficient mini-batch setting can
 168 be readily employed using stochastic gradient descent and its modern vari-
 169 ants [36, 37]. Despite the fact that there is no theoretical guarantee that this
 170 procedure converges to a global minimum, our empirical evidence indicates
 171 that, if the given partial differential equation is well-posed and its solution is
 172 unique, our method is capable of achieving good prediction accuracy given
 173 a sufficiently expressive neural network architecture and a sufficient num-
 174 ber of collocation points N_f . This general observation deeply relates to the
 175 resulting optimization landscape induced by the mean square error loss of

176 equation 4, and defines an open question for research that is in sync with
 177 recent theoretical developments in deep learning [38, 39]. To this end, we
 178 will test the robustness of the proposed methodology using a series of sys-
 179 tematic sensitivity studies that are provided in Appendix A and Appendix B.
 180

181 3.1.1. Example (Schrödinger Equation)

182 This example aims to highlight the ability of our method to handle pe-
 183 riodic boundary conditions, complex-valued solutions, as well as different
 184 types of nonlinearities in the governing partial differential equations. The
 185 one-dimensional nonlinear Schrödinger equation is a classical field equation
 186 that is used to study quantum mechanical systems, including nonlinear wave
 187 propagation in optical fibers and/or waveguides, Bose-Einstein condensates,
 188 and plasma waves. In optics, the nonlinear term arises from the intensity
 189 dependent index of refraction of a given material. Similarly, the nonlinear
 190 term for Bose-Einstein condensates is a result of the mean-field interactions
 191 of an interacting, N-body system. The nonlinear Schrödinger equation along
 192 with periodic boundary conditions is given by

$$\begin{aligned} ih_t + 0.5h_{xx} + |h|^2h &= 0, \quad x \in [-5, 5], \quad t \in [0, \pi/2], \\ h(0, x) &= 2 \operatorname{sech}(x), \\ h(t, -5) &= h(t, 5), \\ h_x(t, -5) &= h_x(t, 5), \end{aligned} \quad (5)$$

193 where $h(t, x)$ is the complex-valued solution. Let us define $f(t, x)$ to be given
 194 by

$$f := ih_t + 0.5h_{xx} + |h|^2h,$$

195 and proceed by placing a complex-valued neural network prior on $h(t, x)$.
 196 In fact, if u denotes the real part of h and v is the imaginary part, we
 197 are placing a multi-out neural network prior on $h(t, x) = [u(t, x) \ v(t, x)]$.
 198 This will result in the complex-valued (multi-output) *physic-informed neural*
 199 *network* $f(t, x)$. The shared parameters of the neural networks $h(t, x)$ and
 200 $f(t, x)$ can be learned by minimizing the mean squared error loss

$$MSE = MSE_0 + MSE_b + MSE_f, \quad (6)$$

201 where

$$MSE_0 = \frac{1}{N_0} \sum_{i=1}^{N_0} |h(0, x_0^i) - h_0^i|^2,$$

202

$$MSE_b = \frac{1}{N_b} \sum_{i=1}^{N_b} (|h^i(t_b^i, -5) - h^i(t_b^i, 5)|^2 + |h_x^i(t_b^i, -5) - h_x^i(t_b^i, 5)|^2),$$

203 and

$$MSE_f = \frac{1}{N_f} \sum_{i=1}^{N_f} |f(t_f^i, x_f^i)|^2.$$

204 Here, $\{x_0^i, h_0^i\}_{i=1}^{N_0}$ denotes the initial data, $\{t_b^i\}_{i=1}^{N_b}$ corresponds to the collocation
 205 points on the boundary, and $\{t_f^i, x_f^i\}_{i=1}^{N_f}$ represents the collocation points
 206 on $f(t, x)$. Consequently, MSE_0 corresponds to the loss on the initial data,
 207 MSE_b enforces the periodic boundary conditions, and MSE_f penalizes the
 208 Schrödinger equation not being satisfied on the collocation points.

209

210 In order to assess the accuracy of our method, we have simulated equation
 211 (5) using conventional spectral methods to create a high-resolution data set.
 212 Specifically, starting from an initial state $h(0, x) = 2 \operatorname{sech}(x)$ and assuming
 213 periodic boundary conditions $h(t, -5) = h(t, 5)$ and $h_x(t, -5) = h_x(t, 5)$, we
 214 have integrated equation (5) up to a final time $t = \pi/2$ using the Chebfun
 215 package [40] with a spectral Fourier discretization with 256 modes and a
 216 fourth-order explicit Runge-Kutta temporal integrator with time-step $\Delta t =$
 217 $\pi/2 \cdot 10^{-6}$. Under our data-driven setting, all we observe are measurements
 218 $\{x_0^i, h_0^i\}_{i=1}^{N_0}$ of the latent function $h(t, x)$ at time $t = 0$. In particular, the train-
 219 ing set consists of a total of $N_0 = 50$ data points on $h(0, x)$ randomly parsed
 220 from the full high-resolution data-set, as well as $N_b = 50$ randomly sampled
 221 collocation points $\{t_b^i\}_{i=1}^{N_b}$ for enforcing the periodic boundaries. Moreover,
 222 we have assumed $N_f = 20,000$ randomly sampled collocation points used
 223 to enforce equation (5) inside the solution domain. All randomly sampled
 224 point locations were generated using a space filling Latin Hypercube Sam-
 225 pling strategy [41].

226

227 Here our goal is to infer the entire spatio-temporal solution $h(t, x)$ of the
 228 Schrödinger equation (5). We chose to jointly represent the latent function
 229 $h(t, x) = [u(t, x) \ v(t, x)]$ using a 5-layer deep neural network with 100 neu-
 230 rons per layer and a hyperbolic tangent activation function. In general, the
 231 neural network should be given sufficient approximation capacity in order to
 232 accommodate the anticipated complexity of $u(t, x)$. **Although more system-**
 233 **atic procedures such as Bayesian optimization [42] can be employed in order**

to fine-tune the design of the neural network, in the absence of theoretical error/convergence estimates, the interplay between the neural architecture/-training procedure and the complexity of the underlying differential equation is still poorly understood. One viable path towards assessing the accuracy of the predicted solution could come by adopting a Bayesian approach and monitoring the variance of the predictive posterior distribution, but this goes beyond the scope of the present work and will be investigated in future studies.

In this example, our setup aims to highlight the robustness of the proposed method with respect to the well known issue of over-fitting. Specifically, the term in MSE_f in equation (6) acts as a regularization mechanism that penalizes solutions that do not satisfy equation (5). Therefore, a key property of *physics-informed neural networks* is that they can be effectively trained using small data sets; a setting often encountered in the study of physical systems for which the cost of data acquisition may be prohibitive. Figure 1 summarizes the results of our experiment. Specifically, the top panel of figure 1 shows the magnitude of the predicted spatio-temporal solution $|h(t, x)| = \sqrt{u^2(t, x) + v^2(t, x)}$, along with the locations of the initial and boundary training data. The resulting prediction error is validated against the test data for this problem, and is measured at $1.97 \cdot 10^{-3}$ in the relative $\mathbb{L}_2$ -norm. A more detailed assessment of the predicted solution is presented in the bottom panel of Figure 1. In particular, we present a comparison between the exact and the predicted solutions at different time instants $t = 0.59, 0.79, 0.98$. Using only a handful of initial data, the *physics-informed neural network* can accurately capture the intricate nonlinear behavior of the Schrödinger equation.

One potential limitation of the continuous time neural network models considered so far stems from the need to use a large number of collocation points N_f in order to enforce physics-informed constraints in the entire spatio-temporal domain. Although this poses no significant issues for problems in one or two spatial dimensions, it may introduce a severe bottleneck in higher dimensional problems, as the total number of collocation points needed to globally enforce a physics-informed constrain (i.e., in our case a partial differential equation) will increase exponentially. Although this limitation could be addressed to some extent using sparse grid or quasi Monte-Carlo sampling schemes [43, 44], in the next section, we put forth a different approach that circumvents the need for collocation points by in-




Figure 1: *Schrödinger equation*: *Top*: Predicted solution $|h(t, x)|$ along with the initial and boundary training data. In addition we are using 20,000 collocation points generated using a Latin Hypercube Sampling strategy. *Bottom*: Comparison of the predicted and exact solutions corresponding to the three temporal snapshots depicted by the dashed vertical lines in the top panel. The relative $\mathbb{L}_2$ error for this case is $1.97 \cdot 10^{-3}$.

272 introducing a more structured neural network representation leveraging the
 273 classical Runge-Kutta time-stepping schemes [45].

274 3.2. Discrete Time Models

275 Let us apply the general form of Runge-Kutta methods with q stages [45]
 276 to equation (2) and obtain

$$\begin{aligned} u^{n+c_i} &= u^n - \Delta t \sum_{j=1}^q a_{ij} \mathcal{N}[u^{n+c_j}], \quad i = 1, \dots, q, \\ u^{n+1} &= u^n - \Delta t \sum_{j=1}^q b_j \mathcal{N}[u^{n+c_j}]. \end{aligned} \quad (7)$$

277 Here, $u^{n+c_j}(x) = u(t^n + c_j \Delta t, x)$ for $j = 1, \dots, q$. This general form en-
 278 capsulates both implicit and explicit time-stepping schemes, depending on
 279 the choice of the parameters $\{a_{ij}, b_j, c_j\}$. Equations (7) can be equivalently

280 expressed as

$$\begin{aligned} u^n &= u_i^n, \quad i = 1, \dots, q, \\ u^n &= u_{q+1}^n, \end{aligned} \tag{8}$$

281 where

$$\begin{aligned} u_i^n &:= u^{n+c_i} + \Delta t \sum_{j=1}^q a_{ij} \mathcal{N}[u^{n+c_j}], \quad i = 1, \dots, q, \\ u_{q+1}^n &:= u^{n+1} + \Delta t \sum_{j=1}^q b_j \mathcal{N}[u^{n+c_j}]. \end{aligned} \tag{9}$$

282 We proceed by placing a multi-output neural network prior on

$$[u^{n+c_1}(x), \dots, u^{n+c_q}(x), u^{n+1}(x)]. \tag{10}$$

283 This prior assumption along with equations (9) result in a *physics-informed*
284 *neural network* that takes x as an input and outputs

$$[u_1^n(x), \dots, u_q^n(x), u_{q+1}^n(x)]. \tag{11}$$

285 3.2.1. Example (Allen-Cahn Equation)

286 This example aims to highlight the ability of the proposed discrete time
287 models to handle different types of nonlinearity in the governing partial dif-
288 ferential equation. To this end, let us consider the Allen-Cahn equation along
289 with periodic boundary conditions

$$\begin{aligned} u_t - 0.0001u_{xx} + 5u^3 - 5u &= 0, \quad x \in [-1, 1], \quad t \in [0, 1], \\ u(0, x) &= x^2 \cos(\pi x), \\ u(t, -1) &= u(t, 1), \\ u_x(t, -1) &= u_x(t, 1). \end{aligned} \tag{12}$$

290 The Allen-Cahn equation is a well-known equation from the area of reaction-
291 diffusion systems. It describes the process of phase separation in multi-
292 component alloy systems, including order-disorder transitions. For the Allen-
293 Cahn equation, the nonlinear operator in equation (9) is given by

$$\mathcal{N}[u^{n+c_j}] = -0.0001u_{xx}^{n+c_j} + 5(u^{n+c_j})^3 - 5u^{n+c_j},$$

294 and the shared parameters of the neural networks (10) and (11) can be
295 learned by minimizing the sum of squared errors

$$SSE = SSE_n + SSE_b, \tag{13}$$

296 where

$$SSE_n = \sum_{j=1}^{q+1} \sum_{i=1}^{N_n} |u_j^n(x^{n,i}) - u^{n,i}|^2,$$

297 and

$$\begin{aligned} SSE_b &= \sum_{i=1}^q |u^{n+c_i}(-1) - u^{n+c_i}(1)|^2 + |u^{n+1}(-1) - u^{n+1}(1)|^2 \\ &+ \sum_{i=1}^q |u_x^{n+c_i}(-1) - u_x^{n+c_i}(1)|^2 + |u_x^{n+1}(-1) - u_x^{n+1}(1)|^2. \end{aligned}$$

298 Here, $\{x^{n,i}, u^{n,i}\}_{i=1}^{N_n}$ corresponds to the data at time-step t^n . In classical nu-
 299 merical analysis, these time-steps are usually confined to be small due to sta-
 300 bility constraints for explicit schemes or computational complexity constrains
 301 for implicit formulations [45]. These constraints become more severe as the
 302 total number of Runge-Kutta stages q is increased, and, for most problems
 303 of practical interest, one needs to take thousands to millions of such steps
 304 until the solution is resolved up to a desired final time. In sharp contrast to
 305 classical methods, here we can employ implicit Runge-Kutta schemes with
 306 an arbitrarily large number of stages at effectively very little extra cost.¹
 307 This enables us to take very large time steps while retaining stability and
 308 high predictive accuracy, therefore allowing us to resolve the entire spatio-
 309 temporal solution in a single step.

310

311 In this example, we have generated a training and test data-set set by
 312 simulating the Allen-Cahn equation (12) using conventional spectral meth-
 313 ods. Specifically, starting from an initial condition $u(0, x) = x^2 \cos(\pi x)$ and
 314 assuming periodic boundary conditions $u(t, -1) = u(t, 1)$ and $u_x(t, -1) =$
 315 $u_x(t, 1)$, we have integrated equation (12) up to a final time $t = 1.0$ using the
 316 Chebfun package [40] with a spectral Fourier discretization with 512 modes
 317 and a fourth-order explicit Runge-Kutta temporal integrator with time-step
 318 $\Delta t = 10^{-5}$.

319

320 Our training data-set consists of $N_n = 200$ initial data points that are
 321 randomly sub-sampled from the exact solution at time $t = 0.1$, and our goal

¹To be precise, it is only the number of parameters in the last layer of the neural network that increases linearly with the total number of stages.

322 is to predict the solution at time $t = 0.9$ using a single time-step with size
 323 $\Delta t = 0.8$. To this end, we employ a discrete time *physics-informed neural*
 324 *network* with 4 hidden layers and 200 neurons per layer, while the output
 325 layer predicts 101 quantities of interest corresponding to the $q = 100$ Runge-
 326 Kutta stages $u^{n+c_i}(x)$, $i = 1, \dots, q$, and the solution at final time $u^{n+1}(x)$.
 327 The theoretical error estimates for this scheme predict a temporal error ac-
 328 cumulation of $\mathcal{O}(\Delta t^{2q})$ [45], which in our case translates into an error way
 329 below machine precision, i.e., $\Delta t^{2q} = 0.8^{200} \approx 10^{-20}$. To our knowledge, this
 330 is the first time that an implicit Runge-Kutta scheme of that high-order has
 331 ever been used. Remarkably, starting from smooth initial data at $t = 0.1$ we
 332 can predict the nearly discontinuous solution at $t = 0.9$ in a single time-step
 333 with a relative $\mathbb{L}_2$ error of $6.99 \cdot 10^{-3}$, as illustrated in Figure 2. This error is
 334 entirely attributed to the neural network’s capacity to approximate $u(t, x)$,
 335 as well as to the degree that the sum of squared errors loss allows interpola-
 336 tion of the training data.

337
 338 The key parameters controlling the performance of our discrete time al-
 339 gorithm are the total number of Runge-Kutta stages q and the time-step
 340 size Δt . As we demonstrate in the systematic studies provided in Appendix
 341 A and Appendix B, low-order methods, such as the case $q = 1$ correspond-
 342 ing to the classical trapezoidal rule, and the case $q = 2$ corresponding to the
 343 4th-order Gauss-Legendre method, cannot retain their predictive accuracy for
 344 large time-steps, thus mandating a solution strategy with multiple time-steps
 345 of small size. On the other hand, the ability to push the number of Runge-
 346 Kutta stages to 32 and even higher allows us to take very large time steps,
 347 and effectively resolve the solution in a single step without sacrificing the
 348 accuracy of our predictions. Moreover, numerical stability is not sacrificed
 349 either as implicit Gauss-Legendre is the only family of time-stepping schemes
 350 that remain A-stable regardless of their order, thus making them ideal for
 351 stiff problems [45]. These properties are unprecedented for an algorithm of
 352 such implementation simplicity, and illustrate one of the key highlights of
 353 our discrete time approach.

354 4. Data-driven discovery of partial differential equations

355 In the current part of our study, we shift our attention to the problem of
 356 data-driven discovery of partial differential equations [5, 9, 14]. In sections 4.1
 357 and 4.2, we put forth two distinct types of algorithms, namely continuous




Figure 2: *Allen-Cahn equation*: *Top*: Solution $u(t, x)$ along with the location of the initial training snapshot at $t = 0.1$ and the final prediction snapshot at $t = 0.9$. *Bottom*: Initial training data and final prediction at the snapshots depicted by the white vertical lines in the top panel. The relative $\mathbb{L}_2$ error for this case is $6.99 \cdot 10^{-3}$.

and discrete time models, and highlight their properties and performance through the lens of various canonical problems.

4.1. Continuous Time Models

Let us recall equation (1) and similar to section 3.1 define $f(t, x)$ to be given by the left-hand-side of equation (1); i.e.,

$$f := u_t + \mathcal{N}[u; \lambda]. \quad (14)$$

We proceed by approximating $u(t, x)$ by a deep neural network. This assumption along with equation (14) result in a *physics-informed neural net*

365 *work* $f(t, x)$. This network can be derived by applying the chain rule for
 366 differentiating compositions of functions using automatic differentiation [12].
 367 It is worth highlighting that the parameters of the differential operator λ
 368 turn into parameters of the *physics-informed neural network* $f(t, x)$.

369 4.1.1. Example (Navier-Stokes Equation)

370 Our next example involves a realistic scenario of incompressible fluid flow
 371 described by the ubiquitous Navier-Stokes equations. Navier-Stokes equa-
 372 tions describe the physics of many phenomena of scientific and engineering
 373 interest. They may be used to model the weather, ocean currents, water flow
 374 in a pipe and air flow around a wing. The Navier-Stokes equations in their
 375 full and simplified forms help with the design of aircrafts and cars, the study
 376 of blood flow, the design of power stations, the analysis of the dispersion of
 377 pollutants, and many other applications. Let us consider the Navier-Stokes
 378 equations in two dimensions² (2D) given explicitly by

$$\begin{aligned} u_t + \lambda_1(uu_x + vu_y) &= -p_x + \lambda_2(u_{xx} + u_{yy}), \\ v_t + \lambda_1(uv_x + vv_y) &= -p_y + \lambda_2(v_{xx} + v_{yy}), \end{aligned} \quad (15)$$

379 where $u(t, x, y)$ denotes the x -component of the velocity field, $v(t, x, y)$ the
 380 y -component, and $p(t, x, y)$ the pressure. Here, $\lambda = (\lambda_1, \lambda_2)$ are the unknown
 381 parameters. Solutions to the Navier-Stokes equations are searched in the set
 382 of divergence-free functions; i.e.,

$$u_x + v_y = 0. \quad (16)$$

383 This extra equation is the continuity equation for incompressible fluids that
 384 describes the conservation of mass of the fluid. We make the assumption
 385 that

$$u = \psi_y, \quad v = -\psi_x, \quad (17)$$

386 for some latent function $\psi(t, x, y)$.³ Under this assumption, the continuity
 387 equation (16) will be automatically satisfied. Given noisy measurements

$$\{t^i, x^i, y^i, u^i, v^i\}_{i=1}^N$$

²It is straightforward to generalize the proposed framework to the Navier-Stokes equations in three dimensions (3D).

³This construction can be generalized to three dimensional problems by employing the notion of vector potentials.

of the velocity field, we are interested in learning the parameters λ as well as the pressure $p(t, x, y)$. We define $f(t, x, y)$ and $g(t, x, y)$ to be given by

$$\begin{aligned} f &:= u_t + \lambda_1(uu_x + vv_y) + p_x - \lambda_2(u_{xx} + u_{yy}), \\ g &:= v_t + \lambda_1(uv_x + vv_y) + p_y - \lambda_2(v_{xx} + v_{yy}), \end{aligned} \quad (18)$$

and proceed by jointly approximating $[\psi(t, x, y) \ p(t, x, y)]$ using a single neural network with two outputs. This prior assumption along with equations (17) and (18) results into a *physics-informed neural network* $[f(t, x, y) \ g(t, x, y)]$. The parameters λ of the Navier-Stokes operator as well as the parameters of the neural networks $[\psi(t, x, y) \ p(t, x, y)]$ and $[f(t, x, y) \ g(t, x, y)]$ can be trained by minimizing the mean squared error loss

$$\begin{aligned} MSE &:= \frac{1}{N} \sum_{i=1}^N (|u(t^i, x^i, y^i) - u^i|^2 + |v(t^i, x^i, y^i) - v^i|^2) \\ &+ \frac{1}{N} \sum_{i=1}^N (|f(t^i, x^i, y^i)|^2 + |g(t^i, x^i, y^i)|^2). \end{aligned} \quad (19)$$

Here we consider the prototype problem of incompressible flow past a circular cylinder; a problem known to exhibit rich dynamic behavior and transitions for different regimes of the Reynolds number $Re = u_\infty D / \nu$. Assuming a non-dimensional free stream velocity $u_\infty = 1$, cylinder diameter $D = 1$, and kinematic viscosity $\nu = 0.01$, the system exhibits a periodic steady state behavior characterized by a asymmetrical vortex shedding pattern in the cylinder wake, known as the Kármán vortex street [46].

To generate a high-resolution data set for this problem we have employed the spectral/*hp*-element solver NekTar [47]. Specifically, the solution domain is discretized in space by a tessellation consisting of 412 triangular elements, and within each element the solution is approximated as a linear combination of a tenth-order hierarchical, semi-orthogonal Jacobi polynomial expansion [47]. We have assumed a uniform free stream velocity profile imposed at the left boundary, a zero pressure outflow condition imposed at the right boundary located 25 diameters downstream of the cylinder, and periodicity for the top and bottom boundaries of the $[-15, 25] \times [-8, 8]$ domain. We integrate equation (15) using a third-order stiffly stable scheme [47] until the system reaches a periodic steady state, as depicted in figure 3(a). In what follows, a small portion of the resulting data-set corresponding to this steady state

416 solution will be used for model training, while the remaining data will be
 417 used to validate our predictions. For simplicity, we have chosen to confine
 418 our sampling in a rectangular region downstream of cylinder as shown in
 419 figure 3(a).

420
 421 Given scattered and potentially noisy data on the stream-wise $u(t, x, y)$
 422 and transverse $v(t, x, y)$ velocity components, our goal is to identify the un-
 423 known parameters λ_1 and λ_2 , as well as to obtain a qualitatively accurate
 424 reconstruction of the entire pressure field $p(t, x, y)$ in the cylinder wake, which
 425 by definition can only be identified up to a constant. To this end, we have
 426 created a training data-set by randomly sub-sampling the full high-resolution
 427 data-set. To highlight the ability of our method to learn from scattered and
 428 scarce training data, we have chosen $N = 5,000$, corresponding to a mere
 429 1% of the total available data as illustrated in figure 3(b). Also plotted are
 430 representative snapshots of the predicted velocity components $u(t, x, y)$ and
 431 $v(t, x, y)$ after the model was trained. The neural network architecture used
 432 here consists of 9 layers with 20 neurons in each layer.

433
 434 A summary of our results for this example is presented in figure 4. We
 435 observe that the *physics-informed neural network* is able to correctly identify
 436 the unknown parameters λ_1 and λ_2 with very high accuracy even when the
 437 training data was corrupted with noise. Specifically, for the case of noise-
 438 free training data, the error in estimating λ_1 and λ_2 is 0.078%, and 4.67%,
 439 respectively. The predictions remain robust even when the training data are
 440 corrupted with 1% uncorrelated Gaussian noise, returning an error of 0.17%,
 441 and 5.70%, for λ_1 and λ_2 , respectively.

442
 443 A more intriguing result stems from the network’s ability to provide a
 444 qualitatively accurate prediction of the entire pressure field $p(t, x, y)$ in the
 445 absence of any training data on the pressure itself. A visual comparison
 446 against the exact pressure solution is presented in figure 4 for a represen-
 447 tative pressure snapshot. Notice that the difference in magnitude between
 448 the exact and the predicted pressure is justified by the very nature of the
 449 *incompressible* Navier-Stokes system, as the pressure field is only identifiable
 450 up to a constant. This result of inferring a continuous quantity of interest
 451 from auxiliary measurements by leveraging the underlying physics is a great
 452 example of the enhanced capabilities that *physics-informed neural networks*
 453 have to offer, and highlights their potential in solving high-dimensional in-




Figure 3: *Navier-Stokes equation*: *Top*: Incompressible flow and dynamic vortex shedding past a circular cylinder at $Re = 100$. The spatio-temporal training data correspond to the depicted rectangular region in the cylinder wake. *Bottom*: Locations of training data-points for the the stream-wise and transverse velocity components, $u(t, x, y)$ and $v(t, x, t)$, respectively.

verse problems.

Our approach so far assumes availability of scattered data throughout the entire spatio-temporal domain. However, in many cases of practical interest, one may only be able to observe the system at distinct time instants. In the next section, we introduce a different approach that tackles the data-driven discovery problem using only two data snapshots. We will see how, by leveraging the classical Runge-Kutta time-stepping schemes, one can construct discrete time *physics-informed neural networks* that can retain high predictive accuracy even when the temporal gap between the data snapshots is very large.




Figure 4: *Navier-Stokes equation*: *Top*: Predicted versus exact instantaneous pressure field $p(t, x, y)$ at a representative time instant. By definition, the pressure can be recovered up to a constant, hence justifying the different magnitude between the two plots. This remarkable qualitative agreement highlights the ability of *physics-informed neural networks* to identify the entire pressure field, despite the fact that no data on the pressure are used during model training. *Bottom*: Correct partial differential equation along with the identified one obtained by learning λ_1, λ_2 and $p(t, x, y)$.

4.2. Discrete Time Models

We begin by applying the general form of Runge-Kutta methods [45] with q stages to equation (1) and obtain

$$\begin{aligned}
 u^{n+c_i} &= u^n - \Delta t \sum_{j=1}^q a_{ij} \mathcal{N}[u^{n+c_j}; \lambda], \quad i = 1, \dots, q, \\
 u^{n+1} &= u^n - \Delta t \sum_{j=1}^q b_j \mathcal{N}[u^{n+c_j}; \lambda].
 \end{aligned} \tag{20}$$

Here, $u^{n+c_j}(x) = u(t^n + c_j \Delta t, x)$ is the hidden state of the system at time $t^n + c_j \Delta t$ for $j = 1, \dots, q$. This general form encapsulates both implicit and explicit time-stepping schemes, depending on the choice of the parameters $\{a_{ij}, b_j, c_j\}$. Equations (20) can be equivalently expressed as

$$\begin{aligned}
 u^n &= u_i^n, \quad i = 1, \dots, q, \\
 u^{n+1} &= u_i^{n+1}, \quad i = 1, \dots, q.
 \end{aligned} \tag{21}$$

472 where

$$\begin{aligned} u_i^n &:= u^{n+c_i} + \Delta t \sum_{j=1}^q a_{ij} \mathcal{N}[u^{n+c_j}; \lambda], \quad i = 1, \dots, q, \\ u_i^{n+1} &:= u^{n+c_i} + \Delta t \sum_{j=1}^q (a_{ij} - b_j) \mathcal{N}[u^{n+c_j}; \lambda], \quad i = 1, \dots, q. \end{aligned} \quad (22)$$

473 We proceed by placing a multi-output neural network prior on

$$[u^{n+c_1}(x), \dots, u^{n+c_q}(x)]. \quad (23)$$

474 This prior assumption along with equations (22) result in two *physics-informed*
475 *neural networks*

$$[u_1^n(x), \dots, u_q^n(x), u_{q+1}^n(x)], \quad (24)$$

476 and

$$[u_1^{n+1}(x), \dots, u_q^{n+1}(x), u_{q+1}^{n+1}(x)]. \quad (25)$$

477 Given noisy measurements at two distinct temporal snapshots $\{\mathbf{x}^n, \mathbf{u}^n\}$ and
478 $\{\mathbf{x}^{n+1}, \mathbf{u}^{n+1}\}$ of the system at times t^n and t^{n+1} , respectively, the shared
479 parameters of the neural networks (23), (24), and (25) along with the pa-
480 rameters λ of the differential operator can be trained by minimizing the sum
481 of squared errors

$$SSE = SSE_n + SSE_{n+1}, \quad (26)$$

482 where

$$SSE_n := \sum_{j=1}^q \sum_{i=1}^{N_n} |u_j^n(x^{n,i}) - u^{n,i}|^2,$$

483 and

$$SSE_{n+1} := \sum_{j=1}^q \sum_{i=1}^{N_{n+1}} |u_j^{n+1}(x^{n+1,i}) - u^{n+1,i}|^2.$$

484 Here, $\mathbf{x}^n = \{x^{n,i}\}_{i=1}^{N_n}$, $\mathbf{u}^n = \{u^{n,i}\}_{i=1}^{N_n}$, $\mathbf{x}^{n+1} = \{x^{n+1,i}\}_{i=1}^{N_{n+1}}$, and $\mathbf{u}^{n+1} =$
485 $\{u^{n+1,i}\}_{i=1}^{N_{n+1}}$.

486 4.2.1. Example (Kortewegde Vries Equation)

487 Our final example aims to highlight the ability of the proposed frame-
488 work to handle governing partial differential equations involving higher or-
489 der derivatives. Here, we consider a mathematical model of waves on shallow
490 water surfaces; the Korteweg-de Vries (KdV) equation. This equation can
491 also be viewed as Burgers equation with an added dispersive term. The KdV

equation has several connections to physical problems. It describes the evolution of long one-dimensional waves in many physical settings. Such physical settings include shallow-water waves with weakly non-linear restoring forces, long internal waves in a density-stratified ocean, ion acoustic waves in a plasma, and acoustic waves on a crystal lattice. Moreover, the KdV equation is the governing equation of the string in the Fermi-Pasta-Ulam problem [48] in the continuum limit. The KdV equation reads as

$$u_t + \lambda_1 u u_x + \lambda_2 u_{xxx} = 0, \quad (27)$$

with (λ_1, λ_2) being the unknown parameters. For the KdV equation, the nonlinear operator in equations (22) is given by

$$\mathcal{N}[u^{n+c_j}] = \lambda_1 u^{n+c_j} u_x^{n+c_j} - \lambda_2 u_{xxx}^{n+c_j}$$

and the shared parameters of the neural networks (23), (24), and (25) along with the parameters $\lambda = (\lambda_1, \lambda_2)$ of the KdV equation can be learned by minimizing the sum of squared errors (26).

To obtain a set of training and test data we simulated (27) using conventional spectral methods. Specifically, starting from an initial condition $u(0, x) = \cos(\pi x)$ and assuming periodic boundary conditions, we have integrated equation (27) up to a final time $t = 1.0$ using the Chebfun package [40] with a spectral Fourier discretization with 512 modes and a fourth-order explicit Runge-Kutta temporal integrator with time-step $\Delta t = 10^{-6}$. Using this data-set, we then extract two solution snapshots at time $t^n = 0.2$ and $t^{n+1} = 0.8$, and randomly sub-sample them using $N_n = 199$ and $N_{n+1} = 201$ to generate a training data-set. We then use these data to train a discrete time *physics-informed neural network* by minimizing the sum of squared error loss of equation (26) using L-BFGS [35]. The network architecture used here comprises of 4 hidden layers, 50 neurons per layer, and an output layer predicting the solution at the q Runge-Kutta stages, i.e., $u^{n+c_j}(x)$, $j = 1, \dots, q$, where q is empirically chosen to yield a temporal error accumulation of the order of machine precision ϵ by setting⁴

$$q = 0.5 \log \epsilon / \log(\Delta t), \quad (28)$$

⁴This is motivated by the theoretical error estimates for implicit Runge-Kutta schemes suggesting a truncation error of $\mathcal{O}(\Delta t^{2q})$ [45].

520 where the time-step for this example is $\Delta t = 0.6$.

521

522 The results of this experiment are summarized in figure 5. In the top
523 panel, we present the exact solution $u(t, x)$, along with the locations of the
524 two data snapshots used for training. A more detailed overview of the exact
525 solution and the training data is given in the middle panel. It is worth notic-
526 ing how the complex nonlinear dynamics of equation (27) causes dramatic
527 differences in the form of the solution between the two reported snapshots.
528 Despite these differences, and the large temporal gap between the two train-
529 ing snapshots, our method is able to correctly identify the unknown param-
530 eters regardless of whether the training data is corrupted with noise or not.
531 Specifically, for the case of noise-free training data, the error in estimating
532 λ_1 and λ_2 is 0.023%, and 0.006%, respectively, while the case with 1% noise
533 in the training data returns errors of 0.057%, and 0.017%, respectively.

534 5. Conclusions

535 We have introduced *physics-informed neural networks*, a new class of
536 universal function approximators that is capable of encoding any underlying
537 physical laws that govern a given data-set, and can be described by par-
538 tial differential equations. In this work, we design data-driven algorithms for
539 inferring solutions to general nonlinear partial differential equations, and con-
540 structing computationally efficient physics-informed surrogate models. The
541 resulting methods showcase a series of promising results for a diverse collec-
542 tion of problems in computational science, and open the path for endowing
543 deep learning with the powerful capacity of mathematical physics to model
544 the world around us. As deep learning technology is continuing to grow
545 rapidly both in terms of methodological and algorithmic developments, we
546 believe that this is a timely contribution that can benefit practitioners across
547 a wide range of scientific domains. Specific applications that can readily en-
548 joy these benefits include, but are not limited to, data-driven forecasting of
549 physical processes, model predictive control, multi-physics/multi-scale mod-
550 eling and simulation.

551

552 We must note however that the proposed methods should not be viewed
553 as replacements of classical numerical methods for solving partial differential
554 equations (e.g., finite elements, spectral methods, etc.). Such methods have
555 matured over the last 50 years and, in many cases, meet the robustness and




Figure 5: *KdV equation*: *Top*: Solution $u(t, x)$ along with the temporal locations of the two training snapshots. *Middle*: Training data and exact solution corresponding to the two temporal snapshots depicted by the dashed vertical lines in the top panel. *Bottom*: Correct partial differential equation along with the identified one obtained by learning λ_1, λ_2 .

556 computational efficiency standards required in practice. Our message here,
557 as advocated in Section 3.2, is that classical methods such as the Runge-
558 Kutta time-stepping schemes can coexist in harmony with deep neural net-
559 works, and offer invaluable intuition in constructing structured predictive

560 algorithms. Moreover, the implementation simplicity of the latter greatly
561 favors rapid development and testing of new ideas, potentially opening the
562 path for a new era in data-driven scientific computing.

563

564 Although a series of promising results was presented, the reader may per-
565 haps agree this work creates more questions than it answers. How deep/wide
566 should the neural network be? How much data is really needed? Why does
567 the algorithm converge to unique values for the parameters of the differen-
568 tial operators, i.e., why is the algorithm not suffering from local optima for
569 the parameters of the differential operator? Does the network suffer from
570 vanishing gradients for deeper architectures and higher order differential op-
571 erators? Could this be mitigated by using different activation functions?
572 Can we improve on initializing the network weights or normalizing the data?
573 Are the mean square error and the sum of squared errors the appropriate
574 loss functions? Why are these methods seemingly so robust to noise in the
575 data? How can we quantify the uncertainty associated with our predictions?
576 Throughout this work, we have attempted to answer some of these questions,
577 but we have observed that specific settings that yielded impressive results for
578 one equation could fail for another. Admittedly, more work is needed collec-
579 tively to set the foundations in this field.

580

581 In a broader context, and along the way of seeking answers to those
582 questions, we believe that this work advocates a fruitful synergy between
583 machine learning and classical computational physics that has the potential
584 to enrich both fields and lead to high-impact developments.

585 Acknowledgements

586 This work received support by the DARPA EQUiPS grant N66001-15-2-
587 4055 and the AFOSR grant FA9550-17-1-0013.

588 Appendix A. Data-driven solution of partial differential equations

589 This Appendix accompanies the main manuscript, and contains a series
590 of systematic studies that aim to demonstrate the performance of the pro-
591 posed algorithms for problems pertaining to *data-driven solution of partial*
592 *differential equations*. Throughout this document, we will use the Burgers’
593 equation as a canonical example.

594 *Appendix A.1. Continuous Time Models*

595 In one space dimension, the Burger's equation along with Dirichlet bound-
596 ary conditions reads as

$$\begin{aligned} u_t + uu_x - (0.01/\pi)u_{xx} &= 0, \quad x \in [-1, 1], \quad t \in [0, 1], \\ u(0, x) &= -\sin(\pi x), \\ u(t, -1) &= u(t, 1) = 0. \end{aligned} \quad (\text{A.1})$$

597 Let us define $f(t, x)$ to be given by

$$f := u_t + uu_x - (0.01/\pi)u_{xx},$$

598 and proceed by approximating $u(t, x)$ by a deep neural network. To highlight
599 the simplicity in implementing this idea we have included a Python code
600 snippet using Tensorflow [49]; currently one of the most popular and well
601 documented open source libraries for machine learning computations. To
602 this end, $u(t, x)$ can be simply defined as

```
603 def u(t, x):
604     u = neural_net(tf.concat([t, x], 1), weights, biases)
605     return u
```

606 Correspondingly, the *physics-informed neural network* $f(t, x)$ takes the form

```
607 def f(t, x):
608     u = u(t, x)
609     u_t = tf.gradients(u, t)[0]
610     u_x = tf.gradients(u, x)[0]
611     u_xx = tf.gradients(u_x, x)[0]
612     f = u_t + u*u_x - (0.01/tf.pi)*u_xx
613     return f
```

614 The shared parameters between the neural networks $u(t, x)$ and $f(t, x)$ can
615 be learned by minimizing the mean squared error loss

$$MSE = MSE_u + MSE_f, \quad (\text{A.2})$$

616 where

$$MSE_u = \frac{1}{N_u} \sum_{i=1}^{N_u} |u(t_u^i, x_u^i) - u^i|^2,$$

617 and

$$MSE_f = \frac{1}{N_f} \sum_{i=1}^{N_f} |f(t_f^i, x_f^i)|^2.$$

618 Here, $\{t_u^i, x_u^i, u^i\}_{i=1}^{N_u}$ denote the initial and boundary training data on $u(t, x)$
 619 and $\{t_f^i, x_f^i\}_{i=1}^{N_f}$ specify the collocations points for $f(t, x)$. The loss MSE_u
 620 corresponds to the initial and boundary data while MSE_f enforces the struc-
 621 ture imposed by equation (A.1) at a finite set of collocation points. Although
 622 similar ideas for constraining neural networks using physical laws have been
 623 explored in previous studies [15, 16], here we revisit them using modern
 624 computational tools, and apply them to more challenging dynamic problems
 625 described by time-dependent nonlinear partial differential equations.

626
 627 The Burgers equation is often considered as a prototype example of a
 628 hyperbolic conservation law (as $\nu \rightarrow 0$). Notice that if we want to “fabri-
 629 cate” an “exact” solution to this equation we would select a solution $u(t, x)$
 630 (e.g., $e^{-t} \sin(\pi x)$) and obtain the corresponding right hand side $f(t, x)$ by
 631 differentiation. The resulting $u(t, x)$ and $f(t, x)$ are “guaranteed” to satisfy
 632 the Burgers equation and conserve all associated invariances by construction.
 633 In our work, we replace $u(t, x)$ by a neural network $u(t, x; W, b)$ and obtain
 634 a physics-informed neural network $f(t, x; W, b)$ by automatic differentiation.
 635 Consequently, the resulting pair $u(t, x; W, b)$ and $f(t, x; W, b)$ must satisfy
 636 the Burgers equation regardless of the choice of the weights W and bias b
 637 parameters. Hence, at this “prior” level, i.e. before we train the networks
 638 on a given set of data, our model should exactly preserves the continuity
 639 and momentum equations by construction. During training, given a data-set
 640 t_i, x_i, u_i and t_j, x_j, f_j , we then try to find the “correct” parameters W^* and b^*
 641 such that we get as good a fit as possible to both the observed data and the
 642 differential equation residual. During this process the residual, albeit small,
 643 will not be exactly zero, and therefore our approximation will conserve mass
 644 and momentum within the accuracy of the residual loss. Similar behavior is
 645 observed in classical Galerkin finite element methods, while the only numer-
 646 ical methods that are known to have exact conservation properties in this
 647 setting are discontinuous Galerkin and finite volumes.

648
 649 In all benchmarks considered in this work, the total number of training
 650 data N_u is relatively small (a few hundred up to a few thousand points), and
 651 we chose to optimize all loss functions using L-BFGS a quasi-Newton, full-

652 batch gradient-based optimization algorithm [35]. For larger data-sets a more
 653 computationally efficient mini-batch setting can be readily employed using
 654 stochastic gradient descent and its modern variants [36, 37]. Despite the
 655 fact that there is no theoretical guarantee that this procedure converges to
 656 a global minimum, our empirical evidence indicates that, if the given partial
 657 differential equation is well-posed and its solution is unique, our method is
 658 capable of achieving good prediction accuracy given a sufficiently expressive
 659 neural network architecture and a sufficient number of collocation points N_f .
 660 This general observation deeply relates to the resulting optimization land-
 661 scape induced by the mean square error loss of equation 4, and defines an
 662 open question for research that is in sync with recent theoretical develop-
 663 ments in deep learning [38, 39]. Here, we will test the robustness of the
 664 proposed methodology using a series of systematic sensitivity studies that
 665 accompany the numerical results presented in the following.

666
 667 Figure A.6 summarizes our results for the data-driven solution of the
 668 Burgers equation. Specifically, given a set of $N_u = 100$ randomly distributed
 669 initial and boundary data, we learn the latent solution $u(t, x)$ by training all
 670 3021 parameters of a 9-layer deep neural network using the mean squared
 671 error loss of (A.2). Each hidden layer contained 20 neurons and a hyperbolic
 672 tangent activation function. The top panel of Figure A.6 shows the predicted
 673 spatio-temporal solution $u(t, x)$, along with the locations of the initial and
 674 boundary training data. We must underline that, unlike any classical nu-
 675 merical method for solving partial differential equations, this prediction is
 676 obtained without any sort of discretization of the spatio-temporal domain.
 677 The exact solution for this problem is analytically available [13], and the
 678 resulting prediction error is measured at $6.7 \cdot 10^{-4}$ in the relative $\mathbb{L}_2$ -norm.
 679 Note that this error is about two orders of magnitude lower than the one
 680 reported in our previous work on data-driven solution of partial differential
 681 equation using Gaussian processes [8]. A more detailed assessment of the
 682 predicted solution is presented in the bottom panel of figure A.6. In partic-
 683 ular, we present a comparison between the exact and the predicted solutions
 684 at different time instants $t = 0.25, 0.50, 0.75$. Using only a handful of ini-
 685 tial and boundary data, the *physics-informed neural network* can accurately
 686 capture the intricate nonlinear behavior of the Burgers' equation that leads
 687 to the development of a sharp internal layer around $t = 0.4$. The latter is
 688 notoriously hard to accurately resolve with classical numerical methods and
 689 requires a laborious spatio-temporal discretization of equation (A.1).




Figure A.6: *Burgers' equation*: *Top*: Predicted solution $u(t, x)$ along with the initial and boundary training data. In addition we are using 10,000 collocation points generated using a Latin Hypercube Sampling strategy. *Bottom*: Comparison of the predicted and exact solutions corresponding to the three temporal snapshots depicted by the white vertical lines in the top panel. The relative $\mathbb{L}_2$ error for this case is $6.7 \cdot 10^{-4}$. Model training took approximately 60 seconds on a single NVIDIA Titan X GPU card.

690

691 To further analyze the performance of our method, we have performed
692 the following systematic studies to quantify its predictive accuracy for differ-
693 ent number of training and collocation points, as well as for different neural
694 network architectures. In table A.1 we report the resulting relative $\mathbb{L}_2$ error
695 for different number of initial and boundary training data N_u and different
696 number of collocation points N_f , while keeping the 9-layer network archi-
697 tecture fixed. The general trend shows increased prediction accuracy as the
698 total number of training data N_u is increased, given a sufficient number of
699 collocation points N_f . This observation highlights a key strength of *physics-*
700 *informed neural networks*: by encoding the structure of the underlying phys-

$N_u \backslash N_f$	2000	4000	6000	7000	8000	10000
20	2.9e-01	4.4e-01	8.9e-01	1.2e+00	9.9e-02	4.2e-02
40	6.5e-02	1.1e-02	5.0e-01	9.6e-03	4.6e-01	7.5e-02
60	3.6e-01	1.2e-02	1.7e-01	5.9e-03	1.9e-03	8.2e-03
80	5.5e-03	1.0e-03	3.2e-03	7.8e-03	4.9e-02	4.5e-03
100	6.6e-02	2.7e-01	7.2e-03	6.8e-04	2.2e-03	6.7e-04
200	1.5e-01	2.3e-03	8.2e-04	8.9e-04	6.1e-04	4.9e-04

Table A.1: *Burgers' equation*: Relative $\mathbb{L}_2$ error between the predicted and the exact solution $u(t, x)$ for different number of initial and boundary training data N_u , and different number of collocation points N_f . Here, the network architecture is fixed to 9 layers with 20 neurons per hidden layer.

$\text{Layers} \backslash \text{Neurons}$	10	20	40
2	7.4e-02	5.3e-02	1.0e-01
4	3.0e-03	9.4e-04	6.4e-04
6	9.6e-03	1.3e-03	6.1e-04
8	2.5e-03	9.6e-04	5.6e-04

Table A.2: *Burgers' equation*: Relative $\mathbb{L}_2$ error between the predicted and the exact solution $u(t, x)$ for different number of hidden layers and different number of neurons per layer. Here, the total number of training and collocation points is fixed to $N_u = 100$ and $N_f = 10,000$, respectively.

701 ical law through the collocation points N_f , one can obtain a more accurate
702 and data-efficient learning algorithm.⁵ Finally, table A.2 shows the resulting
703 relative $\mathbb{L}_2$ for different number of hidden layers, and different number of
704 neurons per layer, while the total number of training and collocation points
705 is kept fixed to $N_u = 100$ and $N_f = 10,000$, respectively. As expected, we
706 observe that as the number of layers and neurons is increased (hence the
707 capacity of the neural network to approximate more complex functions), the
708 predictive accuracy is increased.

⁵Note that the case $N_f = 0$ corresponds to a standard neural network model, i.e., a neural network that does not take into account the underlying governing equation.

709 *Appendix A.2. Discrete Time Models*

710 Let us apply the general form of Runge-Kutta methods with q stages [45]
 711 to a general equation of the form

$$u_t + \mathcal{N}[u] = 0, \quad x \in \Omega, \quad t \in [0, T], \quad (\text{A.3})$$

712 and obtain

$$\begin{aligned} u^{n+c_i} &= u^n - \Delta t \sum_{j=1}^q a_{ij} \mathcal{N}[u^{n+c_j}], \quad i = 1, \dots, q, \\ u^{n+1} &= u^n - \Delta t \sum_{j=1}^q b_j \mathcal{N}[u^{n+c_j}]. \end{aligned} \quad (\text{A.4})$$

713 Here, $u^{n+c_j}(x) = u(t^n + c_j \Delta t, x)$ for $j = 1, \dots, q$. This general form en-
 714 capsulates both implicit and explicit time-stepping schemes, depending on
 715 the choice of the parameters $\{a_{ij}, b_j, c_j\}$. Equations (7) can be equivalently
 716 expressed as

$$\begin{aligned} u^n &= u_i^n, \quad i = 1, \dots, q, \\ u^n &= u_{q+1}^n, \end{aligned} \quad (\text{A.5})$$

717 where

$$\begin{aligned} u_i^n &:= u^{n+c_i} + \Delta t \sum_{j=1}^q a_{ij} \mathcal{N}[u^{n+c_j}], \quad i = 1, \dots, q, \\ u_{q+1}^n &:= u^{n+1} + \Delta t \sum_{j=1}^q b_j \mathcal{N}[u^{n+c_j}]. \end{aligned} \quad (\text{A.6})$$

718 We proceed by placing a multi-output neural network prior on

$$[u^{n+c_1}(x), \dots, u^{n+c_q}(x), u^{n+1}(x)]. \quad (\text{A.7})$$

719 This prior assumption along with equations (A.6) result in a *physics-informed*
 720 *neural network* that takes x as an input and outputs

$$[u_1^n(x), \dots, u_q^n(x), u_{q+1}^n(x)]. \quad (\text{A.8})$$

721 To highlight the key features of the discrete time representation we revisit
 722 the problem of data-driven solution of the Burgers' equation. For this case,
 723 the nonlinear operator in equation (A.6) is given by

$$\mathcal{N}[u^{n+c_j}] = u^{n+c_j} u_x^{n+c_j} - (0.01/\pi) u_{xx}^{n+c_j},$$

724 and the shared parameters of the neural networks (A.7) and (A.8) can be
 725 learned by minimizing the sum of squared errors

$$SSE = SSE_n + SSE_b, \quad (\text{A.9})$$

726 where

$$SSE_n = \sum_{j=1}^{q+1} \sum_{i=1}^{N_n} |u_j^n(x^{n,i}) - u^{n,i}|^2,$$

727 and

$$SSE_b = \sum_{i=1}^q (|u^{n+c_i}(-1)|^2 + |u^{n+c_i}(1)|^2) + |u^{n+1}(-1)|^2 + |u^{n+1}(1)|^2.$$

728 Here, $\{x^{n,i}, u^{n,i}\}_{i=1}^{N_n}$ corresponds to the data at time t^n . The Runge-Kutta
 729 scheme now allows us to infer the latent solution $u(t, x)$ in a sequential fash-
 730 ion. Starting from initial data $\{x^{n,i}, u^{n,i}\}_{i=1}^{N_n}$ at time t^n and data at the
 731 domain boundaries $x = -1$ and $x = 1$, we can use the aforementioned loss
 732 function (A.9) to train the networks of (A.7), (A.8), and predict the solu-
 733 tion at time t^{n+1} . A Runge-Kutta time-stepping scheme would then use this
 734 prediction as initial data for the next step and proceed to train again and
 735 predict $u(t^{n+2}, x)$, $u(t^{n+3}, x)$, etc., one step at a time.

736

737 The result of applying this process to the Burgers' equation is presented
 738 in figure A.7. For illustration purposes, we start with a set of $N_n = 250$ initial
 739 data at $t = 0.1$, and employ a *physics-informed neural network* induced by an
 740 implicit Runge-Kutta scheme with 500 stages to predict the solution at time
 741 $t = 0.9$ in a single step. The theoretical error estimates for this scheme predict
 742 a temporal error accumulation of $\mathcal{O}(\Delta t^{2q})$ [45], which in our case translates
 743 into an error way below machine precision, i.e., $\Delta t^{2q} = 0.8^{1000} \approx 10^{-97}$. To
 744 our knowledge, this is the first time that an implicit Runge-Kutta scheme
 745 of that high-order has ever been used. Remarkably, starting from smooth
 746 initial data at $t = 0.1$ we can predict the nearly discontinuous solution at
 747 $t = 0.9$ in a single time-step with a relative $\mathbb{L}_2$ error of $8.2 \cdot 10^{-4}$. This error is
 748 two orders of magnitude lower than the one reported in [8], and it is entirely
 749 attributed to the neural network's capacity to approximate $u(t, x)$, as well as
 750 to the degree that the sum of squared errors loss allows interpolation of the
 751 training data. The network architecture used here consists of 4 layers with
 752 50 neurons in each hidden layer.

753

754 A detailed systematic study to quantify the effect of different network
 755 architectures is presented in table A.5. By keeping the number of Runge-
 756 Kutta stages fixed to $q = 500$ and the time-step size to $\Delta t = 0.8$, we have




Figure A.7: *Burgers equation*: Top: Solution $u(t, x)$ along with the location of the initial training snapshot at $t = 0.1$ and the final prediction snapshot at $t = 0.9$. Bottom: Initial training data and final prediction at the snapshots depicted by the white vertical lines in the top panel. The relative $\mathbb{L}_2$ error for this case is $8.2 \cdot 10^{-4}$.

757 varied the number of hidden layers and the number of neurons per layer, and
758 monitored the resulting relative $\mathbb{L}_2$ error for the predicted solution at time
759 $t = 0.9$. Evidently, as the neural network capacity is increased the predictive
760 accuracy is enhanced.

761

762 The key parameters controlling the performance of our discrete time al-
763 gorithm are the total number of Runge-Kutta stages q and the time-step size
764 Δt . In table A.4 we summarize the results of an extensive systematic study
765 where we fix the network architecture to 4 hidden layers with 50 neurons

Layers \ Neurons	Neurons		
	10	25	50
1	4.1e-02	4.1e-02	1.5e-01
2	2.7e-03	5.0e-03	2.4e-03
3	3.6e-03	1.9e-03	9.5e-04

Table A.3: *Burgers' equation*: Relative final prediction error measure in the $\mathbb{L}_2$ norm for different number of hidden layers and neurons in each layer. Here, the number of Runge-Kutta stages is fixed to 500 and the time-step size to $\Delta t = 0.8$.

per layer, and vary the number of Runge-Kutta stages q and the time-step size Δt . Specifically, we see how cases with low numbers of stages fail to yield accurate results when the time-step size is large. For instance, the case $q = 1$ corresponding to the classical trapezoidal rule, and the case $q = 2$ corresponding to the 4th-order Gauss-Legendre method, cannot retain their predictive accuracy for time-steps larger than 0.2, thus mandating a solution strategy with multiple time-steps of small size. On the other hand, the ability to push the number of Runge-Kutta stages to 32 and even higher allows us to take very large time steps, and effectively resolve the solution in a single step without sacrificing the accuracy of our predictions. Moreover, numerical stability is not sacrificed either as implicit Gauss-Legendre is the only family of time-stepping schemes that remain A-stable regardless of their order, thus making them ideal for stiff problems [45]. These properties are unprecedented for an algorithm of such implementation simplicity, and illustrate one of the key highlights of our discrete time approach.

Finally, in table A.5 we provide a systematic study to quantify the accuracy of the predicted solution as we vary the spatial resolution of the input data. As expected, increasing the total number of training data results in enhanced prediction accuracy.

Appendix B. Data-driven discovery of partial differential equations

This Appendix accompanies the main manuscript, and contains a series of systematic studies that aim to demonstrate the performance of the proposed algorithms for problems pertaining to *data-driven discovery of partial differential equations*. Throughout this document, we will use the Burgers' equation as a canonical example.

$q \backslash \Delta t$	0.2	0.4	0.6	0.8
1	3.5e-02	1.1e-01	2.3e-01	3.8e-01
2	5.4e-03	5.1e-02	9.3e-02	2.2e-01
4	1.2e-03	1.5e-02	3.6e-02	5.4e-02
8	6.7e-04	1.8e-03	8.7e-03	5.8e-02
16	5.1e-04	7.6e-02	8.4e-04	1.1e-03
32	7.4e-04	5.2e-04	4.2e-04	7.0e-04
64	4.5e-04	4.8e-04	1.2e-03	7.8e-04
100	5.1e-04	5.7e-04	1.8e-02	1.2e-03
500	4.1e-04	3.8e-04	4.2e-04	8.2e-04

Table A.4: *Burgers' equation*: Relative final prediction error measured in the $\mathbb{L}_2$ norm for different number of Runge-Kutta stages q and time-step sizes Δt . Here, the network architecture is fixed to 4 hidden layers with 50 neurons in each layer.

N	250	200	150	100	50	10
Error	4.02e-4	2.93e-3	9.39e-3	5.54e-2	1.77e-2	7.58e-1

Table A.5: *Burgers equation*: Relative $\mathcal{L}_2$ error between the predicted and the exact solution $u(t, x)$ for different number of training data N_n . Here, we have fixed $q = 500$, and used a neural network architecture with 3 hidden layers and 50 neurons per hidden layer.

791 Appendix B.1. Continuous Time Models

792 As a first example, let us consider the Burgers' equation. This equation
793 arises in various areas of applied mathematics, including fluid mechanics,
794 nonlinear acoustics, gas dynamics, and traffic flow [13]. It is a fundamen-
795 tal partial differential equation and can be derived from the Navier-Stokes
796 equations for the velocity field by dropping the pressure gradient term. For
797 small values of the viscosity parameters, Burgers' equation can lead to shock
798 formation that is notoriously hard to resolve by classical numerical methods.
799 In one space dimension the equation reads as

$$u_t + \lambda_1 u u_x - \lambda_2 u_{xx} = 0. \quad (\text{B.1})$$

800 Let us define $f(t, x)$ to be given by

$$f := u_t + \lambda_1 u u_x - \lambda_2 u_{xx}, \quad (\text{B.2})$$

801 and proceed by approximating $u(t, x)$ by a deep neural network. This will
802 result in the *physics-informed neural network* $f(t, x)$. The shared parameters

803 of the neural networks $u(t, x)$ and $f(t, x)$ along with the parameters $\lambda =$
 804 (λ_1, λ_2) of the differential operator can be learned by minimizing the mean
 805 squared error loss

$$MSE = MSE_u + MSE_f, \quad (\text{B.3})$$

806 where

$$MSE_u = \frac{1}{N} \sum_{i=1}^N |u(t_u^i, x_u^i) - u^i|^2,$$

807 and

$$MSE_f = \frac{1}{N} \sum_{i=1}^N |f(t_u^i, x_u^i)|^2.$$

808 Here, $\{t_u^i, x_u^i, u^i\}_{i=1}^N$ denote the training data on $u(t, x)$. The loss MSE_u cor-
 809 responds to the training data on $u(t, x)$ while MSE_f enforces the structure
 810 imposed by equation (B.1) at a finite set of collocation points, whose number
 811 and location is taken to be the same as the training data.

812

813 To illustrate the effectiveness of our approach, we have created a train-
 814 ing data-set by randomly generating $N = 2,000$ points across the entire
 815 spatio-temporal domain from the exact solution corresponding to $\lambda_1 = 1.0$
 816 and $\lambda_2 = 0.01/\pi$. The locations of the training points are illustrated in the
 817 top panel of figure B.8. This data-set is then used to train a 9-layer deep
 818 neural network with 20 neurons per hidden layer by minimizing the mean
 819 square error loss of (B.3) using the L-BFGS optimizer [35]. Upon training,
 820 the network is calibrated to predict the entire solution $u(t, x)$, as well as the
 821 unknown parameters $\lambda = (\lambda_1, \lambda_2)$ that define the underlying dynamics. A
 822 visual assessment of the predictive accuracy of the *physics-informed neural*
 823 *network* is given in the middle and bottom panels of figure B.8. The network
 824 is able to identify the underlying partial differential equation with remark-
 825 able accuracy, even in the case where the scattered training data is corrupted
 826 with 1% uncorrelated noise.

827

828 To further scrutinize the performance of our algorithm, we have per-
 829 formed a systematic study with respect to the total number of training data,
 830 the noise corruption levels, and the neural network architecture. The results
 831 are summarized in tables B.6 and B.7. The key observation here is that the
 832 proposed methodology appears to be very robust with respect to noise levels
 833 in the data, and yields a reasonable identification accuracy even for noise




Figure B.8: *Burgers equation*: *Top*: Predicted solution $u(t, x)$ along with the training data. *Middle*: Comparison of the predicted and exact solutions corresponding to the three temporal snapshots depicted by the dashed vertical lines in the top panel. *Bottom*: Correct partial differential equation along with the identified one obtained by learning λ_1 and λ_2 .

834 corruption up to 10%. This enhanced robustness seems to greatly outper-
835 form competing approaches using Gaussian process regression as previously
836 reported in [9] as well as approaches relying on sparse regression that require
837 relatively clean data for accurately computing numerical gradients [50]. We
838 also observe some variability and non monotonic trends in tables B.6 and B.7
839 as the network architecture and total number of training points are changed.
840 This variability could be potentially attributed to different factors pertaining
841 to the equation itself as well as the particular neural network setup, and gives
842 rise to a series of questions that require further investigation, as discussed in
843 the concluding remarks section of this paper.

		% error in λ_1				% error in λ_2			
N_u	noise	0%	1%	5%	10%	0%	1%	5%	10%
500		0.131	0.518	0.118	1.319	13.885	0.483	1.708	4.058
1000		0.186	0.533	0.157	1.869	3.719	8.262	3.481	14.544
1500		0.432	0.033	0.706	0.725	3.093	1.423	0.502	3.156
2000		0.096	0.039	0.190	0.101	0.469	0.008	6.216	6.391

Table B.6: *Burgers' equation*: Percentage error in the identified parameters λ_1 and λ_2 for different number of training data N corrupted by different noise levels. Here, the neural network architecture is kept fixed to 9 layers and 20 neurons per layer.

		% error in λ_1			% error in λ_2		
Layers	Neurons	10	20	40	10	20	40
2		11.696	2.837	1.679	103.919	67.055	49.186
4		0.332	0.109	0.428	4.721	1.234	6.170
6		0.668	0.629	0.118	3.144	3.123	1.158
8		0.414	0.141	0.266	8.459	1.902	1.552

Table B.7: *Burgers' equation*: Percentage error in the identified parameters λ_1 and λ_2 for different number of hidden layers and neurons per layer. Here, the training data is considered to be noise-free and fixed to $N = 2,000$.

844 Appendix B.2. Discrete Time Models

845 Our starting point here is similar to as described in section 3.2. Now
846 equations (7) can be equivalently expressed as

$$\begin{aligned} u^n &= u_i^n, \quad i = 1, \dots, q, \\ u^{n+1} &= u_i^{n+1}, \quad i = 1, \dots, q. \end{aligned} \tag{B.4}$$

847 where

$$\begin{aligned} u_i^n &:= u^{n+c_i} + \Delta t \sum_{j=1}^q a_{ij} \mathcal{N}[u^{n+c_j}; \lambda], \quad i = 1, \dots, q, \\ u_i^{n+1} &:= u^{n+c_i} + \Delta t \sum_{j=1}^q (a_{ij} - b_j) \mathcal{N}[u^{n+c_j}; \lambda], \quad i = 1, \dots, q. \end{aligned} \tag{B.5}$$

848 We proceed by placing a multi-output neural network prior on

$$[u^{n+c_1}(x), \dots, u^{n+c_q}(x)]. \tag{B.6}$$

849 This prior assumption along with equations (22) result in two *physics-informed*
 850 *neural networks*

$$[u_1^n(x), \dots, u_q^n(x), u_{q+1}^n(x)], \quad (\text{B.7})$$

851 and

$$[u_1^{n+1}(x), \dots, u_q^{n+1}(x), u_{q+1}^{n+1}(x)]. \quad (\text{B.8})$$

852 Given noisy measurements at two distinct temporal snapshots $\{\mathbf{x}^n, \mathbf{u}^n\}$ and
 853 $\{\mathbf{x}^{n+1}, \mathbf{u}^{n+1}\}$ of the system at times t^n and t^{n+1} , respectively, the shared
 854 parameters of the neural networks (B.6), (B.7), and (B.8) along with the
 855 parameters λ of the differential operator can be trained by minimizing the
 856 sum of squared errors

$$SSE = SSE_n + SSE_{n+1}, \quad (\text{B.9})$$

857 where

$$SSE_n := \sum_{j=1}^q \sum_{i=1}^{N_n} |u_j^n(x^{n,i}) - u^{n,i}|^2,$$

858 and

$$SSE_{n+1} := \sum_{j=1}^q \sum_{i=1}^{N_{n+1}} |u_j^{n+1}(x^{n+1,i}) - u^{n+1,i}|^2.$$

859 Here, $\mathbf{x}^n = \{x^{n,i}\}_{i=1}^{N_n}$, $\mathbf{u}^n = \{u^{n,i}\}_{i=1}^{N_n}$, $\mathbf{x}^{n+1} = \{x^{n+1,i}\}_{i=1}^{N_{n+1}}$, and $\mathbf{u}^{n+1} =$
 860 $\{u^{n+1,i}\}_{i=1}^{N_{n+1}}$.

861 *Appendix B.3. Example (Burgers' Equation)*

862 Let us illustrate the key features of this method through the lens of the
 863 Burgers' equation. Recall the equation's form

$$u_t + \lambda_1 u u_x - \lambda_2 u_{xx} = 0, \quad (\text{B.10})$$

864 and notice that the nonlinear spatial operator in equation (B.5) is given by

$$\mathcal{N}[u^{n+c_j}] = \lambda_1 u^{n+c_j} u_x^{n+c_j} - \lambda_2 u_{xx}^{n+c_j}.$$

865 Given merely two training data snapshots, the shared parameters of the neu-
 866 ral networks (B.6), (B.7), and (B.8) along with the parameters $\lambda = (\lambda_1, \lambda_2)$
 867 of the Burgers' equation can be learned by minimizing the sum of squared
 868 errors in equation (B.9). Here, we have created a training data-set compris-
 869 ing of $N_n = 199$ and $N_{n+1} = 201$ spatial points by randomly sampling the

870 exact solution at time instants $t^n = 0.1$ and $t^{n+1} = 0.9$, respectively. The
871 training data are shown in the top and middle panel of figure B.9. The neural
872 network architecture used here consists of 4 hidden layers with 50 neurons
873 each, while the number of Runge-Kutta stages is empirically chosen to yield
874 a temporal error accumulation of the order of machine precision ϵ by setting⁶

$$q = 0.5 \log \epsilon / \log(\Delta t), \quad (\text{B.11})$$

875 where the time-step for this example is $\Delta t = 0.8$. The bottom panel of fig-
876 ure B.9 summarizes the identified parameters $\lambda = (\lambda_1, \lambda_2)$ for the cases of
877 noise-free data, as well as noisy data with 1% of Gaussian uncorrelated noise
878 corruption. For both cases, the proposed algorithm is able to learn the cor-
879 rect parameter values $\lambda_1 = 1.0$ and $\lambda_2 = 0.01/\pi$ with remarkable accuracy,
880 despite the fact that the two data snapshots used for training are very far
881 apart, and potentially describe different regimes of the underlying dynamics.

882
883 A sensitivity analysis is performed to quantify the accuracy of our predic-
884 tions with respect to the gap between the training snapshots Δt , the noise
885 levels in the training data, and the *physics-informed neural network* architec-
886 ture. As shown in table B.8, the proposed algorithm is quite robust to both
887 Δt and the noise corruption levels, and it returns reasonable estimates for
888 the unknown parameters. This robustness is mainly attributed to the flexi-
889 bility of the underlying implicit Runge-Kutta scheme to admit an arbitrarily
890 high number of stages, allowing the data snapshots to be very far apart in
891 time, while not compromising the accuracy with which the nonlinear dynam-
892 ics of equation (B.10) are resolved. This is the key highlight of our discrete
893 time formulation for identification problems, setting it apart from competing
894 approaches [9, 50]. Lastly, table B.9 presents the percentage error in the
895 identified parameters, demonstrating the robustness of our estimates with
896 respect to the underlying neural network architecture. Despite the overall
897 positive results, the variability observed in tables B.8 and B.9 is still largely
898 unexplained and naturally motivates a series of questions provided in the
899 concluding remarks section of this paper.

⁶This is motivated by the theoretical error estimates for implicit Runge-Kutta schemes suggesting a truncation error of $\mathcal{O}(\Delta t^{2q})$ [45].




Figure B.9: *Burgers equation*: *Top*: Solution $u(t, x)$ along with the temporal locations of the two training snapshots. *Middle*: Training data and exact solution corresponding to the two temporal snapshots depicted by the dashed vertical lines in the top panel. *Bottom*: Correct partial differential equation along with the identified one obtained by learning λ_1, λ_2 .

900 References

- 901 [1] A. Krizhevsky, I. Sutskever, G. E. Hinton, Imagenet classification with
 902 deep convolutional neural networks, in: Advances in neural information
 903 processing systems, pp. 1097–1105.

		% error in λ_1				% error in λ_2			
Δt	noise	0%	1%	5%	10%	0%	1%	5%	10%
0.2		0.002	0.435	6.073	3.273	0.151	4.982	59.314	83.969
0.4		0.001	0.119	1.679	2.985	0.088	2.816	8.396	8.377
0.6		0.002	0.064	2.096	1.383	0.090	0.068	3.493	24.321
0.8		0.010	0.221	0.097	1.233	1.918	3.215	13.479	1.621

Table B.8: *Burgers' equation*: Percentage error in the identified parameters λ_1 and λ_2 for different gap size Δt between two different snapshots and for different noise levels.

		% error in λ_1			% error in λ_2		
Layers	Neurons	10	25	50	10	25	50
1		1.868	4.868	1.960	180.373	237.463	123.539
2		0.443	0.037	0.015	29.474	2.676	1.561
3		0.123	0.012	0.004	7.991	1.906	0.586
4		0.012	0.020	0.011	1.125	4.448	2.014

Table B.9: *Burgers' equation*: Percentage error in the identified parameters λ_1 and λ_2 for different number of hidden layers and neurons in each layer.

- 904 [2] B. M. Lake, R. Salakhutdinov, J. B. Tenenbaum, Human-level concept
905 learning through probabilistic program induction, *Science* 350 (2015)
906 1332–1338.
- 907 [3] B. Alipanahi, A. Delong, M. T. Weirauch, B. J. Frey, Predicting the se-
908 quence specificities of DNA-and RNA-binding proteins by deep learning,
909 *Nature biotechnology* 33 (2015) 831–838.
- 910 [4] M. Raissi, P. Perdikaris, G. E. Karniadakis, Inferring solutions of dif-
911 ferential equations using noisy multi-fidelity data, *Journal of Computa-
912 tional Physics* 335 (2017) 736–746.
- 913 [5] M. Raissi, P. Perdikaris, G. E. Karniadakis, Machine learning of linear
914 differential equations using Gaussian processes, *Journal of Computa-
915 tional Physics* 348 (2017) 683 – 693.
- 916 [6] H. Owhadi, Bayesian numerical homogenization, *Multiscale Modeling
917 & Simulation* 13 (2015) 812–828.

- 918 [7] C. E. Rasmussen, C. K. Williams, Gaussian processes for machine learn-
919 ing, volume 1, MIT press Cambridge, 2006.
- 920 [8] M. Raissi, P. Perdikaris, G. E. Karniadakis, Numerical Gaussian pro-
921 cesses for time-dependent and non-linear partial differential equations,
922 arXiv preprint arXiv:1703.10230 (2017).
- 923 [9] M. Raissi, G. E. Karniadakis, Hidden physics models: Machine
924 learning of nonlinear partial differential equations, arXiv preprint
925 arXiv:1708.00588 (2017).
- 926 [10] H. Owhadi, C. Scovel, T. Sullivan, et al., Brittleness of Bayesian infer-
927 ence under finite information in a continuous world, Electronic Journal
928 of Statistics 9 (2015) 1–79.
- 929 [11] K. Hornik, M. Stinchcombe, H. White, Multilayer feedforward networks
930 are universal approximators, Neural networks 2 (1989) 359–366.
- 931 [12] A. G. Baydin, B. A. Pearlmutter, A. A. Radul, J. M. Siskind, Au-
932 tomatic differentiation in machine learning: a survey, arXiv preprint
933 arXiv:1502.05767 (2015).
- 934 [13] C. Basdevant, M. Deville, P. Haldenwang, J. Lacroix, J. Ouazzani,
935 R. Peyret, P. Orlandi, A. Patera, Spectral and finite difference solu-
936 tions of the Burgers equation, Computers & fluids 14 (1986) 23–41.
- 937 [14] S. H. Rudy, S. L. Brunton, J. L. Proctor, J. N. Kutz, Data-driven
938 discovery of partial differential equations, Science Advances 3 (2017).
- 939 [15] I. E. Lagaris, A. Likas, D. I. Fotiadis, Artificial neural networks for
940 solving ordinary and partial differential equations, IEEE Transactions
941 on Neural Networks 9 (1998) 987–1000.
- 942 [16] D. C. Psychogios, L. H. Ungar, A hybrid neural network-first principles
943 approach to process modeling, AIChE Journal 38 (1992) 1499–1511.
- 944 [17] J.-X. Wang, J. Wu, J. Ling, G. Iaccarino, H. Xiao, A comprehensive
945 physics-informed machine learning framework for predictive turbulence
946 modeling, arXiv preprint arXiv:1701.07102 (2017).

- 947 [18] Y. Zhu, N. Zabaras, Bayesian deep convolutional encoder-decoder net-
948 works for surrogate modeling and uncertainty quantification, arXiv
949 preprint arXiv:1801.06879 (2018).
- 950 [19] T. Hagge, P. Stinis, E. Yeung, A. M. Tartakovsky, Solving differen-
951 tial equations with unknown constitutive relations as recurrent neural
952 networks, arXiv preprint arXiv:1710.02242 (2017).
- 953 [20] R. Tripathy, I. Bilonis, Deep UQ: Learning deep neural network sur-
954rogate models for high dimensional uncertainty quantification, arXiv
955 preprint arXiv:1802.00850 (2018).
- 956 [21] P. R. Vlachas, W. Byeon, Z. Y. Wan, T. P. Sapsis, P. Koumoutsakos,
957 Data-driven forecasting of high-dimensional chaotic systems with long-
958 short term memory networks, arXiv preprint arXiv:1802.07486 (2018).
- 959 [22] E. J. Parish, K. Duraisamy, A paradigm for data-driven predictive mod-
960 eling using field inversion and machine learning, *Journal of Computa-*
961 *tional Physics* 305 (2016) 758–774.
- 962 [23] K. Duraisamy, Z. J. Zhang, A. P. Singh, New approaches in turbulence
963 and transition modeling using data-driven techniques, in: 53rd AIAA
964 Aerospace Sciences Meeting, p. 1284.
- 965 [24] J. Ling, A. Kurzawski, J. Templeton, Reynolds averaged turbulence
966 modelling using deep neural networks with embedded invariance, *Jour-*
967 *nal of Fluid Mechanics* 807 (2016) 155–166.
- 968 [25] Z. J. Zhang, K. Duraisamy, Machine learning methods for data-driven
969 turbulence modeling, in: 22nd AIAA Computational Fluid Dynamics
970 Conference, p. 2460.
- 971 [26] M. Milano, P. Koumoutsakos, Neural network modeling for near wall
972 turbulent flow, *Journal of Computational Physics* 182 (2002) 1–26.
- 973 [27] P. Perdikaris, D. Venturi, G. E. Karniadakis, Multifidelity information
974 fusion algorithms for high-dimensional systems and massive data sets,
975 *SIAM J. Sci. Comput.* 38 (2016) B521–B538.
- 976 [28] R. Rico-Martinez, J. Anderson, I. Kevrekidis, Continuous-time nonlin-
977 ear signal processing: a neural network based approach for gray box

- 978 identification, in: Neural Networks for Signal Processing [1994] IV. Pro-
 979 ceedings of the 1994 IEEE Workshop, IEEE, pp. 596–605.
- 980 [29] J. Ling, J. Templeton, Evaluation of machine learning algorithms for
 981 prediction of regions of high reynolds averaged navier stokes uncertainty,
 982 Physics of Fluids 27 (2015) 085103.
- 983 [30] H. W. Lin, M. Tegmark, D. Rolnick, Why does deep and cheap learning
 984 work so well?, Journal of Statistical Physics 168 (2017) 1223–1247.
- 985 [31] R. Kondor, N-body networks: a covariant hierarchical neural net-
 986 work architecture for learning atomic potentials, arXiv preprint
 987 arXiv:1803.01588 (2018).
- 988 [32] R. Kondor, S. Trivedi, On the generalization of equivariance and con-
 989 volution in neural networks to the action of compact groups, arXiv
 990 preprint arXiv:1802.03690 (2018).
- 991 [33] M. Hirn, S. Mallat, N. Poilvert, Wavelet scattering regression of quan-
 992 tum chemical energies, Multiscale Modeling & Simulation 15 (2017)
 993 827–863.
- 994 [34] S. Mallat, Understanding deep convolutional networks, Phil. Trans. R.
 995 Soc. A 374 (2016) 20150203.
- 996 [35] D. C. Liu, J. Nocedal, On the limited memory BFGS method for large
 997 scale optimization, Mathematical programming 45 (1989) 503–528.
- 998 [36] I. Goodfellow, Y. Bengio, A. Courville, Deep learning, MIT press, 2016.
- 999 [37] D. Kingma, J. Ba, Adam: A method for stochastic optimization, arXiv
 1000 preprint arXiv:1412.6980 (2014).
- 1001 [38] A. Choromanska, M. Henaff, M. Mathieu, G. B. Arous, Y. LeCun, The
 1002 loss surfaces of multilayer networks, in: Artificial Intelligence and Statis-
 1003 tics, pp. 192–204.
- 1004 [39] R. Shwartz-Ziv, N. Tishby, Opening the black box of deep neural net-
 1005 works via information, arXiv preprint arXiv:1703.00810 (2017).
- 1006 [40] T. A. Driscoll, N. Hale, L. N. Trefethen, Chebfun guide, 2014.

- 1007 [41] M. Stein, Large sample properties of simulations using latin hypercube
1008 sampling, *Technometrics* 29 (1987) 143–151.
- 1009 [42] J. Snoek, H. Larochelle, R. P. Adams, Practical bayesian optimization
1010 of machine learning algorithms, in: *Advances in neural information*
1011 *processing systems*, pp. 2951–2959.
- 1012 [43] H.-J. Bungartz, M. Griebel, Sparse grids, *Acta numerica* 13 (2004)
1013 147–269.
- 1014 [44] I. H. Sloan, H. Woźniakowski, When are quasi-monte carlo algorithms
1015 efficient for high dimensional integrals?, *Journal of Complexity* 14 (1998)
1016 1–33.
- 1017 [45] A. Iserles, *A first course in the numerical analysis of differential equa-*
1018 *tions*, 44, Cambridge University Press, 2009.
- 1019 [46] T. Von Kármán, *Aerodynamics*, volume 9, McGraw-Hill New York,
1020 1963.
- 1021 [47] G. Karniadakis, S. Sherwin, *Spectral/hp element methods for computa-*
1022 *tional fluid dynamics*, Oxford University Press, 2013.
- 1023 [48] T. Dauxois, Fermi, Pasta, Ulam and a mysterious lady, *arXiv preprint*
1024 *arXiv:0801.1590* (2008).
- 1025 [49] M. Abadi, A. Agarwal, P. Barham, E. Brevdo, Z. Chen, C. Citro, G. S.
1026 Corrado, A. Davis, J. Dean, M. Devin, et al., *Tensorflow: Large-scale*
1027 *machine learning on heterogeneous distributed systems*, *arXiv preprint*
1028 *arXiv:1603.04467* (2016).
- 1029 [50] S. L. Brunton, J. L. Proctor, J. N. Kutz, Discovering governing equa-
1030 tions from data by sparse identification of nonlinear dynamical systems,
1031 *Proceedings of the National Academy of Sciences* 113 (2016) 3932–3937.