

Sound and speech retrieval


Stanislav Protasov

Agenda

- Sound as a wave
- Music search
- Speech recognition

What is the sound?

Sound is a **vibration** that propagates through a transmission medium such as a gas, liquid or solid.




Vinyl player



How ear works

Neurotransmitters




Auditory Nerve





Euler's identity to link complex exponent with frequencies

$$e^{ix} = \cos x + i \sin x,$$



Fourier Transforms


$$FT: \hat{f}(\omega) = \int_{-\infty}^{+\infty} f(x) e^{-2\pi i x \omega} dx$$

$$DTFT: X_T(\omega) = \sum_{n=-\infty}^{+\infty} f(nT) e^{-\pi i \omega nT}$$


$$DTFT + window: X_T(\omega) = \sum_{n=0}^M f(nT) w\left(\frac{n}{M}\right) e^{-2\pi i \omega nT}$$

$$\begin{aligned} DFT: X_{T,N}(k) &= X_T\left(\frac{k}{NT}\right) = & k=0, 1, \dots, N-1 \\ &= \sum_{n=0}^M f(nT) w\left(\frac{n}{M}\right) e^{-2\pi i \frac{kn}{N}} \end{aligned}$$






Fourier transform



Guitar pitch




Wavelets




What is the sound for human?

We percept sound using **frequency** receptors. Each moment looks like this:



Also important — we perceive sounds in **log scale**

Timeline is like this:




Sound *recording* and *playback*

- Digital uncompressed sound consists of regular measurements of signal.
- Measurement frequency is managed using RATE parameter
 - 22050 means 22050 measurements per second**(discretization)**
- How accurate we measure in managed is tuned with format **(quantization)**
 - How many different amplitude values can be encoded
- Channels — number of inputs/outputs (stereo=2, mono=1)
- $\text{BPS} = \text{RATE} * \text{CHANNELS} * \text{FORMAT}$
- Together this is **PCM — pulse code modulation**

Nyquist-Shannon (Kotelnikov) theorem


If a function $x(t)$ contains **no frequencies** higher than B hertz, it is **completely determined** by giving its values at a series of points spaced $1/(2B)$ seconds apart.



What **if contains**? Aliasing. $n(k)$?

$$\{\sin(kx) = \sin(nx), n < k\}$$

- $\sin(a) + \sin(b) = 2 \cdot \sin(\frac{1}{2}(a+b)) \cdot \cos(\frac{1}{2}(a-b))$




Music fingerprinting

Why?

- I like this song, I want to buy it
- Forensic (when was this song playing)
- **Copyrights** (see youtube or instagram policy)




How to form a query

1. Exact sample
2. Humming



Shazam exact match algorithm (1)

1. Robust spectrogram. (Log-scale bins of frequencies)



2. Build **pairs for hashing (32bit)**: anchor point + other point from target zone.




Fig. 1C - Combinatorial Hash Generation




Fig. 1D - Hash details

Shazam algorithm (2)



3. Put those points to a **hashmap**.

Memory: $[4B \text{ (hash)} + 4B \text{ (val)}] * \text{peaks}$.

4. Query for songs with a processed sample.

5. Plot a histogram of offsets

(get times from HT, put them in bins), identify real offset




Other fingerprinting approaches

Exact frequency and tempo are not always important:


- Zero-crossing rate
- Spectrum
- Envelope (spectral flatness, frequency band)
- ...

Query by Humming (QbH)

- Detect **coarse melodic contour**, retrieve by string search
 - S=same note, U=up, D=down
 - E.g., Beethoven's 5th: – **S S D U S S D** *ff*
 - OR U/D/S – but with five contour levels
- Add **rhythm information**
- Use **beat information**
- Use **HMMs** to represent song database
- **Dynamic Time Warping** (DTW)
based algorithm,
match waveform directly



Delta pitch	2	2	1	2	-2	-1	-2	-2
IOI	1	1	1	1	1	1	1	1
IOI ratio	1	1	1	1	1	1	1	1
State	α	α	β	α	χ	δ	χ	χ



Dynamic Time Warping





- Take to sequences of lengths N and M
- Build N*M matrix **d** of distances (difs)
- Build a matrix of deformation,


$$D_{i,j} = d_{i,j} + \min(D_{i-1,j}, D_{i-1,j-1}, D_{i,j-1}). \quad (3)$$

- Search for a path (1,1) - (N,M) with minimal average value weight.

$$DTW(Q, C) = \min \left\{ \frac{\sum_{k=1}^K d(w_k)}{K} \right\}. \quad (4)$$

Can give false positives






Google Hum to search

- Convolutional net to build a fingerprint-based from 8 seconds with 0.5 sec. step
- Inaccurate vector search with space partitioning and vector quantization
- Retrieve all candidate's fingerprints
 - Accurate match on all set of embeddings for candidates

Speech (text) processing

Acoustic model

As text consist of letters, speech consists of phonemes.



AM: spectrum \rightarrow phoneme

Language model (in recognition)

Probabilistic model that predicts probability of a word given a sequence of phonemes.

Similar model is used to model sentences of words.

Speech generation

- 1) Text preprocessing
 - a) Number to text
 - b) Abbreviations to text
 - c) Typo fix
- 2) Split text into phrases (punctuation, constructions)
- 3) Phonetic construction (language model)
 - a) queue - [kju]
 - b) Арбалетчиков**
 - i) aθ r b aθ lʃ e1 t ch iθ k oθ v**

Speech generation

- 1) **Accents** are set
 - a) Using a dictionary
 - b) Using rules
 - c) Using statistics (speaker examples)
- 2) **Reversed acoustic model** is used to consider surrounding
- 3) **Timbre** is generation with **vocoder**
 - a) or RNNs

