

Advanced Topics in Machine Learning

Group 12 Project Report

Reproducing results from “Variational Inference with Normalizing Flows” [Danilo Jimenez, Rezende Shakir Mohamed]



1032626, 1034125, 1034129, 1036969

University of Oxford

Chapter 1

Introduction

The idea of generative models is one of the most promising approaches to Machine Learning tasks. Many such models have been used in recent years to solve the problem of inference of a posterior distribution, given some expert knowledge and assumptions on the prior distribution and using observed data to adapt these. The main obstacle in attempting to generate the true posterior is its computational intractability. Consequently, approximation methods have been employed, aiming to make computation more efficient while at the same time achieving a close estimate of the true posterior.

The paper focusses on the method of variational inference. Essentially, this converts the inference problem to an optimization one where, given a family of posterior approximations, we look for the distribution that is the closest to the true one. To measure this proximity between approximations and the true posterior, we use the Kullback-Leibler divergence. There has been lots of research in the classes of such, efficiently calculatable, approximation families, such as mean-field approximations, but all of these prove to be of limited expressiveness, leading to solutions that are far from the true posterior. In fact, there is strong evidence showing that more expressive classes of posteriors would result in better performance of variational inference, which is what motivates the work of the paper.

To address the above issue, the authors propose constructing the approximations through a normalizing flow, which applies a sequence of invertible transformations to a simple initial density until it achieves a desired level of complexity. The main types of flows considered and used in the experiments are:

1. Invertible, linear-time flows, such as planar and radial flows.
2. Finite, volume-preserving flows, such as the Non-linear Independent Components Estimation (NICE).

The goal of both of the above is to provide a transformation to the original density that ends up being rich and faithful, while at the same time allowing for efficient computation of the determinant. The first kind of flow allows for computing the logdet-Jacobian in linear (in the number of dimensions) time, while the second one gives a Jacobian with a zero upper triangular part and therefore a determinant of

1. Thus, both can be efficiently implemented and used together with a Deep Latent Gaussian Model and an inference network to solve our problem.

- TODO: describe in more depth, after we have results

The paper’s experiments on the binarized MNIST dataset aim to demonstrate how variational inference with normalizing flows can outperform previous methods, compare the performance of different types of flows, and discuss the relation between the length of the flow and the quality of the resulting approximation.

- TODO: after we finish the extension

In our report, we replicate the original contributions of the paper by running the same experiments on MNIST. Additionally, we consider another type of flow, the invertible convolutional flow Finally, we provide an open-source implementation of the above in our Github repository: https://github.com/ATML-Group-12/normalising_flows

Chapter 2

Normalizing Flows

In the attempt to generate more complex families of posterior distributions, which should allow for better estimates of the true posterior, the paper introduces the idea of normalizing flows. A normalizing flow is a sequence of invertible transformations applied to a simple initial distribution (for example a unit gaussian), resulting in a complex distribution, whose density we can efficiently evaluate by inverting the flow and keeping track of the Jacobian of the composition of transformations, using the change of variable theorem.

2.1 Definition

More formally, consider a member of the flow's sequence of transformations to be an invertible, smooth mapping $f : \mathbb{R}^d \rightarrow \mathbb{R}^d$. Let $\mathbf{y} = f(\mathbf{z})$ be the outcome of applying the transformation to a random variable \mathbf{z} with distribution $q(\mathbf{z})$. Then, using the change of variable theorem, the resulting density is:

$$q(\mathbf{y}) = q(\mathbf{z}) \left| \det \frac{\partial f^{-1}(\mathbf{y})}{\partial \mathbf{y}} \right| = q(\mathbf{z}) \left| \det \frac{\partial f(\mathbf{z})}{\partial \mathbf{z}} \right|^{-1} \quad (2.1)$$

where the second equality follows from the inverse function theorem and the definition of \mathbf{y} .

We can then proceed to build more complicated densities by systematically composing multiple transformations such as the one above, since the composition of invertible transformations remains an invertible transformation. To simplify notation, we define the log-density $\ln q_K$ resulting from applying a sequence of K transformations f_1, f_2, \dots, f_K to a random variable \mathbf{z}_0 with an initial distribution q_0 as:

$$\mathbf{z}_K = f_K \circ \dots \circ f_2 \circ f_1(\mathbf{z}_0) \quad (2.2)$$

$$\ln q_K(\mathbf{z}_K) = \ln q_0(\mathbf{z}_0) - \sum_{k=1}^K \ln \left| \det \frac{\partial f_k}{\partial \mathbf{z}_{k-1}} \right| \quad (2.3)$$

where the first equation represents the sequence of random variables generated by the flow. The normalizing flow is then defined as the path of the successive distributions q_k .

2.2 Law of the Unconscious Statistician

A useful property of these transformations is what is known as the law of the unconscious statistician (LOTUS). The LOTUS refers to the fact that we can evaluate expectations with respect to the transformed density q_K without explicitly knowing it, by expressing any such expectation as:

$$\mathbb{E}_{q_K} = \mathbb{E}_{q_0}[h(f_K \circ \dots \circ f_2 \circ f_1(\mathbf{z}_0))] \quad (2.4)$$

This is an expectation over the known density q_0 , which does not require computation of the logdet-Jacobian terms when $h(\mathbf{z})$ does not depend on q_K .

2.3 Invertible Linear-time Transformations

Notice that a naive choice of these transformations would lead to a $O(d^3)$ complexity to compute the determinant of the Jacobian. Therefore, the classes of flows studied in our report are all based on the idea of having an efficient way to calculate this determinant. We begin by investigating two types of linear flows, namely planar and radial flows.

2.3.1 Planar Flows

Consider the following class of transformations:

$$f(\mathbf{z}) = \mathbf{z} + \mathbf{u}h(\mathbf{w}^\top \mathbf{z} + b) \quad (2.5)$$

where $\lambda = \{\mathbf{w} \in \mathbb{R}^D, \mathbf{u} \in \mathbb{R}^D, b \in \mathbb{R}\}$ are free parameters and $h(\cdot)$ is a smooth, element-wise non-linearity. We can use the matrix determinant lemma to calculate the logdet-Jacobian term in linear time, yielding:

$$\left| \det \frac{\partial f}{\partial \mathbf{z}} \right| = |1 + \mathbf{u}^\top \psi(\mathbf{z})| \quad (2.6)$$

where $\psi(\mathbf{z}) = h'(\mathbf{w}^\top \mathbf{z} + b)\mathbf{w}$ and h' is the derivative of the function h . Using this, we can now substitute in the formula for $\ln q_K$ to get the following closed form for planar flows:

$$\ln q_K(\mathbf{z}_K) = \ln q_0(\mathbf{z}) - \sum_{k=1}^K \ln |1 + \mathbf{u}_k^\top \psi_k(\mathbf{z}_{k-1})| \quad (2.7)$$

The name planar comes from the fact that the above transformation applies a series of contractions and expansions in the direction perpendicular to the $\mathbf{w}^\top \mathbf{z} + b = 0$ hyperplane to the initial density q_0 .

2.3.2 Radial Flows

The other family of invertible linear-time transformations studied is defined by the following equation:

$$f(\mathbf{z}) = \mathbf{z} + \beta h(\alpha, r)(\mathbf{z} - \mathbf{z}_0) \quad (2.8)$$

where $r = |\mathbf{z} - \mathbf{z}_0|$, $h(\alpha, r) = 1/(\alpha + r)$, and the set of parameters is $\lambda = \{\mathbf{z}_0 \in \mathbb{R}^D, \alpha \in \mathbb{R}^+, \beta \in \mathbb{R}\}$. The time-complexity of the computation of the determinant of this class is also linear:

$$\left| \det \frac{\partial f}{\partial \mathbf{z}} \right| = [1 + \beta h(\alpha, r)]^{d-1} [1 + \beta h(\alpha, r) + \beta h'(\alpha, r)] \quad (2.9)$$

This transformation results in radial contractions and expansions around the reference point \mathbf{z}_0 , hence the name radial flows.

2.4 NICE

Using the idea of flows, the authors view the coupling layers in the NICE paper as a flow. A coupling layer f is a neural network layer with easy to compute inverse and a trivial Jacobian. For an input vector $\mathbf{z} \in \mathbb{R}^D$, we have

$$f(\mathbf{z}) = (\mathbf{z}_A, g(\mathbf{z}_B, h(\mathbf{z}_A))) \quad (2.10)$$

$$f^{-1}(\mathbf{z}) = (\mathbf{z}_A, g^{-1}(\mathbf{z}_B, h(\mathbf{z}_A))) \quad (2.11)$$

where (A, B) is a partition of $\{1, 2, \dots, D\}$, h is an arbitrary function with input size $|A|$, and g is a coupling law, a function that is invertible for the first argument given the second. In the paper, h is a neural network and $g(a, b) = a + b$, so the Jacobian is just the identity matrix. Since the determinant of the Jacobian is 1, the authors of (variation paper) classify it as a volume-preserving flow. The authors of the NICE paper do point out this issue, and introduce a diagonal scaling layer as the last layer of their models. This approach was not used in the original paper. Moreover, the authors introduced variants NICE-ortho and NICE-perm instead of the original directly, where random orthogonal and permutation matrices are applied to \mathbf{z} before the partition.

We note that the authors of the original paper have not made the choice of h clear in the experiments. For the replicating experiment 6.1, we have chosen h to be a ReLU network of 4 layers with hidden dimensions of 2.

Chapter 3

Extension - Invertible Convolution Flows

As an extension to the paper, we implement another type of flow, from "Invertible Convolutional Flows" [Karami et al., 2019]. In particular, we have chosen to implement a Circular Convolutional Flow. As far as we can tell there are no available implementations of this paper available at the time of writing.

3.1 Circular Convolution Flows

In standard flow-based models, a complex probability density is built up by transforming a simple base density, such as a standard normal, by a chain of smooth bijections. However, using a complex transformation to define a normalised density requires computing the Jacobian determinant of the transformation, which is impractical for general transformations by neural nets. There has been much research on designing families of transformations which are guaranteed to have nice Jacobian forms, such as [Rezende and Mohamed, 2015] which considers transformations whose Jacobian is a perturbation of a diagonal matrix. The authors of Invertible Convolutional Flows have used transformations whose determinants are *circulant matrices*, which will allow computation of the log determinant, as well as the convolution and its inverse, to be calculated in time $\mathcal{O}(N \log N)$ by making use of Discrete Fourier Transforms (DTFs).

3.1.1 Definition

A *circulant matrix* is a matrix \mathbf{C} such that the rows and columns are cyclic permutations of the first row/column, ie

$$\mathbf{C}_{l,m} = \mathbf{C}_{1,(l-m) \bmod N} \quad (3.1)$$

Define the circular convolution as

$$\mathbf{y} := \mathbf{w} \star \mathbf{x} \text{ where } \mathbf{y}(i) := \sum_{n=0}^{N-1} \mathbf{x}(n) \mathbf{w}(i-n)_{\bmod N} \quad (3.2)$$

Then the circular convolution can be expressed as a matrix-vector multiplication $\mathbf{y} = \mathbf{C}_{\mathbf{w}}\mathbf{x}$ where $\mathbf{C}_{\mathbf{w}}$ is a circulant matrix with \mathbf{w} as its first row. This means that the Jacobian of the map is just $\mathbf{C}_{\mathbf{w}}$, and we can calculate the log determinant jacobian as follows [Gray et al. 2006]:

$$\log |\det \mathbf{J}_{\mathbf{y}}| = \sum_{n=0}^{N-1} \log |\mathbf{w}_{\mathcal{F}}(n)| \quad (3.3)$$

where $\mathbf{w}_{\mathcal{F}}$ is the DFT of \mathbf{w} .

Moreover, by continuing to work in the Fourier space, we can also compute the convolution and the inverse in $\mathcal{O}(N \log N)$ by:

$$\mathbf{y}_{\mathcal{F}}(n) = \mathbf{w}_{\mathcal{F}}(n)\mathbf{x}_{\mathcal{F}}(n) \quad (3.4)$$

$$\mathbf{x}_{\mathcal{F}}(n) = \mathbf{w}_{\mathcal{F}}^{-1}(n)\mathbf{y}_{\mathcal{F}}(n) \quad (3.5)$$

3.2 Our Experiment

Chapter 4

Conclusion

4.1 Further Extensions

Time constraints, in combination with the limited computational resources we possessed, forced us to focus this project on a single extension, that of circular convolution flows. However, in our reading prior to completing the project, we came across a variety of other directions in which we could extend the paper’s results. What follows is a summary of some of these ideas, grouped by the part of the paper which they would have to modify.

4.1.1 Different Types of Flows

In our project we considered the two different types of linear flows in section 2.3, as well as NICE in section 2.4. However, there has been lots of ongoing research on flows in recent years, so a possible extension would be to experiment with these and compare the results to the ones from the paper.

Infinitesimal (Continuous) Flows

To begin with, one can consider what happens if we allow for the length of the flows to tend to infinity. Such flows are called infinitesimal flows. Even though they are mentioned in [11], there is no related experiment discussed, and they serve mostly as a theoretical guarantee for the correctness of the normalizing flows framework. However, these can be modeled as partial differential equations and studied in more depth (see [12]).

Autoregressive Flows

Another emerging category of flows is that of autoregressive flows [7], where each dimension of a vector variable is being conditioned on the previous dimensions. Some instances of autoregressive flows in literature are Masked Autoregressive Flows (MAF)[10] and Inverse Autoregressive Flows (IAF) [7].

4.1.2 Additional Datasets

The paper provided comparison and extensive experimenting only on the MNIST dataset, so an obvious extension would be to use different datasets. CIFAR-10 is already discussed in the paper, so given more computational resources we would have liked to build models on that and compared them. Having completed this, it would also make sense to proceed with more complex image datasets of higher data dimensionality, such as ImageNet32 and ImageNet64.

4.1.3 Alternatives to the loss function

Finally, we could have trained our models with different loss functions. Most work has been done in loss functions optimized by minimization of the Kullback-Leibler divergence, similarly what we did in this report. However, there is work on different approaches, see [4] and [1].

References

- [1] Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, page 214–223. JMLR.org, 2017.
- [2] Christopher M. Bishop. *Pattern Recognition and Machine Learning (Information Science and Statistics)*. Springer-Verlag, Berlin, Heidelberg, 2006.
- [3] Laurent Dinh, David Krueger, and Yoshua Bengio. Nice: Non-linear independent components estimation, 2014.
- [4] Aditya Grover, Manik Dhar, and Stefano Ermon. Flow-gan: Combining maximum likelihood and adversarial learning in generative models, 2017.
- [5] Matt Hoffman, David M. Blei, Chong Wang, and John Paisley. Stochastic variational inference, 2012.
- [6] Mahdi Karami, Dale Schuurmans, Jascha Sohl-Dickstein, Laurent Dinh, and Daniel Duckworth. Invertible convolutional flow. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.
- [7] Durk P Kingma, Tim Salimans, Rafal Jozefowicz, Xi Chen, Ilya Sutskever, and Max Welling. Improved variational inference with inverse autoregressive flow. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016.
- [8] Ivan Kobyzev, Simon J.D. Prince, and Marcus A. Brubaker. Normalizing flows: An introduction and review of current methods. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 43(11):3964–3979, nov 2021.
- [9] Yann LeCun and Corinna Cortes. The MNIST database of handwritten digits. 1998.
- [10] George Papamakarios, Theo Pavlakou, and Iain Murray. Masked autoregressive flow for density estimation. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

- [11] Danilo Jimenez Rezende and Shakir Mohamed. Variational inference with normalizing flows, 2015.
- [12] Max Welling and Yee Whye Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th International Conference on International Conference on Machine Learning*, ICML’11, page 681–688, Madison, WI, USA, 2011. Omnipress.