

Aim: Writing script.

1.nano filename.csv:

OUTPUT:

```
[cloudera@quickstart ~]$ nano student.csv
```

```
1, Rohit, 10
2, Zameer, 20
3, Jay, 30
4, Aditya, 40
5, Aayush, 50
```

2.nano load_data.pig:

OUTPUT:

```
[cloudera@quickstart ~]$ nano load_data.pig
```

```
data = LOAD 'student.csv' USING PigStorage(',');
DUMP data;
```

3.pig -x local load_data.pig:

OUTPUT:

```
[cloudera@quickstart ~]$ pig -x local load_data.pig
```

```
2025-11-27 01:33:52,840 [main] INFO org.apache.pig.backend.hadoop.executionengine.util.MapRedUtil - Total input paths to process : 1
(1, Rohit, 10)
(2, Zameer, 20)
(3, Jay, 30)
(4, Aditya, 40)
(5, Aayush, 50)
```

4.Sorting data by descending order with help of Marks.

OUTPUT:

```
[cloudera@quickstart ~]$ nano load_data.pig
```

```
data = LOAD 'student.csv' USING PigStorage(',') AS (RollNo:int, Name:chararray, Marks:int);
sorted_data = ORDER data By Marks DESC;
DUMP sorted_data;
```

OUTPUT:

```
[cloudera@quickstart ~]$ pig -x local load_data.pig
```

```
2025-11-27 01:39:43,716 [main] INFO org.apache.pig.backend.hadoop.executionengine.util.MapRedUtil - Total input paths to process : 1
(5, Aayush, 50)
(4, Aditya, 40)
(3, Jay, 30)
(2, Zameer, 20)
(1, Rohit, 10)
```

5.Sorting data whose Marks are less than a specified range.

OUTPUT:

```
[cloudera@quickstart ~]$ nano load_data.pig
```

```
data = LOAD 'student.csv' USING PigStorage(',') AS (RollNo:int, Name:chararray, Marks:int);
passed = FILTER data By Marks >20;
passed_names = FOREACH passed GENERATE Name, Marks;
passed_count = FOREACH (GROUP passed ALL) GENERATE COUNT(passed);
DUMP passed_count;
DUMP passed_names;
```

OUTPUT:

```
[cloudera@quickstart ~]$ pig -x local load_data.pig
```

```
log4j:WARN No appenders could be found for logger (org.apache.hadoop.util.Shell).
```

```
2025-11-27 01:46:02,281 [main]
```

```
( Jay, 30)
( Aditya, 40)
( Aayush, 50)
```

```
[cloudera@quickstart ~]$
```