

Aim: Write and execute Pig script to load data into a pig relation without a schema.

1.Pig script without schema.

OUTPUT:

```
[cloudera@quickstart ~]$ nano student.csv
[cloudera@quickstart ~]$ nano load_data.pig
data = LOAD 'student.csv' USING PigStorage(',');
DUMP data;

[cloudera@quickstart ~]$ pig -x local load_data.pig

(1, Rohit, 10)
(2, Zameer, 20)
(3, Jay, 30)
(4, Aditya, 40)
(5, Aayush, 50)
[cloudera@quickstart ~]$
```

2.Creating a csv with some missing values.

OUTPUT:

```
[cloudera@quickstart ~]$ nano student.csv
[cloudera@quickstart ~]$ nano load_data.pig
[cloudera@quickstart ~]$ pig -x local load_data.pig

1, Rohit, 10
, Zameer, 20
3, Jay, 30
Aditya, 4, 40
5, Aayush, 50
```

3.Pig script with schema.

OUTPUT:

```
[cloudera@quickstart ~]$ nano student.csv
[cloudera@quickstart ~]$ nano load_data.pig
data = LOAD 'student.csv' USING PigStorage(',') AS (id:int, name:chararray, marks:int);
DUMP data;

[cloudera@quickstart ~]$ pig -x local load_data.pig

(1, Rohit,10)
(, Zameer,20)
(3, Jay,30)
(, 4,40)
(5, Aayush,50)
[cloudera@quickstart ~]$
```

4.Pig script for sorting data.**OUTPUT:**

```
[cloudera@quickstart ~]$ nano student.csv
[cloudera@quickstart ~]$ nano load_data.pig
data = LOAD 'student.csv' USING PigStorage(',') AS (id:int, name:chararray, marks:int);
sorted_data = ORDER data By marks DESC;
DUMP sorted_data;
[cloudera@quickstart ~]$ pig -x local load_data.pig
(5, Aayush,50)
(4, 4,40)
(3, Jay,30)
(2, Zameer,20)
(1, Rohit,10)
[cloudera@quickstart ~]$
```

5.Pig script for filtering data.**OUTPUT:**

```
[cloudera@quickstart ~]$ nano student.csv
[cloudera@quickstart ~]$ nano load_data.pig
data = LOAD 'student.csv' USING PigStorage(',') AS (id:int, name:chararray, marks:int);
passed = FILTER data By marks>30;
passed_names = FOREACH passed GENERATE name, marks;
passed_count = FOREACH (GROUP passed ALL) GENERATE COUNT(passed);
DUMP passed_count;
DUMP passed_names;
[cloudera@quickstart ~]$ pig -x local load_data.pig
-----,-----
(4,40)
(Aayush,50)
[cloudera@quickstart ~]$
```