

Aim: Alter and Deleting table in HBase.**1.Displaying the HBase table.****OUTPUT:**

```
hbase(main):020:0> scan 'stud'
ROW                                COLUMN+CELL
row1                               column=Age:, timestamp=1768269904518, value=45
row1                               column=Gender:, timestamp=1768269940607, value=M
row1                               column=Name:, timestamp=1768269850150, value=Steve
row2                               column=Age:, timestamp=1768269910395, value=40
row2                               column=Gender:, timestamp=1768269946556, value=F
row2                               column=Name:, timestamp=1768269859194, value=Alex
row3                               column=Age:, timestamp=1768269918104, value=100
row3                               column=Gender:, timestamp=1768269952573, value=M
row3                               column=Name:, timestamp=1768269871597, value=Dex
row4                               column=Age:, timestamp=1768269924584, value=15
row4                               column=Gender:, timestamp=1768269957037, value=M
row4                               column=Name:, timestamp=1768269880394, value=Ghost
row5                               column=Age:, timestamp=1768269929899, value=55
row5                               column=Gender:, timestamp=1768269962534, value=M
row5                               column=Name:, timestamp=176826988575, value=Zombie
5 row(s) in 0.0980 seconds
```

2.Altering the table: alter 'table_name', 'alias_colname'**OUTPUT:**

```
hbase(main):022:0> alter 'stud', 'name'
Updating all regions with the new schema...
0/1 regions updated.
1/1 regions updated.
Done.
0 row(s) in 3.0820 seconds
```

3.Inserting values in the new column family: put 'table_name', 'row(n)', 'alias:column_family', 'value'**OUTPUT:**

```
hbase(main):027:0> put 'stud', 'row1', 'name:Address', 'London'
0 row(s) in 0.0040 seconds

hbase(main):028:0> put 'stud', 'row2', 'name:Address', 'London'
0 row(s) in 0.0080 seconds

hbase(main):029:0> put 'stud', 'row3', 'name:Address', 'Mumbai'
0 row(s) in 0.0080 seconds

hbase(main):030:0> put 'stud', 'row4', 'name:Address', 'Mumbai'
0 row(s) in 0.0080 seconds

hbase(main):031:0> put 'stud', 'row5', 'name:Address', 'China'
0 row(s) in 0.0070 seconds
```

4.Displaying the table with the new column family: scan 'table_name'**OUTPUT:**

```
hbase(main):032:0> scan 'stud'
ROW                                COLUMN+CELL
row1                               column=Age:, timestamp=1768269904518, value=45
row1                               column=Gender:, timestamp=1768269940607, value=M
row1                               column=Name:, timestamp=1768269850150, value=Steve
row1                               column=name:Address, timestamp=1768271502754, value=London
row2                               column=Age:, timestamp=1768269910395, value=40
row2                               column=Gender:, timestamp=1768269946556, value=F
row2                               column=Name:, timestamp=1768269859194, value=Alex
row2                               column=name:Address, timestamp=1768271511358, value=London
row3                               column=Age:, timestamp=1768269918104, value=100
row3                               column=Gender:, timestamp=1768269952573, value=M
row3                               column=Name:, timestamp=1768269871597, value=Dex
row3                               column=name:Address, timestamp=1768271523713, value=Mumbai
row4                               column=Age:, timestamp=1768269924584, value=15
row4                               column=Gender:, timestamp=1768269957037, value=M
row4                               column=Name:, timestamp=1768269880394, value=Ghost
row4                               column=name:Address, timestamp=1768271531492, value=Mumbai
row5                               column=Age:, timestamp=1768269929899, value=55
row5                               column=Gender:, timestamp=1768269962534, value=M
```

5.Deleting specific row from the table: delete 'table_name', 'row(n)', 'column_name'

OUTPUT:

```
hbase(main):033:0> delete 'stud', 'row3', 'Gender'
0 row(s) in 0.0690 seconds
```

6.Displaying the changed table: scan 'table_name'

OUTPUT:

```
hbase(main):034:0> scan 'stud'
ROW                                COLUMN+CELL
row1                                column=Age:, timestamp=1768269904518, value=45
row1                                column=Gender:, timestamp=1768269940607, value=M
row1                                column=Name:, timestamp=1768269850150, value=Steve
row1                                column=name:Address, timestamp=1768271502754, value=London
row2                                column=Age:, timestamp=1768269910395, value=40
row2                                column=Gender:, timestamp=1768269946556, value=F
row2                                column=Name:, timestamp=1768269859194, value=Alex
row2                                column=name:Address, timestamp=1768271511358, value=London
row3                                column=Age:, timestamp=1768269918104, value=100
row3                                column=Name:, timestamp=1768269871597, value=Dex
row3                                column=name:Address, timestamp=1768271523713, value=Mumbai
row4                                column=Age:, timestamp=1768269924584, value=15
row4                                column=Gender:, timestamp=1768269957037, value=M
row4                                column=Name:, timestamp=1768269880394, value=Ghost
row4                                column=name:Address, timestamp=1768271531492, value=Mumbai
row5                                column=Age:, timestamp=1768269929899, value=55
row5                                column=Gender:, timestamp=1768269962534, value=M
row5                                column=Name:, timestamp=1768269888575, value=Zombie
row5                                column=name:Address, timestamp=1768271574542, value=China
5 row(s) in 0.0440 seconds
```