

Aim: Table creation in Hive.

1.Starting Hive shell: hive shell

OUTPUT:

```
[cloudera@quickstart ~]$ hive shell
Logging initialized using configuration in file:/etc/hive/conf.dist/hive-log4j.properties
WARNING: Hive CLI is deprecated and migration to Beeline is recommended.
```

2.Creating database and using that database: create database name_of_database; & USE database_name;

OUTPUT:

```
hive> create database stud
> ;
OK
Time taken: 0.474 seconds
hive> USE stud
> ;
OK
Time taken: 0.047 seconds
```

3.Creating table: create table table_name(col_name1 datatype, col_name2 datatype,, n);

OUTPUT:

```
hive> create table info(id INT, name String, age INT);
OK
Time taken: 0.343 seconds
```

4.Inserting values in the table: insert into table_name values(value1, value2,, n);

OUTPUT:

```
hive> insert into info VALUES(1, 'Aayush', 20);
Query ID = cloudera_20260112183939_7680dead-5b77-4e93-acf1-4e81264a1e35
Total jobs = 3
hive> insert into info VALUES(2, 'Aditya', 19), (3, 'Jay', 19);
Query ID = cloudera_20260112184040_55d88bb9-2f26-4f7e-9a92-8db8a18d2f7a
Total jobs = 3
```

5.Selecting values from the table: select * from table_name;

OUTPUT:

```
hive> select * from info;
OK
1      Aayush  20
2      Aditya  19
3      Jay     19
Time taken: 0.103 seconds, Fetched: 3 row(s)
```