

Introduction on how to use API's to retrieve datasets for using in analyzing software

Authors: Marcus Guderle

Contact ATTO Data Management Team: attodbm@mpi-mail.mpg.de

1 Overview

The term API is the short form of "application programming interface". The use of APIs offers a tool to create an interface between an analysis software like R or a browser and the database, where the content is dynamically integrated into the own program. The API is a machine-readable interface tailored for software. Particularly in the ATTO Data Portal, data sets and metadata information can be exchanged quickly in a particularly easy to process and reduced form by using APIs.

Note: Only primary data can be queried via APIs to which the respective user has read permission. In the following HowTo we first give an introduction to the API usage on the ATTO Data Portal. It shows how the APIs can be tested and applied and how the queries are made via the browser.

In the second part rBexis is introduced, an R-Package which has been developed especially for querying data sets between R and Bexis instances.

2 Application of APIs

Every registered user can use APIs and gets a personal token, which is directly linked to the user account. This token is needed to query datasets via APIs. You can find the respective token by clicking on your username in the upper right corner of the menu. A drop-down menu will open where you can click on "Token" (Figure 1).




Figure 1: Drop-down menu for personal user "Profile", "Token", "Api" and to log off.

If you click on "Token" a new page will open with your personalized 65 character long token (Figure 2). First copy it into the cache.




Figure 2: Personalized 65 character long token

As mentioned earlier, APIs provide an interface to the database, which is mainly text-based. While using special software/online applications, the application of APIs can also be visualized. The Swagger UI, which can be used via any browser software, was integrated for testing requests of the ATTO APIs. Swagger can be accessed from the user drop-down menu by clicking on "API" (Figure 3).





Figure 3: Link to the Swagger UI for browser application is provided in the user drop-down menu via "API"

You will now be directed to the ATTO-Swagger interface. First you have to copy your token (Figure 2) into the field "Jason Web Token" and click on the "Explore" button (Figure 4).

On the Swagger page you can see three categories: Data, Metadata and Structures. Click on the category to open the submenu. In each category there are two requests; one for a list of information about all existing datasets and one for information for specific datasets via the respective ID. The respective operations can be expanded either by clicking on "Get", on "/api/..." or on "Expand Operations".

 **swagger**

https://www.attodata.org/swagger/docs/v1

JSON Web Token

Explore

Bexis 2 API's

AttachmentOut	Show/Hide	List Operations	Expand Operations
AttachmentIn	Show/Hide	List Operations	Expand Operations
DataOut	Show/Hide	List Operations	Expand Operations
DataIn	Show/Hide	List Operations	Expand Operations
DataQualityOut	Show/Hide	List Operations	Expand Operations
DatasetOut	Show/Hide	List Operations	Expand Operations
DatasetIn	Show/Hide	List Operations	Expand Operations
DataStatisticOut	Show/Hide	List Operations	Expand Operations
MetadataOut	Show/Hide	List Operations	Expand Operations
MetadataIn	Show/Hide	List Operations	Expand Operations
Structures	Show/Hide	List Operations	Expand Operations
Token	Show/Hide	List Operations	Expand Operations

[BASE URL: , API VERSION: v1]


INVALID 

Figure 4: Categories for API queries on the ATTO Swagger Browser Interface