

Pytest

@__mharrison__



pytest

pytest

- Easy test creation (less boilerplate)
- Test runner
- Test selection
- Test parameterization
- Fixtures
- Plugins

Installation

Create a virtualenv

```
(venv) $ pip install pytest
```

Command line

Installs an executable called `py.test` (previously part of `py` library). With 3.0 can run `pytest` or `py.test`

Basics

Code Layout

```
Project/  
  proj/  
    __init__.py  
    adder.py  
tests/  
  conftest.py  
  testadder.py
```

Simple Code

Basic but fits on slides (adder.py)

```
# adder.py
def adder(x, y):
    return x + y
```

Test Creation

Unittest style (testadder.py)

```
# testadder.py
from proj.adder import adder
import unittest

class TestAdder(unittest.TestCase):
    def test_simple(self):
        res = adder(2, 3)
        self.assertEqual(res, 5)
```

Run Tests

```
$ PYTHONPATH=. pytest tests/*.py
===== test session starts =====
platform darwin -- Python 3.6.4, pytest-3.0.6, py-
1.4.32, pluggy-0.4.0
rootdir: /Users/matt/code_samples/pytest, infile:
plugins: asyncio-0.8.0
collected 1 items

tests/testadder.py .

===== 1 passed in 0.01 seconds =====
```

Unittest style

- Non-PEP 8 compliant
- "Classy"
- Need to remember which assert... method to call

Test Creation

pytest style (testadder2.py)

```
# testadder2.py
from proj.adder import adder

def test_add():
    res = adder(2, 3)
    assert res == 5
```

pytest style

- Just a function that starts with "test"
- Use the `assert` statement

More Test Creation

Can specify a message

```
from proj.adder import adder

def test_add():
    res = adder(2, 3)
    assert res == 5, "Value should be 5"
```

Catching Exceptions

Can specify an exception

```
import pytest
def test_exc():
    with pytest.raises(TypeError):
        adder('', 3)
```

Catching Exceptions (2)

Can specify an exception in decorator

```
@pytest.mark.xfail(raises=TypeError)
def test_exc2():
    adder('', 3)
```

Failing a Test

```
def test_missing_dep():
    try:
        import foo
    except ImportError:
        pytest.fail("No foo import")
```

Approximations

```
def test_small():
    assert adder(1e-10, 2e-10) == \
        pytest.approx(3e-10)
```

How assert works

pytest uses an *import hook* (PEP 302) to rewrite assert statements by introspecting code (AST) the runner has collected.

Care needed

Don't wrap assertion in parentheses (truthy tuple):

```
def test_almost_false():
    assert (False == True, 'Should be false')
```

Care needed (2)

You will get a warning:

```
$ py.test testadder.py
testadder.py s..x [100%]

===== warnings summary =====
testadder.py:15
  assertion is always true, perhaps remove parentheses?

-- Docs: http://doc.pytest.org/en/latest/warnings.html
  2 passed, 1 skipped, 1 xfailed, 1 warnings in 0.11
seconds
```

Context-sensitive Comparisons

- Inlining function/variable results
- Diffs in similar text
- Lines in multiline texts
- List/Dict/Set diffs (-vv for full diff)
- In `(__contains__)` statements

Customize Assert

In conftest.py:

```
def pytest_assertrepr_compare(op, left, right):
    if (isinstance(left, str) and
        isinstance(right, int) and op == '=='):
        return ["'{}' should be an int".format(left)]
```

In testadder.py:

```
def test_custom():
    assert "1" == 1
```

Result

```
$ py.test testadder.py
testadder.py F.x [100%]

===== FAILURES =====
----- test_custom -----
----- test_custom -----  
  
def test_custom():
>     assert "1" == 1
E     assert "1" should be an int  
  
testadder.py:11: AssertionError
===== 1 failed, 1 passed, 1 xfailed in 0.08 seconds =====
```

Test Runner

Test Runner

For unittest add:

```
if __name__ == '__main__':
    unittest.main()
```

or run:

```
$ python3 -m unittest testadder.TestAdder
```

Test Runner

For pytest add:

```
if __name__ == '__main__':
    import pytest
    pytest.main()
```

or run:

```
$ py.test testadder2.TestAdder
```

Test Discovery

- Recurse current directory or testpaths from `pytest.ini`
- Files with `test_*.py` or `*_test.py`
- Functions starting with `test_*`
- Methods starting with `test_*` in class named `Test*` without a `__init__` method

Can customize

- `--ignore path` - Tell pytest to ignore modules or paths
- `norecursedirs` - Dirs to not recurse in `pytest.ini`
- `python_files` - Glob (`validate_*.py`) to discover in `pytest.ini`
- `python_classes, python_methods` - More discovery

Options

- `--doctest-modules` - Run doctests
- `--doctest-glob='*.rst'` - Capture rst files (instead of default `*.txt`)
- `--pdb` - Drop into debugger on fail
- `--collect-only` - Don't run tests, just collect
- `-v` - Verbose (show test ids)
- `-m EXPR` - Run marks
- `-k EXPR` - Run tests with names
- `NODE IDS` - Run tests with NODE IDS

Debugging

Debugging

Options:

- `import pdb;pdb.set_trace()`
- `assert 0` (in code) + `--pdb` (command line)
- Use `-s` to see `stdout` for successful tests

Doctest

Doctest

Update `pytest.ini` to permanently run doctests, with certain flags:

```
[pytest]
addopts = --doctest-modules

doctest_optionflags= NORMALIZE_WHITESPACE
IGNORE_EXCEPTION_DETAIL
```

Doctest

Can use pytest fixtures with `get_fixture`:

```
# file.py
"""
>>> req = get_fixture('request')
>>> req.cache.get('bad_key')
None
"""
```

Injecting into Namespace

Python module that we typically import with shortened name `lf`:

```
# longfilename.py
"""
>>> lf.foo()
"""

def foo(): pass

# confest.py
import longfilename
@pytest.fixture(autouse=True)
def add_lf(doctest_namespace):
    doctest_namespace['lf'] = longfilename
```

Test Selection & Marking

Listing Tests

```
$ PYTHONPATH=./ pytest tests/*.py --collect-only
===== test session starts =====
platform darwin -- Python 3.6.4, pytest-3.0.6, py-
1.4.32, pluggy-0.4.0
rootdir: /Users/matt/code_samples/pytest/Project,
ini file:
plugins: asyncio-0.8.0
collected 1 items
<Module 'tests/testadder.py'>
  <Function 'test_add'>

===== no tests ran in 0.00 seconds =====
```

Test Selection

- Marking tests
- Skip tests

Marking Tests

```
@pytest.mark.small  
@pytest.mark.num  
def test_ints():  
    assert adder(1, 3) == 4
```

Marking Tests

```
$ py.test -m num
```

or

```
$ py.test -m "not num"
```

Named Tests

To run tests with "int" in name:

```
$ py.test -k int
```

Skipping tests

```
@pytest.mark.skipif(  
    not os.environ.get("SLOWTEST"),  
    reason="Don't run slow tests")  
def test_big():  
    assert adder(1e10, 3e10) == 4e10
```

Test Parameterization

Test Parameterization

```
@pytest.mark.parametrize('x, y, z', [  
    (1, 2, 3), # first  
    (-1, -2, -3), # neg  
    (0, 0, 0)]) # test 0s  
def test_add2(x, y, z):  
    assert adder(x, y) == z
```

Test Parameterization

Note that the Node Ids change:

```
$ PYTHONPATH=./ pytest tests/*.py -v
===== test session starts =====
platform darwin -- Python 3.6.4, pytest-3.0.6, py-1.4.32, pluggy-0.4.0 --
/Users/matt/.env/36/bin/python3
cachedir: .cache
rootdir: /Users/matt/code_samples/pytest/Project, configparser:
plugins: asyncio-0.8.0
collected 5 items

tests/testadder.py::test_ints PASSED
tests/testadder.py::test_big SKIPPED
tests/testadder.py::test_add2[1-2-3] PASSED
tests/testadder.py::test_add2[-1--2---3] PASSED
tests/testadder.py::test_add2[0-0-0] PASSED

===== 4 passed, 1 skipped in 0.03 seconds =====
```

Fixtures

Fixtures

Provides dependency injection of setup / teardown

Fixtures

```
@pytest.fixture
def large_num():
    return 1e20

def test_large(large_num):
    assert adder(large_num, 1) ==
large_num
```

Fixtures Parameterization

```
@pytest.fixture(params=[-1, 0, 100])
def num(request):
    return request.param

def test_num(num_num):
    assert adder(num, 1) == num+1
```

Method Fixtures

```
class TestAdder:

    @pytest.fixture
    def other_num(self):
        return 42

    def test_other(self, other_num):
        assert adder(other_num, 1) == 43
```

Module Level

```
def setup_module(module):
```

```
    ...
```

```
def teardown_module(module):
```

```
    ...
```

Class Level

```
class TestFoo:  
    @classmethod  
    def setup_class(cls):  
        ...  
  
    @classmethod  
    def teardown_class(cls):  
        ...
```

Method Level

```
class TestFoo:  
    def setup_method(self, method):  
        ...  
  
    def teardown_method(self, method):  
        ...
```

Function Level

```
def setup_function(function):  
    ...
```

```
def teardown_function(function):  
    ...
```

Teardown in Fixtures

- Use request fixture and call
`request.addfinalizer(fn)`
- Use generator

request

Some parts of the request content:

- `r.addfinalizer(f)` - call when done
- `r.applymarker(m)` - dynamically add marker
- `r.config` - pytest config
- `r.keywords` - keywords and markers
- `r.param` - value of parameterization

Finalizer

```
@pytest.fixture
def db_num(request):
    # connect to db
    num = db.get()
    def fin():
        db.close()
    request.addfinalizer(fin)
    return num
```

Note - can have more than one finalizer function

Generator

```
@pytest.fixture
def db_num(request):
    # connect to db
    num = db.get()
    yield num
    db.close()
```

Generator

Code smell:

```
from contextlib import closing
```

```
@pytest.fixture
def db_num(request):
    # connect to db
    with closing(get_db()) as db:
        num = db.get()
    yield num
```

Fixture Scope

- session - Once per test session
- module - Once per module
- class - Once per test class
- function - Once per test function (default)

Fixture Scope

```
@pytest.fixture(  
    scope='session')  
def start_time():  
    import time  
return time.time()
```

Fixture Scope

```
@pytest.fixture(  
    scope='session')  
def session_db():  
    db = get_db()  
    yield db  
    db.close()
```

Fixture Scope

```
from contextlib import closing

@pytest.fixture(
    scope='session')
def session_db():
    with closing(get_db()) as db:
        yield db
```

Fixture Scope

Finer grained scope can depend on larger grain,
but reverse is not true

Fixture Scope

```
# bad fixture depend
@pytest.fixture(scope='function')
def two():
    return 2

@pytest.fixture(scope='session')
def four(two):
    return two * two

def test4(four):
    assert four == 4
```

Fixture Scope

```
===== ERRORS =====
----- ERROR at setup of test4 -----
ScopeMismatch: You tried to access the 'function'
scoped fixture 'two' with a 'session' scoped
request object, involved factories
tests/testadder.py:45: def four(two)
tests/testadder.py:41: def two()
== 6 passed, 1 skipped, 1 error in 0.03 seconds ==
```

Trigger skip from fixture

```
@pytest.fixture
def db_num(request):
    # connect to db
    try:
        num = db.get()
        return num
    except ConnectionError:
        pytest.skip("No DB")
```

Pass data from marks to fixtures

```
@pytest.fixture
def db_con(request):
    name = request.node.get_marker('pg_db')
    return psycopg2.connect("dbname={}".format(
        name))

@pytest.mark.pg_db('test')
def test_pg(db_con):
    # select from test db
```

Skip tests on Mac

Use `autouse=True` to implicitly enable

```
@pytest.mark.nomac
def test_add_nomac():
    # ...

@pytest.fixture(autouse=True)
def skip_mac(request):
    mark = request.node.get_marker('nomac')
    if mark and sys.platform == 'darwin':
        pytest.skip('Skip on Mac')
```

Configuration

Configuration

- Rootdir
 - Node ids determined from root
 - Plugins may store data there
- `pytest.ini` (or `tox.ini` or `setup.cfg`)
 - Must have `[pytest]` section

Some INI Options

- `minversion = 4.0` - Fail if pytest < 4.0
- `adopts = -v` - Add verbose flag
- `norecursedirs = .git` - Don't look in .git directory
- `testpaths = regression` - Look in regression folder if no locations specified on command
- `python_files = regtest_*.py` - Execute files starting with regtest_ (test_*.py and *_test.py default)
- `python_classes = RegTest*` - Use class starting with RegTest as a test (default Test*)
- `python_functions = *_regtest` - Use function ending with regtest as test (default _test)

Conftest

Can create a `conftest.py` in a root directory or subdirectory. You can put fixtures in here. You don't import this module. Pytest loads it for you

Plugins

You can have local plugins and installable plugins

Many Hooks

- Bootstrap - for setup.py plugins
- Initialization hooks - for conftest.py
- runtest hooks - for execution
- Collection hooks
- Reporting hooks
- Debugging hooks

Examples

- `pytest_adoption(parser)`
- `pytest_ignore_collect(path, config)`
- `pytest_sessionstart(session)`
- `pytest_sessionfinish(session, exitstatus)`
- `pytest_assertrepr_compare(config, op, left, right)`

https://docs.pytest.org/en/latest/writing_plugins.html#writing-hook-functions

Plugin Boilerplate

<https://github.com/pytest-dev/cookiecutter-pytest-plugin>

Installable Plugin

Need to implement `pytest11` entrypoint in `setup.py`, so `pytest` finds it.

Installable Plugin

```
entry_points={  
    'pytest11': [  
        'pytest_cov = pytest_cov.plugin',  
    ],  
    'console_scripts': [  
    ]  
},
```

<https://github.com/pytest-dev/pytest-cov/blob/master/setup.py>

Installable Plugin

```
def pytest_addoption(parser):
    # Register argparse and INI options

@pytest.mark.tryfirst
def pytest_load_initial_conftests(early_config, parser,
args):
    # Bootstrap setuptools plugin

def pytest_configure(config):
    # Perform initial configuration

https://github.com/pytest-dev/pytest-cov/blob/master/src/pytest\_cov/plugin.py
```

Adding Commandline Options

In conftest.py:

```
def pytest_addoption(parser):
    parser.addoption('--mac', action='store_true',
                     help='Run Mac tests')
```

In tests:

```
@pytest.fixture
def a_fixture(request):
    mac = request.config.getoption('mac')

def test_foo(pytestconfig):
    mac = pytestconfig.getoption('mac')
```

3rd Party Plugins

List

Python 2 & 3 compatibility

<http://plugincompat.herokuapp.com/>

pytest-xdist

Distribute tests among (7) CPUs

```
$ pip install pytest-xdist  
$ py.test -n 7
```

pytest-flake8

Run flake8 on all py files

```
$ pip install pytest-flake8  
$ py.test --flake8
```

pytest-cov

Run coverage

```
$ pip install pytest-cov  
$ py.test --cov=add tests/
```

Tox

Tox

3rd party tool for running tests on different pythons

Install

```
pip install tox
```

Configuration

```
# tox.ini
[tox]
envlist = py27,py36
[testenv]
deps=pytest # use pytest
commands=pytest
```

Configuration

Run `tox-quickstart` to generate config for you

Running

At this point, if you run `tox`, it will:

- Create Python 2.7 venv
 - Install pytest
 - Create sdist and install package
 - Run package tests with pytest
- Create Python 3.6 venv
 - Install pytest
 - Create sdist and install package
 - Run package tests with pytest

Jenkins CI

Can integrate with Jenkins by having Tox installed and having pytest output JunitXML files (with the --junitxml option)

CircleCI

Contents of `circle.yml`:

```
dependencies:
```

```
  pre:
```

- pip install tox

```
test:
```

```
  override:
```

- tox

Thanks

Go forth and test!