

ESO 208A

Computational Method in Engineering

Lecture 05

Summary

- Computational methods cannot be studied in isolation of the problem

“The purpose of computing is insight, not numbers”, Hamming

- Significant digits/figures are the numbers that one can use with confidence

Example: $d = 100 \pm 1$ m, $t = 3.0 \pm 0.1$ s, $v = d/t = ?$

- True error = True value – Measured/Computed value
 - approximate error
 - error bound


True error is never known

Summary

- Types of error
 - Model error
 - Data error
 - **Truncation error**
 - **Round-off error**

Computers are finite


Floating point number representation



Real number in Maths and Computer are not the same

Round-off errors can be avoided subtraction of nearly equal nos.

Forward error analysis



Condition number of the problem


$$C_p = \frac{\text{Relative error in } f(x)}{\text{Relative error in } x} = \frac{\Delta f(x)/f(x)}{\Delta x/x} = \left| \frac{xf'(x)}{f(x)} \right|$$

$C_p \leq 1$ - well-conditioned problem

$C_p > 1$ - ill-conditioned problem

Characteristic of the problem

Backward error analysis



Condition number of the algorithm

$$\left| \frac{x - x_A}{x} \right| \leq C_A u \quad u \text{ is machine precision}$$

Characteristic of the numerical stability of the algorithm

small C_A - stable algorithm

large C_A - instable algorithm

Total error in Output

$$\left| \frac{f(x) - f_A(x + \Delta x)}{f(x)} \right| \leq C_p \left(\frac{\Delta x}{x} + C_A u \right)$$

Announcements

- First computer assignment
- Tutorial on Matlab
- Access to Brihaspati: Course TA: pramods@