بسم الله الرحمن الرحيم

تكنولوژي كامپيوتر

جلسهی بیست و یکم کاساندرا

جلسه گذشته

جلسهی جدید

تاریخچه CASSANDRA

Cassandra History

- Summer 2007: start a distributed inbox search on Facebook
- July 2008: Facebook publishes the code under the name Cassandra
- March 2009: The project enters the Apache Incubator
- Sept 2013 v2.0
- 2021 4.0 GA "Stability First"
- 2024 | 5.0 GA Al-era Features

Cassandra

- Full multi-primary database replication
- Global availability at low latency
- Scaling out on commodity hardware
- Linear throughput increase with each additional processor
- Online load balancing and cluster growth
- Partitioned key-oriented queries
- Flexible schema

Cassandra

- Distribution & scale-out
 - Master-less, shared-nothing architecture every node is equal.
 - Virtual nodes (vnodes) slice the ring into hundreds of tiny token ranges, so adding/removing a node only streams a small fraction of data.
 - Elastic multi-datacenter replication with rack-aware placement

Cassandra

- High availability
 - No single point of failure; automatic fail-over.
 - CAP Theorem: AP but tunable consistency
- Consistency options
 - Tunable consistency on every read/write (ANY \rightarrow ALL)
 - Lightweight transactions (LWT) with Paxos for linearizable compare-and-set updates

CASE STUDIES

https://cassandra.apache.org/_/case-studies.html



Ably

Apache Cassandra is trusted to scale at internet level and designed to scale without limits. Which is why, at Ably Realtime, we use Cassandra for our persistent storage of messages.

READ MORE

ACTIVISION.

Activision

Activision built a new system to message players with highly personalised communication. It used large amounts of real-time data and was built with Apache Cassandra

READ MORE



AdStage

AdStage is constantly monitoring performance trends and optimizing campaigns on behalf of advertisers. Apache Cassandra delivered the operational speed the company needed to ensure that the platform has low latency and the required throughput.

READ MORE

AIR SHIP

Airship

Where we originally stored device data in a set of Postgres shards, our scale quickly outpaced our capacity to add new shards, so we moved to a multiple database architecture using HBase and Cassandra.

Apple





Apple

A year ago, Apple said that it was running over 75,000 Cassandra nodes, storing more than 10 petabytes of data. At least one cluster was over 1,000 nodes, and Apple regularly gets millions of operations per second (reads/writes) with Cassandra.

Backblaze

We needed something that would handle really high write throughput and keep scaling on the write throughput. That forced us to look at distributed stores, and Apache Cassandra was the option that fitted what we needed.

Bazaarvoice

EmoDB is an open source RESTful data store built on top of Cassandra that stores JSON documents and, most notably, offers a databus that allows subscribers to watch for changes to those documents in real time.

Best Buy

Best Buy uses Apache Cassandra to manage massive spikes in holiday traffic — 7x traffic spikes and bursts > 50,000 rps — and calls it "flawless."

READ MORE

READ MORE

READ MORE



Discord

Cassandra was the only database that fulfilled all of Discord's requirements, as they can add nodes to scale it and it can tolerate a loss of nodes without any impact on the application. Related data is stored contiguously on disk providing minimum seeks and easy distribution around the cluster.

READ MORE



Dream11

The company started its operations in 2008 and started offering single match fantasy sports in 2012. It is India's Biggest Sports Gaming platform with users playing Fantasy Cricket, Football, Kabaddi, Basketball & Hockey. Dream11 is the Official Fantasy partner of the VIVO Indian Premier League (IPL), International Council of Cricket (ICC)

READ MORE



eBay

A glimpse on our Cassandra deployment: Dozens of nodes across multiple clusters 200 TB+ storage provisioned 400M+ writes & 100M+ reads per day, and growing QA, LnP, and multiple Production clusters.

READ MORE

Equinix

Equinix

Equinix uses Cassandra for its ease of operation, and always-on node architecture — and its peer-to-peer architecture guarantees no single point of failure to collect and store streaming data from infrastructure instruments.



Instana

"Cassandra works well; it runs really nicely and smoothly. We've never lost data, and things are easy to fix. Quite frankly, without Cassandra, we couldn't run Instana."

READ MORE



Instagram

Constant At Instagram, we have one of the world's largest deployments of the Apache Cassandra database. We began using Cassandra in 2012 to replace Redis and support product use cases like fraud detection, Feed, and the Direct inbox.

READ MORE

Intuit Mint

Intuit Mint

Mint Bills selected Apache Cassandra to store user account data. "When you are selecting between accounts on your Mint Bills app, you are actually retrieving information from Cassandra directly," Csasznik-Shaked added

READ MORE

Intuit Turbo

Intuit Turbo Tax

Intuit is supporting over 42,000 Peak TPS in production in AWS, over eight clusters in production. Cassandra has to process massive amounts of data, such as entitlements, tax returns, filings, user experience, and everything needed to support TurboTax.

DATA STRUCTURE

Commit Log

SSTables (Sorted String Table)

Memtable





Figure 3-5. An SSTable with an in-memory index.

Memtable




Constructing and maintaining SSTables

Merging and compacting sstables

Bloom Filter

LSM Trees



DATA MODEL

- Keyspace
 - Similar to database
 - Has replication factor and replication strategy
- Table
 - Tables are composed of rows and columns

- Partition
- Row

■ Column

- Native types (Integers, Boolean, text, timestamp, ...)
- Collection (list, set, map)
- Counters (
- User defined types

- Primary Key
 - Partition Key
 - Clustering Key


CQL


- Like SQL but avoids:
 - Cross-partition transactions
 - Distributed joins
 - Foreign keys or referential integrity.

Data Modeling

- Data modeling is the process of identifying entities and their relationships
- In relational databases:
 - data is placed in normalized tables with foreign keys used to reference related data in other tables
- In Cassandra:
 - data modeling is query-driven

Conceptual data modeling





Design Differences Between RDBMS and Cassandra

- No joins
- No referential integrity
- Denormalization
- Query-first Design
- Designing for optimal storage
- Sorting is a design decision

Data Modeling in Cassandra

■ Learn more:

- https://cassandra.apache.org/doc/latest/cassandra/de veloping/data-modeling/data-modeling logical.html
- https://cassandra.apache.org/doc/latest/cassandra/de veloping/data-modeling/data-modeling physical.html
- https://cassandra.apache.org/doc/latest/cassandra/de veloping/data-modeling/data-modeling refining.html
- https://cassandra.apache.org/doc/latest/cassandra/de veloping/data-modeling/data-modeling_schema.html

GUARANTEES


- Cassandra makes the following guarantees.
 - High Scalability
 - High Availability
 - Durability
 - Eventual Consistency of writes to a single table
 - Lightweight transactions with linearizable consistency
 - Batched writes across multiple tables are guaranteed to succeed completely or not at all
 - Secondary indexes are guaranteed to be consistent with their local replicas' data

Batched Writes


The guarantee for batched writes across multiple tables is that they will eventually succeed, or none will. Batch data is first written to batchlog system data, and when the batch data has been successfully stored in the cluster, the batchlog data is removed. The batch is replicated to another node to ensure that the full batch completes in the event if coordinator node fails.

DISTRIBUTED ARCHITECTURE

Dataset Partitioning: Consistent Hashing



Dataset Partitioning: Consistent Hashing




Conflict resolution: LWW

Replication Strategy

Replica Synchronization

- Replica read repair
- Hinted Handoff
- Merkle trees

Merkle Trees



Tunable Consistency

- ONE
 - Only a single replica must respond.
- TWO
 - Two replicas must respond.
- THREE
 - Three replicas must respond.
- QUORUM
 - A majority (n/2 + 1) of the replicas must respond.

Tunable Consistency

- ALL
 - All of the replicas must respond.
- LOCAL_QUORUM
 - A majority of the replicas in the local datacenter (whichever datacenter the coordinator is in) must respond.
- EACH_QUORUM
 - A majority of the replicas in each datacenter must respond.
- LOCAL_ONE
 - Only a single replica must respond. In a multi-datacenter cluster, this also guarantees that read requests are not sent to replicas in a remote datacenter.
- ANY
 - A single replica may respond, or the coordinator may store a hint. If a hint is stored, the coordinator will later attempt to replay the hint and deliver the mutation to the replicas. This consistency level is only accepted for write operations.

Distributed Cluster Membership and Failure Detection

- Gossip
 - Send information using a vector clock
 - Every node in the Cassandra cluster runs the gossip task independently and periodically

EXAMPLE USAGE

STORAGE ATTACHED INDEX

SHOULD I USE CASSANDRA?