Forces between magnets and multipole arrays of magnets

Will Robertson

December 2, 2009

magnetforces

1. About this file. This is a 'literate programming' approach to writing Matlab code using MATLABWEB[1]. To be honest I don't know if it's any better than simply using the Matlab programming language directly. The big advantage for me is that you have access to the entire LaTeX document environment, which gives you access to vastly better tools for cross-referencing, maths typesetting, structured formatting, bibliography generation, and so on.

The downside is obviously that you miss out on Matlab's IDE with its integrated M-Lint program, debugger, profiler, and so on. Depending on one's work habits, this may be more or less of limiting factor to using literate programming in this way.

[1] http://tug.ctan.org/pkg/matlabweb

2. This work consists of the source file `magnetforces.web` and its associated derived files. It is released under the Apache License v2.0.[2]

This means, in essense, that you may freely modify and distribute this code provided that you acknowledge your changes to the work and retain my copyright. See the License text for the specific language governing permissions and limitations under the License.

3. Calculating forces between magnets. This is the source of some code to calculate the forces and/or stiffnesses between two cuboid-shaped magnets with arbitary displacements and magnetisation direction. (A cuboid is like a three dimensional rectangle; its faces are all orthogonal but may have different side lengths.)

4. The main function is *magnetforces*, which takes three mandatory arguments: *magnet_fixed*, *magnet_float*, and *displ*. These will be described in more detail below.

Optional string arguments may be any combination of `'force'`, and/or `'stiffness'` to indicate which calculations should be output. If no calculation is specified, `'force'` is the default.

Inputs:	*magnet_fixed*	structure describing first magnet
	magnet_float	structure describing the second magnet
	displ	displacement between the magnets
	[*what to calculate*]	'force' and/or 'stiffness'
Outputs:	*forces*	forces on the second magnet
	stiffnesses	stiffnesses on the second magnet
Magnet properties:	*dim*	size of each magnet
	magn	magnetisation magnitude
	magdir	magnetisation direction

⟨ `magnetforces.m` 4 ⟩ ≡

function [varargout] =*magnetforces*(*magnet_fixed*, *magnet_float*, *displ*, varargin)

⟨ Matlab help text (forces) 35 ⟩

⟨ Parse calculation args 9 ⟩
⟨ Initialise main variables 6 ⟩

⟨ Precompute rotation matrices 31 ⟩
⟨ Decompose orthogonal superpositions 7 ⟩
⟨ Calculate everything 12 ⟩

⟨ Combine results and exit 10 ⟩

⟨ Functions for calculating forces and stiffnesses 19 ⟩

end

[2] http://www.apache.org/licenses/LICENSE-2.0

5. Variables and data structures.

6. First of all, address the data structures required for the input and output. Because displacement of a single magnet has three components, plus sizes of the faces another three, plus magnetisation strength and direction (two) makes nine in total, we use one of Matlab's structures to pass the information into the function. Otherwise we'd have an overwhelming number of input arguments.

The input variables *magnet.dim* should be the entire side lengths of the magnets; these dimensions are halved when performing all of the calculations. (Because that's just how the maths is.)

We use spherical coordinates to represent magnetisation angle, where *phi* is the angle from the horizontal plane ($-\pi/2 \leq \phi \leq \pi/2$) and θ is the angle around the horizontal plane ($0 \leq \theta \leq 2\pi$). This follows Matlab's definition; other conventions are commonly used as well. Remember:

$$(1,0,0)_{\text{cartesian}} \equiv (0,0,1)_{\text{spherical}}$$
$$(0,1,0)_{\text{cartesian}} \equiv (\pi/2,0,1)_{\text{spherical}}$$
$$(0,0,1)_{\text{cartesian}} \equiv (0,\pi/2,1)_{\text{spherical}}$$

⟨ Initialise main variables 6 ⟩ ≡

```
size1 = reshape(magnet_fixed.dim/2, [3 1]);
size2 = reshape(magnet_float.dim/2, [3 1]);
J1r = magnet_fixed.magn;
J2r = magnet_float.magn;
J1t = magnet_fixed.magdir(1);
J2t = magnet_float.magdir(1);
J1p = magnet_fixed.magdir(2);
J2p = magnet_float.magdir(2);
```

See also sections 18 and 28.

This code is used in section 4.

7. Superposition is used to turn an arbitrary magnetisation angle into a set of orthogonal magnetisations.

Each magnet can potentially have three components, which can result in up to nine force calculations for a single magnet.

We don't use Matlab's `sph2cart` here, because it doesn't calculate zero accurately (because it uses radians and $\cos(\pi/2)$ can only be evaluated to machine precision rather than symbolically).

⟨ Decompose orthogonal superpositions 7 ⟩ ≡

```
displ = reshape(displ, [3 1]);          % column vector
J1 = [J1r*cosd(J1p)*cosd(J1t); ...
  J1r*cosd(J1p)*sind(J1t); ...
  J1r*sind(J1p)];
J2 = [J2r*cosd(J2p)*cosd(J2t); ...
  J2r*cosd(J2p)*sind(J2t); ...
  J2r*sind(J2p)];
```

This code is used in section 4.

8. Wrangling user input and output.

9. We now have a choice of calculations to take based on the user input. Take the opportunity to bail out in case the user has requested more calculations than provided as outputs to the function.

This chunk and the next are used in both `magnetforces.m` and `multipoleforces.m`.

⟨ Parse calculation args 9 ⟩ ≡

```
Nvargin = length(varargin);
if ( Nvargin ≠ 0 ∧ ∧ Nvargin ≠ nargout )
error('Must␣have␣as␣many␣outputs␣as␣calculations␣requested.')
end
calc_force_bool = false;
calc_stiffness_bool = false;
if Nvargin ≡ 0
  calc_force_bool = true;
else
  for ii = 1 : Nvargin
    switch varargin{ii}
    case 'force'
      calc_force_bool = true;
    case 'stiffness'
      calc_stiffness_bool = true;
    otherwise
      error(['Unknown␣calculation␣option␣''', varargin{ii}, ''''])
    end
  end
end
```

This code is used in sections 4 and 59.

10. After all of the calculations have occured, they're placed back into `varargout`.

⟨ Combine results and exit 10 ⟩ ≡

```
if Nvargin ≡ 0
  varargout{1} = forces_out;
else
  for ii = 1 : Nvargin
    switch varargin{ii}
    case 'force'
      varargout{ii} = forces_out;
    case 'stiffness'
      varargout{ii} = stiffnesses_out;
    end
  end
end
```

This code is used in sections 4 and 59.

11. The actual mechanics.

12. The expressions we have to calculate the forces assume a fixed magnet with positive z magnetisation only. Secondly, magnetisation direction of the floating magnet may only be in the positive z- or y-directions.

The parallel forces are more easily visualised; if `J1z` is negative, then transform the coordinate system so that up is down and down is up. Then proceed as usual and reverse the vertical forces in the last step.

The orthogonal forces require reflection and/or rotation to get the displacements in a form suitable for calculation.

Initialise a 9×3 array to store each force component in each direction, and then fill 'er up.

⟨ Calculate everything 12 ⟩ ≡

```
⟨ Print diagnostics 13 ⟩
⟨ Calculate x 15 ⟩
⟨ Calculate y 16 ⟩
⟨ Calculate z 14 ⟩
⟨ Combine calculations 17 ⟩
```

This code is used in section 4.

13. Let's print some information to the terminal to aid debugging. This is especially important (for me) when looking at the rotated coordinate systems.

⟨ Print diagnostics 13 ⟩ ≡

```
debug_disp('␣␣')
debug_disp('CALCULATING␣THINGS')
debug_disp('==================')
debug_disp('Displacement:')
debug_disp(displ')
debug_disp('Magnetisations:')
debug_disp(J1')
debug_disp(J2')
```

This code is used in section 12.

14. The easy one first, where our magnetisation components align with the direction expected by the force functions.

⟨ Calculate z 14 ⟩ ≡

```
if calc_force_bool
  debug_disp('z-z force:')
  force_components(9, :) = forces_calc_z_z(size1, size2, displ, J1, J2);
  debug_disp('z-y force:')
  force_components(8, :) = forces_calc_z_y(size1, size2, displ, J1, J2);
  debug_disp('z-x force:')
  force_components(7, :) = forces_calc_z_x(size1, size2, displ, J1, J2);
end
if calc_stiffness_bool
  debug_disp('z-z stiffness:')
  stiffness_components(9, :) = stiffnesses_calc_z_z(size1, size2, displ, J1,
      J2);
  debug_disp('z-y stiffness:')
  stiffness_components(8, :) = stiffnesses_calc_z_y(size1, size2, displ, J1,
      J2);
  debug_disp('z-x stiffness:')
  stiffness_components(7, :) = stiffnesses_calc_z_x(size1, size2, displ, J1,
      J2);
end
```

This code is used in section 12.

15. The other forces (i.e., x and y components) require a rotation to get the magnetisations correctly aligned. In the case of the magnet sizes, the lengths are just flipped rather than rotated (in rotation, sign is important). After the forces are calculated, rotate them back to the original coordinate system.

⟨ Calculate x 15 ⟩ ≡

```
size1_rot = swap_x_z(size1);
size2_rot = swap_x_z(size2);
d_rot = rotate_x_to_z(displ);
J1_rot = rotate_x_to_z(J1);
J2_rot = rotate_x_to_z(J2);
if calc_force_bool
  debug_disp('Forces␣x-x:')
  forces_x_x = forces_calc_z_z(size1_rot, size2_rot, d_rot, J1_rot, J2_rot);
  force_components(1, :) = rotate_z_to_x(forces_x_x);
  debug_disp('Forces␣x-y:')
  forces_x_y = forces_calc_z_y(size1_rot, size2_rot, d_rot, J1_rot, J2_rot);
  force_components(2, :) = rotate_z_to_x(forces_x_y);
  debug_disp('Forces␣x-z:')
  forces_x_z = forces_calc_z_y(size1_rot, size2_rot, d_rot, J1_rot, J2_rot);
  force_components(3, :) = rotate_z_to_x(forces_x_z);
end
if calc_stiffness_bool
  debug_disp('x-z␣stiffness:')
  stiffness_components(3, :) = rotate_z_to_x(stiffnesses_calc_z_x(size1_rot,
      size2_rot, d_rot, J1_rot, J2_rot));
  debug_disp('x-y␣stiffness:')
  stiffness_components(2, :) = rotate_z_to_x(stiffnesses_calc_z_y(size1_rot,
      size2_rot, d_rot, J1_rot, J2_rot));
  debug_disp('x-x␣stiffness:')
  stiffness_components(1, :) = rotate_z_to_x(stiffnesses_calc_z_z(size1_rot,
      size2_rot, d_rot, J1_rot, J2_rot));
end
```

This code is used in section 12.

16. Same again, this time making y the 'up' direction.

⟨ Calculate y 16 ⟩ ≡

```
size1_rot = swap_y_z(size1);
size2_rot = swap_y_z(size2);
d_rot = rotate_y_to_z(displ);
J1_rot = rotate_y_to_z(J1);
J2_rot = rotate_y_to_z(J2);
if calc_force_bool
  debug_disp('Forces␣y-x:')
  forces_y_x = forces_calc_z_x(size1_rot, size2_rot, d_rot, J1_rot, J2_rot);
  force_components(4, :) = rotate_z_to_y(forces_y_x);
  debug_disp('Forces␣y-y:')
  forces_y_y = forces_calc_z_z(size1_rot, size2_rot, d_rot, J1_rot, J2_rot);
  force_components(5, :) = rotate_z_to_y(forces_y_y);
  debug_disp('Forces␣y-z:')
  forces_y_z = forces_calc_z_y(size1_rot, size2_rot, d_rot, J1_rot, J2_rot);
  force_components(6, :) = rotate_z_to_y(forces_y_z);
end
if calc_stiffness_bool
  debug_disp('y-z␣stiffness:')
  stiffness_components(6, :) = rotate_z_to_y(stiffnesses_calc_z_y(size1_rot,
      size2_rot, d_rot, J1_rot, J2_rot));
  debug_disp('y-y␣stiffness:')
  stiffness_components(5, :) = rotate_z_to_y(stiffnesses_calc_z_z(size1_rot,
      size2_rot, d_rot, J1_rot, J2_rot));
  debug_disp('y-x␣stiffness:')
  stiffness_components(4, :) = rotate_z_to_y(stiffnesses_calc_z_x(size1_rot,
      size2_rot, d_rot, J1_rot, J2_rot));
end
```

This code is used in section 12.

17. Finally sum all the components in each direction to get the total forces.

⟨ Combine calculations 17 ⟩ ≡

```
if calc_force_bool
  forces_out = sum(force_components);
end
if calc_stiffness_bool
  stiffnesses_out = sum(stiffness_components);
end
```

This code is used in section 12.

18. You might have noticed that the initialisation of the *force_components* (and other) variables has not yet been listed. That's because the code is boring.

⟨ Initialise main variables 6 ⟩ +≡

```
if calc_force_bool
  force_components = repmat(NaN, [9 3]);
end
if calc_stiffness_bool
  stiffness_components = repmat(NaN, [9 3]);
end
```

19. Functions for calculating forces and stiffnesses. The calculations for forces between differently-oriented cuboid magnets are all directly from the literature. The stiffnesses have been derived by differentiating the force expressions, but that's the easy part.

⟨ Functions for calculating forces and stiffnesses 19 ⟩ ≡

⟨ Parallel magnets force calculation 20 ⟩
⟨ Orthogonal magnets force calculation 21 ⟩
⟨ Parallel magnets stiffness calculation 24 ⟩
⟨ Orthogonal magnets stiffness calculation 25 ⟩
⟨ Helper functions 32 ⟩

This code is used in section 4.

20. The expressions here follow directly from Akoun and Yonnet [1].

Inputs:	*size1*=(a, b, c)	the half dimensions of the fixed magnet
	size2=(A, B, C)	the half dimensions of the floating magnet
	displ=(*dx*, *dy*, *dz*)	distance between magnet centres
	$(J,$ *J2*$)$	magnetisations of the magnet in the z-direction
Outputs:	*forces_xyz*=(*Fx*, *Fy*, *Fz*)	Forces of the second magnet

⟨ Parallel magnets force calculation 20 ⟩ ≡

function *calc_out* = *forces_calc_z_z*(*size1*, *size2*, *offset*, *J1*, *J2*)

J1 = *J1*(3);
J2 = *J2*(3);
⟨ Initialise subfunction variables 27 ⟩
component_x = ...
$+0.5*(v .\hat{} 2 - w .\hat{} 2) .* \log(r - u) \ldots$
$+u .* v .* \log(r - v) \ldots$
$+v .* w .* \mathtt{atan2}(u .* v, r .* w) \ldots$
$+0.5*r .* u;$
component_y = ...
$+0.5*(u .\hat{} 2 - w .\hat{} 2) .* \log(r - v) \ldots$
$+u .* v .* \log(r - u) \ldots$
$+u .* w .* \mathtt{atan2}(u .* v, r .* w) \ldots$
$+0.5*r .* v;$
component_z = ...
$-u .* w .* \log(r - u) \ldots$
$-v .* w .* \log(r - v) \ldots$
$+u .* v .* \mathtt{atan2}(u .* v, r .* w) \ldots$
$-r .* w;$
⟨ Finish up 29 ⟩

This code is used in section 19.

21. Orthogonal magnets forces given by Yonnet and Allag [2].

⟨ Orthogonal magnets force calculation 21 ⟩ ≡

```
function calc_out = forces_calc_z_y(size1, size2, offset, J1, J2)
    J1 = J1(3);
    J2 = J2(2);
    ⟨ Initialise subfunction variables 27 ⟩
    component_x = ...
    −multiply_x_log_y(v .* w, r − u)...
    +multiply_x_log_y(v .* u, r + w)...
    +multiply_x_log_y(u .* w, r + v)...
    −0.5*u .^ 2 .* atan1(v .* w, u .* r)...
    −0.5*v .^ 2 .* atan1(u .* w, v .* r)...
    −0.5*w .^ 2 .* atan1(u .* v, w .* r);
    component_y = ...
    0.5*multiply_x_log_y(u .^ 2 − v .^ 2, r + w)...
    −multiply_x_log_y(u .* w, r − u)...
    −u .* v .* atan1(u .* w, v .* r)...
    −0.5*w .* r;
    component_z = ...
    0.5*multiply_x_log_y(u .^ 2 − w .^ 2, r + v)...
    −multiply_x_log_y(u .* v, r − u)...
    −u .* w .* atan1(u .* v, w .* r)...
    −0.5*v .* r;
    allag_correction = −1;
    component_x = allag_correction*component_x;
    component_y = allag_correction*component_y;
    component_z = allag_correction*component_z;
    if 0
      ⟨ Test against Janssen results 22 ⟩
    end
    ⟨ Finish up 29 ⟩
```

See also section 23.

This code is used in section 19.

22. This is the same calculation with Janssen's equations instead. By default this code never runs, but if you like it can be enabled to prove that the equations are consistent.

⟨ Test against Janssen results 22 ⟩ ≡

```
S = u;
T = v;
U = w;
R = r;
component_x_ii = ...
(0.5*atan1(U, S) + 0.5*atan1(T .* U, S .* R)) .* S .^ 2...
+T .* S - 3/2*U .* S - multiply_x_log_y(S .* T, U + R) - T .^ 2 .* atan1(S,
    T)...
+U .* (U .* (...
    0.5*atan1(S, U) + 0.5*atan1(S .* T, U .* R)...
    )...
  -multiply_x_log_y(T, S + R) + multiply_x_log_y(S, R - T)...
  )...
+0.5*T .^ 2 .* atan1(S .* U, T .* R)...
;
component_y_ii = ...
0.5*U .* (R - 2*S) + ...
multiply_x_log_y(0.5*(T .^ 2 - S .^ 2), U + R) + ...
S .* T .* (atan1(U, T) + atan1(S .* U, T .* R)) + ...
multiply_x_log_y(S .* U, R - S)...
;
component_z_ii = ...
0.5*T .* (R - 2*S) + ...
multiply_x_log_y(0.5*(U .^ 2 - S .^ 2), T + R) + ...
S .* U .* (atan1(T, U) + atan1(S .* T, U .* R)) + ...
multiply_x_log_y(S .* T, R - S)...
;
if 1
  xx = index_sum .* component_x;
  xx_ii = index_sum .* component_x_ii;
  assert(abs(sum(xx(:)) - sum(xx_ii(:))) < 1 · 10^-8)
end
if 1
  yy = index_sum .* component_y;
  yy_ii = index_sum .* component_y_ii;
  assert(abs(sum(yy(:)) - sum(yy_ii(:))) < 1 · 10^-8)
end
if 1
  zz = index_sum .* component_z;
  zz_ii = index_sum .* component_z_ii;
```

```
    assert(abs(sum(zz(:)) − sum(zz_ii(:))) < 1 · 10^−8)
  end
  if 1
    component_x = component_x_ii;
    component_y = component_y_ii;
    component_z = component_z_ii;
  end
```

This code is used in section 21.

23. Don't need to swap *J1* because it should only contain z components anyway. (This is assumption isn't tested because it it's wrong we're in more trouble anyway; this should all be taken care of earlier when the magnetisation components were separated out.)

⟨ Orthogonal magnets force calculation 21 ⟩ +≡

```
  function calc_out = forces_calc_z_x(size1, size2, offset, J1, J2)
    forces_xyz = forces_calc_z_y(...
      rotate_x_to_y(size1), rotate_x_to_y(size2), rotate_x_to_y(offset), ...
      J1, rotate_x_to_y(J2));
    calc_out = rotate_y_to_x(forces_xyz);
    end
```

24. Stiffness calculations are derived[3] from the forces.

⟨ Parallel magnets stiffness calculation 24 ⟩ ≡

```
  function calc_out = stiffnesses_calc_z_z(size1, size2, offset, J1, J2)
    J1 = J1(3);
    J2 = J2(3);
    ⟨ Initialise subfunction variables 27 ⟩
    component_x = ...
    −r ...
    −(u .^ 2 .* v) ./ (u .^ 2 + w .^ 2) ...
    −v .* log(r − v);
    component_y = ...
    −r ...
    −(v .^ 2 .* u) ./ (v .^ 2 + w .^ 2) ...
    −u .* log(r − u);
    component_z = −component_x − component_y;
    ⟨ Finish up 29 ⟩
```

This code is used in section 19.

[3] Literally.

25. Orthogonal magnets stiffnesses derived from Yonnet and Allag [2]. First the z–y magnetisation.

⟨ Orthogonal magnets stiffness calculation 25 ⟩ ≡

```
function calc_out = stiffnesses_calc_z_y(size1, size2, offset, J1, J2)
    J1 = J1(3);
    J2 = J2(2);
    ⟨ Initialise subfunction variables 27 ⟩
    component_x = -((u.^2.*v)./(u.^2+v.^2))-(u.^2.*w)./(u.^2+w.^2)...
    +u .* atan1(v .* w, r .* u) - multiply_x_log_y(w, r + v) + ...
    -multiply_x_log_y(v, r + w);
    component_y = v/2-(u.^2.*v)./(u.^2+v.^2)+(u.*v.*w)./(v.^2+w.^2)...
    +u .* atan1(u .* w, r .* v) + multiply_x_log_y(v, r + w);
    component_z = -component_x - component_y;
    allag_correction = -1;
    component_x = allag_correction*component_x;
    component_y = allag_correction*component_y;
    component_z = allag_correction*component_z;
    ⟨ Finish up 29 ⟩
```

See also section 26.

This code is used in section 19.

26. Now the z–x magnetisation, which is z–y rotated.

⟨ Orthogonal magnets stiffness calculation 25 ⟩ +≡

```
function calc_out = stiffnesses_calc_z_x(size1, size2, offset, J1, J2)
    stiffnesses_xyz = stiffnesses_calc_z_y(...
      rotate_x_to_y(size1), rotate_x_to_y(size2), rotate_x_to_y(offset), ...
      J1, rotate_x_to_y(J2));
    calc_out = rotate_y_to_x(stiffnesses_xyz);
    end
```

27. Some shared setup code. First **return** early if either of the magnetisations are zero — that's the trivial solution. Assume that the magnetisation has already been rounded down to zero if necessary; i.e., that we don't need to check for *J1* or *J2* are less than $1 \cdot 10^{-12}$ or whatever.

⟨ Initialise subfunction variables 27 ⟩ ≡

```
if ( J1 ≡ 0 OR J2 ≡ 0 )
debug_disp('Zero␣magnetisation.')
calc_out = [0;  0;  0];
return;
end
u = offset(1) + size2(1)*(-1) .^ index_j - size1(1)*(-1) .^ index_i;
v = offset(2) + size2(2)*(-1) .^ index_l - size1(2)*(-1) .^ index_k;
w = offset(3) + size2(3)*(-1) .^ index_q - size1(3)*(-1) .^ index_p;
r = sqrt(u .^ 2 + v .^ 2 + w .^ 2);
```

This code is used in sections 20, 21, 24, and 25.

28. Here are some variables used above that only need to be computed once. The idea here is to vectorise instead of using **for** loops because it allows more convenient manipulation of the data later on.

⟨ Initialise main variables 6 ⟩ +≡

```
magconst = 1/(4*π*(4*π*1 · 10^-7));
[index_i, index_j, index_k, index_l, index_p, index_q] = ndgrid([0 1]);
[index2_j, index2_l, index2_q] = ndgrid([0 1]);
index_sum = (-1).^(index_i+index_j+index_k+index_l+index_p+index_q);
```

29. And some shared finishing code.

⟨ Finish up 29 ⟩ ≡

```
component_x = index_sum .* component_x;
component_y = index_sum .* component_y;
component_z = index_sum .* component_z;
calc_out = J1*J2*magconst .* ...
[sum(component_x(:));
   sum(component_y(:));
   sum(component_z(:))];
debug_disp(calc_out')
end
```

This code is used in sections 20, 21, 24, and 25.

30. Setup code.

31. When the forces are rotated we use these rotation matrices to avoid having to think too hard. Use degrees in order to compute $\sin(\pi/2)$ exactly!

⟨ Precompute rotation matrices 31 ⟩ ≡

```
swap_x_y =@(vec) vec([2 1 3]);
swap_x_z =@(vec) vec([3 2 1]);
swap_y_z =@(vec) vec([1 3 2]);

Rx =@(θ) [1 0 0; 0 cosd(θ) -sind(θ); 0 sind(θ) cosd(θ)];
Ry =@(θ) [cosd(θ) 0 sind(θ); 0 1 0; -sind(θ) 0 cosd(θ)];
Rz =@(θ) [cosd(θ) -sind(θ) 0; sind(θ) cosd(θ) 0; 0 0 1];

Rx_180 = Rx(180);
Rx_090 = Rx(90);
Rx_270 = Rx(-90);
Ry_180 = Ry(180);
Ry_090 = Ry(90);
Ry_270 = Ry(-90);
Rz_180 = Rz(180);
Rz_090 = Rz(90);
Rz_270 = Rz(-90);

rotate_z_to_x =@(vec) Ry_090*vec;
rotate_x_to_z =@(vec) Ry_270*vec;

rotate_z_to_y =@(vec) Rx_090*vec;
rotate_y_to_z =@(vec) Rx_270*vec;

rotate_x_to_y =@(vec) Rz_090*vec;
rotate_y_to_x =@(vec) Rz_270*vec;
```

This code is used in section 4.

32. The equations contain two singularities. Specifically, the equations contain terms of the form $x\log(y)$, which becomes `NaN` when both x and y are zero since $\log(0)$ is negative infinity.

This function computes $x\log(y)$, special-casing the singularity to output zero, instead. (This is indeed the value of the limit.)

⟨ Helper functions 32 ⟩ ≡

```
function out = multiply_x_log_y(x, y)
    out = x .* log(y);
    out(isnan(out)) = 0;
    end
```

See also sections 33 and 34.

This code is used in section 19.

33. Also, we're using `atan` instead of `atan2` (otherwise the wrong results are calculated — I guess I don't totally understand that), which becomes a problem when trying to compute `atan`$(0/0)$ since $0/0$ is `NaN`.

This function computes `atan` but takes two arguments.

⟨ Helper functions 32 ⟩ +≡

```
function out = atan1(x, y)
    out = zeros(size(x));
    ind = x ≠ 0 ∧ y ≠ 0;
    out(ind) = atan(x(ind) ./ y(ind));
    end
```

34. This function is for easy debugging; in normal use it gobbles its argument but will print diagnostics when required.

⟨ Helper functions 32 ⟩ +≡

```
function debug_disp(str)
    %disp(str)
  end
```

35. When users type `help magnetforces` this is what they see.

⟨ Matlab help text (forces) 35 ⟩ ≡

```
%% MAGNETFORCES  Calculate forces between two cuboid magnets
%
% Finish this off later.
%
```

This code is used in section 4.

36. Test files. The chunks that follow are designed to be saved into individual files and executed automatically to check for (a) correctness and (b) regression problems as the code evolves.

How do I know if the code produces the correct forces? Well, for many cases I can compare with published values in the literature. Beyond that, I'll be setting up some tests that I can logically infer should produce the same results (such as mirror-image displacements) and test that.

There are many Matlab unit test frameworks but I'll be using a fairly low-tech method. In time this test suite should be (somehow) useable for all implementations of `magnetocode`, not just Matlab. But I haven't thought about doing anything like that, yet.

37. Because I'm lazy, just run the tests manually for now. This script must be run twice if it updates itself.

⟨ `testall.m` 37 ⟩ ≡

```
clc;
unix('~/bin/mtangle␣magnetforces');
```

magforce_test001a
magforce_test001b
magforce_test001c
magforce_test001d

38. Force testing.

39. This test checks that square magnets produce the same forces in the each direction when displaced in positive and negative x, y, and z directions, respectively. In other words, this tests the function *forces_calc_z_y* directly. Both positive and negative magnetisations are used.

⟨ magforce_test001a.m 39 ⟩ ≡

```
disp('=================')
fprintf('TEST 001a: ')
magnet_fixed.dim = [0.04 0.04 0.04];
magnet_float.dim = magnet_fixed.dim;
magnet_fixed.magn = 1.3;
magnet_float.magn = 1.3;
offset = 0.1;
⟨ Test z–z magnetisations 40 ⟩
⟨ Assert magnetisations tests 48 ⟩
⟨ Test x–x magnetisations 41 ⟩
⟨ Assert magnetisations tests 48 ⟩
⟨ Test y–y magnetisations 42 ⟩
⟨ Assert magnetisations tests 48 ⟩
fprintf('passed\n')
disp('=================')
```

40. Testing vertical forces.

⟨ Test z–z magnetisations 40 ⟩ ≡

```
f = [];
for ii = [1, -1]
  magnet_fixed.magdir = [0 ii*90];        % ±z
  for jj = [1, -1]
    magnet_float.magdir = [0 jj*90];
    for kk = [1, -1]
      displ = kk*[0 0 offset];
      f(:, end + 1) = magnetforces(magnet_fixed, magnet_float, displ);
    end
  end
end
dirforces = chop(f(3, :), 8);
otherforces = f([1 2], :);
```

This code is used in section 39.

41. Testing horizontal x forces.

⟨ Test x–x magnetisations 41 ⟩ ≡

```
f = [];
for ii = [1, -1]
  magnet_fixed.magdir = [90 + ii*90 0];        % ±x
  for jj = [1, -1]
    magnet_float.magdir = [90 + jj*90 0];
    for kk = [1, -1]
      displ = kk*[offset 0 0];
      f(:, end + 1) = magnetforces(magnet_fixed, magnet_float, displ);
    end
  end
end
dirforces = chop(f(1, :), 8);
otherforces = f([2 3], :);
```

This code is used in section 39.

42. Testing horizontal y forces.

⟨ Test y–y magnetisations 42 ⟩ ≡

```
f = [];
for ii = [1, -1]
  magnet_fixed.magdir = [ii*90 0];        % ±y
  for jj = [1, -1]
    magnet_float.magdir = [jj*90 0];
    for kk = [1, -1]
      displ = kk*[0 offset 0];
      f(:, end + 1) = magnetforces(magnet_fixed, magnet_float, displ);
    end
  end
end
dirforces = chop(f(2, :), 8);
otherforces = f([1 3], :);
```

This code is used in section 39.

43. This test does the same thing but for orthogonally magnetised magnets.

⟨ magforce_test001b.m 43 ⟩ ≡

```
disp('=================')
fprintf('TEST 001b: ')
magnet_fixed.dim = [0.04 0.04 0.04];
magnet_float.dim = magnet_fixed.dim;
magnet_fixed.magn = 1.3;
magnet_float.magn = 1.3;
⟨ Test ZYZ 44 ⟩
⟨ Assert magnetisations tests 48 ⟩
⟨ Test ZXZ 45 ⟩
⟨ Assert magnetisations tests 48 ⟩
⟨ Test ZXX 47 ⟩
⟨ Assert magnetisations tests 48 ⟩
⟨ Test ZYY 46 ⟩
⟨ Assert magnetisations tests 48 ⟩
fprintf('passed\n')
disp('=================')
```

44. z–y magnetisations, z displacement.

⟨ Test ZYZ 44 ⟩ ≡

```
fzyz = [];
for ii = [1, -1]
  for jj = [1, -1]
    for kk = [1, -1]
      magnet_fixed.magdir = ii*[0 90];      % ±z
      magnet_float.magdir = jj*[90 0];      % ±y
      displ = kk*[0 0 0.1];      % ±z
      fzyz(:, end+1) = magnetforces(magnet_fixed, magnet_float, displ);
    end
  end
end
dirforces = chop(fzyz(2, :), 8);
otherforces = fzyz([1 3], :);
```

This code is used in section 43.

45. z–x magnetisations, z displacement.

⟨ Test ZXZ 45 ⟩ ≡

```
fzxz = [];
for ii = [1, -1]
  for jj = [1, -1]
    for kk = [1, -1]
      magnet_fixed.magdir = ii*[0 90];        % ±z
      magnet_float.magdir = [90 + jj*90 0];       % ±x
      displ = kk*[0.1 0 0];        % ±x
      fzxz(:, end + 1) = magnetforces(magnet_fixed, magnet_float, displ);
    end
  end
end
dirforces = chop(fzxz(3, :), 8);
otherforces = fzxz([1 2], :);
```

This code is used in section 43.

46. z–y magnetisations, y displacement.

⟨ Test ZYY 46 ⟩ ≡

```
fzyy = [];
for ii = [1, -1]
  for jj = [1, -1]
    for kk = [1, -1]
      magnet_fixed.magdir = ii*[0 90];        % ±z
      magnet_float.magdir = jj*[90 0];        % ±y
      displ = kk*[0 0.1 0];        % ±y
      fzyy(:, end + 1) = magnetforces(magnet_fixed, magnet_float,
          displ);
    end
  end
end
dirforces = chop(fzyy(3, :), 8);
otherforces = fzyy([1 2], :);
```

This code is used in section 43.

47. z–x magnetisations, x displacement.

⟨ Test ZXX 47 ⟩ ≡

```
fzxx = [];
for ii = [1, -1]
  for jj = [1, -1]
    for kk = [1, -1]
      magnet_fixed.magdir = ii*[0 90];        % ±z
      magnet_float.magdir = [90 + jj*90 0];       % ±x
      displ = kk*[0 0 0.1];        % ±z
      fzxx(:, end+1) = magnetforces(magnet_fixed, magnet_float, displ);
    end
  end
end
dirforces = chop(fzxx(1, :), 8);
otherforces = fzxx([2 3], :);
```

This code is used in section 43.

48. The assertions, common between directions.

⟨ Assert magnetisations tests 48 ⟩ ≡

```
assert(...
  all(abs(otherforces(:)) < 1 · 10^-11), ...
  'Orthogonal␣forces␣should␣be␣zero' ...
  )
assert(...
  all(abs(dirforces) ≡ abs(dirforces(1))), ...
  'Force␣magnitudes␣should␣be␣equal' ...
  )
assert(...
  all(dirforces(1 : 4) ≡ −dirforces(5 : 8)), ...
  'Forces␣should␣be␣opposite␣with␣reversed␣fixed␣magnet␣magnetisation' ...
  )
assert(...
  all(dirforces([1 3 5 7]) ≡ −dirforces([2 4 6 8])), ...
  'Forces␣should␣be␣opposite␣with␣reversed␣float␣magnet␣magnetisation' ...
  )
```

This code is used in sections 39 and 43.

49. Now try combinations of displacements.

⟨ magforce_test001c.m 49 ⟩ ≡

```
disp('=================')
fprintf('TEST␣001c:␣')

magnet_fixed.dim = [0.04 0.04 0.04];
magnet_float.dim = magnet_fixed.dim;

magnet_fixed.magn = 1.3;
magnet_float.magn = 1.3;

⟨ Test combinations ZZ 50 ⟩
⟨ Assert combinations tests 52 ⟩
⟨ Test combinations ZY 51 ⟩
⟨ Assert combinations tests 52 ⟩

fprintf('passed\n')
disp('=================')
```

50. Tests.

⟨ Test combinations ZZ 50 ⟩ ≡

```
f = [];
for ii = [-1 1]
  for jj = [-1 1]
    for xx = 0.12*[-1, 1]
      for yy = 0.12*[-1, 1]
        for zz = 0.12*[-1, 1]
          magnet_fixed.magdir = [0 ii*90];        % z
          magnet_float.magdir = [0 jj*90];        % z
          displ = [xx yy zz];
          f(:, end + 1) = magnetforces(magnet_fixed, magnet_float,
              displ);
        end
      end
    end
  end
end

f = chop(f, 8);

uniquedir = f(3, :);
otherdir = f([1 2], :);
```

This code is used in section 49.

51. Tests.

⟨ Test combinations ZY 51 ⟩ ≡

```
f = [];
for ii = [−1 1]
  for jj = [−1 1]
    for xx = 0.12∗[−1, 1]
      for yy = 0.12∗[−1, 1]
        for zz = 0.12∗[−1, 1]
          magnet_fixed.magdir = [0 ii∗90];        % ±z
          magnet_float.magdir = [jj∗90 0];        % ±y
          displ = [xx yy zz];
          f(:, end + 1) = magnetforces(magnet_fixed, magnet_float,
              displ);
        end
      end
    end
  end
end
f = chop(f, 8);
uniquedir = f(1, :);
otherdir = f([2 3], :);
```

This code is used in section 49.

52. Shared tests, again.

⟨ Assert combinations tests 52 ⟩ ≡

```
test1 = abs(diff(abs(f(1, :)))) < 1 · 10^−10;
test2 = abs(diff(abs(f(2, :)))) < 1 · 10^−10;
test3 = abs(diff(abs(f(3, :)))) < 1 · 10^−10;
assert( all(test1) ∧ ∧ all(test2) ∧ ∧ all(test3), ...
  'All␣forces␣in␣a␣single␣direction␣should␣be␣equal' )
test = abs(diff(abs(otherdir))) < 1 · 10^−11;
assert(all(test), 'Orthogonal␣forces␣should␣be␣equal')
test1 = f(:, 1 : 8) ≡ f(:, 25 : 32);
test2 = f(:, 9 : 16) ≡ f(:, 17 : 24);
assert( all(test1(:)) ∧ ∧ all(test2(:)), ...
  'Reverse␣magnetisation␣shouldn''t␣make␣a␣difference' )
```

This code is used in section 49.

53. Now we want to try non-orthogonal magnetisation.

⟨ magforce_test001d.m 53 ⟩ ≡

```
disp('=================')
fprintf('TEST␣001d:␣')
magnet_fixed.dim = [0.04 0.04 0.04];
magnet_float.dim = magnet_fixed.dim;
    % Fixed parameters:
magnet_fixed.magn = 1.3;
magnet_float.magn = 1.3;
magnet_fixed.magdir = [0 90];        % z
displ = 0.12*[1 1 1];
⟨ Test XY superposition 54 ⟩
⟨ Assert superposition 57 ⟩
⟨ Test XZ superposition 55 ⟩
⟨ Assert superposition 57 ⟩
⟨ Test planar superposition 56 ⟩
⟨ Assert superposition 57 ⟩
fprintf('passed\n')
disp('=================')
```

54. Test with a magnetisation unit vector of $(1, 1, 0)$.

⟨ Test XY superposition 54 ⟩ ≡

```
magnet_float.magdir = [45 0];        % e_x + e_y
f1 = magnetforces(magnet_fixed, magnet_float, displ);
    % Components:
magnet_float.magdir = [0 0];         % e_x
fc1 = magnetforces(magnet_fixed, magnet_float, displ);
magnet_float.magdir = [90 0];        % e_y
fc2 = magnetforces(magnet_fixed, magnet_float, displ);
f2 = (fc1 + fc2)/sqrt(2);
```

This code is used in section 53.

55. Test with a magnetisation unit vector of $(1, 0, 1)$.

⟨ Test XZ superposition 55 ⟩ ≡

```
magnet_float.magdir = [0 45];        % e_y + e_z
f1 = magnetforces(magnet_fixed, magnet_float, displ);
    % Components:
magnet_float.magdir = [0 0];         % e_x
fc1 = magnetforces(magnet_fixed, magnet_float, displ);
magnet_float.magdir = [0 90];        % e_z
fc2 = magnetforces(magnet_fixed, magnet_float, displ);
f2 = (fc1 + fc2)/sqrt(2);
```

This code is used in section 53.

56. Test with a magnetisation unit vector of $(1, 1, 1)$. This is about as much as I can be bothered testing for now. Things seem to be working.

⟨ Test planar superposition 56 ⟩ ≡

```
[t p r] = cart2sph(1/sqrt(3), 1/sqrt(3), 1/sqrt(3));
magnet_float.magdir = [t p]*180/π;        % e_y + e_z + e_z
f1 = magnetforces(magnet_fixed, magnet_float, displ);
    % Components:
magnet_float.magdir = [0 0];         % e_x
fc1 = magnetforces(magnet_fixed, magnet_float, displ);
magnet_float.magdir = [90 0];        % e_y
fc2 = magnetforces(magnet_fixed, magnet_float, displ);
magnet_float.magdir = [0 90];        % e_z
fc3 = magnetforces(magnet_fixed, magnet_float, displ);
f2 = (fc1 + fc2 + fc3)/sqrt(3);
```

This code is used in section 53.

57. The assertion is the same each time.

⟨ Assert superposition 57 ⟩ ≡

```
assert(...
  isequal(chop(f1, 4), chop(f2, 4)), ...
  'Components␣should␣sum␣due␣to␣superposition' ...
  )
```

This code is used in section 53.

58. Forces between (multipole) magnet arrays.

59. This function uses `magnetforces.m` to compute the forces between two multipole magnet arrays. As before, we can calculate either force and/or stiffness in all three directions.

Inputs:	*fixed_array*	structure describing first magnet array
	float_array	structure describing the second magnet array
	displ	displacement between first magnet of each array
	[*what to calculate*]	'force' and/or 'stiffness'
Outputs:	*forces*	forces on the second array
	stiffnesses	stiffnesses on the second array
Array properties:	*mcount*	$[i\ j\ k]$ magnets in each direction
	msize	size of each magnet
	mgap	gap between successive magnets
	magn	magnetisation magnitude
	magdir_fn	function to calculate the magnetisation direction

⟨ `multipoleforces.m` 59 ⟩ ≡

function [varargout] =*multipoleforces*(*fixed_array*, *float_array*, *displ*, varargin)

⟨ Matlab help text (multipole) 68 ⟩

⟨ Parse calculation args 9 ⟩
⟨ Calculate array forces 60 ⟩
⟨ Combine results and exit 10 ⟩

end

⟨ Multipole sub-functions 67 ⟩

60. To calculate the forces between the magnet arrays, let's assume that we have two large arrays enumerating the positions and magnetisations of each individual magnet in each magnet array.

Required fields for each magnet array:

`total` M total number of magnets in the array
`dim` $(M \times 3)$ size of each magnet
`loc` $(M \times 3)$ location of each magnet
`magn` $(M \times 1)$ magnetisation magnitude of each magnet
`magdir` $(M \times 2)$ magnetisation direction of each magnet in spherical coordinates

⟨ Calculate array forces 60 ⟩ ≡

```
fixed_array = complete_array_from_input(fixed_array);
float_array = complete_array_from_input(float_array);
if calc_force_bool
  array_forces = repmat(NaN, [fixed_array.total float_array.total 3]);
end
if calc_stiffness_bool
  array_stiffnesses = repmat(NaN, [fixed_array.total float_array.total 3]);
end
for mm = 1 : fixed_array.total
  fixed_magnet = struct(...
    'dim', fixed_array.dim(mm, :), ...
    'magn', fixed_array.magn(mm), ...
    'magdir', fixed_array.magdir(mm, :) ...
    );
  for nn = 1 : float_array.total
    float_magnet = struct(...
      'dim', float_array.dim(nn, :), ...
      'magn', float_array.magn(nn), ...
      'magdir', float_array.magdir(nn, :) ...
      );
    mag_displ = displ - fixed_array.loc(mm, :) + float_array.loc(nn, :);
    if calc_force_bool
      array_forces(mm, nn, :) = ...
      magnetforces(fixed_magnet, float_magnet, mag_displ, 'force');
    end
    if calc_stiffness_bool
      array_stiffnesses(mm, nn, :) = ...
      magnetforces(fixed_magnet, float_magnet, mag_displ,
          'stiffness');
    end
  end
end
debug_disp('Forces:')
debug_disp(reshape(array_forces, [], 3))
```

```
if calc_force_bool
  forces_out = squeeze(sum(sum(array_forces, 1), 2));
end
if calc_stiffness_bool
  stiffnesses_out = squeeze(sum(sum(array_stiffnesses, 1), 2));
end
```

This code is used in section 59.

61. We separate the force calculation from transforming the inputs into an intermediate form used for that purpose. This will hopefully allow us a little more flexibility.

As input variables for a linear multipole array, we want to use some combination of the following:

w wavelength of magnetisation

l length of the array

N number of wavelengths

d magnet length

T total number of magnets

M number of magnets per wavelength

ϕ rotation between successive magnets

And the following are linearly independent:

ϕ_0 magnetisation direction of the first magnet

g additional gap between adjacent magnet faces (optional)

e array height (or magnet height)

f array depth (or magnet depth)

These are related via the following equations of constraint:

$$w = Md \qquad l = Td \qquad N = T/M \qquad M = 360^\circ/\phi \tag{1}$$

Taking logarithms and writing in matrix form yields

$$\begin{bmatrix} 1 & 0 & 0 & -1 & 0 & -1 & 0 \\ 0 & 1 & 0 & -1 & -1 & 0 & 0 \\ 0 & 0 & 1 & 0 & -1 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 1 \end{bmatrix} \log \begin{bmatrix} w \\ l \\ N \\ d \\ T \\ M \\ \phi \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \\ 0 \\ \log(360^\circ) \end{bmatrix} \tag{2}$$

We can use this matrix to compute whichever variables we need given enough inputs.

However, we generally do not want an integer number of wavelengths of magnetisation in the magnet arrays; if $T = MN$ then we get small lateral forces that are undesirable for stability. We prefer instead to have $T = MN + 1$, but this cannot be represented by our linear (logarithmic) algebra above. Therefore, if the user requests a total number of wavelengths of magnetisation, we automatically add one end magnet to restore the symmetry of the forces.

```
⟨ Create arrays from input variables 61 ⟩ ≡
  function array_out = complete_array_from_input(array)
      if NOTisfield(array, 'type')
        array.type = 'generic';
      end
      switch array.type
      case 'generic'
      case 'linear-x'
        linear_index = 1;
      otherwise
        error(['Unknown␣array␣type␣''', array.type, '''.'])
      end
      array.mcount_extra = 0;
      if isfield(array, 'Nwaves')
        array.mcount_extra = 1;
      end
      if strncmp(array.type, 'linear', 6)
        var_names = {'wavelength', 'length', 'Nwaves', 'mlength', ...
          'Nmag', 'Nmag_per_wave', 'magdir_rotate'};
        variables = repmat(NaN, [7 1]);
        for ii = 1:length (var_names);
          if isfield(array, var_names(ii))
            variables(ii) = array.(var_names{ii});
          end
        end
        var_matrix = ...
        [1, 0, 0, −1, 0, −1, 0;
          0, 1, 0, −1, −1, 0, 0;
          0, 0, 1, 0, −1, 1, 0;
          0, 0, 0, 0, 0, 1, 1];
        var_results = [0 0 0 log(360)]′;
        variables = log(variables);
        idx = NOTisnan(variables);
        var_known = var_matrix(:, idx)∗variables(idx);
        var_calc = var_matrix(:, NOTidx)\(var_results − var_known);
        variables(NOTidx) = var_calc;
        variables = exp(variables);
        for ii = 1:length (var_names);
          array.(var_names{ii}) = variables(ii);
        end
        array.Nmag = round(array.Nmag) + array.mcount_extra;
        array.Nmag_per_wave = round(array.Nmag_per_wave);
```

```
    array.mlength = array.mlength*(array.Nmag −
        array.mcount_extra)/array.Nmag;
    array.mcount = ones(1, 3);
    array.mcount(linear_index) = array.Nmag;
  end
  array.total = prod(array.mcount);
  ⟨ Array sizes 62 ⟩
  ⟨ Array magnetisation strengths 63 ⟩
  ⟨ Array gaps 64 ⟩
  ⟨ Array magnetisation directions 65 ⟩
  ⟨ Array locs 66 ⟩
  array_out = array;
  end
```

This code is used in section 67.

62. Sizes.

⟨ Array sizes 62 ⟩ ≡

```
if NOTisfield(array, 'msize')
  array.msize = [array.mlength array.width array.height];
end
if length(array.msize) ≡ 3
  array.dim_array = ...
  repmat(reshape(array.msize, [1 1 1 3]), array.mcount);
  array.dim = reshape(array.dim_array, [array.total 3]);
else
  error('Not␣yet␣implemented.')
end
```

This code is used in section 61.

63. Magnetisation strength of each magnet.

⟨ Array magnetisation strengths 63 ⟩ ≡

```
if length(array.magn) ≡ 1
  array.magn = repmat(array.magn, [array.total 1]);
else
  error('Not␣yet␣implemented.')
end
```

This code is used in section 61.

64. Gaps, if any, between each magnet.

⟨ Array gaps 64 ⟩ ≡

```
if NOTisfield(array, 'mgap')
  array.mgap = [0;  0;  0];
end
if length(array.mgap) ≡ 1
  array.mgap = repmat(array.mgap, [3 1]);
end
```

This code is used in section 61.

65. Magnetisation direction of each magnet.

⟨ Array magnetisation directions 65 ⟩ ≡

```
array.magdir = repmat(NaN, [array.total 2]);
if NOTisfield(array, 'magdir_rotate_sign')
  array.magdir_rotate_sign = 1;
else
  switch array.face
  case 'up'
    array.magdir_rotate_sign = 1;
  case 'down'
    array.magdir_rotate_sign = -1;
  otherwise
    error('Not␣sure␣what␣this␣means.')
  end
end
if NOTisfield(array, 'magdir_fn')
  switch array.type
  case 'linear-x'
    array.magdir_fn =@(ii, jj, kk) ...
    [0  array.magdir_first +
        array.magdir_rotate_sign*array.magdir_rotate*(ii - 1)];
  end
end
ii = 0;
for xx = 1 : array.mcount (1)
  for yy = 1 : array.mcount (2)
    for zz = 1 : array.mcount (3)
      ii = ii + 1;
      array.magdir(ii, :) = array.magdir_fn(xx, yy, zz);
    end
  end
end
debug_disp('Magnetisation␣directions')
debug_disp(mod(array.magdir, 360))
```

This code is used in section 61.

66. Location of each magnet.

⟨ Array locs 66 ⟩ ≡

```
array.loc = repmat(NaN, [array.total 3]);
ii = 0;
for xx = 1 : array.mcount (1)
  for yy = 1 : array.mcount (2)
    for zz = 1 : array.mcount (3)
      ii = ii + 1;
      array.loc(ii, :) = ...
      [xx − 1;  yy − 1;  zz − 1] .* ...
      (squeeze(array.dim_array(xx, yy, zz, :)) + array.mgap);
    end
  end
end
debug_disp('Magnet␣locations:')
debug_disp(array.loc)
```

This code is used in section 61.

67. Sub-functions.

⟨ Multipole sub-functions 67 ⟩ ≡

```
⟨ Create arrays from input variables 61 ⟩
function debug_disp(str)
  disp(str)
  end
```

This code is used in section 59.

68. When users type `help multipoleforces` this is what they see.

⟨ Matlab help text (multipole) 68 ⟩ ≡

```
%% MULTIPOLEFORCES  Calculate forces between two multipole arrays of magnets
%
% Finish this off later.
%
```

This code is used in section 59.

69. Test files for multipole arrays.

⟨ multiforce_test001a.m 69 ⟩ ≡

```
fixed_array = ...
struct(...
  'type', 'linear-x', ...
  'face', 'up', ...
  'length', 0.01, ...
  'width', 0.01, ...
  'height', 0.01, ...
  'Nmag_per_wave', 4, ...
  'Nwaves', 1, ...
  'magn', 1, ...
  'magdir_first', 90...
  );
float_array = fixed_array;
float_array.face = 'down';
float_array.magdir_first = −90;
displ = [0 0 0.02];
f_total = multipoleforces(fixed_array, float_array, displ);
disp('Total force:')
disp(f_total′)
```

70. These are MATLABWEB declarations to improve the formatting of this document. Ignore unless you're editing `magnetforces.web`.

define end ≡ **end**
format *END* *TeX*

Index of magnetforces

List of Refinements in `magnetforces`

⟨ Decompose orthogonal superpositions 7 ⟩ Used in section 4.
⟨ Finish up 29 ⟩ Used in sections 20, 21, 24, and 25.
⟨ Functions for calculating forces and stiffnesses 19 ⟩ Used in section 4.
⟨ Helper functions 32, 33, 34 ⟩ Used in section 19.
⟨ Initialise main variables 6, 18, 28 ⟩ Used in section 4.
⟨ Initialise subfunction variables 27 ⟩ Used in sections 20, 21, 24, and 25.
⟨ Matlab help text (forces) 35 ⟩ Used in section 4.
⟨ Matlab help text (multipole) 68 ⟩ Used in section 59.
⟨ Multipole sub-functions 67 ⟩ Used in section 59.
⟨ Orthogonal magnets force calculation 21, 23 ⟩ Used in section 19.
⟨ Orthogonal magnets stiffness calculation 25, 26 ⟩ Used in section 19.
⟨ Parallel magnets force calculation 20 ⟩ Used in section 19.
⟨ Parallel magnets stiffness calculation 24 ⟩ Used in section 19.
⟨ Parse calculation args 9 ⟩ Used in sections 4 and 59.
⟨ Precompute rotation matrices 31 ⟩ Used in section 4.
⟨ Print diagnostics 13 ⟩ Used in section 12.
⟨ Test x–x magnetisations 41 ⟩ Used in section 39.
⟨ Test y–y magnetisations 42 ⟩ Used in section 39.
⟨ Test z–z magnetisations 40 ⟩ Used in section 39.
⟨ Test XY superposition 54 ⟩ Used in section 53.
⟨ Test XZ superposition 55 ⟩ Used in section 53.
⟨ Test ZXX 47 ⟩ Used in section 43.
⟨ Test ZXZ 45 ⟩ Used in section 43.
⟨ Test ZYY 46 ⟩ Used in section 43.
⟨ Test ZYZ 44 ⟩ Used in section 43.
⟨ Test against Janssen results 22 ⟩ Used in section 21.
⟨ Test combinations ZY 51 ⟩ Used in section 49.
⟨ Test combinations ZZ 50 ⟩ Used in section 49.
⟨ Test planar superposition 56 ⟩ Used in section 53.

References

[1] Gilles Akoun and Jean-Paul Yonnet. "3D analytical calculation of the forces exerted between two cuboidal magnets". In: *IEEE Transactions on Magnetics* MAG-20.5 (Sept. 1984), pp. 1962–1964. DOI: 10.1109/TMAG.1984.1063554.

[2] Jean-Paul Yonnet and Hicham Allag. "Analytical Calculation of Cubodal Magnet Interactions in 3D". In: *The 7th International Symposium on Linear Drives for Industry Application*. 2009.